

## AWS-SysOps Dumps

### Amazon AWS Certified SysOps Administrator - Associate

<https://www.certleader.com/AWS-SysOps-dumps.html>



**NEW QUESTION 1**

- (Topic 1)

Your team is excited about the use of AWS because now they have access to programmable Infrastructure. You have been asked to manage your AWS infrastructure in a manner similar to the way you might manage application code. You want to be able to deploy exact copies of different versions of your infrastructure, stage changes into different environments, revert back to previous versions, and identify what versions are running at any particular time (development, test, QA, production).

Which approach addresses this requirement?

- A. Use cost allocation reports and AWS Opsworks to deploy and manage your infrastructure
- B. Use AWS CloudWatch metrics and alerts along with resource tagging to deploy and manage your infrastructure
- C. Use AWS Beanstalk and a version control system like GIT to deploy and manage your infrastructure
- D. Use AWS CloudFormation and a version control system like GIT to deploy and manage your infrastructure

**Answer: B**

**Explanation:**

Reference:

<http://aws.amazon.com/opsworks/faqs/>

**NEW QUESTION 2**

- (Topic 1)

A media company produces new video files on-premises every day with a total size of around 100GBs after compression. All files have a size of 1-2 GB and need to be uploaded to Amazon S3 every night in a fixed time window between 3am and 5am. Current upload takes almost 3 hours, although less than half of the available bandwidth is used.

What step(s) would ensure that the file uploads are able to complete in the allotted time window?

- A. Increase your network bandwidth to provide faster throughput to S3
- B. Upload the files in parallel to S3
- C. Pack all files into a single archive, upload it to S3, then extract the files in AWS
- D. Use AWS Import/Export to transfer the video files

**Answer: B**

**Explanation:**

Reference:

<http://aws.amazon.com/importexport/faqs/>

**NEW QUESTION 3**

- (Topic 1)

You are tasked with setting up a cluster of EC2 Instances for a NoSQL database. The database requires random read IO disk performance up to a 100,000 IOPS at 4KB block size per node.

Which of the following EC2 instances will perform the best for this workload?

- A. A High-Memory Quadruple Extra Large (m2.4xlarge) with EBS-Optimized set to true and a Provisioned IOPS EBS volume
- B. A Cluster Compute Eight Extra Large (cc2.8xlarge) using instance storage
- C. High I/O Quadruple Extra Large (hi1.4xlarge) using instance storage
- D. A Cluster GPU Quadruple Extra Large (cg1.4xlarge) using four separate 4000 PIOPS EBS volumes in a RAID 0 configuration

**Answer: C**

**Explanation:**

Explanation: Reference:

<http://aws.amazon.com/ec2/instance-types/>

**NEW QUESTION 4**

- (Topic 1)

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    }
  ],
  "Principal": {
    "AWS": [
      "*"
    ]
  }
}
```

- A. Denies the server with the IP address 192 168 100 0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192 168 100 188 full access to the "mybucket" bucket
- C. Grants all the servers within the 192 168 100 0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192 168 100 188/32 subnet full access to the "mybucket" bucket

**Answer: B**

#### NEW QUESTION 5

- (Topic 1)

A customer has a web application that uses cookie Based sessions to track logged in users It Is deployed on AWS using ELB and Auto Scaling The customer observes that when load increases. Auto Scaling launches new Instances but the load on the easting Instances does not decrease, causing all existing users to have a sluggish experience.

Which two answer choices independently describe a behavior that could be the cause of the sluggish user experience? Choose 2 answers

- A. ELB's normal behavior sends requests from the same user to the same backend instance
- B. ELB's behavior when sticky sessions are enabled causes ELB to send requests in the same session to the same backend instance
- C. A faulty browser is not honoring the TTL of the ELB DNS nam
- D. The web application uses long polling such as comet or websocket
- E. Thereby keeping a connection open to a web server tor a long time
- F. The web application uses long polling such as comet or websocket
- G. Thereby keeping a connection open to a web server for a long tim

**Answer: BD**

#### NEW QUESTION 6

- (Topic 1)

You use S3 to store critical data for your company Several users within your group currently have lull permissions to your S3 buckets You need to come up with a solution mat does not impact your users and also protect against the accidental deletion of objects.

Which two options will address this issue? Choose 2 answers

- A. Enable versioning on your S3 Buckets
- B. Configure your S3 Buckets with MFA delete
- C. Create a Bucket policy and only allow read only permissions to all users at the bucket level
- D. Enable object life cycle policies and configure the data older than 3 months to be archived in Glacier

**Answer: AB**

#### NEW QUESTION 7

- (Topic 1)

You have been asked to leverage Amazon VPC BC2 and SOS to implement an application that submits and receives millions of messages per second to a message queue. You want to ensure your application has sufficient bandwidth between your EC2 instances and SQS Which option will provide the most scalable solution for communicating between the application and SQS?

- A. Ensure the application instances are properly configured with an Elastic Load Balancer
- B. Ensure the application instances are launched in private subnets with the EBS-optimized option enabled
- C. Ensure the application instances are launched in public subnets with the associate-public-IP-address=true option enabled
- D. Launch application instances in private subnets with an Auto Scaling group and Auto Scaling triggers configured to watch the SQS queue size

**Answer: B**

**Explanation:**

Reference:

<http://www.cardinalpath.com/autoscaling-your-website-with-amazon-web-services-part-2/>

**NEW QUESTION 8**

- (Topic 1)

You have a server with a 500GB Amazon EBS data volume. The volume is 80% full. You need to back up the volume at regular intervals and be able to re-create the volume in a new Availability Zone in the shortest time possible. All applications using the volume can be paused for a period of a few minutes with no discernible user impact.

Which of the following backup methods will best fulfill your requirements?

- A. Take periodic snapshots of the EBS volume
- B. Use a third party Incremental backup application to back up to Amazon Glacier
- C. Periodically back up all data to a single compressed archive and archive to Amazon S3 using a parallelized multi-part upload
- D. Create another EBS volume in the second Availability Zone attach it to the Amazon EC2 instance, and use a disk manager to mirror the two disks

**Answer: D**

**Explanation:**

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-creating-snapshot.html>

**NEW QUESTION 9**

- (Topic 1)

You are designing a system that has a Bastion host. This component needs to be highly available without human intervention.

Which of the following approaches would you select?

- A. Run the bastion on two instances one in each AZ
- B. Run the bastion on an active Instance in one AZ and have an AMI ready to boot up in the event of failure
- C. Configure the bastion instance in an Auto Scaling group Specify the Auto Scaling group to include multiple AZs but have a min-size of 1 and max-size of 1
- D. Configure an ELB in front of the bastion instance

**Answer: C**

**NEW QUESTION 10**

- (Topic 1)

When assessing an organization's use of AWS API access credentials which of the following three credentials should be evaluated?

Choose 3 answers

- A. Key pairs
- B. Console passwords
- C. Access keys
- D. Signing certificates
- E. Security Group memberships

**Answer: ACD**

**Explanation:**

Reference:

[http://media.amazonwebservices.com/AWS\\_Operational\\_Checklists.pdf](http://media.amazonwebservices.com/AWS_Operational_Checklists.pdf)

**NEW QUESTION 10**

- (Topic 1)

You run a web application where web servers on EC2 Instances are in an Auto Scaling group. Monitoring over the last 6 months shows that 6 web servers are necessary to handle the minimum load. During the day up to 12 servers are needed. Five to six days per year, the number of web servers required might go up to 15.

What would you recommend to minimize costs while being able to provide high availability?

- A. 6 Reserved instances (heavy utilization). 6 Reserved instances (medium utilization), rest covered by On-Demand instances
- B. 6 Reserved instances (heavy utilization). 6 On-Demand instances, rest covered by Spot Instances
- C. 6 Reserved instances (heavy utilization). 6 Spot instances, rest covered by On-Demand instances
- D. 6 Reserved instances (heavy utilization). 6 Reserved instances (medium utilization) rest covered by Spot instances

**Answer: B**

**NEW QUESTION 13**

- (Topic 1)

You are tasked with the migration of a highly trafficked Node JS application to AWS. In order to comply with organizational standards, Chef recipes must be used to configure the application servers that host this application and to support application lifecycle events.

Which deployment option meets these requirements while minimizing administrative burden?

- A. Create a new stack within Opsworks, add the appropriate layers to the stack and deploy the application
- B. Create a new application within Elastic Beanstalk and deploy this application to a new environment
- C. Launch a Node JS server from a community AMI and manually deploy the application to the launched EC2 instance
- D. Launch and configure Chef Server on an EC2 instance and leverage the AWS CLI to launch application servers and configure those instances using Chef

**Answer: B**

**Explanation:**

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.html>

**NEW QUESTION 17**

- (Topic 1)

What is a placement group?

- A. A collection of Auto Scaling groups in the same Region
- B. Feature that enables EC2 instances to interact with each other via high bandwidth, low latency connections
- C. A collection of Elastic Load Balancers in the same Region or Availability Zone
- D. A collection of authorized Cloud Front edge locations for a distribution

**Answer:** B

**Explanation:**

Reference:

<http://aws.amazon.com/ec2/faqs/>

**NEW QUESTION 22**

- (Topic 1)

When an EC2 EBS-backed (EBS root) instance is stopped, what happens to the data on any ephemeral store volumes?

- A. Data will be deleted and will no longer be accessible
- B. Data is automatically saved in an EBS volume
- C. Data is automatically saved as an EBS snapshot
- D. Data is unavailable until the instance is restarted

**Answer:** D

**NEW QUESTION 24**

- (Topic 1)

You are creating an Auto Scaling group whose Instances need to insert a custom metric into CloudWatch.

Which method would be the best way to authenticate your CloudWatch PUT request?

- A. Create an IAM role with the PutMetricData permission and modify the Auto Scaling launch configuration to launch instances in that role
- B. Create an IAM user with the PutMetricData permission and modify the Auto Scaling launch configuration to inject the user's credentials into the instance User Data
- C. Modify the appropriate CloudWatch metric policies to allow the PutMetricData permission to instances from the Auto Scaling group
- D. Create an IAM user with the PutMetricData permission and put the credentials in a private repository and have applications on the server pull the credentials as needed

**Answer:** A

**NEW QUESTION 25**

- (Topic 1)

If you want to launch Amazon Elastic Compute Cloud (EC2) Instances and assign each Instance a predetermined private IP address you should:

- A. Assign a group or sequential Elastic IP address to the instances
- B. Launch the instances in a Placement Group
- C. Launch the instances in the Amazon virtual Private Cloud (VPC).
- D. Use standard EC2 instances since each instance gets a private Domain Name Service (DNS) already
- E. Launch the Instance from a private Amazon Machine image (AMI)

**Answer:** C

**Explanation:**

Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-ip-addressing.html>

**NEW QUESTION 26**

- (Topic 1)

You have started a new job and are reviewing your company's infrastructure on AWS. You notice one web application where they have an Elastic Load Balancer (ELB) in front of web instances in an Auto Scaling Group. When you check the metrics for the ELB in CloudWatch, you see four healthy instances in Availability Zone (AZ) A and zero in AZ B. There are zero unhealthy instances.

What do you need to fix to balance the instances across AZs?

- A. Set the ELB to only be attached to another AZ
- B. Make sure Auto Scaling is configured to launch in both AZs
- C. Make sure your AMI is available in both AZs
- D. Make sure the maximum size of the Auto Scaling Group is greater than 4

**Answer:** B

**NEW QUESTION 29**

- (Topic 1)

You are using ElastiCache Memcached to store session state and cache database queries in your infrastructure. You notice in CloudWatch that Evictions and GetMisses are both very high.

What two actions could you take to rectify this?



Choose 2 answers

- A. Increase the number of nodes in your cluster
- B. Tweak the max\_item\_size parameter
- C. Shrink the number of nodes in your cluster
- D. Increase the size of the nodes in the duster

**Answer:** BD

#### NEW QUESTION 31

- (Topic 1)

An organization's security policy requires multiple copies of all critical data to be replicated across at least a primary and backup data center. The organization has decided to store some critical data on Amazon S3.

Which option should you implement to ensure this requirement is met?

- A. Use the S3 copy API to replicate data between two S3 buckets in different regions
- B. You do not need to implement anything since S3 data is automatically replicated between regions
- C. Use the S3 copy API to replicate data between two S3 buckets in different facilities within an AWS Region
- D. You do not need to implement anything since S3 data is automatically replicated between multiple facilities within an AWS Region

**Answer:** D

#### NEW QUESTION 36

- (Topic 1)

Which services allow the customer to retain full administrative privileges of the underlying EC2 instances?

Choose 2 answers

- A. Amazon Elastic Map Reduce
- B. Elastic Load Balancing
- C. AWS Elastic Beanstalk
- D. Amazon ElastiCache
- E. Amazon Relational Database service

**Answer:** AC

#### NEW QUESTION 40

- (Topic 1)

You are attempting to connect to an instance in Amazon VPC without success. You have already verified that the VPC has an Internet Gateway (IGW) the instance has an associated Elastic IP (EIP) and correct security group rules are in place.

Which VPC component should you evaluate next?

- A. The configuration of a NAT instance
- B. The configuration of the Routing Table
- C. The configuration of the Internet Gateway (IGW)
- D. The configuration of SRC/DST checking

**Answer:** B

#### Explanation:

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosF orVPC.html>

#### NEW QUESTION 42

- (Topic 1)

You have been asked to automate many routine systems administrator backup and recovery activities. Your current plan is to leverage AWS-managed solutions as much as possible and automate the rest with the AWS CLI and scripts.

Which task would be best accomplished with a script?

- A. Creating daily EBS snapshots with a monthly rotation of snapshots
- B. Creating daily RDS snapshots with a monthly rotation of snapshots
- C. Automatically detect and stop unused or underutilized EC2 instances
- D. Automatically add Auto Scaled EC2 instances to an Amazon Elastic Load Balancer

**Answer:** A

#### NEW QUESTION 47

- (Topic 1)

You have a Linux EC2 web server instance running inside a VPC. The instance is in a public subnet and has an EIP associated with it so you can connect to it over the Internet via HTTP or SSH. The instance was also fully accessible when you last logged in via SSH, and was also serving web requests on port 80.

Now you are not able to SSH into the host nor does it respond to web requests on port 80 that were working fine last time you checked. You have double-checked that all networking configuration parameters (security groups, route tables, IGW/EIP, NACLs, etc) are properly configured (and you haven't made any changes to those anyway since you were last able to reach the instance). You look at the EC2 console and notice that system status check shows "impaired."

Which should be your next step in troubleshooting and attempting to get the instance back to a healthy state so that you can log in again?

- A. Stop and start the instance so that it will be able to be redeployed on a healthy host system that most likely will fix the "impaired" system status
- B. Reboot your instance so that the operating system will have a chance to boot in a clean healthy state that most likely will fix the "impaired" system status
- C. Add another dynamic private IP address to the instance and try to connect via the new path, since the networking stack of the OS may be locked up causing the "impaired" system status

- D. Add another Elastic Network Interface to the instance and try to connect via that new path since the networking stack of the OS may be locked up causing the "impaired" system status
- E. un-map and then re-map the EIP to the instance, since the IGWVNat gateway may not be working properly, causing the "impaired" system status

**Answer:** A

#### NEW QUESTION 51

- (Topic 2)

A user is accessing RDS from an application. The user has enabled the Multi AZ feature with the MS SQL RDS DB. During a planned outage how will AWS ensure that a switch from DB to a standby replica will not affect access to the application?

- A. RDS will have an internal IP which will redirect all requests to the new DB
- B. RDS uses DNS to switch over to stand by replica for seamless transition
- C. The switch over changes Hardware so RDS does not need to worry about access
- D. RDS will have both the DBs running independently and the user has to manually switch over

**Answer:** B

#### Explanation:

In the event of a planned or unplanned outage of a DB instance, Amazon RDS automatically switches to a standby replica in another Availability Zone if the user has enabled Multi AZ. The automatic failover mechanism simply changes the DNS record of the DB instance to point to the standby DB instance. As a result, the user will need to re-establish any existing connections to the DB instance. However, as the DNS is the same, the application can access DB seamlessly.

#### NEW QUESTION 54

- (Topic 2)

A user is trying to connect to a running EC2 instance using SSH. However, the user gets a connection time out error. Which of the below mentioned options is not a possible reason for rejection?

- A. The access key to connect to the instance is wrong
- B. The security group is not configured properly
- C. The private key used to launch the instance is not correct
- D. The instance CPU is heavily loaded

**Answer:** A

#### Explanation:

If the user is trying to connect to a Linux EC2 instance and receives the connection time out error the probable reasons are: Security group is not configured with the SSH port The private key pair is not right The user name to login is wrong The instance CPU is heavily loaded, so it does not allow more connections

#### NEW QUESTION 57

- (Topic 2)

A user is planning to use AWS Cloudformation. Which of the below mentioned functionalities does not help him to correctly understand Cloudfromation?

- A. Cloudformation follows the DevOps model for the creation of Dev & Test
- B. AWS Cloudfromation does not charge the user for its service but only charges for the AWS resources created with it
- C. Cloudformation works with a wide variety of AWS services, such as EC2, EBS, VPC, IAM, S3, RDS, ELB, etc
- D. CloudFormation provides a set of application bootstrapping scripts which enables the user to install Software

**Answer:** A

#### Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. It supports a wide variety of AWS services, such as EC2, EBS, AS, ELB, RDS, VPC, etc. It also provides application bootstrapping scripts which enable the user to install software packages or create folders. It is free of the cost and only charges the user for the services created with it. The only challenge is that it does not follow any model, such as DevOps; instead customers can define templates and use them to provision and manage the AWS resources in an orderly way.

#### NEW QUESTION 58

- (Topic 2)

You are managing the AWS account of a big organization. The organization has more than 1000+ employees and they want to provide access to the various services to most of the employees. Which of the below mentioned options is the best possible solution in this case?

- A. The user should create a separate IAM user for each employee and provide access to them as per the policy
- B. The user should create an IAM role and attach STS with the rol
- C. The user should attach that role to the EC2 instance and setup AWS authentication on that server
- D. The user should create IAM groups as per the organization's departments and add each user to the group for better access control
- E. Attach an IAM role with the organization's authentication service to authorize each user for various AWS services

**Answer:** D

#### Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user is managing an AWS account for an organization that already has an identity system, such as the login system for the corporate network (SSO.. In this case, instead of creating individual IAM users or groups for each user who need AWS access, it may be more practical to use a proxy server to translate the user identities from the organization network into the temporary AWS security credentials. This proxy server will attach an IAM role to the user after authentication.

**NEW QUESTION 61**

- (Topic 2)

A user has configured an Auto Scaling group with ELB. The user has enabled detailed CloudWatch monitoring on Auto Scaling. Which of the below mentioned statements will help the user understand the functionality better?

- A. It is not possible to setup detailed monitoring for Auto Scaling
- B. In this case, Auto Scaling will send data every minute and will charge the user extra
- C. Detailed monitoring will send data every minute without additional charges
- D. Auto Scaling sends data every minute only and does not charge the user

**Answer:** B

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Auto Scaling includes 7 metrics and 1 dimension, and sends data to CloudWatch every 5 minutes by default. The user can enable detailed monitoring for Auto Scaling, which sends data to CloudWatch every minute. However, this will have some extra-costs.

**NEW QUESTION 66**

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 with only a private subnet and VPN connection using the VPC wizard. The user wants to connect to the instance in a private subnet over SSH. How should the user define the security rule for SSH?

- A. Allow Inbound traffic on port 22 from the user's network
- B. The user has to create an instance in EC2 Classic with an elastic IP and configure the security group of a private subnet to allow SSH from that elastic IP
- C. The user can connect to a instance in a private subnet using the NAT instance
- D. Allow Inbound traffic on port 80 and 22 to allow the user to connect to a private subnet over the Internet

**Answer:** A

**Explanation:**

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, the user can setup a case with a VPN only subnet (private. which uses VPN access to connect with his data centre. When the user has configured this setup with Wizard, all network connections to the instances in the subnet will come from his data centre. The user has to configure the security group of the private subnet which allows the inbound traffic on SSH (port 22. from the data centre's network range.

**NEW QUESTION 69**

- (Topic 2)

A user has setup an EBS backed instance and a CloudWatch alarm when the CPU utilization is more than 65%. The user has setup the alarm to watch it for 5 periods of 5 minutes each. The CPU utilization is 60% between 9 AM to 6 PM. The user has stopped the EC2 instance for 15 minutes between 11 AM to 11:15 AM. What will be the status of the alarm at 11:30 AM?

- A. Alarm
- B. OK
- C. Insufficient Data
- D. Error

**Answer:** B

**Explanation:**

Amazon CloudWatch alarm watches a single metric over a time period the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The state of the alarm will be OK for the whole day. When the user stops the instance for three periods the alarm may not receive the data

**NEW QUESTION 74**

- (Topic 2)

An organization is planning to create 5 different AWS accounts considering various security requirements. The organization wants to use a single payee account by using the consolidated billing option. Which of the below mentioned statements is true with respect to the above information?

- A. Master (Payee
- B. account will get only the total bill and cannot see the cost incurred by each account
- C. Master (Payee
- D. account can view only the AWS billing details of the linked accounts
- E. It is not recommended to use consolidated billing since the payee account will have access to the linked accounts
- F. Each AWS account needs to create an AWS billing policy to provide permission to the payee account

**Answer:** B

**Explanation:**

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account. The payee account will not have any other access than billing data of linked accounts.



**NEW QUESTION 75**

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created public and VPN only subnets along with hardware VPN access to connect to the user's datacenter. The user wants to make so that all traffic coming to the public subnet follows the organization's proxy policy. How can the user make this happen?

- A. Setting up a NAT with the proxy protocol and configure that the public subnet receives traffic from NAT
- B. Settin up a proxy policy in the internet gateway connected with the public subnet
- C. It is not possible to setup the proxy policy for a public subnet
- D. Setting the route table and security group of the public subnet which receives traffic from a virtual private gateway

**Answer:** D

**Explanation:**

The user can create subnets within a VPC. If the user wants to connect to VPC from his own data centre, he can setup public and VPN only subnets which uses hardware VPN access to connect with his data centre. When the user has configured this setup, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. By default the internet traffic of the VPN subnet is routed to a virtual private gateway while the internet traffic of the public subnet is routed through the internet gateway. The user can set up the route and security group rules. These rules enable the traffic to come from the organization's network over the virtual private gateway to the public subnet to allow proxy settings on that public subnet.

**NEW QUESTION 79**

- (Topic 2)

A sys admin is maintaining an application on AWS. The application is installed on EC2 and user has configured ELB and Auto Scaling. Considering future load increase, the user is planning to launch new servers proactively so that they get registered with ELB. How can the user add these instances with Auto Scaling?

- A. Increase the desired capacity of the Auto Scaling group
- B. Increase the maximum limit of the Auto Scaling group
- C. Launch an instance manually and register it with ELB on the fly
- D. Decrease the minimum limit of the Auto Scaling grou

**Answer:** A

**Explanation:**

A user can increase the desired capacity of the Auto Scaling group and Auto Scaling will launch a new instance as per the new capacity. The newly launched instances will be registered with ELB if Auto Scaling group is configured with ELB. If the user decreases the minimum size the instances will be removed from Auto Scaling. Increasing the maximum size will not add instances but only set the maximum instance cap.

**NEW QUESTION 83**

- (Topic 2)

A user has created an ELB with three instances. How many security groups will ELB create by default?

- A. 3
- B. 5
- C. 2
- D. 1

**Answer:** C

**Explanation:**

Elastic Load Balancing provides a special Amazon EC2 source security group that the user can use to ensure that back-end EC2 instances receive traffic only from Elastic Load Balancing. This feature needs two security groups: the source security group and a security group that defines the ingress rules for the back-end instances. To ensure that traffic only flows between the load balancer and the back-end instances, the user can add or modify a rule to the back-end security group which can limit the ingress traffic. Thus, it can come only from the source security group provided by Elastic load Balancing.

**NEW QUESTION 88**

- (Topic 2)

A user has created a photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Glacier
- B. AWS Elastic Transcoder
- C. AWS Simple Notification Service
- D. AWS Simple Queue Service

**Answer:** D

**Explanation:**

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

**NEW QUESTION 89**

- (Topic 2)

A user is planning to evaluate AWS for their internal use. The user does not want to incur any charge on his account during the evaluation. Which of the below

mentioned AWS services would incur a charge if used?

- A. AWS S3 with 1 GB of storage
- B. AWS micro instance running 24 hours daily
- C. AWS ELB running 24 hours a day
- D. AWS PIOPS volume of 10 GB size

**Answer:** D

**Explanation:**

AWS is introducing a free usage tier for one year to help the new AWS customers get started in Cloud. The free tier can be used for anything that the user wants to run in the Cloud. AWS offers a handful of AWS services as a part of this which includes 750 hours of free micro instances and 750 hours of ELB. It includes the AWS S3 of 5 GB and AWS EBS general purpose volume upto 30 GB. PIOPS is not part of free usage tier.

#### NEW QUESTION 92

- (Topic 2)

A user has setup a billing alarm using CloudWatch for \$200. The usage of AWS exceeded \$200 after some days. The user wants to increase the limit from \$200 to \$400? What should the user do?

- A. Create a new alarm of \$400 and link it with the first alarm
- B. It is not possible to modify the alarm once it has crossed the usage limit
- C. Update the alarm to set the limit at \$400 instead of \$200
- D. Create a new alarm for the additional \$200 amount

**Answer:** C

**Explanation:**

AWS CloudWatch supports enabling the billing alarm on the total AWS charges. The estimated charges are calculated and sent several times daily to CloudWatch in the form of metric data. This data will be stored for 14 days. This data also includes the estimated charges for every service in AWS used by the user, as well as the estimated overall AWS charges. If the user wants to increase the limit, the user can modify the alarm and specify a new threshold.

#### NEW QUESTION 93

- (Topic 2)

A user has launched an EC2 instance from an instance store backed AMI. The infrastructure team wants to create an AMI from the running instance. Which of the below mentioned steps will not be performed while creating the AMI?

- A. Define the AMI launch permissions
- B. Upload the bundled volume
- C. Register the AMI
- D. Bundle the volume

**Answer:** A

**Explanation:**

When the user has launched an EC2 instance from an instance store backed AMI, it will need to follow certain steps, such as “Bundling the root volume”, “Uploading the bundled volume” and “Register the AMI”. Once the AMI is created the user can setup the launch permission. However, it is not required to setup during the launch.

#### NEW QUESTION 98

- (Topic 2)

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department’s employees

**Answer:** A

**Explanation:**

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

#### NEW QUESTION 102

- (Topic 2)

A root AWS account owner is trying to understand various options to set the permission to AWS S3. Which of the below mentioned options is not the right option to grant permission for S3?

- A. User Access Policy
- B. S3 Object Access Policy
- C. S3 Bucket Access Policy
- D. S3 ACL

**Answer:** B

**Explanation:**

Amazon S3 provides a set of operations to work with the Amazon S3 resources. Managing S3 resource access refers to granting others permissions to work with S3. There are three ways the root account owner can define access with S3: S3 ACL: The user can use ACLs to grant basic read/write permissions to other AWS accounts. S3 Bucket Policy: The policy is used to grant other AWS accounts or IAM users permissions for the bucket and the objects in it. User Access Policy: Define an IAM user and assign him the IAM policy which grants him access to S3.

#### NEW QUESTION 103

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25. The user is trying to create the private subnet with CIDR 20.0.0.128/25. Which of the below mentioned statements is true in this scenario?

- A. It will not allow the user to create the private subnet due to a CIDR overlap
- B. It will allow the user to create a private subnet with CIDR as 20.0.0.128/25
- C. This statement is wrong as AWS does not allow CIDR 20.0.0.0/25
- D. It will not allow the user to create a private subnet due to a wrong CIDR range

**Answer:** B

**Explanation:**

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. The CIDR block of a subnet can be the same as the CIDR block for the VPC (for a single subnet in the VPC., or a subset (to enable multiple subnets.. If the user creates more than one subnet in a VPC, the CIDR blocks of the subnets must not overlap. Thus, in this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255.. The user can break this CIDR block into two subnets, each supporting 128 IP addresses. One subnet uses the CIDR block 20.0.0.0/25 (for addresses 20.0.0.0 - 20.0.0.127. and the other uses the CIDR block 20.0.0.128/25 (for addresses 20.0.0.128 - 20.0.0.255..

#### NEW QUESTION 105

- (Topic 2)

A user has configured Elastic Load Balancing by enabling a Secure Socket Layer (SSL. negotiation configuration known as a Security Policy. Which of the below mentioned options is not part of this secure policy while negotiating the SSL connection between the user and the client?

- A. SSL Protocols
- B. Client Order Preference
- C. SSL Ciphers
- D. Server Order Preference

**Answer:** B

**Explanation:**

Elastic Load Balancing uses a Secure Socket Layer (SSL. negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. A security policy is a combination of SSL Protocols, SSL Ciphers, and the Server Order Preference option.

#### NEW QUESTION 110

- (Topic 2)

A user has setup connection draining with ELB to allow in-flight requests to continue while the instance is being deregistered through Auto Scaling. If the user has not specified the draining time, how long will ELB allow inflight requests traffic to continue?

- A. 600 seconds
- B. 3600 seconds
- C. 300 seconds
- D. 0 seconds

**Answer:** C

**Explanation:**

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can specify a maximum time (3600 seconds. for the load balancer to keep the connections alive before reporting the instance as deregistered. If the user does not specify the maximum timeout period, by default, the load balancer will close the connections to the deregistering instance after 300 seconds.

#### NEW QUESTION 114

- (Topic 2)

A user has created an S3 bucket which is not publicly accessible. The bucket is having thirty objects which are also private. If the user wants to make the objects public, how can he configure this with minimal efforts?

- A. The user should select all objects from the console and apply a single policy to mark them public
- B. The user can write a program which programmatically makes all objects public using S3 SDK
- C. Set the AWS bucket policy which marks all objects as public
- D. Make the bucket ACL as public so it will also mark all objects as public

**Answer:** C

**Explanation:**

A system admin can grant permission of the S3 objects or buckets to any user or make the objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket.

**NEW QUESTION 119**

- (Topic 2)

A user is checking the CloudWatch metrics from the AWS console. The user notices that the CloudWatch data is coming in UTC. The user wants to convert the data to a local time zone. How can the user perform this?

- A. In the CloudWatch dashboard the user should set the local timezone so that CloudWatch shows the data only in the local time zone
- B. In the CloudWatch console select the local timezone under the Time Range tab to view the data as per the local timezone
- C. The CloudWatch data is always in UTC; the user has to manually convert the data
- D. The user should have send the local timezone while uploading the data so that CloudWatch will show the data only in the local timezone

**Answer:** B

**Explanation:**

If the user is viewing the data inside the CloudWatch console, the console provides options to filter values either using the relative period, such as days/hours or using the Absolute tab where the user can provide data with a specific date and time. The console also provides the option to search using the local timezone under the time range caption in the console because the time range tab allows the user to change the time zone.

**NEW QUESTION 121**

- (Topic 2)

A customer is using AWS for Dev and Test. The customer wants to setup the Dev environment with Cloudformation. Which of the below mentioned steps are not required while using Cloudformation?

- A. Create a stack
- B. Configure a service
- C. Create and upload the template
- D. Provide the parameters configured as part of the template

**Answer:** B

**Explanation:**

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. AWS CloudFormation introduces two concepts: the template and the stack. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. The stack is a collection of AWS resources which are created and managed as a single unit when AWS CloudFormation instantiates a template. While creating a stack, the user uploads the template and provides the data for the parameters if required.

**NEW QUESTION 125**

- (Topic 2)

A user has created a web application with Auto Scaling. The user is regularly monitoring the application and he observed that the traffic is highest on Thursday and Friday between 8 AM to 6 PM. What is the best solution to handle scaling in this case?

- A. Add a new instance manually by 8 AM Thursday and terminate the same by 6 PM Friday
- B. Schedule Auto Scaling to scale up by 8 AM Thursday and scale down after 6 PM on Friday
- C. Schedule a policy which may scale up every day at 8 AM and scales down by 6 PM
- D. Configure a batch process to add a instance by 8 AM and remove it by Friday 6 PM

**Answer:** B

**Explanation:**

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. In this case the load increases by Thursday and decreases by Friday. Thus, the user can setup the scaling activity based on the predictable traffic patterns of the web application using Auto Scaling scale by Schedule.

**NEW QUESTION 126**

- (Topic 2)

A sys admin is trying to understand the Auto Scaling activities. Which of the below mentioned processes is not performed by Auto Scaling?

- A. Reboot Instance
- B. Schedule Actions
- C. Replace Unhealthy
- D. Availability Zone Balancing

**Answer:** A

**Explanation:**

There are two primary types of Auto Scaling processes: Launch and Terminate, which launch or terminate instances, respectively. Some other actions performed by Auto Scaling are:

AddToLoadbalancer,  
AlarmNotification, HealthCheck, AZRebalance, ReplaceUnHealthy, and ScheduledActions.



**NEW QUESTION 127**

- (Topic 2)

A user wants to make so that whenever the CPU utilization of the AWS EC2 instance is above 90%, the redlight of his bedroom turns on. Which of the below mentioned AWS services is helpful for this purpose?

- A. AWS CloudWatch + AWS SES
- B. AWS CloudWatch + AWS SNS
- C. Non
- D. It is not possible to configure the light with the AWS infrastructure services
- E. AWS CloudWatch and a dedicated software turning on the light

**Answer:** B

**Explanation:**

Amazon Simple Notification Service (Amazon SNS. is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS. queues or to any HTTP endpoint. The user can configure some sensor devices at his home which receives data on the HTTP end point (REST calls. and turn on the red light. The user can configure the CloudWatch alarm to send a notification to the AWS SNS HTTP end point (the sensor device. and it will turn the light red when there is an alarm condition.

**NEW QUESTION 132**

- (Topic 2)

A user has created an ELB with Auto Scaling. Which of the below mentioned offerings from ELB helps the user to stop sending new requests traffic from the load balancer to the EC2 instance when the instance is being deregistered while continuing in-flight requests?

- A. ELB sticky session
- B. ELB deregistration check
- C. ELB connection draining
- D. ELB auto registration Off

**Answer:** C

**Explanation:**

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served.

**NEW QUESTION 133**

- (Topic 2)

A user has launched a large EBS backed EC2 instance in the US-East-1a region. The user wants to achieve Disaster Recovery (DR. for that instance by creating another small instance in Europe. How can the user achieve DR?

- A. Copy the running instance using the “Instance Copy” command to the EU region
- B. Create an AMI of the instance and copy the AMI to the EU regio
- C. Then launch the instance from the EU AMI
- D. Copy the instance from the US East region to the EU region
- E. Use the “Launch more like this” option to copy the instance from one region to another

**Answer:** B

**Explanation:**

To launch an EC2 instance it is required to have an AMI in that region. If the AMI is not available in that region, then create a new AMI or use the copy command to copy the AMI from one region to the other region.

**NEW QUESTION 137**

- (Topic 2)

A user has configured CloudWatch monitoring on an EBS backed EC2 instance. If the user has not attached any additional device, which of the below mentioned metrics will always show a 0 value?

- A. DiskReadBytes
- B. NetworkIn
- C. NetworkOut
- D. CPUUtilization

**Answer:** A

**Explanation:**

CloudWatch is used to monitor AWS as the well custom services. For EC2 when the user is monitoring the EC2 instances, it will capture the 7 Instance level and 3 system check parameters for the EC2 instance. Since this is an EBS backed instance, it will not have ephemeral storage attached to it. Out of the 7 EC2 metrics, the 4 metrics DiskReadOps, DiskWriteOps, DiskReadBytes and DiskWriteBytes are disk related data and available only when there is ephemeral storage attached to an instance. For an EBS backed instance without any additional device, this data will be 0.

**NEW QUESTION 138**

- (Topic 2)

A user has created numerous EBS volumes. What is the general limit for each AWS account for the maximum number of EBS volumes that can be created?

- A. 10000



- B. 5000
- C. 100
- D. 1000

**Answer:** B

**Explanation:**

A user can attach multiple EBS volumes to the same instance within the limits specified by his AWS account. Each AWS account has a limit on the number of Amazon EBS volumes that the user can create, and the total storage available. The default limit for the maximum number of volumes that can be created is 5000.

#### NEW QUESTION 139

- (Topic 2)

An organization has created 50 IAM users. The organization has introduced a new policy which will change the access of an IAM user. How can the organization implement this effectively so that there is no need to apply the policy at the individual user level?

- A. Use the IAM groups and add users as per their role to different groups and apply policy to group
- B. The user can create a policy and apply it to multiple users in a single go with the AWS CLI
- C. Add each user to the IAM role as per their organization role to achieve effective policy setup
- D. Use the IAM role and implement access at the role level

**Answer:** A

**Explanation:**

With AWS IAM, a group is a collection of IAM users. A group allows the user to specify permissions for a collection of users, which can make it easier to manage the permissions for those users. A group helps an organization manage access in a better way; instead of applying at the individual level, the organization can apply at the group level which is applicable to all the users who are a part of that group.

#### NEW QUESTION 142

- (Topic 2)

An organization, which has the AWS account ID as 999988887777, has created 50 IAM users. All the users are added to the same group cloudacademy. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use?

- A. [https:// 999988887777.signin.aws.amazon.com/console/](https://999988887777.signin.aws.amazon.com/console/)
- B. [https:// signin.aws.amazon.com/cloudacademy/](https://signin.aws.amazon.com/cloudacademy/)
- C. [https:// cloudacademy.signin.aws.amazon.com/999988887777/console/](https://cloudacademy.signin.aws.amazon.com/999988887777/console/)
- D. [https:// 999988887777.aws.amazon.com/ cloudacademy/](https://999988887777.aws.amazon.com/cloudacademy/)

**Answer:** A

**Explanation:**

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be [https:// AWS\\_Account\\_ID.signin.aws.amazon.com/console/](https://AWS_Account_ID.signin.aws.amazon.com/console/). It uses only the AWS account ID and does not depend on the group or user ID.

#### NEW QUESTION 144

- (Topic 2)

An organization is using AWS since a few months. The finance team wants to visualize the pattern of AWS spending. Which of the below AWS tool will help for this requirement?

- A. AWS Cost Manager
- B. AWS Cost Explorer
- C. AWS CloudWatch
- D. AWS Consolidated Billing

**Answer:** B

**Explanation:**

The AWS Billing and Cost Management console includes the Cost Explorer tool for viewing AWS cost data as a graph. It does not charge extra to user for this service. With Cost Explorer the user can filter graphs using resource tags or with services in AWS. If the organization is using Consolidated Billing it helps generate report based on linked accounts. This will help organization to identify areas that require further inquiry. The organization can view trends and use that to understand spend and to predict future costs.

#### NEW QUESTION 148

- (Topic 2)

A user has configured an Auto Scaling group with ELB. The user has enabled detailed CloudWatch monitoring on Elastic Load balancing. Which of the below mentioned statements will help the user understand this functionality better?

- A. ELB sends data to CloudWatch every minute only and does not charge the user
- B. ELB will send data every minute and will charge the user extra
- C. ELB is not supported by CloudWatch
- D. It is not possible to setup detailed monitoring for ELB

**Answer:** A

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Elastic Load Balancing includes 10 metrics and 2 dimensions, and sends data to CloudWatch every minute. This does not cost extra.

**NEW QUESTION 152**

- (Topic 2)

A user has setup Auto Scaling with ELB on the EC2 instances. The user wants to configure that whenever the CPU utilization is below 10%, Auto Scaling should remove one instance. How can the user configure this?

- A. The user can get an email using SNS when the CPU utilization is less than 10%. The user can use the desired capacity of Auto Scaling to remove the instance
- B. Use CloudWatch to monitor the data and Auto Scaling to remove the instances using scheduled actions
- C. Configure CloudWatch to send a notification to Auto Scaling Launch configuration when the CPU utilization is less than 10% and configure the Auto Scaling policy to remove the instance
- D. Configure CloudWatch to send a notification to the Auto Scaling group when the CPU Utilization is less than 10% and configure the Auto Scaling policy to remove the instance

**Answer:** D

**Explanation:**

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup to receive a notification on the Auto Scaling group with the CloudWatch alarm when the CPU utilization is below a certain threshold. The user can configure the Auto Scaling policy to take action for removing the instance. When the CPU utilization is below 10% CloudWatch will send an alarm to the Auto Scaling group to execute the policy.

**NEW QUESTION 154**

- (Topic 2)

An organization has created 50 IAM users. The organization wants that each user can change their password but cannot change their access keys. How can the organization achieve this?

- A. The organization has to create a special password policy and attach it to each user
- B. The root account owner has to use CLI which forces each IAM user to change their password on first login
- C. By default each IAM user can modify their passwords
- D. The root account owner can set the policy from the IAM console under the password policy screen

**Answer:** D

**Explanation:**

With AWS IAM, organizations can use the AWS Management Console to display, create, change or delete a password policy. As a part of managing the password policy, the user can enable all users to manage their own passwords. If the user has selected the option which allows the IAM users to modify their password, he does not need to set a separate policy for the users. This option in the AWS console allows changing only the password.

**NEW QUESTION 159**

- (Topic 2)

A user is launching an instance. He is on the “Tag the instance” screen. Which of the below mentioned information will not help the user understand the functionality of an AWS tag?

- A. Each tag will have a key and value
- B. The user can apply tags to the S3 bucket
- C. The maximum value of the tag key length is 64 unicode characters
- D. AWS tags are used to find the cost distribution of various resources

**Answer:** C

**Explanation:**

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV file) with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. The maximum size of a tag key is 128 unicode characters.

**NEW QUESTION 164**

- (Topic 2)

A user has setup an RDS DB with Oracle. The user wants to get notifications when someone modifies the security group of that DB. How can the user configure that?

- A. It is not possible to get the notifications on a change in the security group
- B. Configure SNS to monitor security group changes
- C. Configure event notification on the DB security group
- D. Configure the CloudWatch alarm on the DB for a change in the security group

**Answer:** C

**Explanation:**

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group. If the user is subscribed to a Configuration Change category for a DB security group, he will be notified when the DB security group is changed.

**NEW QUESTION 167**

- (Topic 2)

An organization wants to move to Cloud. They are looking for a secure encrypted database storage option. Which of the below mentioned AWS functionalities helps them to achieve this?

- A. AWS MFA with EBS
- B. AWS EBS encryption
- C. Multi-tier encryption with Redshift
- D. AWS S3 server side storage

**Answer:** B

**Explanation:**

AWS EBS supports encryption of the volume while creating new volumes. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. The data at rest, the I/O as well as all the snapshots of EBS will be encrypted. The encryption occurs on the servers that host the EC2 instances, providing encryption of data as it moves between the EC2 instances and EBS storage. EBS encryption is based on the AES-256 cryptographic algorithm, which is the industry standard

**NEW QUESTION 172**

- (Topic 2)

You are building an online store on AWS that uses SQS to process your customer orders. Your backend system needs those messages in the same sequence the customer orders have been put in. How can you achieve that?

- A. It is not possible to do this with SQS
- B. You can use sequencing information on each message
- C. You can do this with SQS but you also need to use SWF
- D. Messages will arrive in the same order by default

**Answer:** B

**Explanation:**

Amazon SQS is engineered to always be available and deliver messages. One of the resulting tradeoffs is that SQS does not guarantee first in, first out delivery of messages. For many distributed applications, each message can stand on its own, and as long as all messages are delivered, the order is not important. If your system requires that order be preserved, you can place sequencing information in each message, so that you can reorder the messages when the queue returns them.

**NEW QUESTION 174**

- (Topic 2)

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. Email JSON
- B. HTTP
- C. AWS SQS
- D. AWS SES

**Answer:** D

**Explanation:**

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", "and SMS".

**NEW QUESTION 178**

- (Topic 2)

A system admin is planning to setup event notifications on RDS. Which of the below mentioned services will help the admin setup notifications?

- A. AWS SES
- B. AWS Cloudtrail
- C. AWS Cloudwatch
- D. AWS SNS

**Answer:** D

**Explanation:**

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. These notifications can be in any notification form supported by Amazon SNS for an AWS region, such as an email, a text message or a call to an HTTP endpoint

**NEW QUESTION 181**

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25 and a private subnet with CIDR 20.0.0.128/25. The user has launched one instance each in the private and public subnets. Which of the below mentioned options cannot be the correct IP address (private IP) assigned to an instance in the public or private subnet?

- A. 20.0.0.255

- B. 20.0.0.132
- C. 20.0.0.122
- D. 20.0.0.55

**Answer:** A

**Explanation:**

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. In this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255.. The public subnet will have IP addresses between 20.0.0.0 - 20.0.0.127 and the private subnet will have IP addresses between 20.0.0.128 -20.0.0.255. AWS reserves the first four IP addresses and the last IP address in each subnet's CIDR block. These are not available for the user to use. Thus, the instance cannot have an IP address of 20.0.0.255

#### NEW QUESTION 186

- (Topic 2)

A user has launched an EBS backed EC2 instance. What will be the difference while performing the restart or stop/start options on that instance?

- A. For restart it does not charge for an extra hour, while every stop/start it will be charged as a separate hour
- B. Every restart is charged by AWS as a separate hour, while multiple start/stop actions during a single hour will be counted as a single hour
- C. For every restart or start/stop it will be charged as a separate hour
- D. For restart it charges extra only once, while for every stop/start it will be charged as a separate hour

**Answer:** A

**Explanation:**

For an EC2 instance launched with an EBS backed AMI, each time the instance state is changed from stop to start/ running, AWS charges a full instance hour, even if these transitions happen multiple times within a single hour. Anyway, rebooting an instance AWS does not charge a new instance billing hour.

#### NEW QUESTION 188

- (Topic 3)

A user has deployed an application on an EBS backed EC2 instance. For a better performance of application, it requires dedicated EC2 to EBS traffic. How can the user achieve this?

- A. Launch the EC2 instance as EBS dedicated with PIOPS EBS
- B. Launch the EC2 instance as EBS enhanced with PIOPS EBS
- C. Launch the EC2 instance as EBS dedicated with PIOPS EBS
- D. Launch the EC2 instance as EBS optimized with PIOPS EBS

**Answer:** D

**Explanation:**

Any application which has performance sensitive workloads and requires minimal variability with dedicated EC2 to EBS traffic should use provisioned IOPS EBS volumes, which are attached to an EBS-optimized EC2 instance or it should use an instance with 10 Gigabit network connectivity. Launching an instance that is EBSoptimized provides the user with a dedicated connection between the EC2 instance and the EBS volume.

#### NEW QUESTION 189

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. The user has attached an additional instance store volume to the instance. The user wants to create an AMI from the running instance. Will the AMI have the additional instance store volume data?

- A. Yes, the block device mapping will have information about the additional instance store volume
- B. No, since the instance store backed AMI can have only the root volume bundled
- C. It is not possible to attach an additional instance store volume to the existing instance store backed AMI instance
- D. No, since this is ephemeral storage it will not be a part of the AMI

**Answer:** A

**Explanation:**

When the user has launched an EC2 instance from an instance store backed AMI and added an instance store volume to the instance in addition to the root device volume, the block device mapping for the new AMI contains the information for these volumes as well. In addition, the block device mappings for the instances those are launched from the new AMI will automatically contain information for these volumes.

#### NEW QUESTION 192

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling terminate process only for a while. What will happen to the availability zone rebalancing process (AZRebalance. during this period?

- A. Auto Scaling will not launch or terminate any instances
- B. Auto Scaling will allow the instances to grow more than the maximum size
- C. Auto Scaling will keep launching instances till the maximum instance size
- D. It is not possible to suspend the terminate process while keeping the launch active

**Answer:** B

**Explanation:**



Auto Scaling performs various processes, such as Launch, Terminate, Availability Zone Rebalance (AZRebalance. etc. The AZRebalance process type seeks to maintain a balanced number of instances across Availability Zones within a region. If the user suspends the Terminate process, the AZRebalance process can cause the Auto Scaling group to grow up to ten percent larger than the maximum size. This is because Auto Scaling allows groups to temporarily grow larger than the maximum size during rebalancing activities. If Auto Scaling cannot terminate instances, the Auto Scaling group could remain up to ten percent larger than the maximum size until the user resumes the Terminate process type.

**NEW QUESTION 197**

- (Topic 3)

A user is trying to understand the CloudWatch metrics for the AWS services. It is required that the user should first understand the namespace for the AWS services. Which of the below mentioned is not a valid namespace for the AWS services?

- A. AWS/StorageGateway
- B. AWS/CloudTrail
- C. AWS/ElastiCache
- D. AWS/SWF

**Answer:** B

**Explanation:**

Amazon CloudWatch is basically a metrics repository. The AWS product puts metrics into this repository, and the user can retrieve the data or statistics based on those metrics. To distinguish the data for each service, the CloudWatch metric has a namespace. Namespaces are containers for metrics. All AWS services that provide the Amazon CloudWatch data use a namespace string, beginning with "AWS/". All the services which are supported by CloudWatch will have some namespace. CloudWatch does not monitor CloudTrail. Thus, the namespace "AWS/CloudTrail" is incorrect.

**NEW QUESTION 199**

- (Topic 3)

A user is trying to understand the detailed CloudWatch monitoring concept. Which of the below mentioned services does not provide detailed monitoring with CloudWatch?

- A. AWS EMR
- B. AWS RDS
- C. AWS ELB
- D. AWS Route53

**Answer:** A

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Services, such as RDS, EC2, Auto Scaling, ELB, and Route 53 can provide the monitoring data every minute.

**NEW QUESTION 200**

- (Topic 3)

When an EC2 instance is backed by an S3-Dased AML is terminated, what happens to the data on the root volume?

- A. Data is automatically deleted
- B. Data is automatically saved as an EBS snapsho
- C. Data is unavailable until the instance is restarted
- D. Data is automatically saved as an EBS volum

**Answer:** A

**NEW QUESTION 201**

- (Topic 3)

A user has setup a VPC with CIDR 20.0.0.0/16. The VPC has a private subnet (20.0.1.0/24. and a public subnet (20.0.0.0/24.. The user's data centre has CIDR of 20.0.54.0/24 and 20.1.0.0/24. If the private subnet wants to communicate with the data centre, what will happen?

- A. It will allow traffic communication on both the CIDRs of the data centre
- B. It will not allow traffic with data centre on CIDR 20.1.0.0/24 but allows traffic communication on 20.0.54.0/24
- C. It will not allow traffic communication on any of the data centre CIDRs
- D. It will allow traffic with data centre on CIDR 20.1.0.0/24 but does not allow on 20.0.54.0/24

**Answer:** D

**Explanation:**

VPC allows the user to set up a connection between his VPC and corporate or home network data centre. If the user has an IP address prefix in the VPC that overlaps with one of the networks' prefixes, any traffic to the network's prefix is dropped. In this case CIDR 20.0.54.0/24 falls in the VPC's CIDR range of 20.0.0.0/16. Thus, it will not allow traffic on that IP. In the case of 20.1.0.0/24, it does not fall in the VPC's CIDR range. Thus, traffic will be allowed on it.

**NEW QUESTION 206**

- (Topic 3)

A user has launched two EBS backed EC2 instances in the US-East-1a region. The user wants to change the zone of one of the instances. How can the user change it?



- A. The zone can only be modified using the AWS CLI
- B. It is not possible to change the zone of an instance after it is launched
- C. Stop one of the instances and change the availability zone
- D. From the AWS EC2 console, select the Actions - > Change zones and specify the new zone

**Answer:** B

**Explanation:**

With AWS EC2, when a user is launching an instance he can select the availability zone (AZ. at the time of launch. If the zone is not selected, AWS selects it on behalf of the user. Once the instance is launched, the user cannot change the zone of that instance unless he creates an AMI of that instance and launches a new instance from it.

#### NEW QUESTION 211

- (Topic 3)

A system admin wants to add more zones to the existing ELB. The system admin wants to perform this activity from CLI. Which of the below mentioned command helps the system admin to add new zones to the existing ELB?

- A. elb-enable-zones-for-lb
- B. elb-add-zones-for-lb
- C. It is not possible to add more zones to the existing ELB
- D. elb-configure-zones-for-lb

**Answer:** A

**Explanation:**

The user has created an Elastic Load Balancer with the availability zone and wants to add more zones to the existing ELB. The user can do so in two ways: From the console or CLI, add new zones to ELB;

#### NEW QUESTION 213

- (Topic 3)

A user is sending the data to CloudWatch using the CloudWatch API. The user is sending data 90 minutes in the future. What will CloudWatch do in this case?

- A. CloudWatch will accept the data
- B. It is not possible to send data of the future
- C. It is not possible to send the data manually to CloudWatch
- D. The user cannot send data for more than 60 minutes in the future

**Answer:** A

**Explanation:**

With Amazon CloudWatch, each metric data point must be marked with a time stamp. The user can send the data using CLI but the time has to be in the UTC format. If the user does not provide the time, CloudWatch will take the data received time in the UTC timezone. The time stamp sent by the user can be up to two weeks in the past and up to two hours into the future.

#### NEW QUESTION 214

- (Topic 3)

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    }
  ],
  "Principal": {
    "AWS": [
      "*"
    ]
  }
}
```

- A. Denies the server with the IP address 192.166 100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.166 100.188 full access to the "mybucket" bucket

- C. Grants all the servers within the 192 168 100 0/24 subnet full access to the "mybucket" bucket  
D. Grants all the servers within the 192 168 100 188/32 subnet full access to the "mybucket" bucket

**Answer:** C

#### NEW QUESTION 218

- (Topic 3)

An organization has configured two single availability zones. The Auto Scaling groups are configured in separate zones. The user wants to merge the groups such that one group spans across multiple zones. How can the user configure this?

- A. Run the command as-join-auto-scaling-group to join the two groups  
B. Run the command as-update-auto-scaling-group to configure one group to span across zones and delete the other group  
C. Run the command as-copy-auto-scaling-group to join the two groups  
D. Run the command as-merge-auto-scaling-group to merge the groups

**Answer:** B

#### Explanation:

If the user has configured two separate single availability zone Auto Scaling groups and wants to merge them then he should update one of the groups and delete the other one. While updating the first group it is recommended that the user should increase the size of the minimum, maximum and desired capacity as a summation of both the groups.

#### NEW QUESTION 219

- (Topic 3)

A user has launched an RDS MySQL DB with the Multi AZ feature. The user has scheduled the scaling of instance storage during maintenance window. What is the correct order of events during maintenance window?

Perform maintenance on standby  
Promote standby to primary  
Perform maintenance on original primary  
Promote original master back as primary

- A. 1, 2, 3, 4  
B. 1, 2, 3  
C. 2, 3, 1, 4

**Answer:** B

#### Explanation:

Running MySQL on the RDS DB instance as a Multi-AZ deployment can help the user reduce the impact of a maintenance event, as the Amazon will conduct maintenance by following the steps in the below mentioned order: Perform maintenance on standby Promote standby to primary Perform maintenance on original primary, which becomes the new standby.

#### NEW QUESTION 221

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. Which of the below mentioned statements is true in this scenario?

- A. The AWS VPC will automatically create a NAT instance with the micro size  
B. VPC bounds the main route table with a private subnet and a custom route table with a public subnet  
C. The user has to manually create a NAT instance  
D. VPC bounds the main route table with a public subnet and a custom route table with a private subnet

**Answer:** B

#### Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance of a smaller or higher size, respectively. The VPC has an implied router and the VPC wizard updates the main route table used with the private subnet, creates a custom route table and associates it with the public subnet.

#### NEW QUESTION 222

- (Topic 3)

Which method can be used to prevent an IP address block from accessing public objects in an S3 bucket?

- A. Create a bucket policy and apply it to the bucket  
B. Create a NACL and attach it to the VPC of the bucket  
C. Create an ACL and apply it to all objects in the bucket  
D. Modify the IAM policies of any users that would access the bucket

**Answer:** A

#### Explanation:

Reference:  
<http://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

**NEW QUESTION 223**

- (Topic 3)

A user is planning to scale up an application by 8 AM and scale down by 7 PM daily using Auto Scaling. What should the user do in this case?

- A. Setup the scaling policy to scale up and down based on the CloudWatch alarms
- B. The user should increase the desired capacity at 8 AM and decrease it by 7 PM manually
- C. The user should setup a batch process which launches the EC2 instance at a specific time
- D. Setup scheduled actions to scale up or down at a specific time

**Answer:** A

**Explanation:**

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. To configure the Auto Scaling group to scale based on a schedule, the user needs to create scheduled actions. A scheduled action tells Auto Scaling to perform a scaling action at a certain time in the future.

**NEW QUESTION 227**

- (Topic 3)

An organization has configured Auto Scaling with ELB. One of the instance health check returns the status as Impaired to Auto Scaling. What will Auto Scaling do in this scenario?

- A. Perform a health check until cool down before declaring that the instance has failed
- B. Terminate the instance and launch a new instance
- C. Notify the user using SNS for the failed state
- D. Notify ELB to stop sending traffic to the impaired instance

**Answer:** B

**Explanation:**

The Auto Scaling group determines the health state of each instance periodically by checking the results of the Amazon EC2 instance status checks. If the instance status description shows any other state other than “running” or the system status description shows impaired, Auto Scaling considers the instance to be unhealthy. Thus, it terminates the instance and launches a replacement.

**NEW QUESTION 229**

- (Topic 3)

A user wants to upload a complete folder to AWS S3 using the S3 Management console. How can the user perform this activity?

- A. Just drag and drop the folder using the flash tool provided by S3
- B. Use the Enable Enhanced Folder option from the S3 console while uploading objects
- C. The user cannot upload the whole folder in one go with the S3 management console
- D. Use the Enable Enhanced Uploader option from the S3 console while uploading objects

**Answer:** D

**Explanation:**

AWS S3 provides a console to upload objects to a bucket. The user can use the file upload screen to upload the whole folder in one go by clicking on the Enable Enhanced Uploader option. When the user uploads a folder, Amazon S3 uploads all the files and subfolders from the specified folder to the user's bucket. It then assigns a key value that is a combination of the uploaded file name and the folder name.

**NEW QUESTION 232**

- (Topic 3)

A user wants to find the particular error that occurred on a certain date in the AWS MySQL RDS DB. Which of the below mentioned activities may help the user to get the data easily?

- A. It is not possible to get the log files for MySQL RDS
- B. Find all the transaction logs and query on those records
- C. Direct the logs to the DB table and then query that table
- D. Download the log file to DynamoDB and search for the record

**Answer:** C

**Explanation:**

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI) or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow query log, and general logs. The user can also view the MySQL logs easily by directing the logs to a database table in the main database and querying that table.

**NEW QUESTION 233**

- (Topic 3)

A root account owner has given full access of his S3 bucket to one of the IAM users using the bucket ACL. When the IAM user logs in to the S3 console, which actions can he perform?

- A. He can just view the content of the bucket
- B. He can do all the operations on the bucket
- C. It is not possible to give access to an IAM user using ACL
- D. The IAM user can perform all operations on the bucket using only API/SDK

**Answer:** C

**Explanation:**

Each AWS S3 bucket and object has an ACL (Access Control List. associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3–specific XML schema. The user cannot grant permissions to other users (IAM users. in his account.

#### NEW QUESTION 237

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. The user has not launched any instance manually and is trying to delete the VPC. What will happen in this scenario?

- A. It will not allow to delete the VPC as it has subnets with route tables
- B. It will not allow to delete the VPC since it has a running route instance
- C. It will terminate the VPC along with all the instances launched by the wizard
- D. It will not allow to delete the VPC since it has a running NAT instance

**Answer:** D

**Explanation:**

A Virtual Private Cloud (VPC. is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. If the user is trying to delete the VPC it will not allow as the NAT instance is still running.

#### NEW QUESTION 239

- (Topic 3)

George has shared an EC2 AMI created in the US East region from his AWS account with Stefano. George copies the same AMI to the US West region. Can Stefano access the copied AMI of George's account from the US West region?

- A. No, copy AMI does not copy the permission
- B. It is not possible to share the AMI with a specific account
- C. Yes, since copy AMI copies all private account sharing permissions
- D. Yes, since copy AMI copies all the permissions attached with the AMI

**Answer:** A

**Explanation:**

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source. AMI. AWS does not copy launch the permissions, user-defined tags or the Amazon S3 bucket permissions from the source AMI to the new AMI. Thus, in this case by default Stefano will not have access to the AMI in the US West region.

#### NEW QUESTION 244

- (Topic 3)

A user is planning to set up the Multi AZ feature of RDS. Which of the below mentioned conditions won't take advantage of the Multi AZ feature?

- A. Availability zone outage
- B. A manual failover of the DB instance using Reboot with failover option
- C. Region outage
- D. When the user changes the DB instance's server type

**Answer:** C

**Explanation:**

Amazon RDS when enabled with Multi AZ will handle failovers automatically. Thus, the user can resume database operations as quickly as possible without administrative intervention. The primary DB instance switches over automatically to the standby replica if any of the following conditions occur: An Availability Zone outage The primary DB instance fails The DB instance's server type is changed The DB instance is undergoing software patching A manual failover of the DB instance was initiated using Reboot with failover

#### NEW QUESTION 246

- (Topic 3)

The compliance department within your multi-national organization requires that all data for your customers that reside in the European Union (EU) must not leave the EU and also

data for customers that reside in the US must not leave the US without explicit authorization.

What must you do to comply with this requirement for a web based profile management application running on EC2?

- A. Run EC2 instances in multiple AWS Availability Zones in single Region and leverage an Elastic Load Balancer with session stickiness to route traffic to the appropriate zone to create their profile
- B. Run EC2 instances in multiple Regions and leverage Route 53's Latency Based Routing capabilities to route traffic to the appropriate region to create their profile
- C. Run EC2 instances in multiple Regions and leverage a third party data provider to determine if a user needs to be redirect to the appropriate region to create their profile
- D. Run EC2 instances in multiple AWS Availability Zones in a single Region and leverage a third party data provider to determine if a user needs to be redirect to the appropriate zone to create their profile

**Answer:** C

#### NEW QUESTION 247

- (Topic 3)

A user is planning to use AWS services for his web application. If the user is trying to set up his own billing management system for AWS, how can he configure it?

- A. Set up programmatic billing acces
- B. Download and parse the bill as per the requirement
- C. It is not possible for the user to create his own billing management service with AWS
- D. Enable the AWS CloudWatch alarm which will provide APIs to download the alarm data
- E. Use AWS billing APIs to download the usage report of each service from the AWS billing console

**Answer:** A

#### Explanation:

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3). APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value. file stored in an Amazon S3 bucket. AWS will upload the bill to the bucket every few hours and the user can download the bill CSV from the bucket, parse it and create a billing system as per the requirement.

#### NEW QUESTION 252

- (Topic 3)

A user has created an EBS volume of 10 GB and attached it to a running instance. The user is trying to access EBS for first time. Which of the below mentioned options is the correct statement with respect to a first time EBS access?

- A. The volume will show a size of 8 GB
- B. The volume will show a loss of the IOPS performance the first time
- C. The volume will be blank
- D. If the EBS is mounted it will ask the user to create a file system

**Answer:** B

#### Explanation:

A user can create an EBS volume either from a snapshot or as a blank volume. If the volume is from a snapshot it will not be blank. The volume shows the right size only as long as it is mounted. This shows that the file system is created. When the user is accessing the volume the AWS EBS will wipe out the block storage or instantiate from the snapshot. Thus, the volume will show a loss of IOPS. It is recommended that the user should pre warm the EBS before use to achieve better IO.

#### NEW QUESTION 255

- (Topic 3)

An organization has configured Auto Scaling for hosting their application. The system admin wants to understand the Auto Scaling health check process. If the instance is unhealthy, Auto Scaling launches an instance and terminates the unhealthy instance. What is the order execution?

- A. Auto Scaling launches a new instance first and then terminates the unhealthy instance
- B. Auto Scaling performs the launch and terminate processes in a random order
- C. Auto Scaling launches and terminates the instances simultaneously
- D. Auto Scaling terminates the instance first and then launches a new instance

**Answer:** D

#### Explanation:

Auto Scaling keeps checking the health of the instances at regular intervals and marks the instance for replacement when it is unhealthy. The ReplaceUnhealthy process terminates instances which are marked as unhealthy and subsequently creates new instances to replace them. This process first terminates the instance and then launches a new instance.

#### NEW QUESTION 257

- (Topic 3)

Your business is building a new application that will store its entire customer database on a RDS MySQL database, and will have various applications and users that will query that data for different purposes.

Large analytics jobs on the database are likely to cause other applications to not be able to get the query results they need to, before time out. Also, as your data grows, these analytics jobs will start to take more time, increasing the negative effect on the other applications.

How do you solve the contention issues between these different workloads on the same data?

- A. Enable Multi-AZ mode on the RDS instance
- B. Use ElastiCache to offload the analytics job data
- C. Create RDS Read-Replicas for the analytics work
- D. Run the RDS instance on the largest size possible

**Answer:** B

#### NEW QUESTION 259

- (Topic 3)

A user is trying to understand the detailed CloudWatch monitoring concept. Which of the below mentioned services provides detailed monitoring with CloudWatch without charging the user extra?



- A. AWS Auto Scaling
- B. AWS Route 53
- C. AWS EMR
- D. AWS SNS

**Answer:** B

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Services, such as RDS, ELB, OpsWorks, and Route 53 can provide the monitoring data every minute without charging the user.

#### NEW QUESTION 262

- (Topic 3)

When you put objects in Amazon S3, what is the indication that an object was successfully stored?

- A. Each S3 account has a special bucket named\_s3\_log
- B. Success codes are written to this bucket with a timestamp and checksu
- C. A success code is inserted into the S3 object metadat
- D. A HTTP 200 result code and MD5 checksum, taken together, indicate that the operation was successfu
- E. Amazon S3 is engineered for 99.999999999% durabilit
- F. Therefore there is no need to confirm that data was inserte

**Answer:** B

**Explanation:**

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/API/RESTObjectPUT.html>

#### NEW QUESTION 265

- (Topic 3)

A user has created a VPC with the public subnet. The user has created a security group for that VPC. Which of the below mentioned statements is true when a security group is created?

- A. It can connect to the AWS services, such as S3 and RDS by default
- B. It will have all the inbound traffic by default
- C. It will have all the outbound traffic by default
- D. It will by default allow traffic to the internet gateway

**Answer:** C

**Explanation:**

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level while ACLs work at the subnet level. When a user creates a security group with AWS VPC, by default it will allow all the outbound traffic but block all inbound traffic.

#### NEW QUESTION 266

- (Topic 3)

A user has enabled versioning on an S3 bucket. The user is using server side encryption for data at rest. If the user is supplying his own keys for encryption (SSE-C), what is recommended to the user for the purpose of security?

- A. The user should not use his own security key as it is not secure
- B. Configure S3 to rotate the user's encryption key at regular intervals
- C. Configure S3 to store the user's keys securely with SSL
- D. Keep rotating the encryption key manually at the client side

**Answer:** D

**Explanation:**

AWS S3 supports client side or server side encryption to encrypt all data at Rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C). Since S3 does not store the encryption keys in SSE-C, it is recommended that the user should manage keys securely and keep rotating them regularly at the client side version.

#### NEW QUESTION 269

- (Topic 3)

You have private video content in S3 that you want to serve to subscribed users on the Internet. User IDs, credentials, and subscriptions are stored in an Amazon RDS database.

Which configuration will allow you to securely serve private content to your users?

- A. Generate pre-signed URLs for each user as they request access to protected S3 content
- B. Create an IAM user for each subscribed user and assign the GetObject permission to each IAM user
- C. Create an S3 bucket policy that limits access to your private content to only your subscribed users' credentials
- D. Create a CloudFront Origin Identity user for your subscribed users and assign the GetObject permission to this user

**Answer:** C

**Explanation:**

Reference:

<https://java.awsblog.com/post/Tx1VE22EWFR4H86/Accessing-Private-Content-in-Amazon-CloudFront>**NEW QUESTION 274**

- (Topic 3)

A user is trying to create an EBS volume with the highest PIOPS supported by EBS. What is the minimum size of EBS required to have the maximum IOPS?

- A. 124
- B. 150
- C. 134
- D. 128

**Answer:** C**Explanation:**

A provisioned IOPS EBS volume can range in size from 10 GB to 1 TB and the user can provision up to 4000 IOPS per volume. The ratio of IOPS provisioned to the volume size requested should be a maximum of 30.

**NEW QUESTION 275**

- (Topic 3)

An organization has created 10 IAM users. The organization wants each of the IAM users to have access to a separate DyanmoDB table. All the users are added to the same group and the organization wants to setup a group level policy for this. How can the organization achieve this?

- A. Define the group policy and add a condition which allows the access based on the IAM name
- B. Create a DynamoDB table with the same name as the IAM user name and define the policy rule which grants access based on the DynamoDB ARN using a variable
- C. Create a separate DynamoDB database for each user and configure a policy in the group based on the DB variable
- D. It is not possible to have a group level policy which allows different IAM users to different DynamoDB Tables

**Answer:** D**Explanation:**

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. AWS DynamoDB has only tables and the organization cannot make separate databases. The organization should create a table with the same name as the IAM user name and use the ARN of DynamoDB as part of the group policy. The sample policy is shown below:

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Action": ["dynamodb:*"],
    "Resource": "arn:aws:dynamodb:region:account-number-without-hyphens:table/${aws:username}"
  }]
}
```

**NEW QUESTION 279**

- (Topic 3)

A user has setup a custom application which generates a number in decimals. The user wants to track that number and setup the alarm whenever the number is above a certain limit. The application is sending the data to CloudWatch at regular intervals for this purpose. Which of the below mentioned statements is not true with respect to the above scenario?

- A. The user can get the aggregate data of the numbers generated over a minute and send it to CloudWatch
- B. The user has to supply the timezone with each data point
- C. CloudWatch will not truncate the number until it has an exponent larger than 126 (i.
- D.  $(1 \times 10^{126})$ .
- E. The user can create a file in the JSON format with the metric name and value and supply it to CloudWatch

**Answer:** B**NEW QUESTION 280**

- (Topic 3)

Amazon EBS snapshots have which of the following two characteristics? (Choose 2.) Choose 2 answers

- A. EBS snapshots only save incremental changes from snapshot to snapshot
- B. EBS snapshots can be created in real-time without stopping an EC2 instance
- C. EBS snapshots can only be restored to an EBS volume of the same size or smaller
- D. EBS snapshots can only be restored and mounted to an instance in the same Availability Zone as the original EBS volume

**Answer:** AD**NEW QUESTION 283**

- (Topic 3)

A user has scheduled the maintenance window of an RDS DB on Monday at 3 AM. Which of the below mentioned events may force to take the DB instance offline during the maintenance window?

- A. Enabling Read Replica
- B. Making the DB Multi AZ
- C. DB password change
- D. Security patching

**Answer:** D

**Explanation:**

Amazon RDS performs maintenance on the DB instance during a user-definable maintenance window. The system may be offline or experience lower performance during that window. The only maintenance events that may require RDS to make the DB instance offline are: Scaling compute operations Software patching. Required software patching is automatically scheduled only for patches that are security and durability related. Such patching occurs infrequently (typically once every few months. and seldom requires more than a fraction of the maintenance window.

#### NEW QUESTION 284

- (Topic 3)

A user had aggregated the CloudWatch metric data on the AMI ID. The user observed some abnormal behaviour of the CPU utilization metric while viewing the last 2 weeks of data. The user wants to share that data with his manager. How can the user achieve this easily with the AWS console?

- A. The user can use the copy URL functionality of CloudWatch to share the exact details
- B. The user can use the export data option from the CloudWatch console to export the current data point
- C. The user has to find the period and data and provide all the aggregation information to the manager
- D. The user can use the CloudWatch data copy functionality to copy the current data points

**Answer:** A

**Explanation:**

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. The console provides the option to save the URL or bookmark it so that it can be used in the future by typing the same URL. The Copy URL functionality is available under the console when the user selects any metric to view.

#### NEW QUESTION 289

- (Topic 3)

A user has created a mobile application which makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK and root account access/secret access key to connect to DynamoDB from mobile. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should create a separate IAM user for each mobile application and provide DynamoDB access with it
- B. The user should create an IAM role with DynamoDB and EC2 acces
- C. Attach the role with EC2 and route all calls from the mobile through EC2
- D. The application should use an IAM role with web identity federation which validates calls to DynamoDB with identity providers, such as Google, Amazon, and Facebook
- E. Create an IAM Role with DynamoDB access and attach it with the mobile application

**Answer:** C

**Explanation:**

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. If the user is creating an app that runs on a mobile phone and makes requests to AWS, the user should not create an IAMuser and distribute the user's access key with the app. Instead, he should use an identity provider, such as Login with Amazon, Facebook, or Google to authenticate the users, and then use that identity to get temporary security credentials.

#### NEW QUESTION 291

- (Topic 3)

A user has provisioned 2000 IOPS to the EBS volume. The application hosted on that EBS is experiencing less IOPS than provisioned. Which of the below mentioned options does not affect the IOPS of the volume?

- A. The application does not have enough IO for the volume
- B. The instance is EBS optimized
- C. The EC2 instance has 10 Gigabit Network connectivity
- D. The volume size is too large

**Answer:** D

**Explanation:**

When the application does not experience the expected IOPS or throughput of the PIOPS EBS volume that was provisioned, the possible root cause could be that the EC2 bandwidth is the limiting factor and the instance might not be either EBS-optimized or might not have 10 Gigabit network connectivity. Another possible cause for not experiencing the expected IOPS could also be that the user is not driving enough I/O to the EBS volumes. The size of the volume may not affect IOPS.

#### NEW QUESTION 293

- (Topic 3)

A sys admin is planning to subscribe to the RDS event notifications. For which of the below mentioned source categories the subscription cannot be configured?

- A. DB security group
- B. DB snapshot
- C. DB options group
- D. DB parameter group

**Answer:** C

**Explanation:**

Amazon RDS uses the Amazon Simple Notification Service (SNS) to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group.

#### NEW QUESTION 294

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. Which of the below mentioned statements is not true in this scenario?

- A. The VPC will create a routing instance and attach it with a public subnet
- B. The VPC will create two subnets
- C. The VPC will create one internet gateway and attach it to VPC
- D. The VPC will launch one NAT instance with an elastic IP

**Answer:** A

**Explanation:**

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. Wizard will also create two subnets with route tables. It will also create an internet gateway and attach it to the VPC.

#### NEW QUESTION 297

- (Topic 3)

A user runs the command “dd if=/dev/xvdf of=/dev/null bs=1M” on an EBS volume created from a snapshot and attached to a Linux instance. Which of the below mentioned activities is the user performing with the step given above?

- A. Pre warming the EBS volume
- B. Initiating the device to mount on the EBS volume
- C. Formatting the volume
- D. Copying the data from a snapshot to the device

**Answer:** A

**Explanation:**

When the user creates an EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a volume created from a snapshot and attached with a Linux OS, the “dd” command pre warms the existing data on EBS and any restored snapshots of volumes that have been previously fully pre warmed. This command maintains incremental snapshots; however, because this operation is read-only, it does not pre warm unused space that has never been written to on the original volume. In the command “dd if=/dev/xvdf of=/dev/null bs=1M”, the parameter “if=input file” should be set to the drive that the user wishes to warm. The “of=output file” parameter should be set to the Linux null virtual device, /dev/null. The “bs” parameter sets the block size of the read operation; for optimal performance, this should be set to 1 MB.

#### NEW QUESTION 299

- (Topic 3)

A sysadmin has created the below mentioned policy on an S3 bucket named cloudacademy. The bucket has both AWS.jpg and index.html objects. What does this policy define?

```
"Statement": [{  
  "Sid": "Stmnt1388811069831",  
  "Effect": "Allow",  
  "Principal": { "AWS": "*" },  
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject" ],  
  "Resource": [ "arn:aws:s3:::cloudacademy/*.*jpg" ]  
}]
```

- A. It will make all the objects as well as the bucket public
- B. It will throw an error for the wrong action and does not allow to save the policy
- C. It will make the AWS.jpg object as public
- D. It will make the AWS.jpg as well as the cloudacademy bucket as public

**Answer:** B

#### NEW QUESTION 302

- (Topic 3)

An organization has configured Auto Scaling with ELB. There is a memory issue in the application which is causing CPU utilization to go above 90%. The higher CPU usage triggers an event for Auto Scaling as per the scaling policy. If the user wants to find the root cause inside the application without triggering a scaling activity, how can he achieve this?

- A. Stop the scaling process until research is completed
- B. It is not possible to find the root cause from that instance without triggering scaling
- C. Delete Auto Scaling until research is completed



D. Suspend the scaling process until research is completed

**Answer:** D

**Explanation:**

Auto Scaling allows the user to suspend and then resume one or more of the Auto Scaling processes in the Auto Scaling group. This is very useful when the user wants to investigate a configuration problem or some other issue, such as a memory leak with the web application and then make changes to the application, without triggering the Auto Scaling process.

#### NEW QUESTION 306

- (Topic 3)

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. The ELB security policy supports various ciphers. Which of the below mentioned options helps identify the matching cipher at the client side to the ELB cipher list when client is requesting ELB DNS over SSL?

- A. Cipher Protocol
- B. Client Configuration Preference
- C. Server Order Preference
- D. Load Balancer Preference

**Answer:** C

**Explanation:**

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. When client is requesting ELB DNS over SSL and if the load balancer is configured to support the Server Order Preference, then the load balancer gets to select the first cipher in its list that matches any one of the ciphers in the client's list. Server Order Preference ensures that the load balancer determines which cipher is used for the SSL connection.

#### NEW QUESTION 308

- (Topic 3)

A user is running a batch process on EBS backed EC2 instances. The batch process starts a few instances to process hadoop Map reduce jobs which can run between 50 – 600 minutes or sometimes for more time. The user wants to configure that the instance gets terminated only when the process is completed. How can the user configure this with CloudWatch?

- A. Setup the CloudWatch action to terminate the instance when the CPU utilization is less than 5%
- B. Setup the CloudWatch with Auto Scaling to terminate all the instances
- C. Setup a job which terminates all instances after 600 minutes
- D. It is not possible to terminate instances automatically

**Answer:** D

**Explanation:**

Amazon CloudWatch alarm watches a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup an action which terminates the instances when their CPU utilization is below a certain threshold for a certain period of time. The EC2 action can either terminate or stop the instance as part of the EC2 action.

#### NEW QUESTION 310

- (Topic 3)

Which of the below mentioned AWS RDS logs cannot be viewed from the console for MySQL?

- A. Error Log
- B. Slow Query Log
- C. Transaction Log
- D. General Log

**Answer:** C

**Explanation:**

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI), or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow querylog, and general logs. RDS does not support viewing the transaction logs.

#### NEW QUESTION 314

- (Topic 3)

A user has launched multiple EC2 instances for the purpose of development and testing in the same region. The user wants to find the separate cost for the production and development instances. How can the user find the cost distribution?

- A. The user should download the activity report of the EC2 services as it has the instance ID wise data
- B. It is not possible to get the AWS cost usage data of single region instances separately
- C. The user should use Cost Distribution Metadata and AWS detailed billing
- D. The user should use Cost Allocation Tags and AWS billing reports

**Answer:** D

**Explanation:**



AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources (such as Amazon EC2 instances or Amazon S3 buckets.), AWS generates a cost allocation report as a comma-separated value (CSV file. with the usage and costs aggregated by those tags. The user can apply tags which represent business categories (such as cost centres, application names, or instance type – Production/Dev. to organize usage costs across multiple services.

**NEW QUESTION 319**

- (Topic 3)

A user is trying to create a PIOPS EBS volume with 4000 IOPS and 100 GB size. AWS does not allow the user to create this volume. What is the possible root cause for this?

- A. The ratio between IOPS and the EBS volume is higher than 30
- B. The maximum IOPS supported by EBS is 3000
- C. The ratio between IOPS and the EBS volume is lower than 50
- D. PIOPS is supported for EBS higher than 500 GB size

**Answer:** A

**Explanation:**

A provisioned IOPS EBS volume can range in size from 10 GB to 1 TB and the user can provision up to 4000 IOPS per volume. The ratio of IOPS provisioned to the volume size requested should be a maximum of 30; for example, a volume with 3000 IOPS must be at least 100 GB.

**NEW QUESTION 320**

- (Topic 3)

A user has created a launch configuration for Auto Scaling where CloudWatch detailed monitoring is disabled. The user wants to now enable detailed monitoring. How can the user achieve this?

- A. Update the Launch config with CLI to set InstanceMonitoringDisabled = false
- B. The user should change the Auto Scaling group from the AWS console to enable detailed monitoring
- C. Update the Launch config with CLI to set InstanceMonitoring.Enabled = true
- D. Create a new Launch Config with detail monitoring enabled and update the Auto Scaling group

**Answer:** D

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates the AutoScaling launch config as the first step for creating an Auto Scaling group, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. When the user has created a launch configuration with InstanceMonitoring.Enabled = false it will involve multiple steps to enable detail monitoring. The steps are: Create a new Launch config with detailed monitoring enabled Update the Auto Scaling group with a new launch config Enable detail monitoring on each EC2 instance

**NEW QUESTION 322**

- (Topic 3)

A user has setup an Auto Scaling group. The group has failed to launch a single instance for more than 24 hours. What will happen to Auto Scaling in this condition?

- A. Auto Scaling will keep trying to launch the instance for 72 hours
- B. Auto Scaling will suspend the scaling process
- C. Auto Scaling will start an instance in a separate region
- D. The Auto Scaling group will be terminated automatically

**Answer:** B

**Explanation:**

If Auto Scaling is trying to launch an instance and if the launching of the instance fails continuously, it will suspend the processes for the Auto Scaling groups since it repeatedly failed to launch an instance. This is known as an administrative suspension. It commonly applies to the Auto Scaling group that has no running instances which is trying to launch instances for more than 24 hours, and has not succeeded in that to do so.

**NEW QUESTION 327**

- (Topic 3)

A user is using a small MySQL RDS DB. The user is experiencing high latency due to the Multi AZ feature. Which of the below mentioned options may not help the user in this situation?

- A. Schedule the automated back up in non-working hours
- B. Use a large or higher size instance
- C. Use PIOPS
- D. Take a snapshot from standby Replica

**Answer:** D

**Explanation:**

An RDS DB instance which has enabled Multi AZ deployments may experience increased write and commit latency compared to a Single AZ deployment, due to synchronous data replication. The user may also face changes in latency if deployment fails over to the standby replica. For production workloads, AWS recommends the user to use provisioned IOPS and DB instance classes (m1.large and larger. as they are optimized for provisioned IOPS to give a fast, and consistent performance. With Multi AZ feature, the user can not have option to take snapshot from replica.

**NEW QUESTION 329**

- (Topic 3)

A .NET application that you manage is running in Elastic Beanstalk. Your developers tell you they will need access to application log files to debug issues that arise. The infrastructure will scale up and down.

How can you ensure the developers will be able to access only the log files?

- A. Access the log files directly from Elastic Beanstalk
- B. Enable log file rotation to S3 within the Elastic Beanstalk configuration
- C. Ask your developers to enable log file rotation in the applications web.config file
- D. Connect to each Instance launched by Elastic Beanstalk and create a Windows Scheduled task to rotate the log files to S3.

**Answer:** D

**Explanation:**

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.loggingS3.title.html>

**NEW QUESTION 330**

- (Topic 3)

A user is trying to pre-warm a blank EBS volume attached to a Linux instance. Which of the below mentioned steps should be performed by the user?

- A. There is no need to pre-warm an EBS volume
- B. Contact AWS support to pre-warm
- C. Unmount the volume before pre-warming
- D. Format the device

**Answer:** C

**Explanation:**

When the user creates a new EBS volume or restores a volume from the snapshot, the back-end storage blocks are immediately allocated to the user EBS. However, the first time when the user is trying to access a block of the storage, it is recommended to either be wiped from the new volumes or instantiated from the snapshot (for restored volumes. before the user can access the block. This preliminary action takes time and can cause a 5 to 50 percent loss of IOPS for the volume when the block is accessed for the first time. To avoid this it is required to pre warm the volume. Pre-warming an EBS volume on a Linux instance requires that the user should unmount the blank device first and then write all the blocks on the device using a command, such as “dd”.

**NEW QUESTION 333**

- (Topic 3)

A user has created an application which will be hosted on EC2. The application makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK to connect with from the EC2 instance. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should attach an IAM role with DynamoDB access to the EC2 instance
- B. The user should create an IAM user with DynamoDB access and use its credentials within the application to connect with DynamoDB
- C. The user should create an IAM role, which has EC2 access so that it will allow deploying the application
- D. The user should create an IAM user with DynamoDB and EC2 acces
- E. Attach the user with the application so that it does not use the root account credentials

**Answer:** A

**Explanation:**

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. Instead, the user should use roles for EC2 and give that role access to DynamoDB /S3. When the roles are attached to EC2, it will give temporary security credentials to the application hosted on that EC2, to connect with DynamoDB / S3.

**NEW QUESTION 334**

- (Topic 3)

A user is using the AWS EC2. The user wants to make so that when there is an issue in the EC2 server, such as instance status failed, it should start a new instance in the user's private cloud. Which AWS service helps to achieve this automation?

- A. AWS CloudWatch + Cloudformation
- B. AWS CloudWatch + AWS AutoScaling + AWS ELB
- C. AWS CloudWatch + AWS VPC
- D. AWS CloudWatch + AWS SNS

**Answer:** D

**Explanation:**

Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS. queues or to any HTTP endpoint. The user can configure a web service (HTTP End point. in his data centre which receives data and launches an instance in the private cloud. The user should configure the CloudWatch alarm to send a notification to SNS when the “StatusCheckFailed” metric is true for the EC2 instance. The SNS topic can be configured to send a notification to the user's HTTP end point which launches an instance in the private cloud.

**NEW QUESTION 339**

- (Topic 3)

A user is displaying the CPU utilization, and Network in and Network out CloudWatch metrics data of a single instance on the same graph. The graph uses one Y-axis for CPU utilization and Network in and another Y-axis for Network out. Since Network in is too high, the CPU utilization data is not visible clearly on graph to the user. How can the data be viewed better on the same graph?

- A. It is not possible to show multiple metrics with the different units on the same graph
- B. Add a third Y-axis with the console to show all the data in proportion
- C. Change the axis of Network by using the Switch command from the graph
- D. Change the units of CPU utilization so it can be shown in proportion with Network

**Answer:** C

**Explanation:**

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. It is possible to show the multiple metrics with different units on the same graph. If the graph is not plotted properly due to a difference in the unit data over two metrics, the user can change the Y-axis of one of the graph by selecting that graph and clicking on the Switch option.

#### NEW QUESTION 344

- (Topic 3)

A user has enabled termination protection on an EC2 instance. The user has also set Instance initiated shutdown behaviour to terminate. When the user shuts down the instance from the OS, what will happen?

- A. The OS will shutdown but the instance will not be terminated due to protection
- B. It will terminate the instance
- C. It will not allow the user to shutdown the instance from the OS
- D. It is not possible to set the termination protection when an Instance initiated shutdown is set to Terminate

**Answer:** B

**Explanation:**

It is always possible that someone can terminate an EC2 instance using the Amazon EC2 console, command line interface or API by mistake. If the admin wants to prevent the instance from being accidentally terminated, he can enable termination protection for that instance. The user can also setup shutdown behaviour for an EBS backed instance to guide the instance on what should be done when he initiates shutdown from the OS using Instance initiated shutdown behaviour. If the instance initiated behaviour is set to terminate and the user shuts off the OS even though termination protection is enabled, it will still terminate the instance.

#### NEW QUESTION 349

- (Topic 3)

A user has created an Auto Scaling group using CLI. The user wants to enable CloudWatch detailed monitoring for that group. How can the user configure this?

- A. When the user sets an alarm on the Auto Scaling group, it automatically enables detail monitoring
- B. By default detailed monitoring is enabled for Auto Scaling
- C. Auto Scaling does not support detailed monitoring
- D. Enable detail monitoring from the AWS console

**Answer:** B

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates an Auto Scaling launch config as the first step for creating an Auto Scaling group, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. Thus, the user does not need to set this flag if he wants detailed monitoring.

#### NEW QUESTION 353

- (Topic 3)

A user has granted read/write permission of his S3 bucket using ACL. Which of the below mentioned options is a valid ID to grant permission to other AWS accounts (grantee. using ACL)?

- A. IAM User ID
- B. S3 Secure ID
- C. Access ID
- D. Canonical user ID

**Answer:** D

**Explanation:**

An S3 bucket ACL grantee can be an AWS account or one of the predefined Amazon S3 groups. The user can grant permission to an AWS account by the email address of that account or by the canonical user ID. If the user provides an email in the grant request, Amazon S3 finds the canonical user ID for that account and adds it to the ACL. The resulting ACL will always contain the canonical user ID for the AWS account, and not the AWS account's email address.

#### NEW QUESTION 356

- (Topic 3)

A sys admin is using server side encryption with AWS S3. Which of the below mentioned statements helps the user understand the S3 encryption functionality?

- A. The server side encryption with the user supplied key works when versioning is enabled
- B. The user can use the AWS console, SDK and APIs to encrypt or decrypt the content for server side encryption with the user supplied key

- C. The user must send an AES-128 encrypted key
- D. The user can upload his own encryption key to the S3 console

**Answer:** A

**Explanation:**

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key. The encryption with the user supplied key (SSE-C. does not work with the AWS console. The S3 does not store the keys and the user has to send a key with each request. The SSE-C works when the user has enabled versioning.

**NEW QUESTION 358**

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your AWS-SysOps Exam with Our Prep Materials Via below:**

<https://www.certleader.com/AWS-SysOps-dumps.html>