

Exam Questions AWS-SysOps

Amazon AWS Certified SysOps Administrator - Associate

<https://www.2passeasy.com/dumps/AWS-SysOps/>



NEW QUESTION 1

- (Topic 1)

A media company produces new video files on-premises every day with a total size of around 100GBS after compression All files have a size of 1 -2 GB and need to be uploaded to Amazon S3 every night in a fixed time window between 3am and 5am Current upload takes almost 3 hours, although less than half of the available bandwidth is used.

What step(s) would ensure that the file uploads are able to complete in the allotted time window?

- A. Increase your network bandwidth to provide faster throughput to S3
- B. Upload the files in parallel to S3
- C. Pack all files into a single archive, upload it to S3, then extract the files in AWS
- D. Use AWS Import/Export to transfer the video files

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/importexport/faqs/>

NEW QUESTION 2

- (Topic 1)

You need to design a VPC for a web-application consisting of an Elastic Load Balancer (ELB), a fleet of web/application servers, and an RDS database The entire Infrastructure must be distributed over 2 availability zones.

Which VPC configuration works while assuring the database is not available from the Internet?

- A. One public subnet for ELB one public subnet for the web-servers, and one private subnet for the database
- B. One public subnet for ELB two private subnets for the web-servers, two private subnets for RDS
- C. Two public subnets for ELB two private subnets for the web-servers and two private subnets for RDS
- D. Two public subnets for ELB two public subnets for the web-servers, and two public subnets for RDS

Answer: A

NEW QUESTION 3

- (Topic 1)

You are designing a system that has a Bastion host. This component needs to be highly available without human intervention.

Which of the following approaches would you select?

- A. Run the bastion on two instances one in each AZ
- B. Run the bastion on an active Instance in one AZ and have an AMI ready to boot up in the event of failure
- C. Configure the bastion instance in an Auto Scaling group Specify the Auto Scaling group to include multiple AZs but have a min-size of 1 and max-size of 1
- D. Configure an ELB in front of the bastion instance

Answer: C

NEW QUESTION 4

- (Topic 1)

When assessing an organization s use of AWS API access credentials which of the following three credentials should be evaluated?

Choose 3 answers

- A. Key pairs
- B. Console passwords
- C. Access keys
- D. Signing certificates
- E. Security Group memberships

Answer: ACD

Explanation:

Reference:

http://media.amazonwebservices.com/AWS_Operational_Checklists.pdf

NEW QUESTION 5

- (Topic 1)

The majority of your Infrastructure is on premises and you have a small footprint on AWS Your company has decided to roll out a new application that is heavily dependent on low latency connectivity to LOAP for authentication Your security policy requires minimal changes to the company's existing application user management processes.

What option would you implement to successfully launch this application1?

- A. Create a second, independent LOAP server in AWS for your application to use for authentication
- B. Establish a VPN connection so your applications can authenticate against your existing on-premises LDAP servers
- C. Establish a VPN connection between your data center and AWS create a LDAP replica on AWS and configure your application to use the LDAP replica for authentication
- D. Create a second LDAP domain on AWS establish a VPN connection to establish a trust relationship between your new and existing domains and use the new domain for authentication

Answer: D

Explanation:

Reference:

<http://msdn.microsoft.com/en-us/library/azure/jj156090.aspx>

NEW QUESTION 6

- (Topic 1)

Your organization's security policy requires that all privileged users either use frequently rotated passwords or one-time access credentials in addition to username/password.

Which two of the following options would allow an organization to enforce this policy for AWS users?

Choose 2 answers

- A. Configure multi-factor authentication for privileged IAM users
- B. Create IAM users for privileged accounts
- C. Implement identity federation between your organization's Identity provider leveraging the IAM Security Token Service
- D. Enable the IAM single-use password policy option for privileged users

Answer: CD

NEW QUESTION 7

- (Topic 1)

If you want to launch Amazon Elastic Compute Cloud (EC2) Instances and assign each Instance a predetermined private IP address you should:

- A. Assign a group or sequential Elastic IP address to the instances
- B. Launch the instances in a Placement Group
- C. Launch the instances in the Amazon virtual Private Cloud (VPC).
- D. Use standard EC2 instances since each instance gets a private Domain Name Service (DNS) already
- E. Launch the Instance from a private Amazon Machine image (AMI)

Answer: C

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-ip-addressing.html>

NEW QUESTION 8

- (Topic 1)

You receive a frantic call from a new DBA who accidentally dropped a table containing all your customers.

Which Amazon RDS feature will allow you to reliably restore your database to within 5 minutes of when the mistake was made?

- A. Multi-AZ RDS
- B. RDS snapshots
- C. RDS read replicas
- D. RDS automated backup

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 9

- (Topic 1)

Which services allow the customer to retain full administrative privileges of the underlying EC2 instances?

Choose 2 answers

- A. Amazon Elastic Map Reduce
- B. Elastic Load Balancing
- C. AWS Elastic Beanstalk
- D. Amazon ElastiCache
- E. Amazon Relational Database service

Answer: AC

NEW QUESTION 10

- (Topic 1)

You have been asked to propose a multi-region deployment of a web-facing application where a controlled portion of your traffic is being processed by an alternate region.

Which configuration would achieve that goal?

- A. Route53 record sets with weighted routing policy
- B. Route53 record sets with latency based routing policy
- C. Auto Scaling with scheduled scaling actions set
- D. Elastic Load Balancing with health checks enabled

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

NEW QUESTION 10

- (Topic 1)

When attached to an Amazon VPC which two components provide connectivity with external networks? Choose 2 answers

- A. Elastic IPS (EIP)
- B. NAT Gateway (NAT)
- C. Internet Gateway (IGW)
- D. Virtual Private Gateway (VGW)

Answer: CD

NEW QUESTION 12

- (Topic 1)

You are attempting to connect to an instance in Amazon VPC without success. You have already verified that the VPC has an Internet Gateway (IGW), the instance has an associated Elastic IP (EIP), and correct security group rules are in place.

Which VPC component should you evaluate next?

- A. The configuration of a NAT instance
- B. The configuration of the Routing Table
- C. The configuration of the Internet Gateway (IGW)
- D. The configuration of SRC/DST checking

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosForVPC.html>

NEW QUESTION 17

- (Topic 2)

A user wants to disable connection draining on an existing ELB. Which of the below mentioned statements helps the user disable connection draining on the ELB?

- A. The user can only disable connection draining from CLI
- B. It is not possible to disable the connection draining feature once enabled
- C. The user can disable the connection draining feature from EC2 -> ELB console or from CLI
- D. The user needs to stop all instances before disabling connection draining

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that in-flight requests continue to be served. The user can enable or disable connection draining from the AWS EC2 console -> ELB or using CLI.

NEW QUESTION 21

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24) and VPN-only subnets CIDR (20.0.1.0/24) along with the VPN gateway (vgw-12345) to connect to the user's data centre. Which of the below mentioned options is a valid entry for the main route table in this scenario?

- A. Destination: 20.0.0.0/24 and Target: vgw-12345
- B. Destination: 20.0.0.0/16 and Target: ALL
- C. Destination: 20.0.1.0/16 and Target: vgw-12345
- D. Destination: 0.0.0.0/0 and Target: vgw-12345

Answer: D

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN-only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. Here are the valid entries for the main route table in this scenario: Destination: 0.0.0.0/0 & Target: vgw-12345 (To route all internet traffic to the VPN gateway). Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC).

NEW QUESTION 25

- (Topic 2)

A user has setup an EBS-backed instance and a CloudWatch alarm when the CPU utilization is more than 65%. The user has setup the alarm to watch it for 5 periods of 5 minutes each. The CPU utilization is 60% between 9 AM to 6 PM. The user has stopped the EC2 instance for 15 minutes between 11 AM to 11:15 AM. What will be the status of the alarm at 11:30 AM?

- A. Alarm
- B. OK
- C. Insufficient Data
- D. Error

Answer: B

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The state of the alarm will be OK for the whole day. When the user stops the instance for three periods the alarm may not receive the data

NEW QUESTION 27

- (Topic 2)

A sys admin is maintaining an application on AWS. The application is installed on EC2 and user has configured ELB and Auto Scaling. Considering future load increase, the user is planning to launch new servers proactively so that they get registered with ELB. How can the user add these instances with Auto Scaling?

- A. Increase the desired capacity of the Auto Scaling group
- B. Increase the maximum limit of the Auto Scaling group
- C. Launch an instance manually and register it with ELB on the fly
- D. Decrease the minimum limit of the Auto Scaling group

Answer: A

Explanation:

A user can increase the desired capacity of the Auto Scaling group and Auto Scaling will launch a new instance as per the new capacity. The newly launched instances will be registered with ELB if Auto Scaling group is configured with ELB. If the user decreases the minimum size the instances will be removed from Auto Scaling. Increasing the maximum size will not add instances but only set the maximum instance cap.

NEW QUESTION 29

- (Topic 2)

A sys admin has created the below mentioned policy and applied to an S3 object named aws.jpg. The aws.jpg is inside a bucket named cloudacademy. What does this policy define?

```
"Statement": [{
  "Sid": "Stmt1388811069831",
  "Effect": "Allow",
  "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject" ],
  "Resource": [ "arn:aws:s3:::cloudacademy/* .jpg" ]
}]
```

- A. It is not possible to define a policy at the object level
- B. It will make all the objects of the bucket cloudacademy as public
- C. It will make the bucket cloudacademy as public
- D. the aws.jpg object as public

Answer: A

Explanation:

A system admin can grant permission to the S3 objects or buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level.

NEW QUESTION 34

- (Topic 2)

A user is planning to evaluate AWS for their internal use. The user does not want to incur any charge on his account during the evaluation. Which of the below mentioned AWS services would incur a charge if used?

- A. AWS S3 with 1 GB of storage
- B. AWS micro instance running 24 hours daily
- C. AWS ELB running 24 hours a day
- D. AWS PIOPS volume of 10 GB size

Answer: D

Explanation:

AWS is introducing a free usage tier for one year to help the new AWS customers get started in Cloud. The free tier can be used for anything that the user wants to run in the Cloud. AWS offers a handful of AWS services as a part of this which includes 750 hours of free micro instances and 750 hours of ELB. It includes the AWS S3 of 5 GB and AWS EBS general purpose volume upto 30 GB. PIOPS is not part of free usage tier.

NEW QUESTION 36

- (Topic 2)

A user has setup a billing alarm using CloudWatch for \$200. The usage of AWS exceeded \$200 after some days. The user wants to increase the limit from \$200 to \$400? What should the user do?

- A. Create a new alarm of \$400 and link it with the first alarm
- B. It is not possible to modify the alarm once it has crossed the usage limit
- C. Update the alarm to set the limit at \$400 instead of \$200
- D. Create a new alarm for the additional \$200 amount

Answer: C

Explanation:

AWS CloudWatch supports enabling the billing alarm on the total AWS charges. The estimated charges are calculated and sent several times daily to CloudWatch in the form of metric data. This data will be stored for 14 days. This data also includes the estimated charges for every service in AWS used by the user, as well as the estimated overall AWS charges. If the user wants to increase the limit, the user can modify the alarm and specify a new threshold.

NEW QUESTION 41

- (Topic 2)

A user has created a queue named "myqueue" in US-East region with AWS SQS. The user's AWS account ID is 123456789012. If the user wants to perform some action on this queue, which of the below Queue URL should he use?

- A. <http://sqs.us-east-1.amazonaws.com/123456789012/myqueue>
- B. <http://sqs.amazonaws.com/123456789012/myqueue>
- C. <http://sq>
- D. 123456789012.us-east-1.amazonaws.com/myqueue
- E. [http:// 123456789012.sq](http://123456789012.sq)
- F. us-east-1.amazonaws.com/myqueue

Answer: A

Explanation:

When creating a new queue in SQS, the user must provide a queue name that is unique within the scope of all queues of user's account. If the user creates queues using both the latest WSDL and a previous version, he will have a single namespace for all his queues. Amazon SQS assigns each queue created by user an identifier called a queue URL, which includes the queue name and other components that Amazon SQS determines. Whenever the user wants to perform an action on a queue, he must provide its queue URL. The queue URL for the account id 123456789012 & queue name "myqueue" in US-East-1 region will be <http://sqs.us-east-1.amazonaws.com/123456789012/myqueue>.

NEW QUESTION 45

- (Topic 2)

A root account owner has created an S3 bucket testmycloud. The account owner wants to allow everyone to upload the objects as well as enforce that the person who uploaded the object should manage the permission of those objects. Which is the easiest way to achieve this?

- A. The root account owner should create a bucket policy which allows the IAM users to upload the object
- B. The root account owner should create the bucket policy which allows the other account owners to set the object policy of that bucket
- C. The root account should use ACL with the bucket to allow everyone to upload the object
- D. The root account should create the IAM users and provide them the permission to upload content to the bucket

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List) associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3-specific XML schema. The user cannot grant permissions to other users in his account. ACLs are suitable for specific scenarios. For example, if a bucket owner allows other AWS accounts to upload objects, permissions to these objects can only be managed using the object ACL by the AWS account that owns the object.

NEW QUESTION 48

- (Topic 2)

A user has enabled detailed CloudWatch metric monitoring on an Auto Scaling group. Which of the below mentioned metrics will help the user identify the total number of instances in an Auto Scaling group including pending, terminating and running instances?

- A. GroupTotalInstances
- B. GroupSumInstances
- C. It is not possible to get a count of all the three metrics together
- D. The user has to find the individual number of running, terminating and pending instances and sum it
- E. GroupInstancesCount

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For Auto Scaling, CloudWatch provides various metrics to get the group information, such as the Number of Pending, Running or Terminating instances at any moment. If the user wants to get the total number of Running, Pending and Terminating instances at any moment, he can use the GroupTotalInstances metric.

NEW QUESTION 50

- (Topic 2)

A user has launched an EBS backed EC2 instance. The user has rebooted the instance. Which of the below mentioned statements is not true with respect to the reboot action?

- A. The private and public address remains the same
- B. The Elastic IP remains associated with the instance
- C. The volume is preserved
- D. The instance runs on a new host computer

Answer: D

Explanation:

A user can reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. However, it is recommended that the user use the Amazon EC2 to reboot the instance instead of running the operating system reboot command from the instance. The instance remains on the same host computer and maintains its public DNS name, private IP address, and any data on its instance store volumes. It typically takes a few minutes for the reboot to complete, but the time it takes to reboot depends on the instance configuration.

NEW QUESTION 52

- (Topic 2)

A user is trying to setup a recurring Auto Scaling process. The user has setup one process to scale up every day at 8 am and scale down at 7 PM. The user is trying to setup another recurring process which scales up on the 1st of every month at 8 AM and scales down the same day at 7 PM. What will Auto Scaling do in this scenario?

- A. Auto Scaling will execute both processes but will add just one instance on the 1st
- B. Auto Scaling will add two instances on the 1st of the month
- C. Auto Scaling will schedule both the processes but execute only one process randomly
- D. Auto Scaling will throw an error since there is a conflict in the schedule of two separate Auto Scaling Processes

Answer: D

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can also configure the recurring schedule action which will follow the Linux cron format. As per Auto Scaling, a scheduled action must have a unique time value. If the user attempts to schedule an activity at a time when another existing activity is already scheduled, the call will be rejected with an error message noting the conflict.

NEW QUESTION 57

- (Topic 2)

A user has setup Auto Scaling with ELB on the EC2 instances. The user wants to configure that whenever the CPU utilization is below 10%, Auto Scaling should remove one instance. How can the user configure this?

- A. The user can get an email using SNS when the CPU utilization is less than 10%. The user can use the desired capacity of Auto Scaling to remove the instance
- B. Use CloudWatch to monitor the data and Auto Scaling to remove the instances using scheduled actions
- C. Configure CloudWatch to send a notification to Auto Scaling Launch configuration when the CPU utilization is less than 10% and configure the Auto Scaling policy to remove the instance
- D. Configure CloudWatch to send a notification to the Auto Scaling group when the CPU Utilization is less than 10% and configure the Auto Scaling policy to remove the instance

Answer: D

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup to receive a notification on the Auto Scaling group with the CloudWatch alarm when the CPU utilization is below a certain threshold. The user can configure the Auto Scaling policy to take action for removing the instance. When the CPU utilization is below 10% CloudWatch will send an alarm to the Auto Scaling group to execute the policy.

NEW QUESTION 60

- (Topic 2)

A sys admin has created a shopping cart application and hosted it on EC2. The EC2 instances are running behind ELB. The admin wants to ensure that the end user request will always go to the EC2 instance where the user session has been created. How can the admin configure this?

- A. Enable ELB cross zone load balancing
- B. Enable ELB cookie setup
- C. Enable ELB sticky session
- D. Enable ELB connection draining

Answer: C

Explanation:

Generally AWS ELB routes each request to a zone with the minimum load. The Elastic Load Balancer provides a feature called sticky session which binds the user's session with a specific EC2 instance. If the sticky session is enabled the first request from the user will be redirected to any of the EC2 instances. But, henceforth, all requests from the same user will be redirected to the same EC2 instance. This ensures that all requests coming from the user during the session will be sent to the same application instance.

NEW QUESTION 61

- (Topic 2)

A user has a refrigerator plant. The user is measuring the temperature of the plant every 15 minutes. If the user wants to send the data to CloudWatch to view the data visually, which of the below mentioned statements is true with respect to the information given above?

- A. The user needs to use AWS CLI or API to upload the data
- B. The user can use the AWS Import Export facility to import data to CloudWatch
- C. The user will upload data from the AWS console
- D. The user cannot upload data to CloudWatch since it is not an AWS service metric

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. While sending the data the user has to include the metric name, namespace and timezone as part of the request.

NEW QUESTION 62

- (Topic 2)

An organization wants to move to Cloud. They are looking for a secure encrypted database storage option. Which of the below mentioned AWS functionalities helps them to achieve this?

- A. AWS MFA with EBS
- B. AWS EBS encryption
- C. Multi-tier encryption with Redshift
- D. AWS S3 server side storage

Answer: B

Explanation:

AWS EBS supports encryption of the volume while creating new volumes. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. The data at rest, the I/O as well as all the snapshots of EBS will be encrypted. The encryption occurs on the servers that host the EC2 instances, providing encryption of data as it moves between the EC2 instances and EBS storage. EBS encryption is based on the AES-256 cryptographic algorithm, which is the industry standard

NEW QUESTION 67

- (Topic 2)

You are building an online store on AWS that uses SQS to process your customer orders. Your backend system needs those messages in the same sequence the customer orders have been put in. How can you achieve that?

- A. It is not possible to do this with SQS
- B. You can use sequencing information on each message
- C. You can do this with SQS but you also need to use SWF
- D. Messages will arrive in the same order by default

Answer: B

Explanation:

Amazon SQS is engineered to always be available and deliver messages. One of the resulting tradeoffs is that SQS does not guarantee first in, first out delivery of messages. For many distributed applications, each message can stand on its own, and as long as all messages are delivered, the order is not important. If your system requires that order be preserved, you can place sequencing information in each message, so that you can reorder the messages when the queue returns them.

NEW QUESTION 68

- (Topic 2)

A user has configured the AWS CloudWatch alarm for estimated usage charges in the US East region. Which of the below mentioned statements is not true with respect to the estimated charges?

Exhibit:



- A. It will store the estimated charges data of the last 14 days
- B. It will include the estimated charges of every AWS service
- C. The metric data will represent the data of all the regions
- D. The metric data will show data specific to that region

Answer: D

Explanation:

When the user has enabled the monitoring of estimated charges for the AWS account with AWS CloudWatch, the estimated charges are calculated and sent several times daily to CloudWatch in the form of metric data. This data will be stored for 14 days. The billing metric data is stored in the US East (Northern Virginia) Region and represents worldwide charges. This data also includes the estimated charges for every service in AWS used by the user, as well as the estimated overall AWS charges.

NEW QUESTION 71

- (Topic 2)

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. Email JSON
- B. HTTP
- C. AWS SQS
- D. AWS SES

Answer: D

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", "and SMS".

NEW QUESTION 73

- (Topic 2)

An organization is using cost allocation tags to find the cost distribution of different departments and projects. One of the instances has two separate tags with the key/ value as "InstanceName/HR", "CostCenter/HR". What will AWS do in this case?

- A. InstanceName is a reserved tag for AW
- B. Thus, AWS will not allow this tag
- C. AWS will not allow the tags as the value is the same for different keys
- D. AWS will allow tags but will not show correctly in the cost allocation report due to the same value of the two separate keys
- E. AWS will allow both the tags and show properly in the cost distribution report

Answer: D

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV file. with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. It is required that the key should be different for each tag. The value can be the same for different keys. In this case since the value is different, AWS will properly show the distribution report with the correct values.

NEW QUESTION 75

- (Topic 2)

A system admin is planning to setup event notifications on RDS. Which of the below mentioned services will help the admin setup notifications?

- A. AWS SES
- B. AWS Cloudtrail
- C. AWS Cloudwatch
- D. AWS SNS

Answer: D

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. These notifications can be in any notification form supported by Amazon SNS for an AWS region, such as an email, a text message or a call to an HTTP endpoint

NEW QUESTION 79

- (Topic 2)

A sys admin is trying to understand EBS snapshots. Which of the below mentioned statements will not be useful to the admin to understand the concepts about a snapshot?

- A. The snapshot is synchronous
- B. It is recommended to stop the instance before taking a snapshot for consistent data
- C. The snapshot is incremental
- D. The snapshot captures the data that has been written to the hard disk when the snapshot command was executed

Answer: A

Explanation:

The AWS snapshot is a point in time backup of an EBS volume. When the snapshot command is executed it will capture the current state of the data that is written on the drive and take a backup. For a better and consistent snapshot of the root EBS volume, AWS recommends stopping the instance. For additional volumes it is recommended to unmount the device. The snapshots are asynchronous and incremental.

NEW QUESTION 84

- (Topic 3)

A user has created a VPC with a public subnet. The user has terminated all the instances which are part of the subnet. Which of the below mentioned statements is true with respect to this scenario?

- A. The user cannot delete the VPC since the subnet is not deleted
- B. All network interface attached with the instances will be deleted
- C. When the user launches a new instance it cannot use the same subnet
- D. The subnet to which the instances were launched with will be deleted

Answer: B

Explanation:

A Virtual Private Cloud (VPC. is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface. When the user terminates the instance all the network interfaces attached with it are also deleted.

NEW QUESTION 89

- (Topic 3)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment if the primary DB instance fails?

- A. The IP of the primary DB Instance is switched to the standby DB Instanc
- B. A new DB instance is created in the standby availability zon
- C. The canonical name record (CNAME) is changed from primary to standb

D. The RDS (Relational Database Service) DB instance reboot

Answer: D

Explanation:

Reference:
http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_RebootInstance.html

NEW QUESTION 94

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. The user has attached an additional instance store volume to the instance. The user wants to create an AMI from the running instance. Will the AMI have the additional instance store volume data?

- A. Yes, the block device mapping will have information about the additional instance store volume
- B. No, since the instance store backed AMI can have only the root volume bundled
- C. It is not possible to attach an additional instance store volume to the existing instance store backed AMI instance
- D. No, since this is ephemeral storage it will not be a part of the AMI

Answer: A

Explanation:

When the user has launched an EC2 instance from an instance store backed AMI and added an instance store volume to the instance in addition to the root device volume, the block device mapping for the new AMI contains the information for these volumes as well. In addition, the block device mappings for the instances those are launched from the new AMI will automatically contain information for these volumes.

NEW QUESTION 96

- (Topic 3)

A user is trying to understand the CloudWatch metrics for the AWS services. It is required that the user should first understand the namespace for the AWS services. Which of the below mentioned is not a valid namespace for the AWS services?

- A. AWS/StorageGateway
- B. AWS/CloudTrail
- C. AWS/ElastiCache
- D. AWS/SWF

Answer: B

Explanation:

Amazon CloudWatch is basically a metrics repository. The AWS product puts metrics into this repository, and the user can retrieve the data or statistics based on those metrics. To distinguish the data for each service, the CloudWatch metric has a namespace. Namespaces are containers for metrics. All AWS services that provide the Amazon CloudWatch data use a namespace string, beginning with "AWS/". All the services which are supported by CloudWatch will have some namespace. CloudWatch does not monitor CloudTrail. Thus, the namespace "AWS/CloudTrail" is incorrect.

NEW QUESTION 99

- (Topic 3)

A sys admin has enabled logging on ELB. Which of the below mentioned fields will not be a part of the log file name?

- A. Load Balancer IP
- B. EC2 instance IP
- C. S3 bucket name
- D. Random string

Answer: B

Explanation:

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Elastic Load Balancing publishes a log file from each load balancer node at the interval that the user has specified. The load balancer can deliver multiple logs for the same period. Elastic Load Balancing creates log file names in the following format: "{Bucket}/{Prefix}/AWSLogs/{AWS AccountID}/elasticloadbalancing/{Region}/{Year}/{Month}/{Day}/{AWS Account ID}_elasticloadbalancing_{Region}_{Load Balancer Name}_{End Time}_{Load Balancer IP}_{Random String}.log"

NEW QUESTION 102

- (Topic 3)

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. Which of the below mentioned security policies is supported by ELB?

- A. Dynamic Security Policy
- B. All the other options
- C. Predefined Security Policy
- D. Default Security Policy

Answer: C

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL

connections between a client and the load balancer. ELB supports two policies: Predefined Security Policy, which comes with predefined cipher and SSL protocols; Custom Security Policy, which allows the user to configure a policy.

NEW QUESTION 106

- (Topic 3)

When an EC2 instance that is backed by an S3-based AMI is terminated, what happens to the data on the root volume?

- A. Data is automatically deleted
- B. Data is automatically saved as an EBS snapshot
- C. Data is unavailable until the instance is restarted
- D. Data is automatically saved as an EBS volume

Answer: A

NEW QUESTION 109

- (Topic 3)

A system admin wants to add more zones to the existing ELB. The system admin wants to perform this activity from CLI. Which of the below mentioned commands helps the system admin to add new zones to the existing ELB?

- A. `elb-enable-zones-for-lb`
- B. `elb-add-zones-for-lb`
- C. It is not possible to add more zones to the existing ELB
- D. `elb-configure-zones-for-lb`

Answer: A

Explanation:

The user has created an Elastic Load Balancer with the availability zone and wants to add more zones to the existing ELB. The user can do so in two ways: From the console or CLI, add new zones to ELB;

NEW QUESTION 114

- (Topic 3)

You have a business-to-business web application running in a VPC consisting of an Elastic Load Balancer (ELB), web servers, application servers and a database. Your web application should only accept traffic from pre-defined customer IP addresses.

Which two options meet this security requirement? Choose 2 answers A. Configure web server VPC security groups to allow traffic from your customers' IPs

- A. Configure your web servers to filter traffic based on the ELB's "X-forwarded-for" header
- B. Configure ELB security groups to allow traffic from your customers' IPs and deny all outbound traffic
- C. Configure a VPC NACL to allow web traffic from your customers' IPs and deny all outbound traffic

Answer: AB

NEW QUESTION 115

- (Topic 3)

An organization has created one IAM user and applied the below mentioned policy to the user. What entitlements do the IAM users avail with this policy?

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "ec2:Describe*",
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "cloudwatch:ListMetrics",
        "cloudwatch:GetMetricStatistics",
        "cloudwatch:Describe*"
      ],
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": "autoscaling:Describe*",
      "Resource": "*"
    }
  ]
}
```

- A. The policy will allow the user to perform all read only activities on the EC2 services
- B. The policy will allow the user to list all the EC2 resources except EBS
- C. The policy will allow the user to perform all read and write activities on the EC2 services
- D. The policy will allow the user to perform all read only activities on the EC2 services except load Balancing

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If an organization wants to setup read only access to EC2 for a particular user, they should mention the action in the IAM policy which entitles the user for Describe rights for EC2, CloudWatch, Auto Scaling and ELB. In the policy shown below, the user will have read only access for EC2 and EBS, CloudWatch and Auto Scaling. Since ELB is not mentioned as a part of the list, the user will not have access to ELB.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "ec2:Describe*",
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "cloudwatch:ListMetrics",
        "cloudwatch:GetMetricStatistics",
        "cloudwatch:Describe*"
      ],
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": "autoscaling:Describe*",
      "Resource": "*"
    }
  ]
}
```

NEW QUESTION 119

- (Topic 3)

An organization has configured two single availability zones. The Auto Scaling groups are configured in separate zones. The user wants to merge the groups such that one group spans across multiple zones. How can the user configure this?

- A. Run the command as-join-auto-scaling-group to join the two groups
- B. Run the command as-update-auto-scaling-group to configure one group to span across zones and delete the other group
- C. Run the command as-copy-auto-scaling-group to join the two groups
- D. Run the command as-merge-auto-scaling-group to merge the groups

Answer: B

Explanation:

If the user has configured two separate single availability zone Auto Scaling groups and wants to merge them then he should update one of the groups and delete the other one. While updating the first group it is recommended that the user should increase the size of the minimum, maximum and desired capacity as a summation of both the groups.

NEW QUESTION 120

- (Topic 3)

A user has launched an RDS MySQL DB with the Multi AZ feature. The user has scheduled the scaling of instance storage during maintenance window. What is the correct order of events during maintenance window?

- Perform maintenance on standby
- Promote standby to primary
- Perform maintenance on original primary
- Promote original master back as primary

- A. 1, 2, 3, 4
- B. 1, 2, 3
- C. 2, 3, 1, 4

Answer: B

Explanation:

Running MySQL on the RDS DB instance as a Multi-AZ deployment can help the user reduce the impact of a maintenance event, as the Amazon will conduct maintenance by following the steps in the below mentioned order: Perform maintenance on standby Promote standby to primary Perform maintenance on original primary, which becomes the new standby.

NEW QUESTION 124

- (Topic 3)

Which method can be used to prevent an IP address block from accessing public objects in an S3 bucket?

- A. Create a bucket policy and apply it to the bucket
- B. Create a NACL and attach it to the VPC of the bucket
- C. Create an ACL and apply it to all objects in the bucket
- D. Modify the IAM policies of any users that would access the bucket

Answer: A

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

NEW QUESTION 125

- (Topic 3)

In AWS, which security aspects are the customer's responsibility? Choose 4 answers

- A. Controlling physical access to compute resources
- B. Patch management on the EC2 instances operating system
- C. Encryption of EBS (Elastic Block Storage) volumes
- D. Life-cycle management of IAM credentials
- E. Decommissioning storage devices
- F. Security Group and ACL (Access Control List) settings

Answer: BCEF

NEW QUESTION 126

- (Topic 3)

A user is planning to scale up an application by 8 AM and scale down by 7 PM daily using Auto Scaling. What should the user do in this case?

- A. Setup the scaling policy to scale up and down based on the CloudWatch alarms
- B. The user should increase the desired capacity at 8 AM and decrease it by 7 PM manually
- C. The user should setup a batch process which launches the EC2 instance at a specific time
- D. Setup scheduled actions to scale up or down at a specific time

Answer: A

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. To configure the Auto Scaling group to scale based on a schedule, the user needs to create scheduled actions. A scheduled action tells Auto Scaling to perform a scaling action at a certain time in the future.

NEW QUESTION 127

- (Topic 3)

A user is having data generated randomly based on a certain event. The user wants to upload that data to CloudWatch. It may happen that event may not have data generated for some period due to randomness. Which of the below mentioned options is a recommended option for this case?

- A. For the period when there is no data, the user should not send the data at all
- B. For the period when there is no data the user should send a blank value
- C. For the period when there is no data the user should send the value as 0
- D. The user must upload the data to CloudWatch as having no data for some period will cause an error at CloudWatch monitoring

Answer: C

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. When the user data is more random and not generated at regular intervals, there can be a period which has no associated data. The user can either publish the zero (0) Value for that period or not publish the data at all. It is recommended that the user should publish zero instead of no value to monitor the health of the application. This is helpful in an alarm as well as in the generation of the sample data count.

NEW QUESTION 132

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. The VPC has CIDR 20.0.0.0/16. The private subnet uses CIDR 20.0.0.0/24 . The NAT instance ID is i-a12345. Which of the below mentioned entries are required in the main route table attached with the private subnet to allow instances to connect with the internet?

- A. Destination: 0.0.0.0/0 and Target: i-a12345
- B. Destination: 20.0.0.0/0 and Target: 80
- C. Destination: 20.0.0.0/0 and Target: i-a12345
- D. Destination: 20.0.0.0/24 and Target: i-a12345

Answer: A

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create two route tables and attach to the subnets. The main route table will have the entry "Destination: 0.0.0.0/0 and Target: ia12345", which allows all the instances in the private subnet to connect to the internet using NAT.

NEW QUESTION 135

- (Topic 3)

An organization has configured Auto Scaling with ELB. One of the instance health check returns the status as Impaired to Auto Scaling. What will Auto Scaling do in this scenario?

- A. Perform a health check until cool down before declaring that the instance has failed

- B. Terminate the instance and launch a new instance
- C. Notify the user using SNS for the failed state
- D. Notify ELB to stop sending traffic to the impaired instance

Answer: B

Explanation:

The Auto Scaling group determines the health state of each instance periodically by checking the results of the Amazon EC2 instance status checks. If the instance status description shows any other state other than “running” or the system status description shows impaired, Auto Scaling considers the instance to be unhealthy. Thus, it terminates the instance and launches a replacement.

NEW QUESTION 139

- (Topic 3)

A user wants to upload a complete folder to AWS S3 using the S3 Management console. How can the user perform this activity?

- A. Just drag and drop the folder using the flash tool provided by S3
- B. Use the Enable Enhanced Folder option from the S3 console while uploading objects
- C. The user cannot upload the whole folder in one go with the S3 management console
- D. Use the Enable Enhanced Uploader option from the S3 console while uploading objects

Answer: D

Explanation:

AWS S3 provides a console to upload objects to a bucket. The user can use the file upload screen to upload the whole folder in one go by clicking on the Enable Enhanced Uploader option. When the user uploads a folder, Amazon S3 uploads all the files and subfolders from the specified folder to the user's bucket. It then assigns a key value that is a combination of the uploaded file name and the folder name.

NEW QUESTION 140

- (Topic 3)

A user is collecting 1000 records per second. The user wants to send the data to CloudWatch using the custom namespace. Which of the below mentioned options is recommended for this activity?

- A. Aggregate the data with statistics, such as Min, max, Average, Sum and Sample data and send the data to CloudWatch
- B. Send all the data values to CloudWatch in a single command by separating them with a comm
- C. CloudWatch will parse automatically
- D. Create one csv file of all the data and send a single file to CloudWatch
- E. It is not possible to send all the data in one call
- F. Thus, it should be sent one by one
- G. CloudWatch will aggregate the data automatically

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put-metric-data. It is recommended that when the user is having multiple data points per minute, he should aggregate the data so that it will minimize the number of calls to put-metric-data. In this case it will be single call to CloudWatch instead of 1000 calls if the data is aggregated.

NEW QUESTION 144

- (Topic 3)

A user has created a public subnet with VPC and launched an EC2 instance within it. The user is trying to delete the subnet. What will happen in this scenario?

- A. It will delete the subnet and make the EC2 instance as a part of the default subnet
- B. It will not allow the user to delete the subnet until the instances are terminated
- C. It will delete the subnet as well as terminate the instances
- D. The subnet can never be deleted independently, but the user has to delete the VPC first

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface.

NEW QUESTION 147

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AlarmNotification (which notifies Auto Scaling for CloudWatch alarms) process for a while. What will Auto Scaling do during this period?

- A. AWS will not receive the alarms from CloudWatch
- B. AWS will receive the alarms but will not execute the Auto Scaling policy
- C. Auto Scaling will execute the policy but it will not launch the instances until the process is resumed
- D. It is not possible to suspend the AlarmNotification process

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate Alarm Notification etc. The user can also suspend individual process. The AlarmNotification process type accepts notifications from the Amazon CloudWatch alarms that are associated with the Auto Scaling group. If the user suspends this process type, Auto Scaling will not automatically execute the scaling policies that would be triggered by the alarms.

NEW QUESTION 151

- (Topic 3)

A user has configured Auto Scaling with 3 instances. The user had created a new AMI after updating one of the instances. If the user wants to terminate two specific instances to ensure that Auto Scaling launches an instances with the new launch configuration, which command should he run?

- A. `as-delete-instance-in-auto-scaling-group <Instance ID> --no-decrement-desired-capacity`
- B. `as-terminate-instance-in-auto-scaling-group <Instance ID> --update-desired-capacity`
- C. `as-terminate-instance-in-auto-scaling-group <Instance ID> --decrement-desired-capacity`
- D. `as-terminate-instance-in-auto-scaling-group <Instance ID> --no-decrement-desired-capacity`

Answer: D

Explanation:

The Auto Scaling command `as-terminate-instance-in-auto-scaling-group <Instance ID>` will terminate the specific instance ID. The user is required to specify the parameter `--no-decrement-desired-capacity` to ensure that it launches a new instance from the launch config after terminating the instance. If the user specifies the parameter `--decrement-desired-capacity` then Auto Scaling will terminate the instance and decrease the desired capacity by 1.

NEW QUESTION 152

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. The user has not launched any instance manually and is trying to delete the VPC. What will happen in this scenario?

- A. It will not allow to delete the VPC as it has subnets with route tables
- B. It will not allow to delete the VPC since it has a running route instance
- C. It will terminate the VPC along with all the instances launched by the wizard
- D. It will not allow to delete the VPC since it has a running NAT instance

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. If the user is trying to delete the VPC it will not allow as the NAT instance is still running.

NEW QUESTION 156

- (Topic 3)

George has shared an EC2 AMI created in the US East region from his AWS account with Stefano. George copies the same AMI to the US West region. Can Stefano access the copied AMI of George's account from the US West region?

- A. No, copy AMI does not copy the permission
- B. It is not possible to share the AMI with a specific account
- C. Yes, since copy AMI copies all private account sharing permissions
- D. Yes, since copy AMI copies all the permissions attached with the AMI

Answer: A

Explanation:

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source) AMI. AWS does not copy launch permissions, user-defined tags or the Amazon S3 bucket permissions from the source AMI to the new AMI. Thus, in this case by default Stefano will not have access to the AMI in the US West region.

NEW QUESTION 157

- (Topic 3)

A user is configuring a CloudWatch alarm on RDS to receive a notification when the CPU utilization of RDS is higher than 50%. The user has setup an alarm when there is some inactivity on RDS, such as RDS unavailability. How can the user configure this?

- A. Setup the notification when the CPU is more than 75% on RDS
- B. Setup the notification when the state is Insufficient Data
- C. Setup the notification when the CPU utilization is less than 10%
- D. It is not possible to setup the alarm on RDS

Answer: B

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric

relative to a given threshold over a number of time periods. The alarm has three states: Alarm, OK and Insufficient data. The Alarm will change to Insufficient Data when any of the three situations arise: when the alarm has just started, when the metric is not available or when enough data is not available for the metric to determine the alarm state. If the user wants to find that RDS is not available, he can setup to receive the notification when the state is in Insufficient data.

NEW QUESTION 159

- (Topic 3)

A user has created an EBS volume of 10 GB and attached it to a running instance. The user is trying to access EBS for first time. Which of the below mentioned options is the correct statement with respect to a first time EBS access?

- A. The volume will show a size of 8 GB
- B. The volume will show a loss of the IOPS performance the first time
- C. The volume will be blank
- D. If the EBS is mounted it will ask the user to create a file system

Answer: B

Explanation:

A user can create an EBS volume either from a snapshot or as a blank volume. If the volume is from a snapshot it will not be blank. The volume shows the right size only as long as it is mounted. This shows that the file system is created. When the user is accessing the volume the AWS EBS will wipe out the block storage or instantiate from the snapshot. Thus, the volume will show a loss of IOPS. It is recommended that the user should pre warm the EBS before use to achieve better IO.

NEW QUESTION 163

- (Topic 3)

An organization has configured Auto Scaling for hosting their application. The system admin wants to understand the Auto Scaling health check process. If the instance is unhealthy, Auto Scaling launches an instance and terminates the unhealthy instance. What is the order execution?

- A. Auto Scaling launches a new instance first and then terminates the unhealthy instance
- B. Auto Scaling performs the launch and terminate processes in a random order
- C. Auto Scaling launches and terminates the instances simultaneously
- D. Auto Scaling terminates the instance first and then launches a new instance

Answer: D

Explanation:

Auto Scaling keeps checking the health of the instances at regular intervals and marks the instance for replacement when it is unhealthy. The ReplaceUnhealthy process terminates instances which are marked as unhealthy and subsequently creates new instances to replace them. This process first terminates the instance and then launches a new instance.

NEW QUESTION 165

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. If the user restarts the instance, what will happen to the ephemeral storage data?

- A. All the data will be erased but the ephemeral storage will stay connected
- B. All data will be erased and the ephemeral storage is released
- C. It is not possible to restart an instance launched from an instance store backed AMI
- D. The data is preserved

Answer: D

Explanation:

A user can reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. However, it is recommended that the user use Amazon EC2 to reboot the instance instead of running the operating system reboot command from the instance. When an instance launched from an instance store backed AMI is rebooted all the ephemeral storage data is still preserved.

NEW QUESTION 167

- (Topic 3)

A user has configured Auto Scaling with the minimum capacity as 2 and the desired capacity as 2. The user is trying to terminate one of the existing instance with the command:

```
as-terminate-instance-in-auto-scaling-group<Instance ID> --decrement-desired-capacity
```

What will Auto Scaling do in this scenario?

- A. Terminates the instance and does not launch a new instance
- B. Terminates the instance and updates the desired capacity to 1
- C. Terminates the instance and updates the desired capacity and minimum size to 1
- D. Throws an error

Answer: D

Explanation:

The Auto Scaling command `as-terminate-instance-in-auto-scaling-group <Instance ID>` will terminate the specific instance ID. The user is required to specify the parameter as `--decrement-desired-capacity`. Then Auto Scaling will terminate the instance and decrease the desired capacity by 1. In this case since the minimum size is 2, Auto Scaling will not allow the desired capacity to go below 2. Thus, it will throw an error.

NEW QUESTION 171

- (Topic 3)

A user has launched an EC2 instance and deployed a production application in it. The user wants to prohibit any mistakes from the production team to avoid accidental termination.

How can the user achieve this?

- A. The user can set the DisableApiTermination attribute to avoid accidental termination
- B. It is not possible to avoid accidental termination
- C. The user can set the Deletion termination flag to avoid accidental termination
- D. The user can set the InstanceInitiatedShutdownBehavior flag to avoid accidental termination

Answer: A

Explanation:

It is always possible that someone can terminate an EC2 instance using the Amazon EC2 console, command line interface or API by mistake. If the admin wants to prevent the instance from being accidentally terminated, he can enable termination protection for that instance. The DisableApiTermination attribute controls whether the instance can be terminated using the console, CLI or API. By default, termination protection is disabled for an EC2 instance. When it is set it will not allow the user to terminate the instance from CLI, API or the console.

NEW QUESTION 175

- (Topic 3)

You have private video content in S3 that you want to serve to subscribed users on the Internet. User IDs, credentials, and subscriptions are stored in an Amazon RDS database.

Which configuration will allow you to securely serve private content to your users?

- A. Generate pre-signed URLs for each user as they request access to protected S3 content
- B. Create an IAM user for each subscribed user and assign the GetObject permission to each IAM user
- C. Create an S3 bucket policy that limits access to your private content to only your subscribed users' credentials
- D. Create a CloudFront Origin Identity user for your subscribed users and assign the GetObject permission to this user

Answer: C

Explanation:

Reference:

<https://java.awsblog.com/post/Tx1VE22EWFR4H86/Accessing-Private-Content-in-Amazon-CloudFront>

NEW QUESTION 178

- (Topic 3)

A user has launched an RDS PostgreSQL DB with AWS. The user did not specify the maintenance window during creation. The user has configured RDS to update the DB instance type from micro to large. If the user wants to have it during the maintenance window, what will AWS do?

- A. AWS will not allow to update the DB until the maintenance window is configured
- B. AWS will select the default maintenance window if the user has not provided it
- C. AWS will ask the user to specify the maintenance window during the update
- D. It is not possible to change the DB size from micro to large with RDS

Answer: B

Explanation:

AWS RDS has a compulsory maintenance window which by default is 30 minutes. If the user does not specify the maintenance window during the creation of RDS then AWS will select a 30-minute maintenance window randomly from an 8-hour block of time per region. In this case, Amazon RDS assigns a 30-minute maintenance window on a randomly selected day of the week.

NEW QUESTION 183

- (Topic 3)

A user had aggregated the CloudWatch metric data on the AMI ID. The user observed some abnormal behaviour of the CPU utilization metric while viewing the last 2 weeks of data. The user wants to share that data with his manager. How can the user achieve this easily with the AWS console?

- A. The user can use the copy URL functionality of CloudWatch to share the exact details
- B. The user can use the export data option from the CloudWatch console to export the current data point
- C. The user has to find the period and data and provide all the aggregation information to the manager
- D. The user can use the CloudWatch data copy functionality to copy the current data points

Answer: A

Explanation:

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. The console provides the option to save the URL or bookmark it so that it can be used in the future by typing the same URL. The Copy URL functionality is available under the console when the user selects any metric to view.

NEW QUESTION 188

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. Which of the below mentioned statements is not true in this scenario?

- A. The VPC will create a routing instance and attach it with a public subnet

- B. The VPC will create two subnets
- C. The VPC will create one internet gateway and attach it to VPC
- D. The VPC will launch one NAT instance with an elastic IP

Answer: A

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. Wizard will also create two subnets with route tables. It will also create an internet gateway and attach it to the VPC.

NEW QUESTION 189

- (Topic 3)

A user runs the command “dd if=/dev/xvdf of=/dev/null bs=1M” on an EBS volume created from a snapshot and attached to a Linux instance. Which of the below mentioned activities is the user performing with the step given above?

- A. Pre warming the EBS volume
- B. Initiating the device to mount on the EBS volume
- C. Formatting the volume
- D. Copying the data from a snapshot to the device

Answer: A

Explanation:

When the user creates an EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a volume created from a snapshot and attached with a Linux OS, the “dd” command pre warms the existing data on EBS and any restored snapshots of volumes that have been previously fully pre warmed. This command maintains incremental snapshots; however, because this operation is read-only, it does not pre warm unused space that has never been written to on the original volume. In the command “dd if=/dev/xvdf of=/dev/null bs=1M” , the parameter “if=input file” should be set to the drive that the user wishes to warm. The “of=output file” parameter should be set to the Linux null virtual device, /dev/null. The “bs” parameter sets the block size of the read operation; for optimal performance, this should be set to 1 MB.

NEW QUESTION 193

- (Topic 3)

A user has launched an EC2 Windows instance from an instance store backed AMI. The user has also set the Instance initiated shutdown behavior to stop. What will happen when the user shuts down the OS?

- A. It will not allow the user to shutdown the OS when the shutdown behaviour is set to Stop
- B. It is not possible to set the termination behaviour to Stop for an Instance store backed AMI instance
- C. The instance will stay running but the OS will be shutdown
- D. The instance will be terminated

Answer: B

Explanation:

When the EC2 instance is launched from an instance store backed AMI, it will not allow the user to configure the shutdown behaviour to “Stop”. It gives a warning that the instance does not have the EBS root volume.

NEW QUESTION 198

- (Topic 3)

A user has created a VPC with public and private subnets. The VPC has CIDR 20.0.0.0/16. The private subnet uses CIDR 20.0.1.0/24 and the public subnet uses CIDR 20.0.0.0/24. The user is planning to host a web server in the public subnet (port 80) and a DB server in the private subnet (port 3306). The user is configuring a security group of the NAT instance. Which of the below mentioned entries is not required for the NAT security group?

- A. For Inbound allow Source: 20.0.1.0/24 on port 80
- B. For Outbound allow Destination: 0.0.0.0/0 on port 80
- C. For Inbound allow Source: 20.0.0.0/24 on port 80
- D. For Outbound allow Destination: 0.0.0.0/0 on port 443

Answer: C

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet to host the web server and DB server respectively, the user should configure that the instances in the private subnet can connect to the internet using the NAT instances. The user should first configure that NAT can receive traffic on ports 80 and 443 from the private subnet. Thus, allow ports 80 and 443 in Inbound for the private subnet 20.0.1.0/24. Now to route this traffic to the internet configure ports 80 and 443 in Outbound with destination 0.0.0.0/0. The NAT should not have an entry for the public subnet CIDR.

NEW QUESTION 202

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC Wizard. The VPC has CIDR 20.0.0.0/16. The private subnet uses CIDR 20.0.0.0/24. Which of the below mentioned entries are required in the main route table to allow the instances in VPC to communicate with each other?

- A. Destination : 20.0.0.0/24 and Target : VPC
- B. Destination : 20.0.0.0/16 and Target : ALL

- C. Destination : 20.0.0.0/0 and Target : ALL
- D. Destination : 20.0.0.0/24 and Target : Local

Answer: D

NEW QUESTION 205

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AddToLoadBalancer (which adds instances to the load balancer. process for a while. What will happen to the instances launched during the suspension period?

- A. The instances will not be registered with ELB and the user has to manually register when the process is resumed
- B. The instances will be registered with ELB only once the process has resumed
- C. Auto Scaling will not launch the instance during this period due to process suspension
- D. It is not possible to suspend only the AddToLoadBalancer process

Answer: A

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate, add to Load Balancer etc. The user can also suspend the individual process. The AddToLoadBalancer process type adds instances to the load balancer when the instances are launched. If this process is suspended, Auto Scaling will launch the instances but will not add them to the load balancer. When the user resumes this process, Auto Scaling will resume adding new instances launched after resumption to the load balancer. However, it will not add running instances that were launched while the process was suspended; those instances must be added manually.

NEW QUESTION 209

- (Topic 3)

A user has configured an ELB to distribute the traffic among multiple instances. The user instances are facing some issues due to the back-end servers. Which of the below mentioned CloudWatch metrics helps the user understand the issue with the instances?

- A. HTTPCode_Backend_3XX
- B. HTTPCode_Backend_4XX
- C. HTTPCode_Backend_2XX
- D. HTTPCode_Backend_5XX

Answer: D

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For ELB, CloudWatch provides various metrics including error code by ELB as well as by back-end servers (instances.. It gives data for the count of the number of HTTP response codes generated by the back-end instances. This metric does not include any response codes generated by the load balancer. These metrics are: The 2XX class status codes represents successful actions The 3XX class status code indicates that the user agent requires action The 4XX class status code represents client errors The 5XX class status code represents back-end server errors

NEW QUESTION 214

- (Topic 3)

A user has hosted an application on EC2 instances. The EC2 instances are configured with ELB and Auto Scaling. The application server session time out is 2 hours. The user wants to configure connection draining to ensure that all in-flight requests are supported by ELB even though the instance is being deregistered. What time out period should the user specify for connection draining?

- A. 5 minutes
- B. 1 hour
- C. 30 minutes
- D. 2 hours

Answer: B

NEW QUESTION 218

- (Topic 3)

A user has configured an SSL listener at ELB as well as on the back-end instances. Which of the below mentioned statements helps the user understand ELB traffic handling with respect to the SSL listener?

- A. It is not possible to have the SSL listener both at ELB and back-end instances
- B. ELB will modify headers to add requestor details
- C. ELB will intercept the request to add the cookie details if sticky session is enabled
- D. ELB will not modify the headers

Answer: D

Explanation:

When the user has configured Transmission Control Protocol (TCP. or Secure Sockets Layer (SSL. for both front-end and back-end connections of the Elastic Load Balancer, the load balancer forwards the request to the back-end instances without modifying the request headers unless the proxy header is enabled. SSL does not support sticky sessions. If the user has enabled a proxy protocol it adds the source and destination IP to the header.

NEW QUESTION 223

- (Topic 3)

A user is trying to launch an EBS backed EC2 instance under free usage. The user wants to achieve encryption of the EBS volume. How can the user encrypt the data at rest?

- A. Use AWS EBS encryption to encrypt the data at rest
- B. The user cannot use EBS encryption and has to encrypt the data manually or using a third party tool
- C. The user has to select the encryption enabled flag while launching the EC2 instance
- D. Encryption of volume is not available as a part of the free usage tier

Answer: B

Explanation:

AWS EBS supports encryption of the volume while creating new volumes. It supports encryption of the data at rest, the I/O as well as all the snapshots of the EBS volume. The EBS supports encryption for the selected instance type and the newer generation instances, such as m3, c3, cr1, r3, g2. It is not supported with a micro instance.

NEW QUESTION 227

- (Topic 3)

A user is using a small MySQL RDS DB. The user is experiencing high latency due to the Multi AZ feature. Which of the below mentioned options may not help the user in this situation?

- A. Schedule the automated back up in non-working hours
- B. Use a large or higher size instance
- C. Use PIOPS
- D. Take a snapshot from standby Replica

Answer: D

Explanation:

An RDS DB instance which has enabled Multi AZ deployments may experience increased write and commit latency compared to a Single AZ deployment, due to synchronous data replication. The user may also face changes in latency if deployment fails over to the standby replica. For production workloads, AWS recommends the user to use provisioned IOPS and DB instance classes (m1.large and larger) as they are optimized for provisioned IOPS to give a fast, and consistent performance. With Multi AZ feature, the user can not have option to take snapshot from replica.

NEW QUESTION 230

- (Topic 3)

A user is displaying the CPU utilization, and Network in and Network out CloudWatch metrics data of a single instance on the same graph. The graph uses one Y-axis for CPU utilization and Network in and another Y-axis for Network out. Since Network in is too high, the CPU utilization data is not visible clearly on graph to the user. How can the data be viewed better on the same graph?

- A. It is not possible to show multiple metrics with the different units on the same graph
- B. Add a third Y-axis with the console to show all the data in proportion
- C. Change the axis of Network by using the Switch command from the graph
- D. Change the units of CPU utilization so it can be shown in proportion with Network

Answer: C

Explanation:

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. It is possible to show the multiple metrics with different units on the same graph. If the graph is not plotted properly due to a difference in the unit data over two metrics, the user can change the Y-axis of one of the graph by selecting that graph and clicking on the Switch option.

NEW QUESTION 231

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created public and VPN only subnets along with hardware VPN access to connect to the user's data centre. The user has not yet launched any instance as well as modified or deleted any setup. He wants to delete this VPC from the console. Will the console allow the user to delete the VPC?

- A. Yes, the console will delete all the setups and also delete the virtual private gateway
- B. No, the console will ask the user to manually detach the virtual private gateway first and then allow deleting the VPC
- C. Yes, the console will delete all the setups and detach the virtual private gateway
- D. No, since the NAT instance is running

Answer: C

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. If the virtual private gateway is attached with VPC and the user deletes the VPC from the console it will first detach the gateway automatically and only then delete the VPC.

NEW QUESTION 234

A user is trying to setup a scheduled scaling activity using Auto Scaling. The user wants to setup the recurring schedule. Which of the below mentioned parameters is not required in this case?

- A. Maximum size

- B. Auto Scaling group name
- C. End time
- D. Recurrence value

Answer: A

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can also configure the recurring schedule action which will follow the Linux cron format. If the user is setting a recurring event, it is required that the user specifies the Recurrence value (in a cron format., end time (not compulsory but recurrence will stop after this. and the Auto Scaling group for which the scaling activity is to be scheduled.

NEW QUESTION 239

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AWS-SysOps Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AWS-SysOps Product From:

<https://www.2passeasy.com/dumps/AWS-SysOps/>

Money Back Guarantee

AWS-SysOps Practice Exam Features:

- * AWS-SysOps Questions and Answers Updated Frequently
- * AWS-SysOps Practice Questions Verified by Expert Senior Certified Staff
- * AWS-SysOps Most Realistic Questions that Guarantee you a Pass on Your First Try
- * AWS-SysOps Practice Test Questions in Multiple Choice Formats and Updates for 1 Year