

Cisco

Exam Questions 350-601

Implementing and Operating Cisco Data Center Core Technologies



NEW QUESTION 1

DRAG DROP

An engineer is implementing NetFlow on a Cisco Nexus 7000 Series Switch.

Drag and drop the NetFlow commands from the left into the correct order they must be entered on the right.

Select and Place:

N7K-1(config)# interface <interface> N7K-1(config-if)# ip flow monitor NetflowMonitor input	Step 1
N7K-1(config)# feature netflow	Step 2
N7K-1(config)# flow exporter NetflowMonitor N7K-1(config)# flow record NetflowMonitor	Step 3
N7K-1(config)# flow monitor NetflowMonitor	Step 4

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

N7K-1(config)# interface <interface> N7K-1(config-if)# ip flow monitor NetflowMonitor input	N7K-1(config)# feature netflow
N7K-1(config)# feature netflow	N7K-1(config)# flow exporter NetflowMonitor N7K-1(config)# flow record NetflowMonitor
N7K-1(config)# flow exporter NetflowMonitor N7K-1(config)# flow record NetflowMonitor	N7K-1(config)# flow monitor NetflowMonitor
N7K-1(config)# flow monitor NetflowMonitor	N7K-1(config)# interface <interface> N7K-1(config-if)# ip flow monitor NetflowMonitor input

NEW QUESTION 2

A small remote office is set to connect to the regional hub site via NSSA ASBR.

Which type of LSA is sent to the remote office OSPF area?

- A. type 7 LSA
- B. type 1 LSA
- C. type 5 LSA
- D. type 3 LSA

Answer: A

NEW QUESTION 3

Which configuration implements static ingress replication?

- A. **interface nve 1**
member vni 3716135
ingress-replication protocol bgp
- B. **interface nve 1**
member vni 3716135
peer vtep 10.0.0.4
- C. **interface nve 1**
member vni 3716135
peer vtep 10.0.0.4
ingress-replication protocol static
peer-ip 10.0.0.4
- D.

```
interface nve 1
member vni 3716135
ingress-replication protocol static
peer-ip 10.0.0.4
```

Answer: D

NEW QUESTION 4

Refer to the exhibit.

```
OTV-Site1# show otv
OTV Overlay Information
Site Identifier 0000.0000.0111
Overlay interface Overlay200
VPN name: Overlay200
VPN state: UP
Extended vlans: 178 2500-2563 (Total:65)
Join interface(s): Eth1/2 (20.1.1.1)
Site vlan: 1999 (up)
AED-Capable: Yes
Capability: Unicast-Only
Is Adjacency Server: Yes
Adjacency Server(s): 20.1.1.1/20.2.1.1
```

A network engineer is setting up a multihomed OTV network. The first site has been set up with a primary and secondary adjacency server. Which configuration must be added on the remote OTV AEDs site? A.

- A. **interface Overlay200**
otv join-interface Ethernet1/2
otv extend-vlan 178. 2500-2563
otv use-adjacency-server 20.1.1.1 unicast-only
- B. **interface Overlay200**
otv join-interface Ethernet1/2
otv extend-vlan 178. 2500-2563
- C. **interface Overlay200**
otv join-interface Ethernet1/2
otv extend-vlan 178. 2500-2563
otv use-adjacency-server 20.1.1.1 20.2.1.1 unicast-only
- D. **interface Overlay200**
otv join-interface Ethernet1/2
otv extend-vlan 178. 2500-2563
otv adjacency-server unicast-only

Answer: C

NEW QUESTION 5

A customer has a requirement to deploy a cloud service and needs to have full control over the underlying OS, data and applications. Which cloud model meets this requirement?

- A. MaaS
- B. PaaS
- C. SaaS
- D. IaaS

Answer: D

NEW QUESTION 6

An engineer is implementing an import operation in Cisco UCS Manager. What is the impact of performing this operation?

- A. Information can be modified on the management plane only.
- B. A configuration can be imported from a higher release to a lower release.
- C. An import operation can be scheduled.
- D. Only a configuration file that was exported from the same Cisco UCS Manager can be imported.

Answer: A

NEW QUESTION 7

An engineer is seeking the most optimal on demand CPU performance while configuring the BIOS settings of a UCS C-series rack mount server. What setting will accomplish this goal?

- A. C6 Retention
- B. C6 non-Retention
- C. C2 state
- D. C0/C1 state

Answer: A

NEW QUESTION 8

Which command reduces the amount of time it takes to complete the ISSU on a Cisco Nexus 7000 Series Switch that has dual supervisor modules and two I/O modules?

- A. install all epld bootflash:<image> parallel
- B. install all kickstart <image> system <image> parallel
- C. install all kickstart <image> system <image>
- D. install all epld bootflash: <image>

Answer: B

NEW QUESTION 9

Multiple roles are applied to a user on the Cisco MDS 9000 Series Switch. Which statement is true?

- A. The last role assigned takes precedence over previous roles.
- B. Access to a command takes priority over being denied access to a command.
- C. Any commands that have conflicting settings between roles are denied.
- D. The first role assigned takes precedence over subsequent roles.

Answer: B

NEW QUESTION 10

Refer to the exhibit.

```

FI-1# scope org /
FI-1 /org # create maint-policy maintenance
FI-1 /org/maint-policy* # set reboot-policy timer-automatic
FI-1 /org/maint-policy* # set soft-shutdown-timer never
    
```

Which action must be taken before the maintenance policy can be committed?

- A. Specify a maintenance time by selecting a schedule.
- B. Associate a service profile to the maintenance policy.
- C. Set the soft shutdown timer to a specific time.
- D. Set the policy to apply the changes on the next reboot.

Answer: A

NEW QUESTION 10

A Cisco MDS 9000 Series Storage Switch has reloaded unexpectedly. Where does the engineer look for the latest core dump file?

- A. /mnt/recovery
- B. /mnt/core
- C. /mnt/logs
- D. /mnt/pss

Answer: D

NEW QUESTION 13

An engineer must implement a Cisco UCS system at a customer site. One of the requirements is to implement SAN boot. The storage system maps the source WWPN to a unique LUN. Which method does Cisco recommend to configure the SAN boot?

- A. Define the vHBAs as bootable and leave the boot target definition empty.
- B. Create a SAN boot policy in which every initiator is mapped to a different target LUN.
- C. Define the vHBAs as bootable and leave the default values on the boot target definition.
- D. Create a SAN boot policy in which every initiator is mapped to the same target LUN.

Answer: D

NEW QUESTION 15

In an FCoE environment, for which two sets of data must an interface that implements the PAUSE mechanism always provision sufficient ingress buffer? (Choose two.)

- A. frames that were sent with high credit
- B. frames that were sent on the link but not yet received
- C. frames that were processed and transmitted by the transmitter after the PAUSE frame left the sender
- D. frames that were processed and transmitted by the transmitter before the PAUSE frame left the sender
- E. frames that were sent on the link and received

Answer: BD

NEW QUESTION 16

Which statement about the MAC address that the FCoE Initialization Protocol chooses for use by an E-Node in an FCoE implementation is true?

- A. The FCoE Initialization Protocol uses a 24-bit FC-MAP and concatenates a 24-bit Fibre Channel ID to create a fabric-provided MAC address.
- B. The FCoE Initialization Protocol uses the burned-in MAC address of the converged network adapter for all FCoE operations.
- C. FCoE does not use a MAC address
- D. The FCoE Initialization Protocol is used to acquire a Fibre Channel ID, and the address is used for all FCoE communications in the same way as Fibre Channel Protocol.
- E. The FCoE Initialization Protocol uses 01.00.0C as the first 24 bits of the MAC address and appends a 24-bit Fibre Channel ID to derive a full 48-bit FCoE MAC address.

Answer: AB

NEW QUESTION 17

Which statement about monitoring Fibre Channel traffic on a Cisco UCS 6332 Fabric Interconnect is true?

- A. Fibre Channel traffic can be monitored only on one vHBA per server.
- B. Fibre Channel traffic can be monitored as it is encapsulated as FCoE.
- C. The monitoring of Fibre Channel traffic is limited to the default VSAN.
- D. The destination port for monitoring must be an unassigned Fibre Channel port.

Answer: A

NEW QUESTION 18

An engineer is converting a Cisco MDS switch to support NPIV mode. What should be considered when implementing the solution?

- A. It requires mapping of external interface traffic.
- B. It must be enabled on VSAN 1 only.
- C. It must be enabled globally on all VSANs.
- D. It requires the FLOGI database to be disabled.

Answer: C

NEW QUESTION 21

An administrator needs to configure an automated policy to shut down a link when a given threshold is exceeded on MDS switch. Which feature needs to be used?

- A. RMON
- B. EEM
- C. Call Home
- D. Scheduler

Answer: B

NEW QUESTION 24

An engineer is asked to modify an overridden policy by changing the number of FCNS database entries to 1500 and then generate a message. What Configuration will accomplish this task?

- A. event manager applet fcns_policyevent fcns entries max-per-switch 1500action 1.0 syslog priority warnings msg FCNS DB entries have reached the EEM limit action2.0 policy-default
- B. event manager applet fcns_policy override fcns_entries_max_per_switchaction 1.0 syslog priority errors "CNS DB entries have reached the EEM limit" action 2.0 policy-default
- C. event manager applet fcns_policy override fcns_entries_max_per_switchevent fcns entries max-per-switch 1500action 1.0 syslog priority warnings msg FCNS DB entries have reached the EEM limit
- D. event manager applet fcns_policy action 1.0 syslog priority warnings msg FCNS DB entries have reached the EEM limit action 2.0 event-default

Answer: C

NEW QUESTION 27

An engineer is asked to manage a large-scale data center and collect information from multiple Cisco NX-OS devices using Cisco NX-OS Data Management Engine model.

Which technology should be used to accomplish this goal?

- A. NETCONF
- B. NX Yang
- C. NX-API REST
- D. JSON-RPC

Answer: C

NEW QUESTION 29

Which configuration generates a syslog message when CPU utilization is higher than 60%?

- A. event manager applet HIGH-CPU event snmp oid 1.3.6.1.4.1.9.9.109.1.1.1.1.6.1 get-type exact entry-op gt 60 poll-interval 5 action 1.0 syslog priority notifications msg "cpu high"
- B. event manager applet HIGH-CPU event snmp oid 1.3.6.1.4.1.9.9.109.1.1.1.1.6.1 get-type exact entry-op lt 60 poll-interval 5 action 1.0 syslog priority notifications msg "cpu high"
- C. event manager applet HIGH-CPU event snmp oid 1.3.6.1.4.1.9.9.109.1.1.1.1.6.1 get-type next entry-op gt 60 poll-interval 5 action 1.0 syslog priority notifications msg "cpu high"
- D. event manager applet HIGH-CPU event snmp oid 1.3.6.1.4.1.9.9.109.1.1.1.1.6.1 get-type next entry-op lt 60 poll-interval 5 action 1.0 syslog priority notifications msg "cpu high"

Answer: A

NEW QUESTION 34

Refer to the exhibit.

```
NEXUS (config) # feature tacacs+
NEXUS (config) # tacacs-server timeout 5
NEXUS (config) # tacacs-server directed-request
NEXUS (config) # tacacs-server deadtime 0
NEXUS (config) # tacacs server host 10.1.50.20 port 49
NEXUS (config) # tacacs-server host 10.1.50.20 key 7 "Flwhg123" timeout 1
NEXUS (config) # aaa group server tacacs+ ISE
NEXUS (config-tacacs+) # server 10.1.50.20
NEXUS (config-tacacs+) # deadtime 10
NEXUS (config-tacacs+) # use-vrf management
NEXUS (config-tacacs+) # source-interface mgmt 0
NEXUS (config) # aaa authentication login default group ISE
```

What is the result of implementing this configuration?

- A. The switch queries the TACACS+ server by using an encrypted text PAP login.
- B. The TACACS+ server uses the type-6 encrypted format.
- C. The switch queries the TACACS+ server by using a clear text PAP login.
- D. The timeout value on the TACACS+ server is 10 seconds.

Answer: D

NEW QUESTION 37

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

350-601 Practice Exam Features:

- * 350-601 Questions and Answers Updated Frequently
- * 350-601 Practice Questions Verified by Expert Senior Certified Staff
- * 350-601 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * 350-601 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 350-601 Practice Test Here](#)