



CompTIA

Exam Questions N10-008

CompTIA Network+Exam

About ExamBible

Your Partner of IT Exam

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Guarantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

A local firm has hired a consulting company to clean up its IT infrastructure. The consulting company notices remote printing is accomplished by port forwarding via publicly accessible IPs through the firm's firewall. Which of the following would be the MOST appropriate way to enable secure remote printing?

- A. SSH
- B. VPN
- C. Telnet
- D. SSL

Answer: A

NEW QUESTION 2

A network engineer performs the following tasks to increase server bandwidth: Connects two network cables from the server to a switch stack
Configure LACP on the switchports
Verifies the correct configurations on the switch interfaces
Which of the following needs to be configured on the server?

- A. Load balancing
- B. Multipathing
- C. NIC teaming
- D. Clustering

Answer: C

NEW QUESTION 3

A store owner would like to have secure wireless access available for both business equipment and patron use. Which of the following features should be configured to allow different wireless access through the same equipment?

- A. MIMO
- B. TKIP
- C. LTE
- D. SSID

Answer: D

NEW QUESTION 4

A network technician has multimode fiber optic cable available in an existing IDF. Which of the following Ethernet standards should the technician use to connect the network switch to the existing fiber?

- A. 10GBaseT
- B. 1000BaseT
- C. 1000BaseSX
- D. 1000BaseLX

Answer: A

NEW QUESTION 5

A network technician is observing the behavior of an unmanaged switch when a new device is added to the network and transmits data. Which of the following BEST describes how the switch processes this information?

- A. The data is flooded out of every port
- B. including the one on which it came in.
- C. The data is flooded out of every port but only in the VLAN where it is located.
- D. The data is flooded out of every port, except the one on which it came in
- E. The data is flooded out of every port, excluding the VLAN where it is located

Answer: C

NEW QUESTION 6

Which of the following devices would be used to manage a corporate WLAN?

- A. A wireless NAS
- B. A wireless bridge
- C. A wireless router
- D. A wireless controller

Answer: D

NEW QUESTION 7

A network administrator redesigned the positioning of the APs to create adjacent areas of wireless coverage. After project validation, some users still report poor connectivity when their devices maintain an association to a distanced AP. Which of the following should the network administrator check FIRST?

- A. Validate the roaming settings on the APs and WLAN clients
- B. Verify that the AP antenna type is correct for the new layout
- C. Check to see if MU-MIMO was properly activated on the APs

D. Deactivate the 2.4GHz band on the APS

Answer: A

NEW QUESTION 8

A network technician needs to ensure outside users are unable to telnet into any of the servers at the datacenter. Which of the following ports should be blocked when checking firewall configuration?

- A. 22
- B. 23
- C. 80
- D. 3389
- E. 8080

Answer: B

NEW QUESTION 9

A network technician is installing new software on a Windows-based server in a different geographical location. Which of the following would be BEST for the technician to use to perform this task?

- A. RDP
- B. SSH
- C. FTP
- D. DNS

Answer: A

NEW QUESTION 10

Which of the following would MOST likely be used to review previous upgrades to a system?

- A. Business continuity plan
- B. Change management
- C. System life cycle
- D. Standard operating procedures

Answer: B

NEW QUESTION 10

A customer wants to segregate the traffic between guests on a hypervisor. Which of the following does a technician need to configure to meet the requirement?

- A. Virtual switches
- B. OSPF routing
- C. Load balancers
- D. NIC teaming
- E. Fibre Channel

Answer: A

NEW QUESTION 11

An engineer notices some late collisions on a half-duplex link. The engineer verifies that the devices on both ends of the connection are configured for half duplex. Which of the following is the MOST likely cause of this issue?

- A. The link is improperly terminated
- B. One of the devices is misconfigured
- C. The cable length is excessive
- D. One of the devices has a hardware issue

Answer: C

NEW QUESTION 14

A network technician is investigating an issue with a desktop that is not connecting to the network. The desktop was connecting successfully the previous day, and no changes were made to the environment. The technician locates the switchport where the device is connected and observes the LED status light on the switchport is not lit even though the desktop is turned on. Other devices that are plugged into the switch are connecting to the network successfully. Which of the following is MOST likely the cause of the desktop not connecting?

- A. Transceiver mismatch
- B. VLAN mismatch
- C. Port security
- D. Damaged cable
- E. Duplex mismatch

Answer: C

NEW QUESTION 19

Which of the following BEST describes a network appliance that warns of unapproved devices that are accessing the network?

- A. Firewall
- B. AP
- C. Proxyserver
- D. IDS

Answer: D

NEW QUESTION 21

A technician is installing a new fiber connection to a network device in a datacenter. The connection from the device to the switch also traverses a patch panel connection. The chain of connections is in the following order:

Device
LC/LC patch cable Patch panel
Cross-connect fiber cable Patch panel
LC/LC patch cable Switch

The connection is not working. The technician has changed both patch cables with known working patch cables. The device had been tested and was working properly before being installed. Which of the following is the MOST likely cause of the issue?

- A. TX/RX is reversed
- B. An incorrect cable was used
- C. The device failed during installation
- D. Attenuation is occurring

Answer: A

NEW QUESTION 26

An IDS was installed behind the edge firewall after a network was breached. The network was then breached again even though the IDS logged the attack. Which of the following should be used in place of these devices to prevent future attacks?

- A. A network tap
- B. A proxy server
- C. A UTM appliance
- D. A content filter

Answer: C

NEW QUESTION 31

A lab environment hosts Internet-facing web servers and other experimental machines, which technicians use for various tasks. A technician installs software on one of the web servers to allow communication to the company's file server, but it is unable to connect to it. Other machines in the building are able to retrieve files from the file server. Which of the following is the MOST likely reason the web server cannot retrieve the files, and what should be done to resolve the problem?

- A. The lab environment's IDS is blocking the network traffic. The technician can whitelist the new application in the IDS.
- B. The lab environment is located in the DMZ, and traffic to the LAN zone is denied by default.
- C. The technician can move the computer to another zone or request an exception from the administrator.
- D. The lab environment has lost connectivity to the company router, and the switch needs to be rebooted. The technician can get the key to the wiring closet and manually restart the switch.
- E. The lab environment is currently set up with hubs instead of switches, and the requests are getting bounced back. The technician can submit a request for upgraded equipment to management.

Answer: B

NEW QUESTION 33

Which of the following is MOST likely to generate significant East-West traffic in a datacenter?

- A. A backup of a large video presentation to cloud storage for archival purposes
- B. A duplication of a hosted virtual server to another physical server for redundancy
- C. A download of navigation data to a portable device for offline access
- D. A query from an IoT device to a cloud-hosted server for a firmware update

Answer: B

NEW QUESTION 34

A technician is troubleshooting a wireless connectivity issue in a small office located in a high-rise building. Several APs are mounted in this office. The users report that the network connections frequently disconnect and reconnect throughout the day. Which of the following is the MOST likely cause of this issue?

- A. The AP association time is set too low
- B. EIRP needs to be boosted
- C. Channel overlap is occurring
- D. The RSSI is misreported

Answer: B

NEW QUESTION 38

There are two managed legacy switches running that cannot be replaced or upgraded. These switches do not support cryptographic functions, but they are password protected. Which of the following should a network administrator configure to BEST prevent unauthorized access?

- A. Enable a management access list
- B. Disable access to unnecessary services.

- C. Configure a stronger password for access
- D. Disable access to remote management
- E. Use an out-of-band access method.

Answer: A

NEW QUESTION 43

A small, family-run business uses a single SOHO router to provide Internet and WiFi to its employees. At the start of a new week, employees come in and find their usual WiFi network is no longer available, and there is a new wireless network to which they cannot connect. Given that information, which of the following should have been done to avoid this situation?

- A. The device firmware should have been kept current.
- B. Unsecure protocols should have been disabled.
- C. Parental controls should have been enabled
- D. The default credentials should have been changed

Answer: A

NEW QUESTION 45

A technician receives feedback that some users are experiencing high amounts of jitter while using the wireless network. While troubleshooting the network, the technician uses the ping command with the IP address of the default gateway and verifies large variations in latency. The technician thinks the issue may be interference from other networks and non-802.11 devices. Which of the following tools should the technician use to troubleshoot the issue?

- A. NetFlow analyzer
- B. Bandwidth analyzer
- C. Protocol analyzer
- D. Spectrum analyzer

Answer: D

NEW QUESTION 50

Which of the following DNS records works as an alias to another record?

- A. AAAA
- B. CNAME
- C. MX
- D. SOA

Answer: B

NEW QUESTION 52

A network administrator discovers that users in an adjacent building are connecting to the company's guest wireless network to download inappropriate material. Which of the following can the administrator do to MOST easily mitigate this issue?

- A. Reduce the wireless power levels
- B. Adjust the wireless channels
- C. Enable wireless client isolation
- D. Enable wireless port security

Answer: A

NEW QUESTION 54

A SaaS provider has decided to leave an unpatched VM available via a public DMZ port. With which of the following concepts is this technique MOST closely associated?

- A. Insider threat
- B. War driving
- C. Evil twin
- D. Honey pot

Answer: D

NEW QUESTION 59

A technician wants to install a WAP in the center of a room that provides service in a radius surrounding a radio. Which of the following antenna types should the AP utilize?

- A. Omni
- B. Directional
- C. Yagi
- D. Parabolic

Answer: A

NEW QUESTION 63

A network is experiencing a number of CRC errors during normal network communication. At which of the following layers of the OSI model will the administrator

MOST likely start to troubleshoot?

- A. Layer 1
- B. Layer 2
- C. Layer 3
- D. Layer 4
- E. Layer 5
- F. Layer 6
- G. Layer 7

Answer: B

NEW QUESTION 65

A Chief Information Officer (CIO) wants to improve the availability of a company's SQL database. Which of the following technologies should be utilized to achieve maximum availability?

- A. Clustering
- B. Port aggregation
- C. NIC teaming
- D. Snapshots

Answer: C

NEW QUESTION 68

A network technician is reviewing an upcoming project's requirements to implement IaaS. Which of the following should the technician consider?

- A. Software installation processes
- B. Type of database to be installed
- C. Operating system maintenance
- D. Server hardware requirements

Answer: D

NEW QUESTION 71

A branch of a company recently switched to a new ISP. The network engineer was given a new IP range to assign. The ISP assigned 196.26.4.0/26, and the branch gateway router now has the following configurations on the interface that peers to the ISP:

The network engineer observes that all users have lost Internet connectivity. Which of the following describes the issue?

- A. The incorrect subnet mask was configured
- B. The incorrect gateway was configured
- C. The incorrect IP address was configured
- D. The incorrect interface was configured

Answer: A

NEW QUESTION 72

Several WiFi users are reporting the inability to connect to the network. WLAN users on the guest network are able to access all network resources without any performance issues. The following table summarizes the findings after a site survey of the area in question:

Which of the following should a wireless technician do NEXT to troubleshoot this issue?

- A. Reconfigure the channels to reduce overlap
- B. Replace the omni antennas with directional antennas
- C. Update the SSIDs on all the APs
- D. Decrease power in AP 3 and AP 4

Answer: A

NEW QUESTION 74

You are tasked with verifying the following requirements are met in order to ensure network security. Requirements:

Datacenter

Ensure network is subnetted to allow all devices to communicate properly while minimizing address space usage

Provide a dedicated server to resolve IP addresses and hostnames correctly and handle port 53 traffic Building A

Ensure network is subnetted to allow all devices to communicate properly while minimizing address space usage

Provide devices to support 5 additional different office users Add an additional mobile user

Replace the Telnet server with a more secure solution Screened subnet

Ensure network is subnetted to allow all devices to communicate properly while minimizing address space usage

Provide a server to handle external 80/443 traffic Provide a server to handle port 20/21 traffic INSTRUCTIONS

Drag and drop objects onto the appropriate locations. Objects can be used multiple times and not all placeholders need to be filled.

Available objects are located in both the Servers and Devices tabs of the Drag & Drop menu.

If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Top left subnet – 206.208.134.0/28

Top right subnet – 10.72.63.0/28 Bottom subnet – 192.168.11.0/28

Screened Subnet devices – Web server, FTP server

Building A devices – SSH server top left, workstations on all 5 on the right, laptop on bottom left DataCenter devices – DNS server.

NEW QUESTION 76

A network administrator wants to improve the security of the management console on the company's switches and ensure configuration changes made can be correlated to the administrator who configured them. Which of the following should the network administrator implement?

- A. Port security
- B. Local authentication
- C. TACACS+
- D. Access control list

Answer: C

NEW QUESTION 81

A company that uses VoIP telephones is experiencing intermittent issues with one-way audio and dropped conversations. The manufacturer says the system will work if ping times are less than 50ms. The company has recorded the following ping times:

Which of the following is MOST likely causing the issue?

- A. Attenuation
- B. Latency
- C. VLAN mismatch
- D. Jitter

Answer: A

NEW QUESTION 84

A website administrator is concerned the company's static website could be defaced by hackers or used as a pivot point to attack internal systems. Which of the following should a network security administrator recommend to assist with detecting these activities?

- A. Implement file integrity monitoring.
- B. Change the default credentials.
- C. Use SSL encryption.
- D. Update the web-server software.

Answer: C

NEW QUESTION 89

A network engineer is investigating reports of poor network performance. Upon reviewing a device configuration, the engineer finds that duplex settings are mismatched on both ends. Which of the following would be the MOST likely result of this finding?

- A. Increased CRC errors
- B. Increased giants and runts
- C. Increased switching loops
- D. Increased device temperature

Answer: A

NEW QUESTION 93

A user recently made changes to a PC that caused it to be unable to access websites by both FQDN and IP. Local resources, such as the file server, remain accessible. Which of the following settings did the user MOST likely misconfigure?

- A. Static IP
- B. Default gateway
- C. DNS entries
- D. Local host file

Answer: B

NEW QUESTION 95

Which of the following service models would MOST likely be used to replace on-premises servers with a cloud solution?

- A. PaaS
- B. IaaS
- C. SaaS
- D. Disaster recovery as a Service (DRaaS)

Answer:

B

NEW QUESTION 96

A technician wants to deploy a new wireless network that comprises 30 WAPs installed throughout a three-story office building. All the APs will broadcast the same SSID for client access. Which of the following BEST describes this deployment?

- A. Extended service set
- B. Basic service set
- C. Unified service set
- D. Independent basic service set

Answer: A

NEW QUESTION 97

A user reports a weak signal when walking 20ft (61 m) away from the WAP in one direction, but a strong signal when walking 20ft in the opposite direction. The technician has reviewed the configuration and confirmed the channel type is correct. There is no jitter or latency on the connection. Which of the following would be the MOST likely cause of the issue?

- A. Antenna type
- B. Power levels
- C. Frequency
- D. Encryption type

Answer: A

NEW QUESTION 99

A technician is configuring a network switch to be used in a publicly accessible location. Which of the following should the technician configure on the switch to prevent unintended connections?

- A. DHCP snooping
- B. Geofencing
- C. Port security
- D. Secure SNMP

Answer: C

NEW QUESTION 101

A network administrator has been directed to present the network alerts from the past week to the company's executive staff. Which of the following will provide the BEST collection and presentation of this data?

- A. A port scan printout
- B. A consolidated report of various network devices
- C. A report from the SIEM tool
- D. A report from a vulnerability scan done yesterday

Answer: C

NEW QUESTION 106

An IT organization needs to optimize speeds for global content distribution and wants to reduce latency in high-density user locations. Which of the following technologies BEST meets the organization's requirements?

- A. Load balancing
- B. Geofencing
- C. Public cloud
- D. Content delivery network
- E. Infrastructure as a service

Answer: D

NEW QUESTION 109

A network administrator is downloading a large patch that will be uploaded to several enterprise switches simultaneously during the day's upgrade cycle. Which of the following should the administrator do to help ensure the upgrade process will be less likely to cause problems with the switches?

- A. Confirm the patch's MD5 hash prior to the upgrade
- B. Schedule the switches to reboot after an appropriate amount of time.
- C. Download each switch's current configuration before the upgrade
- D. Utilize FTP rather than TFTP to upload the patch

Answer: C

NEW QUESTION 111

Which of the following TCP ports is used by the Windows OS for file sharing?

- A. 53
- B. 389
- C. 445

D. 1433

Answer: C

NEW QUESTION 115

Which of the following can be used to centrally manage credentials for various types of administrative privileges on configured network devices?

- A. SSO
- B. TACACS+
- C. Zero Trust
- D. Separation of duties
- E. Multifactor authentication

Answer: B

NEW QUESTION 120

A network technician is investigating an IP phone that does not register in the VoIP system. Although it received an IP address, it did not receive the necessary DHCP options. The information that is needed for the registration is distributed by the DHCP scope. All other IP phones are working properly. Which of the following does the technician need to verify?

- A. VLAN mismatch
- B. Transceiver mismatch
- C. Latency
- D. DHCP exhaustion

Answer: A

NEW QUESTION 124

A network technician is installing an analog desk phone for a new receptionist. After running a new phone line, the technician now needs to connect a new connector. Which of the following connectors would MOST likely be used in this case?

- A. DB9
- B. RJ11
- C. RJ45
- D. DB25

Answer: A

NEW QUESTION 127

Which of the following factors should be considered when evaluating a firewall to protect a datacenter's east-west traffic?

- A. Replication traffic between an on-premises server and a remote backup facility
- B. Traffic between VMs running on different hosts
- C. Concurrent connections generated by Internet DDoS attacks
- D. VPN traffic from remote offices to the datacenter's VMs

Answer: A

NEW QUESTION 128

Which of the following provides redundancy on a file server to ensure the server is still connected to a LAN even in the event of a port failure on a switch?

- A. NIC teaming
- B. Load balancer
- C. RAID array
- D. PDUs

Answer: A

NEW QUESTION 131

A network engineer is designing a new secure wireless network. The engineer has been given the following requirements:

- * 1. Must not use plaintext passwords
- * 2. Must be certificate based
- * 3. Must be vendor neutral

Which of the following methods should the engineer select?

- A. TWP-RC4
- B. CCMP-AES
- C. EAP-TLS
- D. WPA2

Answer: C

NEW QUESTION 134

A wireless network was installed in a warehouse for employees to scan crates with a wireless handheld scanner. The wireless network was placed in the corner of the building near the ceiling for maximum coverage. However, users in the offices adjacent to the warehouse have noticed a large amount of signal overlap from the

new network. Additionally, warehouse employees report difficulty connecting to the wireless network from the other side of the building; however, they have no issues when they are near the antenna. Which of the following is MOST likely the cause?

- A. The wireless signal is being refracted by the warehouse's windows.
- B. The antenna's power level was set too high and is overlapping.
- C. An omnidirectional antenna was used instead of a unidirectional antenna.
- D. The wireless access points are using channels from the 5GHz spectrum.

Answer: A

NEW QUESTION 137

A systems administrator needs to improve WiFi performance in a densely populated office tower and use the latest standard. There is a mix of devices that use 2.4 GHz and 5 GHz. Which of the following should the systems administrator select to meet this requirement?

- A. 802.11ac
- B. 802.11ax
- C. 802.11g
- D. 802.11n

Answer: B

NEW QUESTION 140

Which of the following policies is MOST commonly used for guest captive portals?

- A. AUP
- B. DLP
- C. BYOD
- D. NDA

Answer: A

NEW QUESTION 145

.....

Relate Links

100% Pass Your N10-008 Exam with Exam Bible Prep Materials

<https://www.exambible.com/N10-008-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>