

AWS-Certified-Developer-Associate Dumps

Amazon AWS Certified Developer - Associate

<https://www.certleader.com/AWS-Certified-Developer-Associate-dumps.html>



NEW QUESTION 1

How long can you keep your Amazon SQS messages in Amazon SQS queues?

- A. From 120 secs up to 4 weeks
- B. From 10 secs up to 7 days
- C. From 60 secs up to 2 weeks
- D. From 30 secs up to 1 week

Answer: C

Explanation:

The SQS message retention period is configurable and can be set anywhere from 1 minute to 2 weeks. The default is 4 days and once the message retention limit is reached your messages will be automatically deleted. The option for longer message retention provides greater flexibility to allow for longer intervals between message production and consumption.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 2

In regard to DynamoDB, which of the following statements is correct?

- A. An Item should have at least two value sets, a primary key and another attribute.
- B. An Item can have more than one attributes.
- C. A primary key should be single-valued.
- D. An attribute can have one or several other attribute

Answer: B

Explanation:

In Amazon DynamoDB, a database is a collection of tables. A table is a collection of items and each item is a collection of attributes.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 3

A user is planning to make a mobile game which can be played online or offline and will be hosted on EC2.

The user wants to ensure that if someone breaks the highest score or they achieve some milestone they can inform all their colleagues through email. Which of the below mentioned AWS services helps achieve this goal?

- A. AWS Simple Workflow Service.
- B. AWS Simple Queue Service.
- C. Amazon Cognito
- D. AWS Simple Email Service

Answer: D

Explanation:

Amazon Simple Email Service (Amazon SES) is a highly scalable and cost-effective email-sending service for businesses and developers. It integrates with other AWS services, making it easy to send emails from applications that are hosted on AWS.

Reference: <http://aws.amazon.com/ses/faqs/>

NEW QUESTION 4

Which one of the following operations is NOT a DynamoDB operation?

- A. BatchWriteItem
- B. DescribeTable
- C. BatchGetItem
- D. BatchDeleteItem

Answer: D

Explanation:

In DynamoDB, DeleteItem deletes a single item in a table by primary key, but BatchDeleteItem doesn't exist.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/operationlist.html>

NEW QUESTION 5

In Amazon EC2, which of the following is the type of monitoring data for Amazon EBS volumes that is available automatically in 5-minute periods at no charge?

- A. Primary
- B. Basic
- C. Initial
- D. Detailed

Answer: B

Explanation:

Basic is the type of monitoring data (for Amazon EBS volumes) which is available automatically in 5-minute periods at no charge called.

Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/monitoring-volume-status.html>

NEW QUESTION 6

is a task coordination and state management service for cloud applications.

- A. Amazon SES
- B. Amazon SWF
- C. Amazon FPS
- D. Amazon SNS

Answer: B

Explanation:

Amazon Simple Workflow (Amazon SWF) is a task coordination and state management service for cloud applications. With Amazon SWF, you can stop writing complex glue-code and state machinery and invest more in the business logic that makes your applications unique.

Reference: <http://aws.amazon.com/swf/>

NEW QUESTION 7

When you create a table with a hash-and-range key, you must define one or more secondary indexes on that table.

- A. False, hash-range key is another name for secondary index
- B. False, it is optional
- C. True
- D. False, when you have Hash-Range key you cannot define Secondary index

Answer: B

Explanation:

When you create a table with a hash-and-range key in DynamoDB, you can also define one or more secondary indexes on that table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/LSI.html>

NEW QUESTION 8

A user has created a queue named "myqueue" with SQS. There are four messages published to queue which are not received by the consumer yet. If the user tries to delete the queue, what will happen?

- A. A user can never delete a queue manually
- B. AWS deletes it after 30 days of inactivity on queue
- C. It will initiate the delete but wait for four days before deleting until all messages are deleted automatically.
- D. It will ask user to delete the messages first
- E. It will delete the queue

Answer: D

Explanation:

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. The user can delete a queue at any time, whether it is empty or not. It is important to note that queues retain messages for a set period of time. By default, a queue retains messages for four days. Reference:

<http://docs.aws.amazon.com/AWSSimpleQueueService/latest/SQSDeveloperGuide/SQSConcepts.html>

NEW QUESTION 9

In relation to Amazon SQS, how can you ensure that messages are delivered in order?

- A. Increase the size of your queue
- B. Send them with a timestamp
- C. Give each message a unique id.
- D. AWS cannot guarantee that you will receive messages in the exact order you sent them

Answer: D

Explanation:

Amazon SQS makes a best effort to preserve order in messages, but due to the distributed nature of the queue, AWS cannot guarantee that you will receive messages in the exact order you sent them. You typically place sequencing information or timestamps in your messages so that you can reorder them upon receipt.

Reference: <https://aws.amazon.com/items/1343?externalID=1343>

NEW QUESTION 10

An organization has launched two applications: one for blogging and one for ECM on the same AWS Linux EC2 instance running in the AWS VPC. The organization has attached two private IPs (primary and secondary) to the above mentioned instance. The organization wants the instance OS to recognize the secondary IP address. How can the organization configure this?

- A. Use the ec2-net-utility package which updates routing tables, uses DHCP to refresh the secondary IP and adds the network interface.
- B. Use the ec2-net-utils package which will configure an additional network interface and update the routing table
- C. Use the ec2-ip-update package which can configure the network interface as well as update the secondary IP with DHCP.
- D. Use the ec2-ip-utility package which can update the routing tables as well as refresh the secondary IP using DHCP.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the

user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances. The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. This scenario helps when the user wants to host multiple websites on a single EC2 instance. After the user has assigned a secondary private IP address to his instance, he needs to configure the operating system on that instance to recognize the secondary private IP address. For AWS Linux, the ec2-net-utils package can take care of this step. It configures additional network interfaces that the user can attach while the instance is running, refreshes secondary IP addresses during DHCP lease renewal, and updates the related routing rules.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

NEW QUESTION 10

You need to develop and run some new applications on AWS and you know that Elastic Beanstalk and CloudFormation can both help as a deployment mechanism for a broad range of AWS resources. Which of the following statements best describes the differences between Elastic Beanstalk and CloudFormation?

- A. Elastic Beanstalk uses Elastic load balancing and CloudFormation doesn't.
- B. CloudFormation is faster in deploying applications than Elastic Beanstalk.
- C. CloudFormation is much more powerful than Elastic Beanstalk, because you can actually design and script custom resources
- D. Elastic Beanstalk is faster in deploying applications than CloudFormation

Answer: C

Explanation:

These services are designed to complement each other. AWS Elastic Beanstalk provides an environment to easily develop and run applications in the cloud. It is integrated with developer tools and provides a one-stop experience for you to manage the lifecycle of your applications. AWS CloudFormation is a convenient deployment mechanism for a broad range of AWS resources. It supports the infrastructure needs of many different types of applications such as existing enterprise applications, legacy applications, applications built using a variety of AWS resources and container-based solutions (including those built using AWS Elastic Beanstalk).

AWS CloudFormation introduces two new concepts: The template, a JSON-format, text-based file that describes all the AWS resources you need to deploy to run your application and the stack, the set of AWS resources that are created and managed as a single unit when AWS CloudFormation instantiates a template.

Reference: <http://aws.amazon.com/cloudformation/faqs/>

NEW QUESTION 13

Does AWS CloudFormation support Amazon EC2 tagging?

- A. It depends if the Amazon EC2 tagging has been defined in the template.
- B. No, it doesn't support Amazon EC2 tagging.
- C. No, CloudFormation doesn't support any tagging
- D. Yes, AWS CloudFormation supports Amazon EC2 tagging

Answer: D

Explanation:

In AWS CloudFormation, Amazon EC2 resources that support the tagging feature can also be tagged in an AWS template. The tag values can refer to template parameters, other resource names, resource attribute values (e.g. addresses), or values computed by simple functions (e.g., a concatenated list of strings).

Reference: <http://aws.amazon.com/cloudformation/faqs/>

NEW QUESTION 15

An online gaming site asked you if you can deploy a database that is a fast, highly scalable NoSQL database service in AWS for a new site that he wants to build. Which database should you recommend?

- A. Amazon Redshift
- B. Amazon SimpleDB
- C. Amazon DynamoDB
- D. Amazon RDS

Answer: C

Explanation:

Amazon DynamoDB is ideal for database applications that require very low latency and predictable performance at any scale but don't need complex querying capabilities like joins or transactions. Amazon DynamoDB is a fully-managed NoSQL database service that offers high performance, predictable throughput and low cost. It is easy to set up, operate, and scale.

With Amazon DynamoDB, you can start small, specify the throughput and storage you need, and easily scale your capacity requirements on the fly. Amazon DynamoDB automatically partitions data over a number of servers to meet your request capacity. In addition, DynamoDB automatically replicates your data synchronously across multiple Availability Zones within an AWS Region to ensure high-availability and data durability.

Reference: https://aws.amazon.com/running_databases/#dynamodb_anchor

NEW QUESTION 17

Regarding Amazon SWF, the coordination logic in a workflow is contained in a software program called a

- A. Handler
- B. Decider
- C. Coordinator
- D. Worker

Answer: B

Explanation:

In Amazon SWF, the coordination logic in a workflow is contained in a software program called a decider. The decider schedules activity tasks, provides input data to the activity workers, processes events that arrive while the workflow is in progress, and ultimately ends (or closes) the workflow when the objective has been

completed.

Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-intro-to-swf.html>

NEW QUESTION 18

A user has attached one RDS security group with 5 RDS instances. The user has changed the ingress rule for the security group. What will be the initial status of the ingress rule?

- A. Approving
- B. Implementing
- C. Authorizing
- D. It is not possible to assign a single group to multiple DB instances

Answer: C

Explanation:

When the user makes any changes to the RDS security group the rule status will be authorizing for some time until the changes are applied to all instances that the group is connected with. Once the changes are propagated the rule status will change to authorized.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html

NEW QUESTION 20

A user wants to configure AutoScaling which scales up when the CPU utilization is above 70% and scales down when the CPU utilization is below 30%. How can the user configure AutoScaling for the above mentioned condition?

- A. Use AutoScaling with a schedule
- B. Configure ELB to notify AutoScaling on load increase or decrease
- C. Use dynamic AutoScaling with a policy
- D. Use AutoScaling by manually modifying the desired capacity during a condition

Answer: C

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the specified conditions. To configure this, the user must setup policies which will get triggered by the CloudWatch alarms.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 23

A user has created an application which sends data to a log file. The server hosting the log files can be unavailable due to any reason. The user wants to make it so that whenever the log server is up it should be receive the messages. Which of the below mentioned AWS services helps achieve this functionality?

- A. AWS Simple Workflow
- B. AWS Simple Task Service
- C. AWS Simple Notification Service
- D. AWS Simple Queue Service

Answer: D

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available. Using SQS, the application has to just send the data to SQS and SQS transmits it to the log file whenever it is available.

Reference: <http://aws.amazon.com/sqs/>

NEW QUESTION 26

You have a number of image files to encode. In an Amazon SQS worker queue, you create an Amazon SQS message for each file specifying the command (jpeg-encode) and the location of the file in Amazon S3. Which of the following statements best describes the functionality of Amazon SQS?

- A. Amazon SQS is for single-threaded sending or receive speeds.
- B. Amazon SQS is a non-distributed queuing system.
- C. Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receive speeds.
- D. Amazon SQS is a distributed queuing system that is optimized for vertical scalability and for single-threaded sending or receive speeds.

Answer: C

Explanation:

Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receive speeds. A single client can send or receive Amazon SQS messages at a rate of about 5 to 50 messages per second. Higher receive performance can be achieved by requesting multiple messages (up to 10) in a single call. It may take several seconds before a message that has been to a queue is available to be received.

Reference: http://media.amazonwebservices.com/AWS_Storage_Options.pdf

NEW QUESTION 28

Can you configure an RDS Read Replica using CloudFormation templates?

- A. Yes, provided that you have root access.
- B. Yes, when you create a new CloudFormation template
- C. Yes, but not for all Regions.
- D. No, you can add the ReadReplica only when the resource is made available by CloudFormation

Answer: B

Explanation:

AWS CloudFormation gives developers and systems administrators an easy way to create and manage collections of AWS resources. You can now set Read Replicas for your databases with RDS when you create a new CloudFormation template. You can start using it with the sample template of CloudFormation.

Reference:

https://s3.amazonaws.com/cloudformation-templates-us-east-1/RDS_MySQL_With_Read_Replica.template

NEW QUESTION 31

What is the maximum time messages can be stored in SQS?

- A. 14 days
- B. one month
- C. 4 days
- D. 7 days

Answer: A

Explanation:

A message can be stored in the Simple Queue Service (SQS) from 1 minute up to a maximum of 14 days. Reference:

http://aws.amazon.com/sqs/faqs/#How_long_can_I_keep_my_messages_in_Amazon_SQS_queues

NEW QUESTION 36

You want to have multiple versions of your application running at the same time, with all versions launched via AWS Elastic Beanstalk. Is this possible?

- A. N
- B. However if you have 2 AWS accounts this can be done
- C. N
- D. AWS Elastic Beanstalk is not designed to support multiple running environments
- E. Ye
- F. AWS Elastic Beanstalk is designed to support a number of multiple running environments
- G. Ye
- H. However AWS Elastic Beanstalk is designed to support only 2 multiple running environments

Answer: C

Explanation:

AWS Elastic Beanstalk is designed to support multiple running environments. As an example you could have one for integration testing, one for pre-production, and one for production, with each environment independently configured and running on its own separate AWS resources.

Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 37

How does Amazon SQS allow multiple readers to access the same message queue without losing messages or processing them many times?

- A. By identifying a user by his unique id
- B. By using unique cryptography
- C. Amazon SQS queue has a configurable visibility timeout.
- D. Multiple readers can't access the same message queue

Answer: C

Explanation:

Every Amazon SQS queue has a configurable visibility timeout. For the designated amount of time after a message is read from a queue, it will not be visible to any other reader. As long as the amount of time that it takes to process the message is less than the visibility timeout, every message will be processed and deleted. In the event that the component processing the message fails or becomes unavailable, the message will again become visible to any component reading the queue once the visibility timeout ends. This allows you to have many components all reading messages from the same queue, with each working to process different messages.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 40

In DynamoDB, a secondary index is a data structure that contains a subset of attributes from a table, along with an alternate key to support operations.

- A. None of the above
- B. Both
- C. Query
- D. Scan

Answer: C

Explanation:

In DynamoDB, a secondary index is a data structure that contains a subset of attributes from a table, along with an alternate key to support Query operations.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 42

In DynamoDB, could you use IAM to grant access to Amazon DynamoDB resources and API actions?

- A. Yes

- B. Depended to the type of access
- C. In DynamoDB there is no need to grant access
- D. No

Answer: A

Explanation:

Amazon DynamoDB integrates with AWS Identity and Access Management (IAM). You can use AWS IAM to grant access to Amazon DynamoDB resources and API actions. To do this, you first write an AWS IAM policy, which is a document that explicitly lists the permissions you want to grant. You then attach that policy to an AWS IAM user or role.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/UsingIAMWithDDB.html>

NEW QUESTION 45

A user is planning to host a mobile game on EC2 which sends notifications to active users on either high score or the addition of new features. The user should get this notification when he is online on his mobile device. Which of the below mentioned AWS services can help achieve this functionality?

- A. AWS Simple Notification Service.
- B. AWS Simple Queue Service.
- C. AWS Mobile Communication Service.
- D. AWS Simple Email Servic

Answer: A

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS makes it simple and cost-effective to push to mobile devices, such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services.

Reference: <http://aws.amazon.com/sns>

NEW QUESTION 46

Regarding Amazon SQS, what happens if there is no actMty against a queue for more than 30 consecutive days?

- A. Your account will be suspended
- B. The queue may be deleted
- C. Nothing
- D. The queue will be deleted

Answer: B

Explanation:

AWS reserve the right to delete a queue if none of the following requests have been issued against the queue for more than 30 consecutive days:

SendMessage ReceiveMessage DeleteMessage GetQueueAttributes SetQueueAttributes

You should design your application with this in mind. Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 50

In regards to Amazon SQS how many times will you receive each message?

- A. At least twice
- B. Exactly once
- C. As many times as you want
- D. At least once

Answer: D

Explanation:

Amazon SQS is engineered to provide "at least once" delivery of all messages in its queues. Although most of the time, each message will be delivered to your application exactly once, you should design your system so that processing a message more than once does not create any errors or inconsistencies. Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 54

A user has configured ELB. Which of the below mentioned protocols the user can configure for ELB health checks while setting up ELB?

- A. All of the options
- B. TCP
- C. HTTPS
- D. SSL

Answer: A

Explanation:

An ELB performs a health check on its instances to ensure that it diverts traffic only to healthy instances. The ELB can perform a health check on HTTP, HTTPS, TCP and SSL protocols.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/Welcome.html>

NEW QUESTION 58

A user has launched an RDS instance. The user has created 3 databases on the same server. What can the maximum size be for each database?

- A. The size of each DB cannot be more than 3 TB

- B. It is not possible to have more than one DB on a single instance
- C. The total instance storage size cannot be more than 3 TB
- D. The size of each DB cannot be more than 1 TB

Answer: C

Explanation:

The AWS RDS DB instance is an isolated DB environment provided by AWS in which the user can create more than 1 database. The maximum size of the instance should be between 5 GB and 3 TB. The size of each DB can be anything in this range.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 59

A user has created an RDS instance with MySQL. The user is using the HeidiSQL client to connect with the RDS DB. The client is unable to connect to DB from his home machine. What is a possible reason for the failure?

- A. The user has to open port 80 in the RDS security group to connect with RDS DNS
- B. The security group is not configured to allow a request from the user's IP on port 3306
- C. You can never connect to RDS from your desktop
- D. The user has to open port 22 in the RDS security group to connect with RDS DNS

Answer: B

Explanation:

If the user needs to connect to RDS then he has to open port 3306 in the RDS security group for his IP address.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 62

A user is creating a new EBS volume from an existing snapshot. The snapshot size shows 10 GB. Can the user create a volume of 30 GB from that snapshot?

- A. Provided the original volume has set the change size attribute to true
- B. Yes
- C. Provided the snapshot has the modify size attribute set as true
- D. No

Answer: B

Explanation:

A user can always create a new EBS volume of a higher size than the original snapshot size. The user cannot create a volume of a lower size. When the new volume is created the size in the instance will be shown as the original size. The user needs to change the size of the device with `resize2fs` or other OS specific commands.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-expand-volume.html>

NEW QUESTION 66

Can a user associate and use his own DNS with ELB instead of the DNS provided by AWS ELB?

- A. Yes, by creating a CNAME with the existing domain name provider
- B. Yes, by configuring DNS in the AWS Console
- C. No
- D. Yes, only through Route 53 by mapping ELB and DNS

Answer: A

Explanation:

The AWS ELB allows mapping a custom domain name with ELB. The user can map ELB with DNS in two ways: 1) By creating CNAME with the existing domain name service provider or 2) By creating a record with Route 53.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/using-domain-names-with-elb.html>

NEW QUESTION 68

In relation to Amazon Simple Workflow Service (Amazon SWF), what is an "ActMty Worker"?

- A. An individual task undertaken by a workflow
- B. The automation of a business process
- C. A piece of software that implements tasks
- D. All answers listed are correct

Answer: C

Explanation:

In relation to Amazon Simple Workflow Service (Amazon SWF), an actMty worker is a program that receives actMty tasks, performs them, and provides results back. Which translates to a piece of software that implements tasks.

Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-develop-actMty.html>

NEW QUESTION 72

You cannot access your AWS console, so you revert to using the CLI that you are not familiar with. Which of the following commands is not a valid CLI command for EC2 instances?

- A. ec2-allocate-address
- B. ec2-attach-internet-gateway
- C. ec2-associate-route-table
- D. ec2-allocate-interface

Answer: D

Explanation:

You can use the CLI tools to manage your Amazon EC2 resources (such as instances, security groups, and volumes) and your Amazon VPC resources (such as VPCs, subnets, route tables, and Internet gateways). Before you can start using the tools, you must download and configure them.

The following are valid CLI commands for EC2 instances: ec2-accept-vpc-peering-connection

ec2-allocate-address

ec2-assign-private-ip-addresses ec2-associate-address

ec2-associate-dhcp-options ec2-associate-route-table

ec2-attach-internet-gateway

ec2-attach-network-interface (not ec2-allocate-interface) Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/CommandLineReference/command-reference.html>

NEW QUESTION 77

An orgAMzation has 20 employees. The orgAMzation wants to give all the users access to the orgAMzation AWS account. Which of the below mentioned options is the right solution?

- A. Share the root credentials with all the users
- B. Create an IAM user for each employee and provide access to them
- C. It is not advisable to give AWS access to so many users
- D. Use the IAM role to allow access based on STS

Answer: B

Explanation:

AWS Identity and Access Management is a web service that enables the AWS customers to manage users and user permissions in AWS. The IAM is targeted at orgAMzations with multiple users or systems that use AWS products such as Amazon EC2, Amazon RDS, and the AWS Management Console. With IAM, the orgAMzaiton can centrally manage users, security credentials such as access keys, and permissions that control which AWS resources users can access.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_Introduction.html

NEW QUESTION 82

When AutoScaling is launching a new instance based on condition, which of the below mentioned policies will it follow?

- A. Based on the criteria defined with cross zone Load balancing
- B. Launch an instance which has the highest load distribution
- C. Launch an instance in the AZ with the fewest instances
- D. Launch an instance in the AZ which has the highest instances

Answer: C

Explanation:

AutoScaling attempts to distribute instances evenly between the Availability Zones that are enabled for the user's AutoScaling group. Auto Scaling does this by attempting to launch new instances in the Availability Zone with the fewest instances.

Reference: http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS_Concepts.html

NEW QUESTION 86

In AWS Elastic Beanstalk, if the application returns any response other than 200 ,OK or there is no response within the configured InactMtyTimeout period, .

- A. SQS once again makes the message visible in the queue and available for another attempt at processing
- B. SQS waits for another timeout
- C. SQS run DeleteMessagecall and deletes the message from the queue
- D. SQS sends a message to the application with the IVlessageID and pending status

Answer: A

Explanation:

In AWS Elastic Beanstalk, if the application returns any response other than 200, OK or there is no response within the configured InactMtyTimeout period, SQS once again makes the message visible in the queue and available for another attempt at processing.

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features-managing-env-tiers.html#worker-environ>

NEW QUESTION 90

Which of the below mentioned options can be a good use case for storing content in AWS RRS?

- A. Storing mission critical data Files
- B. Storing infrequently used log files
- C. Storing a video file which is not reproducible
- D. Storing image thumbnails

Answer: D

Explanation:

AWS RRS provides the same functionality as AWS S3, but at a cheaper rate. It is ideally suited for non-mission, critical applications, such as files which can be

reproduced.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/UsingRRS.html>

NEW QUESTION 92

A user has an S3 object in the US Standard region with the content "color=red". The user updates the object with the content as "color=white". If the user tries to read the value 1 minute after it was uploaded, what will S3 return?

- A. It will return "color=white"
- B. It will return "color=red"
- C. It will return an error saying that the object was not found
- D. It may return either "color=red" or "color=white" i.
- E. any of the value

Answer: D

Explanation:

AWS S3 follows the eventual consistent model in the US Standard Region. Once the object is updated it may return the new value or the old value based on whether all the content is replicated across multiple servers until it becomes consistent (eventual).
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/Introduction.html>

NEW QUESTION 96

A user is creating a snapshot of an EBS volume. Which of the below statements is incorrect in relation to the creation of an EBS snapshot?

- A. Its incremental
- B. It can be used to launch a new instance
- C. It is stored in the same AZ as the volume
- D. It is a point in time backup of the EBS volume

Answer: C

Explanation:

The EBS snapshots are a point in time backup of the EBS volume. It is an incremental snapshot, but is always specific to the region and never specific to a single AZ.

Hence the statement "It is stored in the same AZ as the volume" is incorrect.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 101

A user is planning to use EBS for his DB requirement. The user already has an EC2 instance running in the VPC private subnet. How can the user attach the EBS volume to a running instance?

- A. The user must create EBS within the same VPC and then attach it to a running instance.
- B. The user can create EBS in the same zone as the subnet of instance and attach that EBS to instance.
- C. It is not possible to attach an EBS to an instance running in VPC until the instance is stopped.
- D. The user can specify the same subnet while creating EBS and then attach it to a running instance

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. The instance launched will always be in the same availability zone of the respective subnet. When creating an EBS the user cannot specify the subnet or VPC. However, the user must create the EBS in the same zone as the instance so that it can attach the EBS volume to the running instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet

NEW QUESTION 102

A user is trying to find the state of an S3 bucket with respect to versioning. Which of the below mentioned states AWS will not return when queried?

- A. versioning-enabled
- B. versioning-suspended
- C. unversioned
- D. versioned

Answer: D

Explanation:

S3 buckets can be in one of the three states: unversioned (the default), versioning-enabled or versioning-suspended. The bucket owner can configure the versioning state of a bucket. The versioning state applies to all (never some) of the objects in that bucket. The first time owner enables a bucket for versioning, objects in it are thereafter always versioned and given a unique version ID.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/Versioning.html>

NEW QUESTION 105

The user has created multiple AutoScaling groups. The user is trying to create a new AS group but it fails. How can the user know that he has reached the AS group limit specified by AutoScaling in that region?

- A. Run the command: as-describe-account-limits
- B. Run the command: as-describe-group-limits
- C. Run the command: as-max-account-limits
- D. Run the command: as-list-account-limits

Answer: A

Explanation:

A user can see the number of AutoScaling resources currently allowed for the AWS account either by using the `as-describe-account-limits` command or by calling the `DescribeAccountLimits` action. Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/ts-as-capacity.html>

NEW QUESTION 107

An orgAMzation is hosting an application as part of the free usage tier. The orgAMzation wants to create IAM users for each of its 150 employees and they may access AWS as part of free usage tier. What will you advise the orgAMzation?

- A. The IAM is not available as a part of the free usage tier
- B. Create IAM roles and give access based on role since it will not cost the user
- C. Do not create more than 100 users as it will cost the orgAMzation.
- D. Create IAM users for each employee as it does not cost

Answer: D

Explanation:

IAM is a free service. You can create as many IAM users or groups as desired free of cost. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_Introduction.htm

NEW QUESTION 110

A user has configured ELB with two instances running in separate AZs of the same region? Which of the below mentioned statements is true?

- A. Nlulti AZ instances will provide HA with ELB
- B. IVlulti AZ instances are not possible with a single ELB
- C. Nlulti AZ instances will provide scalability with ELB
- D. The user can achieve both HA and scalability with ELB

Answer: A

Explanation:

If a user is running two instances in separate AZs, it will provide HA with ELB since ELB will automatically stop routing the traffic to unhealthy instances and send it to healthy instances only.

NEW QUESTION 111

Does Amazon DynamoDB support both increment and decrement atomic operations?

- A. No, neither increment nor decrement operations.
- B. Only increment, since decrement are inherently impossible with DynamoDB's data model.
- C. Only decrement, since increment are inherently impossible with DynamoDB's data model.
- D. Yes, both increment and decrement operation

Answer: D

Explanation:

Amazon DynamoDB supports increment and decrement atomic operations.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/APISummary.html>

NEW QUESTION 114

An orgAMzation has enabled a strict password policy for its IAM users. The orgAMzation is taking help from the IAM console to set the password policy. Which of the below mentioned rules cannot be specified by the user as a part of the policy?

- A. Allow at least one lower case letter
- B. Allow at least one number
- C. Allow at least one non-alphanumeric character
- D. Do not allow the user to use the password from the last three passwords

Answer: D

Explanation:

AWS IAM allows an orgAMzation to create multiple users and provide them access to various AWS services. By default when the user is created, he does not have password enabled and can not login to AWS console. If the orgAMzation wants to allow the users to login to AWS console, they can enable password for each user. It is required that IAM users follow certain guidelines to set their IAM login password. For this IAM provides root account owner to setup passwrod policy. The password policy also lets the specify whether all IAM users can change their own passwords. As part of policy, orgAMzation can specify that passwords for IAM users must be of a certain minimum length, must include certain characters, and a few more criteria such as below.

One upper/ lower or both letters
One alpha numeric

One number

Reference: http://docs.aws.amazon.com/|AM/latest/UserGuide/Using_ManagingPasswordPolicies.htm

NEW QUESTION 119

A user has developed an application which is required to send the data to a NoSQL database. The user wants to decouple the data sending such that the application keeps processing and sending data but does not wait for an acknowledgement of DB. Which of the below mentioned applications helps in this scenario?

- A. AWS Simple Notification Service
- B. AWS Simple Workflow

- C. AWS Simple Query Service
- D. AWS Simple Queue Service

Answer: D

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. In this case, the user can use AWS SQS to send messages which are received from an application and sent to DB. The application can continue processing data without waiting for any acknowledgement from DB. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available.

Reference: <http://aws.amazon.com/sqs/>

NEW QUESTION 121

A user is planning to host MS SQL on an EBS volume. It was recommended to use the AWS RDS. What advantages will the user have if he uses RDS in comparison to an EBS based DB?

- A. Better throughput with PIOPS
- B. Automated backup
- C. NIS SQL is not supported with RDS
- D. High availability with multi AZs

Answer: B

Explanation:

Comparing with on-premises or EC2 based NIS SQL, RDS provides an automated backup feature. PIOPS is available with both RDS and EBS. However, HA is not available with NIS SQL.

Reference: <https://aws.amazon.com/rds/faqs/>

NEW QUESTION 123

The user has configured AutoScaling based on the dynamic policy. Which of the following is not the right command to specify a change in capacity as a part of the policy?

- A. "adjustment=-50" (type is PercentChangeInCapacity)
- B. "adjustment=3" (type is ExactCapacity)
- C. "adjustment=-1" (type is ChangeInCapacity)
- D. "adjustment=-8" (type is ExactCapacity)

Answer: D

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the various specified CloudWatch monitoring conditions. The user needs to provide the adjustment value and the adjustment type. A positive adjustment value increases the current capacity and a negative adjustment value decreases the current capacity. The user can express the change to the current size as an absolute number, an increment or as a percentage of the current group size.

In this option specifying the exact capacity with the adjustment value = -8 will not work as when type is exact capacity the adjustment value cannot be negative.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 125

When you use the AWS Elastic Beanstalk console to deploy a new application .

- A. you'll need to upload each file separately
- B. you'll need to create each file and path
- C. you'll need to upload a source bundle
- D. you'll need to create each file

Answer: C

Explanation:

When you use the AWS Elastic Beanstalk console to deploy a new application or an application version, you'll need to upload a source bundle.

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.source.html>

NEW QUESTION 127

A user has created a snapshot of an EBS volume. Which of the below mentioned usage cases is not possible with respect to a snapshot?

- A. Mirroring the volume from one AZ to another AZ
- B. Launch an instance
- C. Decrease the volume size
- D. Increase the size of the volume

Answer: C

Explanation:

The EBS snapshots are a point in time backup of the volume. It is helpful to move the volume from one AZ to another or launch a new instance. The user can increase the size of the volume but cannot decrease it less than the original snapshot size.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 130

Which of the following solutions is not supported by DynamoDB:

- A. Hash secondary index
- B. Local secondary index
- C. Hash Primary Key
- D. Global secondary index

Answer: A

Explanation:

In DynamoDB, a secondary index is a data structure that contains a subset of attributes from a table, along with an alternate key to support Query operations. DynamoDB supports the following two types of secondary indexes:

Local secondary index is an index that has the same hash key as the table, but a different range key. A local secondary index is "local" in the sense that every partition of a local secondary index is scoped to a table partition that has the same hash key.

Global secondary index is an index with a hash and range key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 132

An ELB is diverting traffic across 5 instances. One of the instances was unhealthy only for 20 minutes. What will happen after 20 minutes when the instance becomes healthy?

- A. ELB will never divert traffic back to the same instance
- B. ELB will not automatically send traffic to the same instance
- C. However, the user can configure to start sending traffic to the same instance
- D. ELB starts sending traffic to the instance once it is healthy
- E. ELB terminates the instance once it is unhealthy
- F. Thus, the instance cannot be healthy after 10 minutes

Answer: C

Explanation:

AWS Elastic Load Balancing continuously checks the health of an instance. If one of the instances is unhealthy it stops sending traffic to it and automatically reroutes the traffic to the remaining running EC2 instances. If the failed EC2 instance is restored, Elastic Load Balancing will again start sending traffic to that instance.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/SvcIntro.html>

NEW QUESTION 133

An orgAMzation has created an application which is hosted on the AWS EC2 instance. The application stores images to S3 when the end user uploads to it. The orgAMzation does not want to store the AWS secure credentials required to access the S3 inside the instance. Which of the below mentioned options is a possible solution to avoid any security threat?

- A. Use the IAM role and assign it to the instance.
- B. Since the application is hosted on EC2, it does not need credentials to access S3.
- C. Use the X.509 certificates instead of the access and the secret access keys.
- D. Use the IAM based single sign between the AWS resources and the orgAMzation applicatio

Answer: A

Explanation:

The AWS IAM role uses temporary security credentials to access AWS services. Once the role is assigned to an instance, it will not need any security credentials to be stored on the instance. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/iam-roles-for-amazon-ec2.html>

NEW QUESTION 135

A user has hosted a website on AWS and uses ELB to load balance the multiple instances. The user application does not have any cookie management. How can the user bind the session of the requestor with a particular instance?

- A. Bind the IP address with a sticky cookie
- B. Create a cookie at the application level to set at ELB
- C. Use session synchronization with ELB
- D. Let ELB generate a cookie for a specified duration

Answer: D

Explanation:

The key to manage the sticky session is determining how long the load balancer should route the user's request to the same application instance. If the application has its own session cookie, then the user can set the Elastic Load Balancing to create the session cookie to follow the duration specified by the application's session cookie. If the user's application does not have its own session cookie, then he can set the Elastic Load Balancing to create a session cookie by specifying his own stickiness duration. Reference: http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/US_StickySessions.html

NEW QUESTION 139

Your supervisor has asked you to build a simple file synchronization service for your department. He doesn't want to spend too much money and he wants to be notified of any changes to files by email. What do you think would be the best Amazon service to use for the email solution?

- A. Amazon CloudSearch
- B. Amazon Elastic Transcoder
- C. Amazon SES
- D. Amazon AppStream

Answer: C

Explanation:

File change notifications can be sent via email to users following the resource with Amazon Simple Email Service (Amazon SES), an easy-to-use, cost-effective email solution.

Reference: http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_filesync_08.pdf

NEW QUESTION 144

ExamKiller has three AWS accounts. They have created separate IAM users within each account. ExamKiller wants a single IAM console URL such as <https://examkiller.signin.aws.amazon.com/console/> for all account users. How can this be achieved?

- A. Merge all the accounts with consolidated billing
- B. Create the same account alias with each account ID
- C. It is not possible to have the same IAM account login URL for separate AWS accounts
- D. Create the S3 bucket with an alias name and use the redirect rule to forward requests to various accounts

Answer: C

Explanation:

If a user wants the URL of the AWS IAM sign-in page to have a company name instead of the AWS account ID, he can create an alias for his AWS account ID. The alias should be unique.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/AccountAlias.html>

NEW QUESTION 146

A user has enabled automated backup for an RDS instance. What is the longest duration for which the user can retain the automated backup?

- A. 25 days
- B. 15 days
- C. 45 days
- D. 35 days

Answer: D

Explanation:

Amazon RDS provides two different methods for backing up and restoring the Amazon DB instances: automated backups and DB snapshots. Automated backups automatically back up the DB instance during a specific, user-definable backup window, and keep the backups for a limited, user-specified period of time. The maximum period can be 35 days.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 151

In regard to DynamoDB, for which one of the following parameters does Amazon not charge you?

- A. Cost per provisioned write units
- B. Cost per provisioned read units
- C. Storage cost
- D. I/O usage within the same Region

Answer: D

Explanation:

In DynamoDB, you will be charged for the storage and the throughput you use rather than for the I/O which has been used.

Reference: <http://aws.amazon.com/dynamodb/pricing/>

NEW QUESTION 153

What is the maximum size for messages stored in SQS?

- A. 256KB
- B. 128KB
- C. 1024KB
- D. 64KB

Answer: A

Explanation:

By default, SQS queues allow you to send the largest supported payload size, currently 256KB. You can choose to specify a limit on how many bytes can be sent per payload, using the `MaximumMessageSize` attribute of the `SetQueueAttributes` method.

Reference: <http://aws.amazon.com/sqs/faqs/>

NEW QUESTION 157

An EC2 instance has one additional EBS volume attached to it. How can a user attach the same volume to another running instance in the same AZ?

- A. Terminate the first instance and only then attach to the new instance
- B. Attach the volume as read only to the second instance
- C. Detach the volume first and attach to new instance
- D. No need to detach
- E. Just select the volume and attach it to the new instance, it will take care of mapping internally

Answer: C

Explanation:

If an EBS volume is attached to a running EC2 instance, the user needs to detach the volume from the original instance and then attach it to a new running instance. The user doesn't need to stop / terminate the original instance.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 160

A user has configured an automated backup between 5 AM — 5:30 AM for the MySQL RDS DB. Will the performance of RDS get frozen momentarily during a backup?

- A. No
- B. Yes, only if the instance size is smaller than large size
- C. Yes, provided it is a single zone implementation
- D. Yes, always

Answer: C

Explanation:

Amazon RDS provides two different methods for backing up and restoring the Amazon DB instances. A brief I/O freeze, typically lasting a few seconds, occurs during both automated backups and DB snapshot operations on Single-AZ DB instances.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 162

To scale up the AWS resources using manual AutoScaling, which of the below mentioned parameters should the user change?

- A. Maximum capacity
- B. Desired capacity
- C. Preferred capacity
- D. Current capacity

Answer: B

Explanation:

The Manual Scaling as part of Auto Scaling allows the user to change the capacity of Auto Scaling group. The user can add / remove EC2 instances on the fly. To execute manual scaling, the user should modify the desired capacity. AutoScaling will adjust instances as per the requirements. If the user is trying to CLI, he can use command `as-set-desired-capacity <Auto Scaling Group Name> --desired-capacity <New Capacity>`

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-manual-scaling.html>

NEW QUESTION 166

Does DynamoDB support in-place atomic updates?

- A. It is not defined
- B. Yes
- C. It does support in-place non-atomic updates
- D. No

Answer: B

Explanation:

DynamoDB supports in-place atomic updates. Reference:

<http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/WorkingWithItems.html#WorkingWithItems.AtomicCounters>

NEW QUESTION 170

A user is having access to objects of an S3 bucket which is not owned by him. If he is trying to set the objects of that bucket public, which of the below mentioned options may be a right fit for this action?

- A. Make the bucket public with full access
- B. Define the policy for the bucket
- C. Provide ACL on the object
- D. Create an IAM user with permission

Answer: C

Explanation:

An S3 object ACL is the only way to manage access to objects which are not owned by the bucket owner. An AWS account that owns the bucket can grant another AWS account permission to upload objects. The bucket owner does not own these objects. The AWS account that created the object must grant permissions using object ACLs.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/access-policy-alternatives-guidelines.html>

NEW QUESTION 173

A user wants to achieve High Availability with PostgreSQL DB. Which of the below mentioned functionalities helps achieve HA?

- A. Read Replica
- B. Multi AZ
- C. Multi region
- D. PostgreSQL does not support HA

Answer: B

Explanation:

The Multi AZ feature allows the user to achieve High Availability. For Multi AZ, Amazon RDS automatically provisions and maintains a synchronous "standby" replica in a different Availability Zone. Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 178

A user is launching an instance with EC2. Which of the below mentioned options does the user need to consider before launching an instance?

- A. Select the region where the instance is being launched.
- B. Select the instance type.
- C. All the options listed should be considered..
- D. Select the OS of the AM

Answer: C

Explanation:

Regarding Amazon EC2, when launching an instance, the user needs to select the region the instance would be launched from. While launching, the user needs to plan for the instance type and the OS of the instance.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-launch-instance_linux.html

NEW QUESTION 180

A user has created an EBS volume with 1000 IOPS. What is the average IOPS that the user will get for most of the year as per EC2 SLA if the instance is attached to the EBS optimized instance?

- A. 900
- B. 990
- C. 950
- D. 1000

Answer: A

Explanation:

As per AWS SLA if the instance is attached to an EBS-Optimized instance, then the Provisioned IOPS volumes are designed to deliver within 10% of the provisioned IOPS performance 99.9% of the time in a given year. Thus, if the user has created a volume of 1000 IOPS, the user will get a minimum 900 IOPS 99.9% time of the year.

Reference: <http://aws.amazon.com/ec2/faqs/>

NEW QUESTION 185

You have an environment that consists of a public subnet using Amazon VPC and 3 instances that are running in this subnet. These three instances can successfully communicate with other hosts on the Internet. You launch a fourth instance in the same subnet, using the same AMI and security group configuration you used for the others, but find that this instance cannot be accessed from the Internet. What should you do to enable internet access?

- A. Deploy a NAT instance into the public subnet.
- B. Modify the routing table for the public subnet
- C. Configure a publically routable IP Address In the host OS of the fourth instance.
- D. Assign an Elastic IP address to the fourth instanc

Answer: D

NEW QUESTION 190

Which of the following are correct statements with policy evaluation logic in AWS Identity and Access Management? Choose 2 answers

- A. By default, all requests are denied
- B. An explicit allow overrides an explicit deny
- C. An explicit allow overrides default deny.
- D. An explicit deny does not override an explicit allow
- E. By default, all request are allowed

Answer: AC

NEW QUESTION 194

Company C has recently launched an online commerce site for bicycles on AWS. They have a "Product" DynamoDB table that stores details for each bicycle, such as, manufacturer, color, price, quantity and size to display in the online store. Due to customer demand, they want to include an image for each bicycle along with the existing details.

Which approach below provides the least impact to provisioned throughput on the "Product" table?

- A. Serialize the image and store it in multiple DynamoDB tables
- B. Create an "Images" DynamoDB table to store the Image with a foreign key constraint to the "Product" table
- C. Add an image data type to the "Product" table to store the images in binary format
- D. Store the images in Amazon S3 and add an S3 URL pointer to the "Product" table item for each image

Answer: D

NEW QUESTION 199

Company D is running their corporate website on Amazon S3 accessed from <http://www.companyd.com>. Their marketing team has published new web fonts to a separate S3 bucket accessed by the S3 endpoint <https://s3-us-west1.amazonaws.com/cdfonts>. While testing the new web fonts, Company D recognized the web fonts are being blocked by the browser. What should Company D do to prevent the web fonts from being blocked by the browser?

- A. Enable versioning on the cdfonts bucket for each web font
- B. Create a policy on the cdfonts bucket to enable access to everyone
- C. Add the Content-NI D5 header to the request for webfonts in the cdfonts bucket from the website
- D. Configure the cdfonts bucket to allow cross-origin requests by creating a CORS configuration

Answer: D

NEW QUESTION 204

What is one key difference between an Amazon EBS-backed and an instance-store backed instance?

- A. Virtual Private Cloud requires EBS backed instances
- B. Amazon EBS-backed instances can be stopped and restarted
- C. Auto scaling requires using Amazon EBS-backed instances.
- D. Instance-store backed instances can be stopped and restarte

Answer: B

NEW QUESTION 209

You have written an application that uses the Elastic Load Balancing service to spread traffic to several web servers Your users complain that they are sometimes forced to login again in the middle of using your application, after they have already toggged in. This is not behavior you have designed. What is a possible solution to prevent this happening?

- A. Use instance memory to save session state.
- B. Use instance storage to save session state.
- C. Use EBS to save session state
- D. Use ElastiCache to save session state.
- E. Use Glacier to save session slat

Answer: D

NEW QUESTION 213

Company C is currently hosting their corporate site in an Amazon S3 bucket with Static Website Hosting enabled. Currently, when visitors go to <http://www.companyc.com> the index.html page is returned. Company C now would like a new page welcome.html to be returned when a visitor enters <http://www.companyc.com> in the browser.

Which of the following steps will allow Company C to meet this requirement? Choose 2 answers

- A. Upload an html page named we|come.htm| to their S3 bucket
- B. Create a welcome subfolder in their S3 bucket
- C. Set the Index Document property to welcome.html
- D. Move the index.html page to a welcome subfolder
- E. Set the Error Document property to welcome.html

Answer: AC

NEW QUESTION 216

What item operation allows the retrieval of multiple items from a DynamoDB table in a single API call?

- A. GetItem
- B. BatchGetItem
- C. GetMultipleItems
- D. GetItemRange

Answer: B

NEW QUESTION 219

An application stores payroll information nightly in DynamoDB for a large number of employees across hundreds of offices. Item attributes consist of indMdual name, office identifier, and cumulative daily hours. Managers run reports for ranges of names working in their office. One query is. "Return all Items in this office for names starting with A through E". Which table configuration will result in the lowest impact on provisioned throughput for this query?

- A. Configure the table to have a hash index on the name attribute, and a range index on the office identifier
- B. Configure the table to have a range index on the name attribute, and a hash index on the office identifier
- C. Configure a hash index on the name attribute and no range index
- D. Configure a hash index on the office Identifier attribute and no range index

Answer: B

NEW QUESTION 221

Which of the following platforms are supported by Elastic Beanstalk? Choose 2 answers

- A. Apache Tomcat
- B. .NET
- C. IBM Websphere
- D. Oracle JBoss

E. Jetty

Answer: AB

NEW QUESTION 226

Which EC2 API call would you use to retrieve a list of Amazon Machine Images (AMIs)?

- A. DescnbeInstances
- B. DescribeAMIs
- C. Describelmages
- D. GetAMIs
- E. You cannot retrieve a list of AMIs as there are over 10,000 AMIs

Answer: E

NEW QUESTION 228

When a Simple Queue Service message triggers a task that takes 5 minutes to complete, which process below will result in successful processing of the message and remove it from the queue while minimizing the chances of duplicate processing?

- A. Retrieve the message with an increased visibility timeout, process the message, delete the message from the queue
- B. Retrieve the message with an increased visibility timeout, delete the message from the queue, process the message
- C. Retrieve the message with increased DelaySeconds, process the message, delete the message from the queue
- D. Retrieve the message with increased DelaySeconds, delete the message from the queue, process the message

Answer: A

NEW QUESTION 229

What AWS products and features can be deployed by Elastic Beanstalk? Choose 3 answers

- A. Auto scaling groups
- B. Route 53 hosted zones
- C. Elastic Load Balancers
- D. RDS Instances
- E. Elastic IP addresses
- F. SQS Queues

Answer: ACD

NEW QUESTION 232

What is the maximum number of S3 Buckets available per AWS account?

- A. 100 per region
- B. there is no limit
- C. 100 per account
- D. 500 per account
- E. 100 per IAM user

Answer: C

NEW QUESTION 234

What is the format of structured notification messages sent by Amazon SNS?

- A. An XML object containing MessageId, UnsubscribeURL, Subject, IVlessage and other values
- B. An JSON object containing MessageId, DuplicateFlag, IVlessage and other values
- C. An XML object containing MessageId, DuplicateFlag, IVlessage and other values
- D. An JSON object containing MessageId, unsubscribeURL, Subject, IVlessage and other values

Answer: D

NEW QUESTION 239

Which of the following services are key/value stores? Choose 3 answers

- A. Amazon ElastiCache
- B. Simple Notification Service
- C. DynamoDB
- D. Simple Workflow Service
- E. Simple Storage Service

Answer: ABC

NEW QUESTION 244

Which of the following is chosen as the default region when making an API call with an AWS SDK?

- A. ap-northeast-1
- B. us-west-2

- C. us-east-1
- D. eu-west-1
- E. us-central-1

Answer: C

NEW QUESTION 248

What happens, by default, when one of the resources in a CloudFormation stack cannot be created?

- A. Previously-created resources are kept but the stack creation terminates.
- B. Previously-created resources are deleted and the stack creation terminates.
- C. The stack creation continues, and the final results indicate which steps failed.
- D. CloudFormation templates are parsed in advance so stack creation is guaranteed to succeed

Answer: B

NEW QUESTION 251

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your AWS-Certified-Developer-Associate Exam with Our Prep Materials Via below:

<https://www.certleader.com/AWS-Certified-Developer-Associate-dumps.html>