

AWS-SysOps Dumps

Amazon AWS Certified SysOps Administrator - Associate

<https://www.certleader.com/AWS-SysOps-dumps.html>



NEW QUESTION 1

- (Topic 1)

Your team is excited about the use of AWS because now they have access to programmable Infrastructure. You have been asked to manage your AWS infrastructure in a manner similar to the way you might manage application code. You want to be able to deploy exact copies of different versions of your infrastructure, stage changes into different environments, revert back to previous versions, and identify what versions are running at any particular time (development, test, QA, production).

Which approach addresses this requirement?

- A. Use cost allocation reports and AWS Opsworks to deploy and manage your infrastructure
- B. Use AWS CloudWatch metrics and alerts along with resource tagging to deploy and manage your infrastructure
- C. Use AWS Beanstalk and a version control system like GIT to deploy and manage your infrastructure
- D. Use AWS CloudFormation and a version control system like GIT to deploy and manage your infrastructure

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/opsworks/faqs/>

NEW QUESTION 2

- (Topic 1)

Your EC2-Based Multi-tier application includes a monitoring instance that periodically makes application-level read-only requests of various application components and if any of those fail more than three times 30 seconds calls CloudWatch to fire an alarm, and the alarm notifies your operations team by email and SMS of a possible application health problem. However, you also need to watch the watcher -the monitoring instance itself - and be notified if it becomes unhealthy.

Which of the following is a simple way to achieve that goal?

- A. Run another monitoring instance that pings the monitoring instance and fires a CloudWatch alarm that notifies your operations team should the primary monitoring instance become unhealthy
- B. Set a CloudWatch alarm based on EC2 system and instance status checks and have the alarm notify your operations team of any detected problem with the monitoring instance
- C. Set a CloudWatch alarm based on the CPU utilization of the monitoring instance and have the alarm notify your operations team if the CPU usage exceeds 50% for more than one minute; then have your monitoring application go into a CPU-bound loop should it detect any application problem
- D. Have the monitoring instances post messages to an SQS queue and then dequeue those messages on another instance should the queue cease to have new messages; the second instance should first terminate the original monitoring instance, start another backup monitoring instance, and assume the role of the previous monitoring instance and begin adding messages to the SQS queue

Answer: D

NEW QUESTION 3

- (Topic 1)

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    }
  ],
  "Principal": {
    "AWS": [
      "*"
    ]
  }
}
```

- A. Denies the server with the IP address 192.168.100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.168.100.188 full access to the "mybucket" bucket
- C. Grants all the servers within the 192.168.100.0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192.168.100.188/32 subnet full access to the "mybucket" bucket

Answer: B

NEW QUESTION 4

- (Topic 1)

A customer has a web application that uses cookie Based sessions to track logged in users It Is deployed on AWS using ELB and Auto Scaling The customer observes that when load increases. Auto Scaling launches new Instances but the load on the easting Instances does not decrease, causing all existing users to have a sluggish experience.

Which two answer choices independently describe a behavior that could be the cause of the sluggish user experience? Choose 2 answers

- A. ELB's normal behavior sends requests from the same user to the same backend instance
- B. ELB's behavior when sticky sessions are enabled causes ELB to send requests in the same session to the same backend instance
- C. A faulty browser is not honoring the TTL of the ELB DNS nam
- D. The web application uses long polling such as comet or websocket
- E. Thereby keeping a connection open to a web server tor a long time
- F. The web application uses long polling such as comet or websocket
- G. Thereby keeping a connection open to a web server for a long tim

Answer: BD

NEW QUESTION 5

- (Topic 1)

When preparing for a compliance assessment of your system built inside of AWS. what are three best-practices for you to prepare for an audit? Choose 3 answers

- A. Gather evidence of your IT operational controls
- B. Request and obtain applicable third-party audited AWS compliance reports and certifications
- C. Request and obtain a compliance and security tour of an AWS data center for a pre-assessment security review
- D. Request and obtain approval from AWS to perform relevant network scans and in-depth penetration tests of your system's Instances and endpoints
- E. Schedule meetings with AWS's third-party auditors to provide evidence of AWS compliance that maps to your control objectives

Answer: ABD

NEW QUESTION 6

- (Topic 1)

You have a web-style application with a stateless but CPU and memory-intensive web tier running on a cc2 8xlarge EC2 instance inside of a VPC The instance when under load is having problems returning requests within the SLA as defined by your business The application maintains its state in a DynamoDB table, but the data tier is properly provisioned and responses are consistently fast.

How can you best resolve the issue of the application responses not meeting your SLA?

- A. Add another cc2 8xlarge application instance, and put both behind an Elastic Load Balancer
- B. Move the cc2 8xlarge to the same Availability Zone as the DynamoDB table
- C. Cache the database responses in ElastiCache for more rapid access
- D. Move the database from DynamoDB to RDS MySQL in scale-out read-replica configuration

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/elasticmapreduce/faqs/>

NEW QUESTION 7

- (Topic 1)

You need to design a VPC for a web-application consisting of an Elastic Load Balancer (ELB). a fleet of web/application servers, and an RDS database The entire Infrastructure must be distributed over 2 availability zones.

Which VPC configuration works while assuring the database is not available from the Internet?

- A. One public subnet for ELB one public subnet for the web-servers, and one private subnet for the database
- B. One public subnet for ELB two private subnets for the web-servers, two private subnets for RDS
- C. Two public subnets for ELB two private subnets for the web-servers and two private subnets for RDS
- D. Two public subnets for ELB two public subnets for the web-servers, and two public subnets for RDS

Answer: A

NEW QUESTION 8

- (Topic 1)

You are designing a system that has a Bastion host. This component needs to be highly available without human intervention.

Which of the following approaches would you select?

- A. Run the bastion on two instances one in each AZ
- B. Run the bastion on an active Instance in one AZ and have an AMI ready to boot up in the event of failure
- C. Configure the bastion instance in an Auto Scaling group Specify the Auto Scaling group to include multiple AZs but have a min-size of 1 and max-size of 1
- D. Configure an ELB in front of the bastion instance

Answer: C

NEW QUESTION 9

- (Topic 1)

You are running a web-application on AWS consisting of the following components an Elastic Load Balancer (ELB) an Auto-Scaling Group of EC2 instances running Linux/PHP/Apache, and Relational DataBase Service (RDS) MySQL.

Which security measures fall into AWS's responsibility?

- A. Protect the EC2 instances against unsolicited access by enforcing the principle of least-privilege access
- B. Protect against IP spoofing or packet sniffing
- C. Assure all communication between EC2 instances and ELB is encrypted
- D. Install latest security patches on EL
- E. RDS and EC2 instances

Answer: B

NEW QUESTION 10

- (Topic 1)

You run a web application where web servers on EC2 Instances are In an Auto Scaling group Monitoring over the last 6 months shows that 6 web servers are necessary to handle the minimum load During the day up to 12 servers are needed Five to six days per year, the number of web servers required might go up to 15.

What would you recommend to minimize costs while being able to provide high availability?

- A. 6 Reserved instances (heavy utilization). 6 Reserved instances (medium utilization), rest covered by On-Demand instances
- B. 6 Reserved instances (heavy utilization). 6 On-Demand instances, rest covered by Spot Instances
- C. 6 Reserved instances (heavy utilization) 6 Spot instances, rest covered by On-Demand instances
- D. 6 Reserved instances (heavy utilization) 6 Reserved instances (medium utilization) rest covered by Spot instances

Answer: B

NEW QUESTION 10

- (Topic 1)

You have a web application leveraging an Elastic Load Balancer (ELB) In front of the web servers deployed using an Auto Scaling Group Your database is running on Relational

Database Service (RDS) The application serves out technical articles and responses to them in general there are more views of an article than there are responses to the article. On occasion, an article on the site becomes extremely popular resulting in significant traffic Increases that causes the site to go down.

What could you do to help alleviate the pressure on the infrastructure while maintaining availability during these events?

Choose 3 answers

- A. Leverage CloudFront for the delivery of the article
- B. Add RDS read-replicas for the read traffic going to your relational database
- C. Leverage ElastiCache for caching the most frequently used data
- D. Use SQS to queue up the requests for the technical posts and deliver them out of the queue
- E. Use Route53 health checks to fail over to an S3 bucket for an error page

Answer: ACE

NEW QUESTION 11

- (Topic 1)

An application that you are managing has EC2 instances & DynamoDB tables deployed to several AWS Regions In order to monitor the performance of the application globally, you would like to see two graphs 1) Avg CPU Utilization across all EC2 instances and 2) Number of Throttled Requests for all DynamoDB tables.

How can you accomplish this?

- A. Tag your resources with the application name, and select the tag name as the dimension in the Cloudwatch Management console to view the respective graphs
- B. Use the Cloud Watch CLI tools to pull the respective metrics from each regional endpoint Aggregate the data offline & store it for graphing in CloudWatch
- C. Add SNMP traps to each instance and DynamoDB table Leverage a central monitoring server to capture data from each instance and table Put the aggregate data into Cloud Watch for graphing
- D. Add a CloudWatch agent to each instance and attach one to each DynamoDB table
- E. When configuring the agent set the appropriate application name & view the graphs in CloudWatch

Answer: C

NEW QUESTION 15

- (Topic 1)

If you want to launch Amazon Elastic Compute Cloud (EC2) Instances and assign each Instance a predetermined private IP address you should:

- A. Assign a group or sequential Elastic IP address to the instances
- B. Launch the instances in a Placement Group
- C. Launch the instances in the Amazon virtual Private Cloud (VPC).
- D. Use standard EC2 instances since each instance gets a private Domain Name Service (DNS) already
- E. Launch the Instance from a private Amazon Machine image (AMI)

Answer: C

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-ip-addressing.html>

NEW QUESTION 19

- (Topic 1)

Your company is moving towards tracking web page users with a small tracking

image loaded on each page Currently you are serving this image out of US-East, but are starting to get concerned about the time it takes to load the image for users on the west coast.

What are the two best ways to speed up serving this image?

Choose 2 answers

- A. Use Route 53's Latency Based Routing and serve the image out of US-West-2 as well as US-East-1
- B. Serve the image out through CloudFront
- C. Serve the image out of S3 so that it isn't being served out of your web application tier
- D. Use EBS PIOPs to serve the image faster out of your EC2 instances

Answer: AD

NEW QUESTION 21

- (Topic 1)

You receive a frantic call from a new DBA who accidentally dropped a table containing all your customers.

Which Amazon RDS feature will allow you to reliably restore your database to within 5 minutes of when the mistake was made?

- A. Multi-AZ RDS
- B. RDS snapshots
- C. RDS read replicas
- D. RDS automated backup

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 25

- (Topic 1)

Which two AWS services provide out-of-the-box user configurable automatic backup-as-a-service and backup rotation options?

Choose 2 answers

- A. Amazon S3
- B. Amazon RDS
- C. Amazon EBS
- D. Amazon Red shift

Answer: BD

NEW QUESTION 30

- (Topic 1)

What are characteristics of Amazon S3? Choose 2 answers

- A. Objects are directly accessible via a URL
- B. S3 should be used to host a relational database
- C. S3 allows you to store objects of virtually unlimited size
- D. S3 allows you to store virtually unlimited amounts of data
- E. S3 offers Provisioned IOPS

Answer: AD

NEW QUESTION 33

- (Topic 2)

A user is accessing RDS from an application. The user has enabled the Multi AZ feature with the MS SQL RDS DB. During a planned outage how will AWS ensure that a switch from DB to a standby replica will not affect access to the application?

- A. RDS will have an internal IP which will redirect all requests to the new DB
- B. RDS uses DNS to switch over to stand by replica for seamless transition
- C. The switch over changes Hardware so RDS does not need to worry about access
- D. RDS will have both the DBs running independently and the user has to manually switch over

Answer: B

Explanation:

In the event of a planned or unplanned outage of a DB instance, Amazon RDS automatically switches to a standby replica in another Availability Zone if the user has enabled Multi AZ. The automatic failover mechanism simply changes the DNS record of the DB instance to point to the standby DB instance. As a result, the user will need to re-establish any existing connections to the DB instance. However, as the DNS is the same, the application can access DB seamlessly.

NEW QUESTION 34

- (Topic 2)

A user wants to disable connection draining on an existing ELB. Which of the below mentioned statements helps the user disable connection draining on the ELB?

- A. The user can only disable connection draining from CLI
- B. It is not possible to disable the connection draining feature once enabled
- C. The user can disable the connection draining feature from EC2 -> ELB console or from CLI
- D. The user needs to stop all instances before disabling connection draining

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can enable or disable connection draining from the AWS EC2 console -> ELB or using CLI.

NEW QUESTION 37

- (Topic 2)

You are managing the AWS account of a big organization. The organization has more than 1000+ employees and they want to provide access to the various services to most of the employees. Which of the below mentioned options is the best possible solution in this case?

- A. The user should create a separate IAM user for each employee and provide access to them as per the policy
- B. The user should create an IAM role and attach STS with the rol
- C. The user should attach that role to the EC2 instance and setup AWS authentication on that server
- D. The user should create IAM groups as per the organization's departments and add each user to the group for better access control
- E. Attach an IAM role with the organization's authentication service to authorize each user for various AWS services

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user is managing an AWS account for an organization that already has an identity system, such as the login system for the corporate network (SSO.. In this case, instead of creating individual IAM users or groups for each user who need AWS access, it may be more practical to use a proxy server to translate the user identities from the organization network into the temporary AWS security credentials. This proxy server will attach an IAM role to the user after authentication.

NEW QUESTION 38

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24. and VPN only subnets CIDR (20.0.1.0/24. along with the VPN gateway (vgw-12345. to connect to the user's data centre. Which of the below mentioned options is a valid entry for the main route table in this scenario?

- A. Destination: 20.0.0.0/24 and Target: vgw-12345
- B. Destination: 20.0.0.0/16 and Target: ALL
- C. Destination: 20.0.1.0/16 and Target: vgw-12345
- D. Destination: 0.0.0.0/0 and Target: vgw-12345

Answer: D

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. Here are the valid entries for the main route table in this scenario: Destination: 0.0.0.0/0 & Target: vgw-12345 (To route all internet traffic to the VPN gateway. Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC.

NEW QUESTION 43

- (Topic 2)

A system admin is managing buckets, objects and folders with AWS S3. Which of the below mentioned statements is true and should be taken in consideration by the sysadmin?

- A. The folders support only ACL
- B. Both the object and bucket can have an Access Policy but folder cannot have policy
- C. Folders can have a policy
- D. Both the object and bucket can have ACL but folders cannot have ACL

Answer: A

Explanation:

A sysadmin can grant permission to the S3 objects or the buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice a versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level. The folders are similar to objects with no content. Thus, folders can have only ACL and cannot have a policy.

NEW QUESTION 47

- (Topic 2)

A user has created an ELB with the availability zone US-East-1A. The user wants to add more zones to ELB to achieve High Availability. How can the user add more zones to the existing ELB?

- A. It is not possible to add more zones to the existing ELB
- B. The only option is to launch instances in different zones and add to ELB
- C. The user should stop the ELB and add zones and instances as required
- D. The user can add zones on the fly from the AWS console

Answer: D

Explanation:

The user has created an Elastic Load Balancer with the availability zone and wants to add more zones to the existing ELB. The user can do so in two ways:

From the console or CLI, add new zones to ELB;
Launch instances in a separate AZ and add instances to the existing ELB.

NEW QUESTION 52

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created public and VPN only subnets along with hardware VPN access to connect to the user's datacenter. The user wants to make so that all traffic coming to the public subnet follows the organization's proxy policy. How can the user make this happen?

- A. Setting up a NAT with the proxy protocol and configure that the public subnet receives traffic from NAT
- B. Settin up a proxy policy in the internet gateway connected with the public subnet
- C. It is not possible to setup the proxy policy for a public subnet
- D. Setting the route table and security group of the public subnet which receives traffic from a virtual private gateway

Answer: D

Explanation:

The user can create subnets within a VPC. If the user wants to connect to VPC from his own data centre, he can setup public and VPN only subnets which uses hardware VPN access to connect with his data centre. When the user has configured this setup, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. By default the internet traffic of the VPN subnet is routed to a virtual private gateway while the internet traffic of the public subnet is routed through the internet gateway. The user can set up the route and security group rules. These rules enable the traffic to come from the organization's network over the virtual private gateway to the public subnet to allow proxy settings on that public subnet.

NEW QUESTION 53

- (Topic 2)

A sys admin is maintaining an application on AWS. The application is installed on EC2 and user has configured ELB and Auto Scaling. Considering future load increase, the user is planning to launch new servers proactively so that they get registered with ELB. How can the user add these instances with Auto Scaling?

- A. Increase the desired capacity of the Auto Scaling group
- B. Increase the maximum limit of the Auto Scaling group
- C. Launch an instance manually and register it with ELB on the fly
- D. Decrease the minimum limit of the Auto Scaling grou

Answer: A

Explanation:

A user can increase the desired capacity of the Auto Scaling group and Auto Scaling will launch a new instance as per the new capacity. The newly launched instances will be registered with ELB if Auto Scaling group is configured with ELB. If the user decreases the minimum size the instances will be removed from Auto Scaling. Increasing the maximum size will not add instances but only set the maximum instance cap.

NEW QUESTION 56

- (Topic 2)

A user has created a photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Glacier
- B. AWS Elastic Transcoder
- C. AWS Simple Notification Service
- D. AWS Simple Queue Service

Answer: D

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

NEW QUESTION 59

- (Topic 2)

A user is planning to use AWS Cloud formation for his automatic deployment requirements. Which of the below mentioned components are required as a part of the template?

- A. Parameters
- B. Outputs
- C. Template version
- D. Resources

Answer: D

Explanation:

AWS Cloud formation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. It can have option fields, such as Template Parameters, Output, Data tables, and Template file format version. The only mandatory value is Resource. The user can define the AWS services which will be used/ created by this template inside the Resource section

NEW QUESTION 61

- (Topic 2)

A user has setup a billing alarm using CloudWatch for \$200. The usage of AWS exceeded \$200 after some days. The user wants to increase the limit from \$200 to \$400? What should the user do?

- A. Create a new alarm of \$400 and link it with the first alarm
- B. It is not possible to modify the alarm once it has crossed the usage limit
- C. Update the alarm to set the limit at \$400 instead of \$200
- D. Create a new alarm for the additional \$200 amount

Answer: C

Explanation:

AWS CloudWatch supports enabling the billing alarm on the total AWS charges. The estimated charges are calculated and sent several times daily to CloudWatch in the form of metric data. This data will be stored for 14 days. This data also includes the estimated charges for every service in AWS used by the user, as well as the estimated overall AWS charges. If the user wants to increase the limit, the user can modify the alarm and specify a new threshold.

NEW QUESTION 65

- (Topic 2)

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department's employees

Answer: A

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

NEW QUESTION 66

- (Topic 2)

An organization is planning to use AWS for their production roll out. The organization wants to implement automation for deployment such that it will automatically create a LAMP stack, download the latest PHP installable from S3 and setup the ELB. Which of the below mentioned AWS services meets the requirement for making an orderly deployment of the software?

- A. AWS Elastic Beanstalk
- B. AWS Cloudfront
- C. AWS CloudFormation
- D. AWS DevOps

Answer: C

Explanation:

AWS CloudFormation is an application management tool which provides application modelling, deployment, configuration, management and related activities. CloudFormation provides an easy way to create and delete the collection of related AWS resources and provision them in an orderly way. AWS CloudFormation automates and simplifies the task of repeatedly and predictably creating groups of related resources that power the user's applications. AWS Cloudfront is a CDN; Elastic Beanstalk does quite a few of the required tasks. However, it is a PAAS which uses a ready AMI. AWS Elastic Beanstalk provides an environment to easily develop and run applications in the cloud.

NEW QUESTION 70

- (Topic 2)

A user has launched an ELB which has 5 instances registered with it. The user deletes the ELB by mistake. What will happen to the instances?

- A. ELB will ask the user whether to delete the instances or not
- B. Instances will be terminated
- C. ELB cannot be deleted if it has running instances registered with it
- D. Instances will keep running

Answer: D

Explanation:

When the user deletes the Elastic Load Balancer, all the registered instances will be deregistered. However, they will continue to run. The user will incur charges if he does not take any action on those instances.

NEW QUESTION 75

- (Topic 2)

A user has configured Elastic Load Balancing by enabling a Secure Socket Layer (SSL) negotiation configuration known as a Security Policy. Which of the below mentioned options is not part of this secure policy while negotiating the SSL connection between the

user and the client?

- A. SSL Protocols
- B. Client Order Preference
- C. SSL Ciphers
- D. Server Order Preference

Answer: B

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. A security policy is a combination of SSL Protocols, SSL Ciphers, and the Server Order Preference option.

NEW QUESTION 77

- (Topic 2)

A user is checking the CloudWatch metrics from the AWS console. The user notices that the CloudWatch data is coming in UTC. The user wants to convert the data to a local time zone. How can the user perform this?

- A. In the CloudWatch dashboard the user should set the local timezone so that CloudWatch shows the data only in the local time zone
- B. In the CloudWatch console select the local timezone under the Time Range tab to view the data as per the local timezone
- C. The CloudWatch data is always in UTC; the user has to manually convert the data
- D. The user should have send the local timezone while uploading the data so that CloudWatch will show the data only in the local timezone

Answer: B

Explanation:

If the user is viewing the data inside the CloudWatch console, the console provides options to filter values either using the relative period, such as days/hours or using the Absolute tab where the user can provide data with a specific date and time. The console also provides the option to search using the local timezone under the time range caption in the console because the time range tab allows the user to change the time zone.

NEW QUESTION 81

- (Topic 2)

A user has created a queue named “myqueue” with SQS. There are four messages published to queue which are not received by the consumer yet. If the user tries to delete the queue, what will happen?

- A. A user can never delete a queue manual
- B. AWS deletes it after 30 days of inactivity on queue
- C. It will delete the queue
- D. It will initiate the delete but wait for four days before deleting until all messages are deleted automaticall
- E. I t will ask user to delete the messages first

Answer: B

Explanation:

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. The user can delete a queue at any time, whether it is empty or not. It is important to note that queues retain messages for a set period of time. By default, a queue retains messages for four days.

NEW QUESTION 83

- (Topic 2)

A root account owner has created an S3 bucket testmycloud. The account owner wants to allow everyone to upload the objects as well as enforce that the person who uploaded the object should manage the permission of those objects. Which is the easiest way to achieve this?

- A. The root account owner should create a bucket policy which allows the IAM users to upload the object
- B. The root account owner should create the bucket policy which allows the other account owners to set the object policy of that bucket
- C. The root account should use ACL with the bucket to allow everyone to upload the object
- D. The root account should create the IAM users and provide them the permission to upload content to the bucket

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List) associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3-specific XML schema. The user cannot grant permissions to other users in his account. ACLs are suitable for specific scenarios. For example, if a bucket owner allows other AWS accounts to upload objects, permissions to these objects can only be managed using the object ACL by the AWS account that owns the object.

NEW QUESTION 86

- (Topic 2)

A user has configured ELB with two EBS backed EC2 instances. The user is trying to understand the DNS access and IP support for ELB. Which of the below mentioned statements may not help the user understand the IP mechanism supported by ELB?

- A. The client can connect over IPV4 or IPV6 using Dualstack
- B. ELB DNS supports both IPV4 and IPV6
- C. Communication between the load balancer and back-end instances is always through IPV4
- D. The ELB supports either IPV4 or IPV6 but not both

Answer: D

Explanation:

Elastic Load Balancing supports both Internet Protocol version 6 (IPv6, and Internet Protocol version 4 (IPv4.. Clients can connect to the user's load balancer using either IPv4 or IPv6 (in EC2-Classic. DNS. However, communication between the load balancer and its back-end instances uses only IPv4. The user can use the Dualstack-prefixed DNS name to enable IPv6 support for communications between the client and the load balancers. Thus, the clients are able to access the load balancer using either IPv4 or IPv6 as their individual connectivity needs dictate.

NEW QUESTION 89

- (Topic 2)

A user has setup a CloudWatch alarm on an EC2 action when the CPU utilization is above 75%. The alarm sends a notification to SNS on the alarm state. If the user wants to simulate the alarm action how can he achieve this?

- A. Run activities on the CPU such that its utilization reaches above 75%
- B. From the AWS console change the state to 'Alarm'
- C. The user can set the alarm state to 'Alarm' using CLI
- D. Run the SNS action manually

Answer: C

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can test an alarm by setting it to any state using the SetAlarmState API (mon-set-alarm-state command.. This temporary state change lasts only until the next alarm comparison occurs.

NEW QUESTION 90

- (Topic 2)

A user has enabled detailed CloudWatch metric monitoring on an Auto Scaling group. Which of the below mentioned metrics will help the user identify the total number of instances in an Auto Scaling group cluding pending, terminating and running instances?

- A. GroupTotalInstances
- B. GroupSumInstances
- C. It is not possible to get a count of all the three metrics togethe
- D. The user has to find the individual number of running, terminating and pending instances and sum it
- E. GroupInstancesCount

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For Auto Scaling, CloudWatch provides various metrics to get the group information, such as the Number of Pending, Running or Terminating instances at any moment. If the user wants to get the total number of Running, Pending and Terminating instances at any moment, he can use the GroupTotalInstances metric.

NEW QUESTION 95

- (Topic 2)

A user has setup a web application on EC2. The user is generating a log of the application performance at every second. There are multiple entries for each second. If the user wants to send that data to CloudWatch every minute, what should he do?

- A. The user should send only the data of the 60th second as CloudWatch will map the receive data timezone with the sent data timezone
- B. It is not possible to send the custom metric to CloudWatch every minute
- C. Give CloudWatch the Min, Max, Sum, and SampleCount of a number of every minute
- D. Calculate the average of one minute and send the data to CloudWatch

Answer: C

Explanation:

Amazon CloudWatch aggregates statistics according to the period length that the user has specified while getting data from CloudWatch. The user can publish as many data points as he wants with the same or similartime stamps. CloudWatch aggregates them by the period length when the user calls get statistics about those data points. CloudWatch records the average (sum of all items divided by the number of items. of the values received for every 1-minute period, as well as the number of samples, maximum value, and minimum value for the same time period. CloudWatch will aggregate all the data which have time stamps within a one-minute period.

NEW QUESTION 99

- (Topic 2)

A user has launched a large EBS backed EC2 instance in the US-East-1a region. The user wants to achieve Disaster Recovery (DR. for that instance by creating another small instance in Europe. How can the user achieve DR?

- A. Copy the running instance using the "Instance Copy" command to the EU region
- B. Create an AMI of the instance and copy the AMI to the EU regio
- C. Then launch the instance from the EU AMI
- D. Copy the instance from the US East region to the EU region
- E. Use the "Launch more like this" option to copy the instance from one region to another

Answer: B

Explanation:

To launch an EC2 instance it is required to have an AMI in that region. If the AMI is not available in that region, then create a new AMI or use the copy command to copy the AMI from one region to the other region.

NEW QUESTION 101

- (Topic 2)

A user has configured the Auto Scaling group with the minimum capacity as 3 and the maximum capacity as 5. When the user configures the AS group, how many instances will Auto Scaling launch?

- A. 3
- B. 0
- C. 5
- D. 2

Answer: C

NEW QUESTION 105

- (Topic 2)

An organization, which has the AWS account ID as 999988887777, has created 50 IAM users. All the users are added to the same group cloudacademy. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use?

- A. [https:// 999988887777.signin.aws.amazon.com/console/](https://999988887777.signin.aws.amazon.com/console/)
- B. [https:// signin.aws.amazon.com/cloudacademy/](https://signin.aws.amazon.com/cloudacademy/)
- C. [https:// cloudacademy.signin.aws.amazon.com/999988887777/console/](https://cloudacademy.signin.aws.amazon.com/999988887777/console/)
- D. [https:// 999988887777.aws.amazon.com/ cloudacademy/](https://999988887777.aws.amazon.com/cloudacademy/)

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be [https:// AWS_Account_ID.signin.aws.amazon.com/console/](https://AWS_Account_ID.signin.aws.amazon.com/console/). It uses only the AWS account ID and does not depend on the group or user ID.

NEW QUESTION 108

- (Topic 2)

An organization is using AWS since a few months. The finance team wants to visualize the pattern of AWS spending. Which of the below AWS tool will help for this requirement?

- A. AWS Cost Manager
- B. AWS Cost Explorer
- C. AWS CloudWatch
- D. AWS Consolidated Billing

Answer: B

Explanation:

The AWS Billing and Cost Management console includes the Cost Explorer tool for viewing AWS cost data as a graph. It does not charge extra to user for this service. With Cost Explorer the user can filter graphs using resource tags or with services in AWS. If the organization is using Consolidated Billing it helps generate report based on linked accounts. This will help organization to identify areas that require further inquiry. The organization can view trends and use that to understand spend and to predict future costs.

NEW QUESTION 113

- (Topic 2)

A user is trying to delete an Auto Scaling group from CLI. Which of the below mentioned steps are to be performed by the user?

- A. Terminate the instances with the `ec2-terminate-instance` command
- B. Terminate the Auto Scaling instances with the `as-terminate-instance` command
- C. Set the minimum size and desired capacity to 0
- D. There is no need to change the capacity
- E. Run the `as-delete-group` command and it will reset all values to 0

Answer: C

Explanation:

If the user wants to delete the Auto Scaling group, the user should manually set the values of the minimum and desired capacity to 0. Otherwise Auto Scaling will not allow for the deletion of the group from CLI. While trying from the AWS console, the user need not set the values to 0 as the Auto Scaling console will automatically do so.

NEW QUESTION 116

- (Topic 2)

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. Email JSON
- B. HTTP

- C. AWS SQS
- D. AWS SES

Answer: D

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", "and SMS".

NEW QUESTION 117

- (Topic 2)

A user has configured a VPC with a new subnet. The user has created a security group. The user wants to configure that instances of the same subnet communicate with each other. How can the user configure this with the security group?

- A. There is no need for a security group modification as all the instances can communicate with each other inside the same subnet
- B. Configure the subnet as the source in the security group and allow traffic on all the protocols and ports
- C. Configure the security group itself as the source and allow traffic on all the protocols and ports
- D. The user has to use VPC peering to configure this

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level. If the user is using the default security group it will have a rule which allows the instances to communicate with other. For a new security group the user has to specify the rule, add it to define the source as the security group itself, and select all the protocols and ports for that source.

NEW QUESTION 121

- (Topic 2)

A user has launched two EBS backed EC2 instances in the US-East-1a region. The user wants to change the zone of one of the instances. How can the user change it?

- A. Stop one of the instances and change the availability zone
- B. The zone can only be modified using the AWS CLI
- C. From the AWS EC2 console, select the Actions - > Change zones and specify new zone
- D. Create an AMI of the running instance and launch the instance in a separate AZ

Answer: D

Explanation:

With AWS EC2, when a user is launching an instance he can select the availability zone (AZ) at the time of launch. If the zone is not selected, AWS selects it on behalf of the user. Once the instance is launched, the user cannot change the zone of that instance unless he creates an AMI of that instance and launches a new instance from it.

NEW QUESTION 123

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25 and a private subnet with CIDR 20.0.0.128/25. The user has launched one instance each in the private and public subnets. Which of the below mentioned options cannot be the correct IP address (private IP) assigned to an instance in the public or private subnet?

- A. 20.0.0.255
- B. 20.0.0.132
- C. 20.0.0.122
- D. 20.0.0.55

Answer: A

Explanation:

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. In this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255). The public subnet will have IP addresses between 20.0.0.0 - 20.0.0.127 and the private subnet will have IP addresses between 20.0.0.128 - 20.0.0.255. AWS reserves the first four IP addresses and the last IP address in each subnet's CIDR block. These are not available for the user to use. Thus, the instance cannot have an IP address of 20.0.0.255

NEW QUESTION 124

- (Topic 3)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment if the primary DB instance fails?

- A. The IP of the primary DB Instance is switched to the standby DB Instance
- B. A new DB instance is created in the standby availability zone
- C. The canonical name record (CNAME) is changed from primary to standby
- D. The RDS (Relational Database Service) DB instance reboots

Answer: D

Explanation:

Reference:

http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_RebootInstance.html**NEW QUESTION 129**

- (Topic 3)

A user has launched an EC2 Windows instance from an instance store backed AMI. The user wants to convert the AMI to an EBS backed AMI. How can the user convert it?

- A. Attach an EBS volume to the instance and unbundle all the AMI bundled data inside the EBS
- B. A Windows based instance store backed AMI cannot be converted to an EBS backed AMI
- C. It is not possible to convert an instance store backed AMI to an EBS backed AMI
- D. Attach an EBS volume and use the copy command to copy all the ephemeral content to the EBS Volume

Answer: B**Explanation:**

Generally when a user has launched an EC2 instance from an instance store backed AMI, it can be converted to an EBS backed AMI provided the user has attached the EBS volume to the instance and unbundles the AMI data to it. However, if the instance is a Windows instance, AWS does not allow this. In this case, since the instance is a Windows instance, the user cannot convert it to an EBS backed AMI.

NEW QUESTION 133

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/24. The user has used all the IPs of CIDR and wants to increase the size of the VPC. The user has two subnets: public (20.0.0.0/28. and private (20.0.1.0/28.. How can the user change the size of the VPC?

- A. The user can delete all the instances of the subne
- B. Change the size of the subnets to 20.0.0.0/32 and 20.0.1.0/32, respective
- C. Then the user can increase the size of the VPC using CLI
- D. It is not possible to change the size of the VPC once it has been created
- E. The user can add a subnet with a higher range so that it will automatically increase the size of the VPC
- F. The user can delete the subnets first and then modify the size of the VPC

Answer: B**Explanation:**

Once the user has created a VPC, he cannot change the CIDR of that VPC. The user has to terminate all the instances, delete the subnets and then delete the VPC. Create a new VPC with a higher size and launch instances with the newly created VPC and subnets.

NEW QUESTION 134

- (Topic 3)

A user has launched an EC2 instance store backed instance in the US-East-1a zone. The user created AMI #1 and copied it to the Europe region. After that, the user made a few updates to the application running in the US-East-1a zone. The user makes an AMI#2 after the changes. If the user launches a new instance in Europe from the AMI #1 copy, which of the below mentioned statements is true?

- A. The new instance will have the changes made after the AMI copy as AWS just copies the reference of the original AMI during the copyin
- B. Thus, the copied AMI will have all the updated data
- C. The new instance will have the changes made after the AMI copy since AWS keeps updating the AMI
- D. It is not possible to copy the instance store backed AMI from one region to another
- E. The new instance in the EU region will not have the changes made after the AMI copy

Answer: D**Explanation:**

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source. AMI. The user can modify the source AMI without affecting the new AMI and vice a versa. Therefore, in this case even if the source AMI is modified, the copied AMI of the EU region will not have the changes. Thus, after copy the user needs to copy the new source AMI to the destination region to get those changes.

NEW QUESTION 135

- (Topic 3)

An AWS account owner has setup multiple IAM users. One IAM user only has CloudWatch access. He has setup the alarm action which stops the EC2 instances when the CPU utilization is below the threshold limit. What will happen in this case?

- A. It is not possible to stop the instance using the CloudWatch alarm
- B. CloudWatch will stop the instance when the action is executed
- C. The user cannot set an alarm on EC2 since he does not have the permission
- D. The user can setup the action but it will not be executed if the user does not have EC2 rights

Answer: D**Explanation:**

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup an action which stops the instances when their CPU utilization is below a certain threshold for a certain period of time. The EC2 action can either terminate or stop the instance as part of the EC2 action. If the IAM user has read/write permissions for Amazon CloudWatch but not for Amazon EC2, he can still create an alarm. However, the stop or terminate actions will not be performed on the

Amazon EC2 instance.

NEW QUESTION 136

- (Topic 3)

When an EC2 instance mat is backed by an S3-Dased AML is terminated, what happens to the data on the root volume?

- A. Data is automatically deleted
- B. Data is automatically saved as an EBS snapsho
- C. Data is unavailable until the instance is restarted
- D. Data is automatically saved as an EBS volum

Answer: A

NEW QUESTION 140

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. Which of the below mentioned statements is true in this scenario?

- A. The AWS VPC will automatically create a NAT instance with the micro size
- B. VPC bounds the main route table with a private subnet and a custom route table with a public subnet
- C. The user has to manually create a NAT instance
- D. VPC bounds the main route table with a public subnet and a custom route table with a private subnet

Answer: B

Explanation:

A Virtual Private Cloud (VPC. is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance of a smaller or higher size, respectively. The VPC has an implied router and the VPC wizard updates the main route table used with the private subnet, creates a custom route table and associates it with the public subnet.

NEW QUESTION 142

- (Topic 3)

A user has setup a CloudWatch alarm on the EC2 instance for CPU utilization. The user has setup to receive a notification on email when the CPU utilization is higher than 60%. The user is running a virus scan on the same instance at a particular time. The user wants to avoid receiving an email at this time. What should the user do?

- A. Remove the alarm
- B. Disable the alarm for a while using CLI
- C. Modify the CPU utilization by removing the email alert
- D. Disable the alarm for a while using the console

Answer: B

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. When the user has setup an alarm and it is know that for some unavoidable event the status may change to Alarm, the user can disable the alarm using the DisableAlarmActions API or from the command line mon-disable-alarm-actions.

NEW QUESTION 143

- (Topic 3)

A user is having data generated randomly based on a certain event. The user wants to upload that data to CloudWatch. It may happen that event may not have data generated for some period due to andomness. Which of the below mentioned options is a recommended option for this case?

- A. For the period when there is no data, the user should not send the data at all
- B. For the period when there is no data the user should send a blank value
- C. For the period when there is no data the user should send the value as 0
- D. The user must upload the data to CloudWatch as having no data for some period will cause an error at CloudWatch monitoring

Answer: C

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. When the user data is more random and not generated at regular intervals, there can be a period which has no associated data. The user can either publish the zero (0. Value for that period or not publish the data at all. It is recommended that the user should publish zero instead of no value to monitor the health of the application. This is helpful in an alarm as well as in the generation of the sample data count.

NEW QUESTION 147

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. The VPC has CIDR 20.0.0.0/16. The private subnet uses CIDR 20.0.0.0/24 . The NAT instance ID is i-a12345. Which of the below mentioned entries are required in the main route table attached with the private subnet to allow instances to connect with the internet?

- A. Destination: 0.0.0.0/0 and Target: i-a12345

- B. Destination: 20.0.0.0/0 and Target: 80
- C. Destination: 20.0.0.0/0 and Target: i-a12345
- D. Destination: 20.0.0.0/24 and Target: i-a12345

Answer: A

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create two route tables and attach to the subnets. The main route table will have the entry “Destination: 0.0.0.0/0 and Target: ia12345”, which allows all the instances in the private subnet to connect to the internet using NAT.

NEW QUESTION 150

- (Topic 3)

You have a proprietary data store on-premises that must be backed up daily by dumping the data store contents to a single compressed 50GB file and sending the file to AWS. Your SLAs state that any dump file backed up within the past 7 days can be retrieved within 2 hours. Your compliance department has stated that all data must be held indefinitely. The time required to restore the data store from a backup is approximately 1 hour. Your on-premise network connection is capable of sustaining 1gbps to AWS.

Which backup methods to AWS would be most cost-effective while still meeting all of your requirements?

- A. Send the daily backup files to Glacier immediately after being generated
- B. Transfer the daily backup files to an EBS volume in AWS and take daily snapshots of the volume
- C. Transfer the daily backup files to S3 and use appropriate bucket lifecycle policies to send to Glacier
- D. Host the backup files on a Storage Gateway with Gateway-Cached Volumes and take daily snapshots

Answer: D

Explanation:

Reference:

<http://aws.amazon.com/storagegateway/faqs/>

NEW QUESTION 153

- (Topic 3)

A user is collecting 1000 records per second. The user wants to send the data to CloudWatch using the custom namespace. Which of the below mentioned options is recommended for this activity?

- A. Aggregate the data with statistics, such as Min, max, Average, Sum and Sample data and send the data to CloudWatch
- B. Send all the data values to CloudWatch in a single command by separating them with a comm
- C. CloudWatch will parse automatically
- D. Create one csv file of all the data and send a single file to CloudWatch
- E. It is not possible to send all the data in one cal
- F. Thus, it should be sent one by on
- G. CloudWatch will aggregate the data automatically

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put-metric-data. It is recommended that when the user is having multiple data points per minute, he should aggregate the data so that it will minimize the number of calls to put-metric-data. In this case it will be single call to CloudWatch instead of 1000 calls if the data is aggregated.

NEW QUESTION 155

- (Topic 3)

Which services allow the customer to retain run administrative privileges or the underlying EC2 instances? Choose 2 answers

- A. AWS Elastic Beanstalk
- B. Amazon Elastic Map Reduce
- C. Elastic Load Balancing
- D. Amazon Relational Database Service
- E. Amazon Elasti Cache

Answer: AB

NEW QUESTION 156

- (Topic 3)

A root account owner has given full access of his S3 bucket to one of the IAM users using the bucket ACL. When the IAM user logs in to the S3 console, which actions can he perform?

- A. He can just view the content of the bucket
- B. He can do all the operations on the bucket
- C. It is not possible to give access to an IAM user using ACL
- D. The IAM user can perform all operations on the bucket using only API/SDK

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List. associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3–specific XML schema. The user cannot grant permissions to other users (IAM users. in his account.

NEW QUESTION 159

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AlarmNotification (which notifies Auto Scaling for CloudWatch alarms. process for a while. What will Auto Scaling do during this period?

- A. AWS will not receive the alarms from CloudWatch
- B. AWS will receive the alarms but will not execute the Auto Scaling policy
- C. Auto Scaling will execute the policy but it will not launch the instances until the process is resumed
- D. It is not possible to suspend the AlarmNotification process

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate Alarm Notification etc. The user can also suspend individual process. The AlarmNotification process type accepts notifications from the Amazon CloudWatch alarms that are associated with the Auto Scaling group. If the user suspends this process type, Auto Scaling will not automatically execute the scaling policies that would be triggered by the alarms.

NEW QUESTION 163

- (Topic 3)

A user runs the command “dd if=/dev/zero of=/dev/xvdfbs=1M” on a fresh blank EBS volume attached to a Linux instance. Which of the below mentioned activities is the user performing with the command given above?

- A. Creating a file system on the EBS volume
- B. Mounting the device to the instance
- C. Pre warming the EBS volume
- D. Formatting the EBS volume

Answer: C

Explanation:

When the user creates a new EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a blank volume attached with a Linux OS, the “dd” command is used to write to all the blocks on the device. In the command “dd if=/dev/zero of=/dev/xvdfbs=1M” the parameter “if =import file” should be set to one of the Linux virtual devices, such as /dev/zero. The “of=output file” parameter should be set to the drive that the user wishes to warm. The “bs” parameter sets the block size of the write operation; for optimal performance, this should be set to 1 MB.

NEW QUESTION 166

- (Topic 3)

A user is configuring a CloudWatch alarm on RDS to receive a notification when the CPU utilization of RDS is higher than 50%. The user has setup an alarm when there is some inactivity on RDS, such as RDS unavailability. How can the user configure this?

- A. Setup the notification when the CPU is more than 75% on RDS
- B. Setup the notification when the state is Insufficient Data
- C. Setup the notification when the CPU utilization is less than 10%
- D. It is not possible to setup the alarm on RDS

Answer: B

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The alarm has three states: Alarm, OK and Insufficient data. The Alarm will change to Insufficient Data when any of the three situations arise: when the alarm has just started, when the metric is not available or when enough data is not available for the metric to determine the alarm state. If the user wants to find that RDS is not available, he can setup to receive the notification when the state is in Insufficient data.

NEW QUESTION 167

- (Topic 3)

A user is trying to understand the detailed CloudWatch monitoring concept. Which of the below mentioned services provides detailed monitoring with CloudWatch without charging the user extra?

- A. AWS Auto Scaling
- B. AWS Route 53
- C. AWS EMR
- D. AWS SNS

Answer: B

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Services, such as RDS, ELB, OpsWorks, and Route 53 can provide the monitoring data every minute without charging the user.

NEW QUESTION 172

- (Topic 3)

An organization (account ID 123412341234. has configured the IAM policy to allow the user to modify his credentials. What will the below mentioned statement allow the user to perform?

```
{
"Version": "2012-10-17",
"Statement": [{
"Effect": "Allow",
"Action": [
"iam:AddUserToGroup",
"iam:RemoveUserFromGroup",
"iam:GetGroup"
],
"Resource": "arn:aws:iam:: 123412341234:group/TestingGroup"
}]
}
```

- A. The IAM policy will throw an error due to an invalid resource name
- B. The IAM policy will allow the user to subscribe to any IAM group
- C. Allow the IAM user to update the membership of the group called TestingGroup
- D. Allow the IAM user to delete the TestingGroup

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (account ID 123412341234. wants their users to manage their subscription to the groups, they should create a relevant policy for that. The below mentioned policy allows the respective IAM user to update the membership of the group called MarketingGroup.

```
{
"Version": "2012-10-17",
"Statement": [{
"Effect": "Allow",
"Action": [
"iam:AddUserToGroup",
"iam:RemoveUserFromGroup",
"iam:GetGroup"
],
"Resource": "arn:aws:iam:: 123412341234:group/ TestingGroup "
}]
}
```

NEW QUESTION 177

- (Topic 3)

A root account owner is trying to understand the S3 bucket ACL. Which of the below mentioned options cannot be used to grant ACL on the object using the authorized predefined group?

- A. Authenticated user group
- B. All users group
- C. Log Delivery Group
- D. Canonical user group

Answer: D

Explanation:

An S3 bucket ACL grantee can be an AWS account or one of the predefined Amazon S3 groups. Amazon S3 has a set of predefined groups. When granting account access to a group, the user can specify one of the URLs of that group instead of a canonical user ID. AWS S3 has the following predefined groups: Authenticated Users group: It represents all AWS accounts. All Users group: Access permission to this group allows anyone to access the resource. Log Delivery group: WRITE permission on a bucket enables this group to write server access logs to the bucket.

NEW QUESTION 181

- (Topic 3)

A user has a weighing plant. The user measures the weight of some goods every 5 minutes and sends data to AWS CloudWatch for monitoring and tracking. Which of the below mentioned parameters is mandatory for the user to include in the request list?

- A. Value
- B. Namespace
- C. Metric Name
- D. Timezone

Answer: B

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish the data to CloudWatch as single data points or as an aggregated set of data points called a statistic set. The user has to always include the namespace as part of the request. The user can supply a file instead of the metric name. If the user does not supply the timezone, it accepts the current time. If the user is sending the data as a single data point it will have parameters, such as value. However, if the user is sending as an aggregate it will have parameters, such as statistic-values.

NEW QUESTION 186

- (Topic 3)

An organization has launched 5 instances: 2 for production and 3 for testing. The organization wants that one particular group of IAM users should only access the test instances and not the production ones. How can the organization set that as a part of the policy?

- A. Launch the test and production instances in separate regions and allow region wise access to the group
- B. Define the IAM policy which allows access based on the instance ID
- C. Create an IAM policy with a condition which allows access to only small instances
- D. Define the tags on the test and production servers and add a condition to the IAM policy which allows access to specific tags

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user can add conditions as a part of the IAM policies. The condition can be set on AWS Tags, Time, and Client IP as well as on various parameters. If the organization wants the user to access only specific instances he should define proper tags and add to the IAM policy condition.

The sample policy is shown below.

```
"Statement": [  
{  
  "Action": "ec2:*",  
  "Effect": "Allow",  
  "Resource": "*",  
  "Condition": {  
    "StringEquals": {  
      "ec2:ResourceTag/InstanceType": "Production"  
    }  
  }  
}]
```

NEW QUESTION 190

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. The infrastructure team wants to create an AMI from the running instance. Which of the below mentioned credentials is not required while creating the AMI?

- A. AWS account ID
- B. X.509 certificate and private key
- C. AWS login ID to login to the console
- D. Access key and secret access key

Answer: C

Explanation:

When the user has launched an EC2 instance from an instance store backed AMI and the admin team wants to create an AMI from it, the user needs to setup the AWS AMI or the API tools first. Once the tool is setup the user will need the following credentials:

AWS account ID;

AWS access and secret access key;

X.509 certificate with private key.

NEW QUESTION 191

- (Topic 3)

A user had aggregated the CloudWatch metric data on the AMI ID. The user observed some abnormal behaviour of the CPU utilization metric while viewing the last 2 weeks of data. The user wants to share that data with his manager. How can the user achieve this easily with the AWS console?

- A. The user can use the copy URL functionality of CloudWatch to share the exact details
- B. The user can use the export data option from the CloudWatch console to export the current data point
- C. The user has to find the period and data and provide all the aggregation information to the manager
- D. The user can use the CloudWatch data copy functionality to copy the current data points

Answer: A

Explanation:

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. The console provides the option to save the URL or bookmark it so that it can be used in the future by typing the same URL. The Copy URL functionality is available under the console when the user selects any metric to view.

NEW QUESTION 196

- (Topic 3)

A sys admin is planning to subscribe to the RDS event notifications. For which of the below mentioned source categories the subscription cannot be configured?

- A. DB security group
- B. DB snapshot
- C. DB options group
- D. DB parameter group

Answer: C

Explanation:

Amazon RDS uses the Amazon Simple Notification Service (SNS) to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group.

NEW QUESTION 200

- (Topic 3)

A user has configured an HTTPS listener on an ELB. The user has not configured any security policy which can help to negotiate SSL between the client and ELB. What will ELB do in this scenario?

- A. By default ELB will select the first version of the security policy
- B. By default ELB will select the latest version of the policy
- C. ELB creation will fail without a security policy
- D. It is not required to have a security policy since SSL is already installed

Answer: B

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. If the user has created an HTTPS/SSL listener without associating any security policy, Elastic Load Balancing will, by default, associate the latest version of the ELBSecurityPolicy-YYYY-MM with the load balancer.

NEW QUESTION 204

- (Topic 3)

A sysadmin has created the below mentioned policy on an S3 bucket named cloudacademy. The bucket has both AWS.jpg and index.html objects. What does this policy define?

```
"Statement": [{  
  "Sid": "Stmnt1388811069831",  
  "Effect": "Allow",  
  "Principal": { "AWS": "*" },  
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject" ],  
  "Resource": [ "arn:aws:s3:::cloudacademy/* .jpg" ]  
}]
```

- A. It will make all the objects as well as the bucket public
- B. It will throw an error for the wrong action and does not allow to save the policy
- C. It will make the AWS.jpg object as public
- D. It will make the AWS.jpg as well as the cloudacademy bucket as public

Answer: B

NEW QUESTION 207

- (Topic 3)

A user has setup an EBS backed instance and attached 2 EBS volumes to it. The user has setup a CloudWatch alarm on each volume for the disk data. The user has stopped the EC2 instance and detached the EBS volumes. What will be the status of the alarms on the EBS volume?

- A. OK
- B. Insufficient Data
- C. Alarm
- D. The EBS cannot be detached until all the alarms are removed

Answer: B

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. Alarms invoke actions only for sustained state changes. There are three states of the alarm: OK, Alarm and Insufficient data. In this case since the EBS is detached and inactive the state will be Insufficient.

NEW QUESTION 212

- (Topic 3)

A user has launched an EC2 instance. However, due to some reason the instance was terminated. If the user wants to find out the reason for termination, where can he find the details?

- A. It is not possible to find the details after the instance is terminated
- B. The user can get information from the AWS console, by checking the Instance description under the State transition reason label
- C. The user can get information from the AWS console, by checking the Instance description under the Instance Status Change reason label
- D. The user can get information from the AWS console, by checking the Instance description under the Instance Termination reason label

Answer: D

Explanation:

An EC2 instance, once terminated, may be available in the AWS console for a while after termination. The user can find the details about the termination from the description tab under the label State transition reason. If the instance is still running, there will be no reason listed. If the user has explicitly stopped or terminated the instance, the reason will be "User initiated shutdown".

NEW QUESTION 215

- (Topic 3)

An AWS account wants to be part of the consolidated billing of his organization's payee account. How can the owner of that account achieve this?

- A. The payee account has to request AWS support to link the other accounts with his account
- B. The owner of the linked account should add the payee account to his master account list from the billing console
- C. The payee account will send a request to the linked account to be a part of consolidated billing
- D. The owner of the linked account requests the payee account to add his account to consolidated billing

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. To add a particular account (linked to the master (payee) account, the payee account has to request the linked account to join consolidated billing. Once the linked account accepts the request henceforth all charges incurred by the linked account will be paid by the payee account.

NEW QUESTION 220

- (Topic 3)

A user is trying to connect to a running EC2 instance using SSH. However, the user gets a Host key not found error. Which of the below mentioned options is a possible reason for rejection?

- A. The user has provided the wrong user name for the OS login
- B. The instance CPU is heavily loaded
- C. The security group is not configured properly
- D. The access key to connect to the instance is wrong

Answer: A

Explanation:

If the user is trying to connect to a Linux EC2 instance and receives the Host Key not found error the probable reasons are: The private key pair is not right The user name to login is wrong

NEW QUESTION 224

- (Topic 3)

A user has launched multiple EC2 instances for the purpose of development and testing in the same region. The user wants to find the separate cost for the production and development instances. How can the user find the cost distribution?

- A. The user should download the activity report of the EC2 services as it has the instance ID wise data
- B. It is not possible to get the AWS cost usage data of single region instances separately
- C. The user should use Cost Distribution Metadata and AWS detailed billing
- D. The user should use Cost Allocation Tags and AWS billing reports

Answer: D

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources (such as Amazon EC2 instances or Amazon S3 buckets), AWS generates a cost allocation report as a comma-separated value (CSV) file, with the usage and costs aggregated by those tags. The user can apply tags which represent business categories (such as cost centres, application names, or instance type – Production/Dev. to organize usage costs across multiple services.

NEW QUESTION 229

- (Topic 3)

A user has created a queue named "awsmodule" with SQS. One of the consumers of queue is down for 3 days and then becomes available. Will that component receive message from queue?

- A. Yes, since SQS by default stores message for 4 days
- B. No, since SQS by default stores message for 1 day only
- C. No, since SQS sends message to consumers who are available that time
- D. Yes, since SQS will not delete message until it is delivered to all consumers

Answer: A

Explanation:

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. Queues retain messages for a set period of time. By default, a queue retains messages for four days. However, the user can configure a queue to retain messages for up to 14 days after the message has been sent.

NEW QUESTION 231

- (Topic 3)

A user has enabled versioning on an S3 bucket. The user is using server side encryption for data at Rest. If the user is supplying his own keys for encryption (SSE-C), which of the below mentioned statements is true?

- A. The user should use the same encryption key for all versions of the same object
- B. It is possible to have different encryption keys for different versions of the same object
- C. AWS S3 does not allow the user to upload his own keys for server side encryption

D. The SSE-C does not work when versioning is enabled

Answer: B

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C.. If the bucket is versioning-enabled, each object version uploaded by the user using the SSE-C feature can have its own encryption key. The user is responsible for tracking which encryption key was used for which object's version

NEW QUESTION 232

- (Topic 3)

A user is using the AWS EC2. The user wants to make so that when there is an issue in the EC2 server, such as instance status failed, it should start a new instance in the user's private cloud. Which AWS service helps to achieve this automation?

- A. AWS CloudWatch + Cloudformation
- B. AWS CloudWatch + AWS AutoScaling + AWS ELB
- C. AWS CloudWatch + AWS VPC
- D. AWS CloudWatch + AWS SNS

Answer: D

Explanation:

Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS. queues or to any HTTP endpoint. The user can configure a web service (HTTP End point. in his data centre which receives data and launches an instance in the private cloud. The user should configure the CloudWatch alarm to send a notification to SNS when the "StatusCheckFailed" metric is true for the EC2 instance. The SNS topic can be configured to send a notification to the user's HTTP end point which launches an instance in the private cloud.

NEW QUESTION 236

- (Topic 3)

A user is displaying the CPU utilization, and Network in and Network out CloudWatch metrics data of a single instance on the same graph. The graph uses one Y-axis for CPU utilization and Network in and another Y-axis for Network out. Since Network in is too high, the CPU utilization data is not visible clearly on graph to the user. How can the data be viewed better on the same graph?

- A. It is not possible to show multiple metrics with the different units on the same graph
- B. Add a third Y-axis with the console to show all the data in proportion
- C. Change the axis of Network by using the Switch command from the graph
- D. Change the units of CPU utilization so it can be shown in proportion with Network

Answer: C

Explanation:

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. It is possible to show the multiple metrics with different units on the same graph. If the graph is not plotted properly due to a difference in the unit data over two metrics, the user can change the Y-axis of one of the graph by selecting that graph and clicking on the Switch option.

NEW QUESTION 237

- (Topic 3)

A user has granted read/write permission of his S3 bucket using ACL. Which of the below mentioned options is a valid ID to grant permission to other AWS accounts (grantee. using ACL?

- A. IAM User ID
- B. S3 Secure ID
- C. Access ID
- D. Canonical user ID

Answer: D

Explanation:

An S3 bucket ACL grantee can be an AWS account or one of the predefined Amazon S3 groups. The user can grant permission to an AWS account by the email address of that account or by the canonical user ID. If the user provides an email in the grant request, Amazon S3 finds the canonical user ID for that account and adds it to the ACL. The resulting ACL will always contain the canonical user ID for the AWS account, and not the AWS account's email address.

NEW QUESTION 241

- (Topic 3)

A user has launched a Windows based EC2 instance. However, the instance has some issues and the user wants to check the log. When the user checks the Instance console output from the AWS console, what will it display?

- A. All the event logs since instance boot
- B. The last 10 system event log error
- C. The Windows instance does not support the console output
- D. The last three system events' log errors

Answer: D

Explanation:

The AWS EC2 console provides a useful tool called Console output for problem diagnosis. It is useful to find out any kernel issues, termination reasons or service configuration issues. For a Windows instance it lists the last three system event log errors. For Linux it displays the exact console output.

NEW QUESTION 246

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created public and VPN only subnets along with hardware VPN access to connect to the user's data centre. The user has not yet launched any instance as well as modified or deleted any setup. He wants to delete this VPC from the console. Will the console allow the user to delete the VPC?

- A. Yes, the console will delete all the setups and also delete the virtual private gateway
- B. No, the console will ask the user to manually detach the virtual private gateway first and then allow deleting the VPC
- C. Yes, the console will delete all the setups and detach the virtual private gateway
- D. No, since the NAT instance is running

Answer: C

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. If the virtual private gateway is attached with VPC and the user deletes the VPC from the console it will first detach the gateway automatically and only then delete the VPC.

NEW QUESTION 247

- (Topic 3)

An AWS root account owner is trying to create a policy to access RDS. Which of the below mentioned statements is true with respect to the above information?

- A. Create a policy which allows the users to access RDS and apply it to the RDS instances
- B. The user cannot access the RDS database if he is not assigned the correct IAM policy
- C. The root account owner should create a policy for the IAM user and give him access to the RDS services
- D. The policy should be created for the user and provide access for RDS

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the account owner wants to create a policy for RDS, the owner has to create an IAM user and define the policy which entitles the IAM user with various RDS services such as Launch Instance, Manage security group, Manage parameter group etc.

NEW QUESTION 250

- (Topic 3)

An organization has setup multiple IAM users. The organization wants that each IAM user accesses the IAM console only within the organization and not from outside. How can it achieve this?

- A. Create an IAM policy with the security group and use that security group for AWS console login
- B. Create an IAM policy with a condition which denies access when the IP address range is not from the organization
- C. Configure the EC2 instance security group which allows traffic only from the organization's IP range
- D. Create an IAM policy with VPC and allow a secure gateway between the organization and AWS Console

Answer: B

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user can add conditions as a part of the IAM policies. The condition can be set on AWS Tags, Time, and Client IP as well as on many other parameters. If the organization wants the user to access only from a specific IP range, they should set an IAM policy condition which denies access when the IP is not in a certain range. E.g. The sample policy given below denies all traffic when the IP is not in a certain range.

```
"Statement": [{  
  "Effect": "Deny",  
  "Action": "*",  
  "Resource": "*",  
  "Condition": {  
    "NotIpAddress": {  
      "aws:SourceIp": ["10.10.10.0/24", "20.20.30.0/24"]  
    }  
  }  
}]
```

NEW QUESTION 254

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using VPC Wizard. The user has created a public CIDR (20.0.0.0/24. and a VPN only subnet CIDR (20.0.1.0/24. along with the hardware VPN access to connect to the user's data centre. Which of the below mentioned components is not present when the VPC is setup with the wizard?

- A. Main route table attached with a VPN only subnet

- B. A NAT instance configured to allow the VPN subnet instances to connect with the internet
- C. Custom route table attached with a public subnet
- D. An internet gateway for a public subnet

Answer: B

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. The wizard does not create a NAT instance by default. The user can create it manually and attach it with a VPN only subnet.

NEW QUESTION 259

A user has deployed an application on his private cloud. The user is using his own monitoring tool. He wants to configure that whenever there is an error, the monitoring tool should notify him via SMS. Which of the below mentioned AWS services will help in this scenario?

- A. None because the user infrastructure is in the private cloud/
- B. AWS SNS
- C. AWS SES
- D. AWS SMS

Answer: B

Explanation:

Amazon Simple Notification Service (Amazon SNS. is a fast, flexible, and fully managed push messaging service. Amazon SNS can be used to make push notifications to mobile devices. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS. queues or to any HTTP endpoint. In this case user can use the SNS apis to send SMS.

NEW QUESTION 261

A user is trying to setup a scheduled scaling activity using Auto Scaling. The user wants to setup the recurring schedule. Which of the below mentioned parameters is not required in this case?

- A. Maximum size
- B. Auto Scaling group name
- C. End time
- D. Recurrence value

Answer: A

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can also configure the recurring schedule action which will follow the Linux cron format. If the user is setting a recurring event, it is required that the user specifies the Recurrence value (in a cron format., end time (not compulsory but recurrence will stop after this. and the Auto Scaling group for which the scaling activity is to be scheduled.

NEW QUESTION 263

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your AWS-SysOps Exam with Our Prep Materials Via below:

<https://www.certleader.com/AWS-SysOps-dumps.html>