



Amazon

Exam Questions AWS-Certified-DevOps-Engineer-Professional

Amazon AWS Certified DevOps Engineer Professional

NEW QUESTION 1

What method should I use to author automation if I want to wait for a CloudFormation stack to finish completing in a script?

- A. Event subscription using SQS.
- B. Event subscription using SNS.
- C. Poll using `ListStacks` / `list-stacks`.
- D. Poll using `GetStackStatus` / `get-stack-status`.

Answer: C

Explanation:

Event driven systems are good for IFTTT logic, but only polling will make a script wait to complete. ListStacks / list-stacks is a real method, GetStackStatus / get-stack-status is not.

Reference: <http://docs.aws.amazon.com/cli/latest/reference/cloudformation/list-stacks.html>

NEW QUESTION 2

Your application consists of 10% writes and 90% reads. You currently service all requests through a Route53 Alias Record directed towards an AWS ELB, which sits in front of an EC2 Auto Scaling Group. Your system is getting very expensive when there are large traffic spikes during certain news events, during which many more people request to read similar data all at the same time. What is the simplest and cheapest way to reduce costs and scale with spikes like this?

- A. Create an S3 bucket and asynchronously replicate common requests responses into S3 object
- B. When a request comes in for a precomputed response, redirect to AWS S3.
- C. Create another ELB and Auto Scaling Group layer mounted on top of the other system, adding a tier to the system
- D. Serve most read requests out of the top layer.
- E. Create a CloudFront Distribution and direct Route53 to the Distribution
- F. Use the ELB as an Origin and specify Cache Behaviours to proxy cache requests which can be served late.
- G. Create a Memcached cluster in AWS ElastiCache
- H. Create cache logic to serve requests which can be served late from the in-memory cache for increased performance.

Answer: C

Explanation:

CloudFront is ideal for scenarios in which entire requests can be served out of a cache and usage patterns involve heavy reads and spikiness in demand.

A cache behavior is the set of rules you configure for a given URL pattern based on file extensions, file names, or any portion of a URL path on your website (e.g., *.jpg). You can configure multiple cache behaviors for your web distribution. Amazon CloudFront will match incoming viewer requests with your list of URL patterns, and if there is a match, the service will honor the cache behavior you configure for that URL pattern. Each cache behavior can include the following Amazon CloudFront configuration values: origin server name, viewer connection protocol, minimum expiration period, query string parameters, cookies, and trusted signers for private content.

Reference: <https://aws.amazon.com/Cloudfront/dynamic-content/>

NEW QUESTION 3

You are building a game high score table in DynamoDB. You will store each user's highest score for each game, with many games, all of which have relatively similar usage levels and numbers of players. You need to be able to look up the highest score for any game. What's the best DynamoDB key structure?

- A. HighestScore as the hash / only key.
- B. GameID as the hash key, HighestScore as the range key.
- C. GameID as the hash / only key.
- D. GameID as the range / only key

Answer: B

Explanation:

Since access and storage for games is uniform, and you need to have ordering within each game for the scores (to access the highest value), your hash (partition) key should be the GameID, and there should be a range key for HighestScore.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/GuidelinesForTables.html#GuidelinesForTables.Partitions>

NEW QUESTION 4

What is server immutability?

- A. Not updating a server after creation.
- B. The ability to change server counts.
- C. Updating a server after creation.
- D. The inability to change server count

Answer: A

Explanation:

disposable upgrades offer a simpler way to know if your application has unknown dependencies. The underlying EC2 instance usage is considered temporary or ephemeral in nature for the period of deployment until the current release is active. During the new release, a new set of EC2 instances are rolled out by terminating older instances. This type of upgrade technique is more common in an immutable infrastructure.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 5

You run a clustered NoSQL database on AWS EC2 using AWS EBS. You need to reduce latency for database response times. Performance is the most important concern, not availability. You did not perform the initial setup, someone without much AWS knowledge did, so you are not sure if they configured everything optimally. Which of the following is NOT likely to be an issue contributing to increased latency?

- A. The EC2 instances are not EBS Optimized.
- B. The database and requesting system are both in the wrong Availability Zone.
- C. The EBS Volumes are not using PIOPS.
- D. The database is not running in a placement group

Answer: B

Explanation:

For the highest possible performance, all instances in a clustered database like this one should be in a single Availability Zone in a placement group, using EBS optimized instances, and using PIOPS SSD EBS Volumes. The particular Availability Zone the system is running in should not be important, as long as it is the same as the requesting resources.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/placement-groups.html>

NEW QUESTION 6

You are creating an application which stores extremely sensitive financial information. All information in the system must be encrypted at rest and in transit. Which of these is a violation of this policy?

- A. ELB SSL termination.
- B. ELB Using Proxy Protocol v1.
- C. CloudFront Viewer Protocol Policy set to HTTPS redirection.
- D. Telling S3 to use AES256 on the server-side

Answer: A

Explanation:

Terminating SSL terminates the security of a connection over HTTP, removing the S for "Secure" in HTTPS. This violates the "encryption in transit" requirement in the scenario.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/elb-listener-config.html>

NEW QUESTION 7

When thinking of AWS Elastic Beanstalk, the 'Swap Environment URLs' feature most directly aids in what?

- A. Immutable Rolling Deployments
- B. Mutable Rolling Deployments
- C. Canary Deployments
- D. Blue-Green Deployments

Answer: D

Explanation:

Simply upload the new version of your application and let your deployment service (AWS Elastic Beanstalk, AWS CloudFormation, or AWS OpsWorks) deploy a new version (green). To cut over to the new version, you simply replace the ELB URLs in your DNS records. Elastic Beanstalk has a Swap Environment URLs feature to facilitate a simpler cutover process.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 8

When thinking of DynamoDB, what are true of Global Secondary Key properties?

- A. The partition key and sort key can be different from the table.
- B. Only the partition key can be different from the table.
- C. Either the partition key or the sort key can be different from the table, but not both.
- D. Only the sort key can be different from the table

Answer: A

Explanation:

Global secondary index — an index with a partition key and a sort key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 9

To monitor API calls against our AWS account by different users and entities, we can use to create a history of calls in bulk for later review, and use for reacting to AWS API calls in real-time.

- A. AWS Config; AWS Inspector
- B. AWS CloudTrail; AWS Config
- C. AWS CloudTrail; CloudWatch Events
- D. AWS Config; AWS Lambda

Answer: C

Explanation:

CloudTrail is a batch API call collection service, CloudWatch Events enables real-time monitoring of calls through the Rules object interface.

Reference: <https://aws.amazon.com/whitepapers/security-at-scale-governance-in-aws/>

NEW QUESTION 10

How does Amazon RDS multi Availability Zone model work?

- A. A second, standby database is deployed and maintained in a different availability zone from master, using synchronous replication.
- B. A second, standby database is deployed and maintained in a different availability zone from master using asynchronous replication.
- C. A second, standby database is deployed and maintained in a different region from master using asynchronous replication.
- D. A second, standby database is deployed and maintained in a different region from master using synchronous replication.

Answer: A

Explanation:

In a Multi-AZ deployment, Amazon RDS automatically provisions and maintains a synchronous standby replica in a different Availability Zone.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Concepts.MultiAZ.html>

NEW QUESTION 10

For AWS Auto Scaling, what is the first transition state an instance enters after leaving steady state when scaling in due to health check failure or decreased load?

- A. Terminating
- B. Detaching
- C. Terminating:Wait
- D. EnteringStandby

Answer: A

Explanation:

When Auto Scaling responds to a scale in event, it terminates one or more instances. These instances are detached from the Auto Scaling group and enter the Terminating state.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AutoScalingGroupLifecycle.html>

NEW QUESTION 12

Which status represents a failure state in AWS CloudFormation?

- A. `UPDATE_COMPLETE_CLEANUP_IN_PROGRESS`
- B. `DELETE_COMPLETE_WITH_ARTIFACTS`
- C. `ROLLBACK_IN_PROGRESS`
- D. `ROLLBACK_FAILED`

Answer: C

Explanation:

ROLLBACK_IN_PROGRESS means an UpdateStack operation failed and the stack is in the process of trying to return to the valid, pre-update state.

UPDATE_COMPLETE_CLEANUP_IN_PROGRESS means an update was successful, and CloudFormation is deleting any replaced, no longer used resources.

ROLLBACK_FAILED is not a CloudFormation state (but UPDATE_ROLLBACK_FAILED is). DELETE_COMPLETE_WITH_ARTIFACTS does not exist at all.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-cfn-updating-stacks.html>

NEW QUESTION 14

For AWS Auto Scaling, what is the first transition state an existing instance enters after leaving steady state in Standby mode?

- A. Detaching
- B. Terminating:Wait
- C. Pending
- D. EnteringStandby

Answer: C

Explanation:

You can put any instance that is in an InService state into a Standby state. This enables you to remove the instance from service, troubleshoot or make changes to it, and then put it back into service. Instances in a Standby state continue to be managed by the Auto Scaling group. However, they are not an active part of your application until you put them back into service.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AutoScalingGroupLifecycle.html>

NEW QUESTION 19

You want to pass queue messages that are 1GB each. How should you achieve this?

- A. Use Kinesis as a buffer stream for message bodies
- B. Store the checkpoint id for the placement in the Kinesis Stream in SQS.
- C. Use the Amazon SQS Extended Client Library for Java and Amazon S3 as a storage mechanism for message bodies.
- D. Use SQS's support for message partitioning and multi-part uploads on Amazon S3.
- E. Use AWS EFS as a shared pool storage medium
- F. Store filesystem pointers to the files on disk in the SQS message bodies.

Answer: B

Explanation:

You can manage Amazon SQS messages with Amazon S3. This is especially useful for storing and retrieving messages with a message size of up to 2 GB. To manage Amazon SQS messages with Amazon S3, use the Amazon SQS Extended Client Library for Java.

Reference:

<http://docs.aws.amazon.com/AWSSimpleQueueService/latest/SQSDeveloperGuide/s3-messages.html>

NEW QUESTION 22

Which deployment method, when using AWS Auto Scaling Groups and Auto Scaling Launch Configurations, enables the shortest time to live for individual servers?

- A. Pre-baking AMIs with all code and configuration on deploys.
- B. Using a Dockerfile bootstrap on instance launch.
- C. Using UserData bootstrapping scripts.
- D. Using AWS EC2 Run Commands to dynamically SSH into fleet

Answer: A

Explanation:

Note that the bootstrapping process can be slower if you have a complex application or multiple applications to install. Managing a fleet of applications with several build tools and dependencies can be a challenging task during rollouts. Furthermore, your deployment service should be designed to do faster rollouts to take advantage of Auto Scaling. Prebaking is a process of embedding a significant portion of your application artifacts within your base AMI. During the deployment process you can customize application installations by using EC2 instance artifacts such as instance tags, instance metadata, and Auto Scaling groups.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 26

Which of these techniques enables the fastest possible rollback times in the event of a failed deployment?

- A. Rolling; Immutable
- B. Rolling; Mutable
- C. Canary or A/B
- D. Blue-Green

Answer: D

Explanation:

AWS specifically recommends Blue-Green for super-fast, zero-downtime deploys - and thus rollbacks, which are redeploying old code.

You use various strategies to migrate the traffic from your current application stack (blue) to a new version of the application (green). This is a popular technique for deploying applications with zero downtime. Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 28

Which major database needs a BYO license?

- A. PostgreSQL
- B. MariaDB
- C. MySQL
- D. Oracle

Answer: D

Explanation:

Oracle is not open source, and requires a bring your own license model.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP_Oracle.html

NEW QUESTION 31

What is the maximum supported single-volume throughput on EBS?

- A. 320 MiB/s
- B. 160 MiB/s
- C. 40 MiB/s
- D. 640 MiB/s

Answer: A

Explanation:

The ceiling throughput for PIOPS on EBS is 320 MiB/s.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 34

For AWS Auto Scaling, what is the first transition state a new instance enters after leaving steady state when scaling out due to increased load?

- A. EnteringStandby
- B. Pending
- C. Terminating:Wait
- D. Detaching

Answer: B

Explanation:

When a scale out event occurs, the Auto Scaling group launches the required number of EC2 instances, using its assigned launch configuration. These instances start in the Pending state. If you add a lifecycle hook to your Auto Scaling group, you can perform a custom action here. For more information, see Lifecycle Hooks.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AutoScalingGroupLifecycle.html>

NEW QUESTION 37

You need to know when you spend \$1000 or more on AWS. What's the easy way for you to see that notification?

- A. AWS CloudWatch Events tied to API calls, when certain thresholds are exceeded, publish to SNS.
- B. Scrape the billing page periodically and pump into Kinesis.
- C. AWS CloudWatch Metrics + Billing Alarm + Lambda event subscription
- D. When a threshold is exceeded, email the manager.
- E. Scrape the billing page periodically and publish to SNS

Answer: C

Explanation:

Even if you're careful to stay within the free tier, it's a good idea to create a billing alarm to notify you if you exceed the limits of the free tier. Billing alarms can help to protect you against unknowingly accruing charges if you inadvertently use a service outside of the free tier or if traffic exceeds your expectations. Reference: <http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/free-tier-alarms.html>

NEW QUESTION 39

Your serverless architecture using AWS API Gateway, AWS Lambda, and AWS DynamoDB experienced a large increase in traffic to a sustained 400 requests per second, and dramatically increased in failure rates. Your requests, during normal operation, last 500 milliseconds on average. Your DynamoDB table did not exceed 50% of provisioned throughput, and Table primary keys are designed correctly. What is the most likely issue?

- A. Your API Gateway deployment is throttling your requests.
- B. Your AWS API Gateway Deployment is bottlenecking on request (de)serialization.
- C. You did not request a limit increase on concurrent Lambda function executions.
- D. You used Consistent Read requests on DynamoDB and are experiencing semaphore lock

Answer: C

Explanation:

AWS API Gateway by default throttles at 500 requests per second steady-state, and 1000 requests per second at spike. Lambda, by default, throttles at 100 concurrent requests for safety. At 500 milliseconds (half of a second) per request, you can expect to support 200 requests per second at 100 concurrency. This is less than the 400 requests per second your system now requires. Make a limit increase request via the AWS Support Console.

AWS Lambda: Concurrent requests safety throttle per account -> 100

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_lambda

NEW QUESTION 43

For AWS CloudFormation, which stack state refuses UpdateStack calls?

- A. `UPDATE_ROLLBACK_FAILED`
- B. `UPDATE_ROLLBACK_COMPLETE`
- C. `UPDATE_COMPLETE`
- D. `CREATE_COMPLETE`

Answer: A

Explanation:

When a stack is in the `UPDATE_ROLLBACK_FAILED` state, you can continue rolling it back to return it to a working state (to `UPDATE_ROLLBACK_COMPLETE`). You cannot update a stack that is in the `UPDATE_ROLLBACK_FAILED` state. However, if you can continue to roll it back, you can return the stack to its original settings and try to update it again.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-cfn-updating-stacks-continueupdaterollback.html>

NEW QUESTION 45

You need to migrate 10 million records in one hour into DynamoDB. All records are 1.5KB in size. The data is evenly distributed across the partition key. How many write capacity units should you provision during this batch load?

- A. 6667
- B. 4166
- C. 5556
- D. 2778

Answer: C

Explanation:

You need 2 units to make a 1.5KB write, since you round up. You need 20 million total units to perform this load. You have 3600 seconds to do so. Divide and round up for 5556.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/HowItWorks.ProvisionedThroughput.html>

NEW QUESTION 50

What is the scope of an EBS volume?

- A. VPC
- B. Region
- C. Placement Group
- D. Availability Zone

Answer: D

Explanation:

An Amazon EBS volume is tied to its Availability Zone and can be attached only to instances in the same Availability Zone.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/resources.html>

NEW QUESTION 51

You are experiencing performance issues writing to a DynamoDB table. Your system tracks high scores for video games on a marketplace. Your most popular game experiences all of the performance issues. What is the most likely problem?

- A. DynamoDB's vector clock is out of sync, because of the rapid growth in request for the most popular game.
- B. You selected the Game ID or equivalent identifier as the primary partition key for the table.
- C. Users of the most popular video game each perform more read and write requests than average.
- D. You did not provision enough read or write throughput to the tabl

Answer: B

Explanation:

The primary key selection dramatically affects performance consistency when reading or writing to DynamoDB. By selecting a key that is tied to the identity of the game, you forced DynamoDB to create a hotspot in the table partitions, and over-request against the primary key partition for the popular game. When it stores data, DynamoDB dMdes a table's items into multiple partitions, and distributes the data primarily based upon the partition key value. The provisioned throughput associated with a table is also dMded evenly among the partitions, with no sharing of provisioned throughput across partitions. Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/GuidelinesForTables.html#Guideli nesForTables.UniformWorkload>

NEW QUESTION 55

You meet once per month with your operations team to review the past month's data. During the meeting, you realize that 3 weeks ago, your monitoring system which pings over HTTP from outside AWS recorded a large spike in latency on your 3-tier web service API. You use DynamoDB for the database layer, ELB, EBS, and EC2 for the business logic tier, and SQS, ELB, and EC2 for the presentation layer. Which of the following techniques will NOT help you figure out what happened?

- A. Check your CloudTrail log history around the spike's time for any API calls that caused slowness.
- B. Review CloudWatch Metrics graphs to determine which component(s) slowed the system down.
- C. Review your ELB access logs in S3 to see if any ELBs in your system saw the latency.
- D. Analyze your logs to detect bursts in traffic at that tim

Answer: B

Explanation:

Metrics data are available for 2 weeks. If you want to store metrics data beyond that duration, you can retrieve it using our GetMetricStatistics API as well as a number of applications and tools offered by AWS partners.
Reference: <https://aws.amazon.com/cloudwatch/faqs/>

NEW QUESTION 60

Which of these is not an intrinsic function in AWS CloudFormation?

- A. Fn::Split
- B. Fn::FindInMap
- C. Fn::Select
- D. Fn::GetAZs

Answer: A

Explanation:

This is the complete list of Intrinsic Functions...: Fn::Base64, Fn::And, Fn::Equals, Fn::If, Fn::Not, Fn::Or, Fn::FindInMap, Fn::GetAtt, Fn::GetAZs, Fn::Join, Fn::Select, Ref
Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/intrinsic-function-reference.html>

NEW QUESTION 65

For AWS CloudFormation, which is true?

- A. Custom resources using SNS have a default timeout of 3 minutes.
- B. Custom resources using SNS do not need a `ServiceToken` property.
- C. Custom resources using Lambda and `Code.ZipFile` allow inline nodejs resource composition.
- D. Custom resources using Lambda do not need a `ServiceToken` property

Answer: C

Explanation:

Code is a property of the AWS::Lambda::Function resource that enables to you specify the source code of an AWS Lambda (Lambda) function. You can point to a file in an Amazon Simple Storage Service (Amazon S3) bucket or specify your source code as inline text (for nodejs runtime environments only). Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/template-custom-resources.html>

NEW QUESTION 70

Your API requires the ability to stay online during AWS regional failures. Your API does not store any state, it only aggregates data from other sources - you do not have a database. What is a simple but effective way to achieve this uptime goal?

- A. Use a CloudFront distribution to serve up your AP
- B. Even if the region your API is in goes down, the edge locations CloudFront uses will be fine.

- C. Use an ELB and a cross-zone ELB deployment to create redundancy across datacenter
- D. Even if a region fails, the other AZ will stay online.
- E. Create a Route53 Weighted Round Robin record, and if one region goes down, have that region redirect to the other region.
- F. Create a Route53 Latency Based Routing Record with Failover and point it to two identical deployments of your stateless API in two different region
- G. Make sure both regions use Auto Scaling Groups behind ELBs.

Answer: D

Explanation:

standard volumes, or Magnetic volumes, are best for: Cold workloads where data is infrequently accessed, or scenarios where the lowest storage cost is important.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 74

You run a 2000-engineer organization. You are about to begin using AWS at a large scale for the first time. You want to integrate with your existing identity management system running on Microsoft Active Directory, because your organization is a power-user of Active Directory. How should you manage your AWS identities in the most simple manner?

- A. Use a large AWS Directory Service Simple AD.
- B. Use a large AWS Directory Service AD Connector.
- C. Use an Sync Domain running on AWS Directory Service.
- D. Use an AWS Directory Sync Domain running on AWS Lambda

Answer: B

Explanation:

You must use AD Connector as a power-user of Microsoft Active Directory. Simple AD only works with a subset of AD functionality. Sync Domains do not exist; they are made up answers.

AD Connector is a directory gateway that allows you to proxy directory requests to your on-premises Microsoft Active Directory, without caching any information in the cloud. AD Connector comes in 2 sizes; small and large. A small AD Connector is designed for smaller organizations of up to 500 users. A large AD Connector is designed for larger organizations of up to 5,000 users.

Reference: <https://aws.amazon.com/directoryservice/details/>

NEW QUESTION 78

Which of these is not a CloudFormation Helper Script?

- A. cfn-signal
- B. cfn-hup
- C. cfn-request
- D. cfn-get-metadata

Answer: C

Explanation:

This is the complete list of CloudFormation Helper Scripts: cfn-init, cfn-signal, cfn-get-metadata, cfn-hup Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/cfn-helper-scripts-reference.html>

NEW QUESTION 80

Your team wants to begin practicing continuous delivery using CloudFormation, to enable automated builds and deploys of whole, versioned stacks or stack layers. You have a 3-tier, mission-critical system. Which of the following is NOT a best practice for using CloudFormation in a continuous delivery environment?

- A. Use the AWS CloudFormation `ValidateTemplate` call before publishing changes to AWS.
- B. Model your stack in one template, so you can leverage CloudFormation's state management and dependency resolution to propagate all changes.
- C. Use CloudFormation to create brand new infrastructure for all stateless resources on each push, and run integration tests on that set of infrastructure.
- D. Parametrize the template and use `Mappings` to ensure your template works in multiple Regions.

Answer: B

Explanation:

Putting all resources in one stack is a bad idea, since different tiers have different life cycles and frequencies of change. For additional guidance about organizing your stacks, you can use two common frameworks: a multi-layered architecture and service-oriented architecture (SOA).

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/best-practices.html#organizingstack>

NEW QUESTION 82

You are building a Ruby on Rails application for internal, non-production use which uses MySQL as a database. You want developers without very much AWS experience to be able to deploy new code with a single command line push. You also want to set this up as simply as possible. Which tool is ideal for this setup?

- A. AWS CloudFormation
- B. AWS OpsWorks
- C. AWS ELB + EC2 with CLI Push
- D. AWS Elastic Beanstalk

Answer: D

Explanation:

Elastic Beanstalk's primary mode of operation exactly supports this use case out of the box. It is simpler than all the other options for this question.

With Elastic Beanstalk, you can quickly deploy and manage applications in the AWS cloud without worrying about the infrastructure that runs those applications.

AWS Elastic Beanstalk reduces management complexity without restricting choice or control. You simply upload your application, and Elastic Beanstalk automatically handles the details of capacity provisioning, load balancing, scaling, and application health monitoring.
Reference: http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/create_deploy_Ruby_rails.html

NEW QUESTION 83

You are building a mobile app for consumers to post cat pictures online. You will be storing the images in AWS S3. You want to run the system very cheaply and simply. Which one of these options allows you to build a photo sharing application without needing to worry about scaling expensive uploads processes, authentication/authorization and so forth?

- A. Build the application out using AWS Cognito and web identity federation to allow users to log in using Facebook or Google Account
- B. Once they are logged in, the secret token passed to that user is used to directly access resources on AWS, like AWS S3.
- C. Use JWT or SANIL compliant systems to build authorization policie
- D. Users log in with a username and password, and are given a token they can use indefinitely to make calls against the photo infrastructure.
- E. Use AWS API Gateway with a constantly rotating API Key to allow access from the client-sid
- F. Construct a custom build of the SDK and include S3 access in it.
- G. Create an AWS oAuth Service Domain ad grant public signup and access to the domai
- H. During setup, add at least one major social media site as a trusted Identity Provider for users.

Answer: A

Explanation:

The short answer is that Amazon Cognito is a superset of the functionality provided by web identity federation. It supports the same providers, and you configure your app and authenticate with those providers in the same way. But Amazon Cognito includes a variety of additional features. For example, it enables your users to start using the app as a guest user and later sign in using one of the supported identity providers.

Reference:

<https://blogs.aws.amazon.com/security/post/Tx3SYCORF5EKRCO/How-Does-Amazon-Cognito-Relate-to-Existing-Web-Identity-Federatio>

NEW QUESTION 88

Your CTO has asked you to make sure that you know what all users of your AWS account are doing to change resources at all times. She wants a report of who is doing what over time, reported to her once per week, for as broad a resource type group as possible. How should you do this?

- A. Create a global AWS CloudTrail Trai
- B. Configure a script to aggregate the log data delivered to S3 once per week and deliver this to the CTO.
- C. Use CloudWatch Events Rules with an SNS topic subscribed to all AWS API call
- D. Subscribe the CTO to an email type delivery on this SNS Topic.
- E. Use AWS IAM credential reports to deliver a CSV of all uses of IAM User Tokens over time to the CTO.
- F. Use AWS Config with an SNS subscription on a Lambda, and insert these changes over time into a DynamoDB tabl
- G. Generate reports based on the contents of this table.

Answer: A

Explanation:

This is the ideal use case for AWS CloudTrail.

CloudTrail provides visibility into user actMty by recording API calls made on your account. CloudTrail records important information about each API call, including the name of the API, the identity of the caller, the time of the API call, the request parameters, and the response elements returned by the AWS service. This information helps you to track changes made to your AWS resources and to troubleshoot operational issues. CloudTrail makes it easier to ensure compliance with internal policies and regulatory standards. Reference: <https://aws.amazon.com/Cloudtrail/faqs/>

NEW QUESTION 91

You need to deploy a new application version to production. Because the deployment is high-risk, you need to roll the new version out to users over a number of hours, to make sure everything is working correctly. You need to be able to control the proportion of users seeing the new version of the application down to the percentage point.

You use ELB and EC2 with Auto Scaling Groups and custom AMIs with your code pre-installed assigned to Launch Configurations. There are no database-level changes during your deployment. You have been told you cannot spend too much money, so you must not increase the number of EC2 instances much at all during the deployment, but you also need to be able to switch back to the original version of code quickly if something goes wrong. What is the best way to meet these requirements?

- A. Create a second ELB, Auto Scaling Launch Configuration, and Auto Scaling Group using the Launch Configuratio
- B. Create AMIs with all code pre-installe
- C. Assign the new AMI to the second Auto Scaling Launch Configuratio
- D. Use Route53 Weighted Round Robin Records to adjust the proportion of traffic hitting the two ELBs.
- E. Use the Blue-Green deployment method to enable the fastest possible rollback if neede
- F. Create a full second stack of instances and cut the DNS over to the new stack of instances, and change the DNS back if a rollback is needed.
- G. Create AMIs with all code pre-installe
- H. Assign the new AMI to the Auto Scaling Launch Configuration, to replace the old on
- I. Gradually terminate instances running the old code (launched with the old Launch Configuration) and allow the new AMIs to boot to adjust the traffic balance to the new cod
- J. On rollback, reverse the process by doing the same thing, but changing the AMI on the Launch Config back to the original code.
- K. Migrate to use AWS Elastic Beanstal
- L. Use the established and well-tested Rolling Deployment setting AWS provides on the new Application Environment, publishing a zip bundle of the new code and adjusting the wait period to spread the deployment over tim
- M. Re-deploy the old code bundle to rollback if needed.

Answer: A

Explanation:

Only Weighted Round Robin DNS Records and reverse proxies allow such fine-grained tuning of traffic splits. The Blue-Green option does not meet the requirement that we mitigate costs and keep overall EC2 fileet size consistent, so we must select the 2 ELB and ASG option with WRR DNS tuning. This method is called A/B deployment and/or Canary deployment.

Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 92

If I want CloudFormation stack status updates to show up in a continuous delivery system in as close to real time as possible, how should I achieve this?

- A. Use a long-poll on the Resources object in your CloudFormation stack and display those state changes in the UI for the system.
- B. Use a long-poll on the `ListStacks` API call for your CloudFormation stack and display those state changes in the UI for the system.
- C. Subscribe your continuous delivery system to an SNS topic that you also tell your CloudFormation stack to publish events into.
- D. Subscribe your continuous delivery system to an SQS queue that you also tell your CloudFormation stack to publish events into.

Answer: C

Explanation:

Use NotificationARNs.member.N when making a CreateStack call to push stack events into SNS in nearly real-time.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-cfn-updating-stacks-monitor-stack.html>

NEW QUESTION 95

What does it mean if you have zero IOPS and a non-empty I/O queue for all EBS volumes attached to a running EC2 instance?

- A. The I/O queue is buffer flushing.
- B. Your EBS disk head(s) is/are seeking magnetic stripes.
- C. The EBS volume is unavailable.
- D. You need to re-mount the EBS volume in the OS

Answer: C

Explanation:

This is the definition of Unavailable from the EC2 and EBS SLA.

"Unavailable" and "Unavailability" mean... For Amazon EBS, when all of your attached volumes perform zero read write IO, with pending IO in the queue.

Reference: <https://aws.amazon.com/ec2/sla/>

NEW QUESTION 98

Your company wants to understand where cost is coming from in the company's production AWS account. There are a number of applications and services running at any given time. Without expending too much initial development time, how best can you give the business a good understanding of which applications cost the most per month to operate?

- A. Create an automation script which periodically creates AWS Support tickets requesting detailed intra-month information about your bill.
- B. Use custom CloudWatch Metrics in your system, and put a metric data point whenever cost is incurred.
- C. Use AWS Cost Allocation Tagging for all resources which support it
- D. Use the Cost Explorer to analyze costs throughout the month.
- E. Use the AWS Price API and constantly running resource inventory scripts to calculate total price based on multiplication of consumed resources over time.

Answer: C

Explanation:

Cost Allocation Tagging is a built-in feature of AWS, and when coupled with the Cost Explorer, provides a simple and robust way to track expenses.

You can also use tags to filter views in Cost Explorer. Note that before you can filter views by tags in Cost Explorer, you must have applied tags to your resources and activate them, as described in the following sections. For more information about Cost Explorer, see Analyzing Your Costs with Cost Explorer. Reference:

<http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/cost-alloc-tags.html>

NEW QUESTION 100

What is a circular dependency in AWS CloudFormation?

- A. When a Template references an earlier version of itself.
- B. When Nested Stacks depend on each other.
- C. When Resources form a DependsOn loop.
- D. When a Template references a region, which references the original Template

Answer: C

Explanation:

To resolve a dependency error, add a DependsOn attribute to resources that depend on other resources in your template. In some cases, you must explicitly declare dependencies so that AWS CloudFormation can create or delete resources in the correct order. For example, if you create an Elastic IP and a VPC with an Internet gateway in the same stack, the Elastic IP must depend on the Internet gateway attachment. For additional information, see DependsOn Attribute.

Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/troubleshooting.html#troubleshooting-errors-dependence-error>

NEW QUESTION 105

You need to run a very large batch data processing job one time per day. The source data exists entirely in S3, and the output of the processing job should also be written to S3 when finished. If you need to version control this processing job and all setup and teardown logic for the system, what approach should you use?

- A. Model an AWS EMR job in AWS Elastic Beanstalk.
- B. Model an AWS EMR job in AWS CloudFormation.
- C. Model an AWS EMR job in AWS OpsWorks.
- D. Model an AWS EMR job in AWS CLI Compose

Answer: B

Explanation:

To declaratively model build and destroy of a cluster, you need to use AWS CloudFormation. OpsWorks and Elastic Beanstalk cannot directly model EMR Clusters. The CLI is not declarative, and CLI Composer does not exist.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/aws-resource-emr-cluster.html>

NEW QUESTION 108

You work for a company that automatically tags photographs using artificial neural networks (ANNs), which run on GPUs using C++. You receive millions of images at a time, but only 3 times per day on average. These images are loaded into an AWS S3 bucket you control for you in a batch, and then the customer publishes a JSON-formatted manifest into another S3 bucket you control as well. Each image takes 10 milliseconds to process using a full GPU. Your neural network software requires 5 minutes to bootstrap. Image tags are JSON objects, and you must publish them to an S3 bucket.

Which of these is the best system architectures for this system?

- A. Create an OpsWorks Stack with two Layer
- B. The first contains lifecycle scripts for launching and bootstrapping an HTTP API on G2 instances for ANN image processing, and the second has an always-on instance which monitors the S3 manifest bucket for new file
- C. When a new file is detected, request instances to boot on the ANN layer
- D. When the instances are booted and the HTTP APIs are up, submit processing requests to individual instances.
- E. Make an S3 notification configuration which publishes to AWS Lambda on the manifest bucket
- F. Make the Lambda create a CloudFormation Stack which contains the logic to construct an autoscaling worker tier of EC2 G2 instances with the ANN code on each instance
- G. Create an SQS queue of the images in the manifest
- H. Tear the stack down when the queue is empty.
- I. Deploy your ANN code to AWS Lambda as a bundled binary for the C++ extension
- J. Make an S3 notification configuration on the manifest, which publishes to another AWS Lambda running controller code
- K. This controller code publishes all the images in the manifest to AWS Kinesis
- L. Your ANN code Lambda Function uses the Kinesis as an Event Source
- M. The system automatically scales when the stream contains image events.
- N. Create an Auto Scaling, Load Balanced Elastic Beanstalk worker tier Application and Environment
- O. Deploy the ANN code to G2 instances in this tier
- P. Set the desired capacity to 1. Make the code periodically check S3 for new manifest
- Q. When a new manifest is detected, push all of the images in the manifest into the SQS queue associated with the Elastic Beanstalk worker tier.

Answer: B

Explanation:

The Elastic Beanstalk option is incorrect because it requires a constantly-polling instance, which may break and costs money.

The Lambda fleet option is incorrect because AWS Lambda does not support GPU usage.

The OpsWorks stack option both requires a constantly-polling instance, and also requires complex timing and capacity planning logic.

The CloudFormation option requires no polling, has no always-on instances, and allows arbitrarily fast processing by simply setting the instance count as high as needed.

Reference: <http://docs.aws.amazon.com/lambda/latest/dg/current-supported-versions.html>

NEW QUESTION 112

You need to create a Route53 record automatically in CloudFormation when not running in production during all launches of a Template. How should you implement this?

- A. Use a `Parameter` for `environment`, and add a `Condition` on the Route53 `Resource` in the template to create the record only when `environment` is not `production`.
- B. Create two templates, one with the Route53 record value and one with a null value for the record
- C. Use the one without it when deploying to production.
- D. Use a `Parameter` for `environment`, and add a `Condition` on the Route53 `Resource` in the template to create the record with a null string when `environment` is `production`.
- E. Create two templates, one with the Route53 record and one without it
- F. Use the one without it when deploying to production.

Answer: A

Explanation:

The best way to do this is with one template, and a Condition on the resource. Route53 does not allow null strings for records.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/conditions-section-structure.html>

NEW QUESTION 115

You have been asked to de-risk deployments at your company. Specifically, the CEO is concerned about outages that occur because of accidental inconsistencies between Staging and Production, which sometimes cause unexpected behaviors in Production even when Staging tests pass.

You already use Docker to get high consistency between Staging and Production for the application environment on your EC2 instances. How do you further de-risk the rest of the execution environment, since in AWS, there are many service components you may use beyond EC2 virtual machines?

- A. Develop models of your entire cloud system in CloudFormation
- B. Use this model in Staging and Production to achieve greater parity.
- C. Use AWS Config to force the Staging and Production stacks to have configuration parity
- D. Any differences will be detected for you so you are aware of risks.
- E. Use AMIs to ensure the whole machine, including the kernel of the virtual machines, is consistent, since Docker uses Linux Container (LXC) technology, and we need to make sure the container environment is consistent.
- F. Use AWS ECS and Docker clustering
- G. This will make sure that the AMIs and machine sizes are the same across both environments.

Answer: A

Explanation:

Only CloudFormation's JSON Templates allow declarative version control of repeatably deployable models of entire AWS clouds.
Reference: <https://blogs.aws.amazon.com/application-management/blog/category/Best+practices>

NEW QUESTION 116

You were just hired as a DevOps Engineer for a startup. Your startup uses AWS for 100% of their infrastructure. They currently have no automation at all for deployment, and they have had many failures while trying to deploy to production. The company has told you deployment process risk mitigation is the most important thing now, and you have a lot of budget for tools and AWS resources.

Their stack: 2-tier API

Data stored in DynamoDB or S3, depending on type. Compute layer is EC2 in Auto Scaling Groups. They use Route53 for DNS pointing to an ELB.

An ELB balances load across the EC2 instances.

The scaling group properly varies between 4 and 12 EC2 instances.

Which of the following approaches, given this company's stack and their priorities, best meets the company's needs?

- A. Model the stack in AWS Elastic Beanstalk as a single Application with multiple Environments.
- B. Use Elastic Beanstalk's Rolling Deploy option to progressively roll out application code changes when promoting across environments.
- C. Model the stack in 3 CloudFormation templates: Data layer, compute layer, and networking layer.
- D. Write stack deployment and integration testing automation following Blue-Green methodologies.
- E. Model the stack in AWS OpsWorks as a single Stack, with 1 compute layer and its associated ELB.
- F. Use Chef and App Deployments to automate Rolling Deployment.
- G. Model the stack in 1 CloudFormation template, to ensure consistency and dependency graph resolution.
- H. Write deployment and integration testing automation following Rolling Deployment methodologies.

Answer: B

Explanation:

AWS recommends Blue-Green for zero-downtime deploys. Since you use DynamoDB, and neither AWS OpsWorks nor AWS Elastic Beanstalk directly supports DynamoDB, the option selecting CloudFormation and Blue-Green is correct.

You use various strategies to migrate the traffic from your current application stack (blue) to a new version of the application (green). This is a popular technique for deploying applications with zero downtime. The deployment services like AWS Elastic Beanstalk, AWS CloudFormation, or AWS OpsWorks are particularly useful as they provide a simple way to clone your running application stack. You can set up a new version of your application (green) by simply cloning the current version of the application (blue). Reference: <https://d0.awsstatic.com/whitepapers/overview-of-deployment-options-on-aws.pdf>

NEW QUESTION 120

You need the absolute highest possible network performance for a cluster computing application. You already selected homogeneous instance types supporting 10 gigabit enhanced networking, made sure that your workload was network bound, and put the instances in a placement group. What is the last optimization you can make?

- A. Use 9001 MTU instead of 1500 for Jumbo Frames, to raise packet body to packet overhead ratios.
- B. Segregate the instances into different peered VPCs while keeping them all in a placement group, so each one has its own Internet Gateway.
- C. Bake an AMI for the instances and relaunch, so the instances are fresh in the placement group and don't have noisy neighbors.
- D. Turn off SYN/ACK on your TCP stack or begin using UDP for higher throughput.

Answer: A

Explanation:

For instances that are colocated inside a placement group, jumbo frames help to achieve the maximum network throughput possible, and they are recommended in this case. For more information, see Placement Groups.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/network_mtu.html#jumbo_frame_instances

NEW QUESTION 124

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-DevOps-Engineer-Professional Practice Exam Features:

- * AWS-Certified-DevOps-Engineer-Professional Questions and Answers Updated Frequently
- * AWS-Certified-DevOps-Engineer-Professional Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-DevOps-Engineer-Professional Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-DevOps-Engineer-Professional Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-DevOps-Engineer-Professional Practice Test Here](#)