

Cisco

Exam Questions 300-815

Implementing Cisco Advanced Call Control and Mobility Services (CLACCM)



NEW QUESTION 1

Which two extended capabilities must be configured on dial peers for fast start-to-early media scenarios (H.323 to SIP interworking)? (Choose two.)

- A. DTMF
- B. BFCP
- C. VIDEO
- D. FAX
- E. AUDIO

Answer: AB

NEW QUESTION 2

When you troubleshoot H.323 call setup, which message informs you that the called party is being notified about the call?

- A. ALERTING
- B. PROCEEDING
- C. CONNECT
- D. RINGING

Answer: C

NEW QUESTION 3

End users at a new site report being unable to hear the remote party when calling or being called by users at headquarters. Calls to and from the PSTN work as expected. To investigate the SIP signaling to troubleshoot the problem, which field can provide a hint for troubleshooting?

- A. Contact: header of the 200 OK response
- B. Allow: header of the 200 OK response
- C. o= line of SDP content
- D. c= line of SDP content

Answer: C

NEW QUESTION 4

An administrator is troubleshooting call failures on an H.323 gateway via the CLI. To see signaling for media and call setup, which debug must the Administrator turn on?

- A. debug H.323 messages
- B. debug H.225 asn1
- C. debug H.246 asn 1
- D. debug H.225 media
- E. debug H.323 asn 1

Answer: B

NEW QUESTION 5

Which section under the Real-Time Monitoring Tool allows for reviewing the call flow and signaling for a SIP call in real time?

- A. Analysis Manager > Inventory > Trace File Repositories
- B. System > Tools > Trace and Log Central
- C. Voice/Video > Session Trace Log View > Real Time Data
- D. Voice/Video > Session Trace Log View > Open From Local Disk

Answer: C

NEW QUESTION 6

Which description of RTP timestamps or sequence numbers is true?

- A. The sequence number is used to detect losses.
- B. Timestamps increase by the time "carrying" by a packet.
- C. Sequence numbers increase by four for each RTP packet transmitted.
- D. The timestamp is used to place the incoming audio and video packets in the correct timing order (playout delay compensation).

Answer: D

NEW QUESTION 7

A company has an SRST gateway running an IOS XE image. The company plans to enable the IPv6 addressing companywide. To enable the IPv6 in a unified SRST gateway to support SIP phones, what are two supported supplementary features for an IPv6 fallback scenario? (Choose two.)

- A. three-way conference
- B. secure SIP lines
- C. T.38 fax relay
- D. transcoding
- E. SIP trunk

Answer:

AC

NEW QUESTION 8

Which action is correct with respect to toll fraud prevention configuration in the Cisco Unified Communications Manager Express?

- A. Configure Direct Inward Dial for Incoming ISDN Calls with overlap dialing.
- B. Configure IP Address Trusted Authentication for Incoming VoIP Calls.
- C. Configure the command `no ip address trusted authenticate` under "voice service voip".
- D. Enable Secondary Dial tone on Analog and Digital FXO Ports.

Answer: B

NEW QUESTION 9

Which top-level IOS command is needed to begin the configuration of a Cisco Unified Communications Manager Express gateway to enable phones to be registered via SIP?

- A. `allow-connections sip to sip`
- B. `voice service voip`
- C. `voice register global`
- D. `voice register dn`

Answer: C

NEW QUESTION 10

```
voice translation-rule 84
rule 1 /^ \ ([2-9]..[2-9].....$) / \2/
```

Refer to the exhibit. Users report that outbound PSTN calls from phones registered to Cisco Unified Communications Manager are not completing. The local service provider in North America has a requirement to receive calls in 10-digit format. The Cisco Unified CM sends the calls to the Cisco Unified Border Element router in a globalized E.164 format. There is an outbound dial peer on Cisco Unified Border Element configured to send the calls to the provider. The dial peer has a voice translation profile applied in the correct direction but an incorrect voice translation rule applied, which is shown in the exhibit. Which rule modified DNIS in the format that the provider is expecting?

- A. `rule 1 /^+\([1].*\)/ /011\1/`
- B. `rule 1 /^+1\([2-9]..[2-9].....$) / \1/`
- C. `rule 1 /^ \([2-9]..[2-9].....$) / \1/`
- D. `rule 1 /^+1\([2-9]..[2-9].....$) / \0/`

Answer: B


NEW QUESTION 10

A network engineer designs a new dial plan and wants to block a certain range of numbers (8135100 through 8135105). What is the most specific route pattern that can be configured to block only the numbers in this range?

- A. `813510[012345]`
- B. `813510[12345]`
- C. `813510[^0-5]`
- D. `81XXXXX`

Answer: A

NEW QUESTION 15



Refer to the exhibit. An administrator is troubleshooting a situation where a call placed from a phone registered to Cisco Unified Communications Manager does not complete. The administrator wants to use the Dialed Number Analyzer on Cisco Unified CM to check which translation pattern the call is matching. However, when logging in to Cisco Unified Serviceability there is no option for Dialed Number Analyzer under the tool menu. Which two steps must be performed to resolve this issue? (Choose two.)

- A. Restart the subscriber
- B. Activate the Cisco Extended Functions service.
- C. Activate the Cisco CallManager service.
- D. Activate the Cisco Dialed Number Analyzer service.
- E. Activate the Cisco Dialed Number Analyzer Server service.

Answer: DE


NEW QUESTION 20

An engineer is configuring a call park feature in Cisco Unified Communications Manager Express. Which command does the engineer use to ensure that the call is reverted to the user after 60 seconds?

- A. R2(config-ephone-dn)#park reservation-group 60
- B. R2(config-ephone-dn)#park-slot timeout 60 limit 2 recall alternate 3002
- C. R2(config-ephone-dn)#park reservation-group 1
- D. R2(config-ephone-dn)#park-slot timeout 30 limit 2 recall alternate 3002

Answer: B

NEW QUESTION 24



Refer to the exhibit. How many maximum hops can an ILS update traverse?

- A. 3
- B. 6
- C. 9
- D. 12

Answer: A

NEW QUESTION 29

When configuring hunt groups, where do you add the individual directory numbers that will be part of the group?

- A. route group
- B. line group
- C. hunt list
- D. hunt pilot

Answer: B

NEW QUESTION 30

A user reports that when they attempt to log out from the Cisco Extension Mobility service by pressing the Services button, they cannot log out. What is the most likely cause of this issue?

- A. The Cisco Extension Mobility service has not been configured on the phone.
- B. There might be a significant delay between the button being pressed and the Cisco Extension Mobility service recognizing it.
- C. It would be best to check network latency.
- D. The user device profile has not been assigned to the user.
- E. The user device profile is not subscribed to the Cisco Extension Mobility service.

Answer: D

NEW QUESTION 32

A user reports when they press the services key they do not receive a user ID and password prompt to assign the phone extension. Which action resolves the issue?

- A. Create the default device profiles for all phone models that are used.
- B. Subscribe the phone to the Cisco Extension Mobility service.
- C. Create the end user and associate it to the device profile.
- D. Assign the extension as a mobile extension.

Answer: B

NEW QUESTION 36

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

300-815 Practice Exam Features:

- * 300-815 Questions and Answers Updated Frequently
- * 300-815 Practice Questions Verified by Expert Senior Certified Staff
- * 300-815 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * 300-815 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 300-815 Practice Test Here](#)