

Exam Questions 2V0-13.25

VMware Cloud Foundation 9.0 Architect

<https://www.2passeasy.com/dumps/2V0-13.25/>



NEW QUESTION 1

Which type of storage is used by VKS pods to store non-persistent data?

- A. Container image storage
- B. vSphere local storage
- C. Object storage
- D. Ephemeral storage

Answer: D

NEW QUESTION 2

A cloud architect is designing a VMware Cloud Foundation (VCF) Automation solution for an organization. The design must fulfill the following requirements:

- ? The design must minimize provider infrastructure lifecycle tasks.
- ? The design must minimize infrastructure management overhead.
- ? Each tenant must have isolated compute infrastructure.

Which of the following deployment models best meets these requirements?

- A. Single VCF instance with dedicated Workload Domains per tenant
- B. Consolidated VCF deployment per tenant
- C. Dedicated VCF instances per tenant in a Standard Architecture
- D. Shared Workload Domain for tenants

Answer: A

NEW QUESTION 3

Requirement: The solution must include high security hardening levels to meet military compliance standards.

Which two physical design decisions will meet this security requirement in the workload domain? (Choose two.)

- A. The vSAN storage policy will be configured as Secondary Failures to Tolerate = 1.
- B. VCF Operations will be configured to renew the SSL certificate for vCenter Server per security policies.
- C. NTP will be configured to the internal NTP servers of 192.168.12.1 and 192.168.24.1.
- D. The advanced setting UserVars.SuppressShellWarning will be configured to 0 across all ESXi hosts.
- E. The certificate of the VI workload domain vCenter Server will be issued by RootCA.Military.Domain.Com.

Answer: DE

NEW QUESTION 4

An architect is responsible for designing a new VMware Cloud Foundation (VCF)-based private cloud. During the discovery workshops, the following information was captured from key customer stakeholders:

? The private cloud will operate with three different monitoring levels: Approved infrastructure applications include: Microsoft IIS, SQL Server, MySQL, PostgreSQL, Tomcat Server, and Apache HTTPD

Each workload must subscribe to a monitoring level

Minimal management overhead is required for agent operations

Which two design decision should the architect make to meet the stated monitoring requirements? (Choose two.)

- A. Configure the Service Discovery for all workloads that subscribe to the Self-Managed service
- B. Deploy the Managed Telegraf Agent for all workloads that subscribe to the Fully Managed service
- C. Deploy the Managed Telegraf Agent for all workloads that subscribe to the OS Managed service
- D. Deploy the Managed Telegraf Agent for all workloads that subscribe Self-Managed service
- E. Deploy the Open Source Telegraf Agent for all workloads that subscribe to the Fully Managed service

Answer: BC

NEW QUESTION 5

As part of a design for a VMware Cloud Foundation (VCF) solution, an architect has documented the following dependencies and constraints:

? CONSO01 - Internet access will not be permitted from anywhere within the VCF solution.

? CONS002 - The password must not be stored in plain text anywhere within the VCF solution.

? DEP001 - The customer must make the required VCF binaries accessible to the VCF Installer appliance during the deployment phase.

Which design decision should the architect include in the design for the download of the VCF binaries?

- A. The VCF Installer appliance will be configured to connect to an online depot.
- B. The VCF Installer appliance will be configured to connect to an offline depot.
- C. The Bundle Transfer Utility will be used on the VCF Installer appliance.
- D. The VCF Download Tool will be used on the VCF Installer appliance.

Answer: B

NEW QUESTION 6

An architect is responsible for designing a VMware Cloud Foundation (VCF)-based private cloud. During the design requirements gathering workshop, the following information was captured:

- The solution must capture events from all infrastructure components of the VCF fleet.
- The solution must provide a single pane of glass management interface for troubleshooting, alerting, and monitoring using metrics, events, and flows.
- The solution must meet a 99.9% Service Level Agreement for Availability.

Which three design decisions should the architect make to meet the stated requirements? (Choose three.)

- A. Configure VCF Operations for logs to capture events from only VCF Management components.
- B. Configure the integration for VCF Operations and VCF Automation.
- C. Deploy VCF Operations for logs in a Simple model.
- D. Configure the integration for VCF Operations and VCF Operations for logs.
- E. Configure VCF Operations for logs to capture events from all VCF infrastructure components.
- F. Deploy VCF Operations for logs in a High Availability model.

Answer: BDF

NEW QUESTION 7

An architect is designing the network model for a new VMware Cloud Foundation (VCF) solution. During the requirements gathering phase, the customer stated that the VCF solution must comply with the organization's security policy for traffic separation. The customer provided the architect with the following information from the policy:

- The physical network architecture is divided into multiple security zones.
- Traffic is not permitted to traverse between the zones with the exception of pre-approved monitoring tools.
- Physical servers may not be connected to multiple zones via a single network interface.
- Management and Storage traffic must be kept within network zone 1.
- Workload traffic must be kept within network zone 2.

The architect makes a design decision to use two vSphere Distributed Switches per cluster for both the Management and VI Workload domains.

Which two additional design decisions should the architect include in the virtual networking design for the separation of traffic between the vSphere Distributed Switches? (Choose two.)

- A. Configure one vSphere Distributed Switch for ESX Management, Storage, and vMotion traffic.
- B. Configure one vSphere Distributed Switch for all storage traffic.
- C. Configure one vSphere Distributed Switch for ESX Management, Storage, vMotion traffic and NSX - Host and Edge TEP/Edge Uplinks.
- D. Configure one vSphere Distributed Switch for all workload traffic and all NSX - Host and Edge TEP/Edge Uplinks.
- E. Configure one vSphere Distributed Switch for all NSX - Host and Edge TEP/Edge Uplinks.

Answer: AD

NEW QUESTION 8

An architect is responsible for designing a new VMware Cloud Foundation (VCF)-based Private Cloud solution. During the requirements gathering workshop with key customer stakeholders, the following information was captured:

- The solution must support running 50,000 workloads concurrently across all sites.
- The solution must support the concurrent deployment of up to 10 workloads.

When creating the design document, which design quality should be used to classify the stated requirements?

- A. Manageability
- B. Recoverability
- C. Performance
- D. Availability

Answer: C

NEW QUESTION 9

During a requirements gathering workshop, several business and technical requirements were captured from the customer. Which requirement will be classified as a Business Requirement?

- A. The solution must provide the best end-user experience.
- B. The solution must allow the migration of legacy server infrastructure.
- C. The solution must consider security and resiliency to ensure business continuity.
- D. The solution must provide a component-level SLA of 99.9% or higher.

Answer: A

NEW QUESTION 10

An architect has compiled a list of statements following a workshop with the business stakeholders. Which statement would be included in a conceptual model?

- A. The solution must meet a Mean Time To Recovery (MTTR) of 6 hours.
- B. Sites A and B will each have a stretched Layer-2 for their management network.
- C. The `das.isolationshutdowntimeout` setting will be configured to 120 seconds.
- D. Users will connect to the application servers via the NSX Advanced Load Balancer.

Answer: D

NEW QUESTION 10

Existing environment:

? 3 vSphere clusters, 5 hosts each.

? Networking = vDS.

? Storage = NFSv3.

? Managed by single vCenter. Architect decides to create a new VCF fleet with a single VCF instance.

What design implication should be documented?

- A. NSX will be automatically deployed during the creation of the VCF fleet.
- B. The vCenter VM must be migrated to a standalone host before fleet creation.
- C. The clusters will be automatically configured to use vSAN storage before the creation of the fleet.
- D. The ESX hosts will be converted to use vSphere Lifecycle Manager baselines during the creation of the fleet.

Answer: B

NEW QUESTION 15

An architect is tasked to plan for an upgrade of an existing vSphere-only deployment utilizing vSAN to VMware Cloud Foundation (VCF). Which three new infrastructure components are required for the upgrade? (Choose three.)

- A. NSX
- B. SDDC Manager
- C. VCF Identity Broker
- D. VCF Operations
- E. vSphere Supervisor

Answer: ABE

NEW QUESTION 17

Requirement: Ensure all management components are redundant at the component level. Which design quality should classify this requirement?

- A. Performance
- B. Manageability
- C. Availability
- D. Recoverability

Answer: C

NEW QUESTION 22

An architect is responsible for designing a VMware Cloud Foundation (VCF)-based solution for a customer. The customer has the following requirement:

- There should be no single points of failure within the solution.

To comply with the customer requirement, the architect has decided to include physical NIC teaming for all ESX servers in the design. When documenting this design decision, which consideration should the architect make?

- A. Embedded NICs should not be used for NIC teaming.
- B. Each NIC team must include NICs from the same physical NIC Card.
- C. Each NIC team must include NICs from different physical NIC Cards.
- D. Only 10GbE NICs should be used for NIC teaming.

Answer: C

NEW QUESTION 24

During the design workshop, the customer stated the following requirement:

- The solution will support secure communication.

Which design decision should be included in the logical design for the workload domain?

- A. Use a SHA-2 algorithm or higher for signed certificates.
- B. Set promiscuous mode port group security policy to reject.
- C. Verify all physical components used for the deployments are on the hardware compatibility list.
- D. Ensure the host servers have TPM 2.0 hardware.

Answer: A

NEW QUESTION 25

As part of the VMware Cloud Foundation (VCF) logical design, the architect has determined that the VCF Private Cloud will encompass multiple VCF instances contained within a single VCF Fleet. The architect documented the following requirements when using VCF Operations:

- ? Monitoring downtime must be minimized.
- ? Alerting downtime must be minimized.

Which design decision supports these requirements?

- A. Deploy two VCF Operations instances and configure the Aggregator Management Pack.
- B. Deploy VCF Operations using the Simple model with Collector nodes at remote sites.
- C. Deploy VCF Operations using the High Availability model with Collector nodes at remote sites.
- D. Deploy a single VCF Operations instance across a multi-VCF instance fleet.

Answer: C

NEW QUESTION 30

An architect is working with an organization on the creation of a new VMware Cloud Foundation (VCF) Private Cloud. The organization has provided the following business objectives:

- ? Reduce costs of duplicate systems.
- ? Eliminate risks of unsupported platforms.
- ? Reduce public cloud costs.
- ? Eliminate risks from poor documentation.

Use cases: Migration, Containerization, Centralization & Consolidation.

When considering these objectives and use cases, what should the architect include in the design documentation as a part of the Conceptual Model?

- A. A constraint that the solution must be accessible via a HTTPS GUI to all relevant areas of the business.
- B. A requirement that the solution will provide support for provisioning and managing workloads based on virtualization and containerization technologies.
- C. An assumption that a complete mapping of application dependencies is not available.

D. A risk that the solution may not support the migration of containerized workloads.

Answer: B

NEW QUESTION 34

During a requirements gathering workshop, the customer has provided a list of business and technical requirements. Which requirement should be classified as a business requirement?

- A. The solution needs to grow by 30% over the next three years.
- B. The solution must consider security and resiliency to ensure continuity.
- C. The solution must provide no Single Point of Failure (SPOF).
- D. The solution should reduce operational costs.

Answer: D

NEW QUESTION 37

A VMware Cloud Foundation (VCF) architect is planning for the expansion of an existing VCF instance. The existing VCF instance is deployed with a single workload domain. The number of ESXi hosts has grown to the maximum number the existing vCenter can support.

Which design decision would the architect need to make to allow the existing VCF Instance to add more ESXi hosts?

- A. Deploy a second vCenter server appliance within the existing workload domain
- B. Deploy a second workload domain within the existing VCF Instance
- C. Deploy a second cluster within the existing vCenter
- D. Deploy a second VCF Instance within the existing VCF Fleet

Answer: B

NEW QUESTION 38

A large financial institution is designing a VMware Cloud Foundation (VCF) solution. During initial discovery meetings:

- Management of the physical network is outsourced.
- VMware team cannot reconfigure the physical network.
- Environment uses Link Aggregation. How does this impact design?

- A. NIC teaming for Virtual Standard Switch (vSS) must be configured.
- B. LACP fallback must be configured.
- C. Link Aggregation cannot be used for Workload Domains.
- D. Link Aggregation cannot be used in the Management Domain.

Answer: B

NEW QUESTION 40

An architect is tasked with designing a new VMware Cloud Foundation (VCF) solution. During workshops with the customer, the following requirements were captured:

- REQ01: The solution must provide a self-service catalog.
- REQ02: The solution must support the segregation of the Development and Production resources (networks, virtual machines, users).

When documenting the design decisions, which statement should the architect include in order to help meet these requirements?

- A. VCF Automation does not support the use of multiple Active Directory domains.
- B. Separate workload domains must be configured to provide segregation between the Development and Production environments.
- C. VCF Automation will be configured with separate service catalog instances for Development and Production.
- D. VCF Automation will be configured with separate organizations for Development and Production.

Answer: D

NEW QUESTION 41

Which design defines how to arrange and use components and features of the infrastructure to satisfy service dependencies and other relationships specified in the Conceptual Model?

- A. Physical Design
- B. High Availability Design
- C. Configuration Guide
- D. Logical Design

Answer: D

NEW QUESTION 44

An architect is tasked with designing a VMware Cloud Foundation (VCF) solution for a financial services organization to modernize its core banking applications and high-frequency trading systems using vSAN.

The following requirements were gathered:

- For critical transactional database workloads, the solution must provide low-latency and high performance storage.
- For all non-critical workloads, the solution must provide the most efficient capacity utilization.

Which three design decisions would the architect make to meet the requirements for the workload domain cluster? (Choose three.)

- A. Configure vSAN Policies (RAID-5) for all critical transactional database workloads.
- B. Deploy a vSAN OSA (All-NVMe) cluster with a minimum of 4 nodes.
- C. Deploy a vSAN ESA cluster with a minimum of 6 nodes.

- D. Configure vSAN Policies (RAID-5/6) for all non-critical workloads.
- E. Configure vSAN Policies (RAID-1) for all workloads.
- F. Configure vSAN Policies (RAID-1) for all critical transactional database workloads.

Answer: CDF

NEW QUESTION 45

A customer is designing a multi-site VMware Cloud Foundation (VCF) and vSAN Data Protection (DP) architecture to ensure business continuity. The customer's support team must validate the failover and recovery processes before being allowed to deploy into production. Which two validation activities should be included in the strategy to meet the objective? (Choose two.)

- A. Conduct recovery plan testing annually, as frequent testing may introduce instability in DR environments.
- B. Assess the impact of failover scenarios on application dependencies and inter-site connectivity.
- C. Configure recovery plans based on generic VMware best practices rather than workload-specific requirements to decrease the architecture complexity.
- D. Perform planned and unplanned failover tests in a controlled environment to validate recovery time objectives.
- E. Configure vSphere HA and DRS features to manage disaster recovery automatically, eliminating the need for additional validation.

Answer: BD

NEW QUESTION 49

Requirement: The solution must identify any configuration changes made to the Management Infrastructure every 30 days. Which three design decisions should the architect make to meet the stated requirements? (Choose three.)

- A. Configure a Configuration Template for the Management Cluster.
- B. Schedule Configuration Drift to Check the configuration every 30 days.
- C. Configure a Configuration Template for the Management vCenter.
- D. Create a Configuration Template for the Management NSX Manager.
- E. Schedule Configuration Drift to Remediate the configuration every 30 days.
- F. Configure Host Profiles for the Workload Domain.

Answer: ABD

NEW QUESTION 50

An architect is designing for a greenfield VMware Cloud Foundation (VCF) solution. This would be the first VCF Fleet in the VCF solution, and the customer would like to start with a minimal footprint with the option to scale up and out later. Which VCF Operations deployment model should the architect choose?

- A. Advanced
- B. High Availability
- C. Simple
- D. Standard

Answer: C

NEW QUESTION 54

An architect is responsible for designing a VMware Cloud Foundation (VCF)-based private cloud for a customer. During the customer requirements gathering workshop, the customer has stated the following:

- ? All Platinum applications/services must have an availability SLA of 99.99%.
- ? All Gold applications/services must have an availability SLA of 99.9%.
- ? All Silver applications/services must have an availability SLA of 99%.
- ? The private cloud must have an availability SLA of 99.9%.

What should the architect recommend to meet the stated requirements?

- A. The private cloud must only be used to host Silver and Gold services.
- B. The private cloud SLA can only be met using multiple VMware Cloud Foundation instances configured as a single VCF Fleet.
- C. The Platinum service availability requirements must be met by the application.
- D. The Platinum service availability requirements must be met by configuring Proactive High Availability (HA) on the workload domain.

Answer: C

NEW QUESTION 55

An architect is responsible for designing a VMware Cloud Foundation (VCF) Private Cloud. During a requirements gathering workshop with key customer stakeholders, the following information was captured:

- The service catalog solution must meet a minimum availability SLA of 99.9%.
- The performance of the service catalog solution must not be impacted by maintenance activities or a single physical ESXi host failure.

During the logical design phase of the project, the following design decisions were made:

- The solution will deploy VCF Automation using the highly available deployment model. Which two corresponding physical design decisions should the architect make to meet the stated requirements? (Choose two.)

- A. The solution will configure the external load balancer to send all traffic to the native Kubernetes load balancer.
- B. The solution will deploy three VCF Automation appliances using the small size.
- C. The solution will create a VM-host affinity rule to ensure all nodes of the VCF Automation cluster are located on the same ESXi host.
- D. The solution will create a VM-host anti-affinity rule to ensure all nodes of the VCF Automation cluster are located on different ESXi hosts.
- E. The solution will deploy an external load balancer to replace the native load balancer.

Answer: DE

NEW QUESTION 59

VMware Kubernetes Service (VKS) cluster exposes three layers of controllers to manage its lifecycle. Which set correctly identifies these layers?

- A. Virtual Machine Service, vCenter Appliance, Supervisor Service.
- B. Cluster API, Node Problem Detector, CNI Plugin.
- C. API Gateway, StatefulSet Controller, Ingress Controller.
- D. Virtual Machine Service, Cluster API, and Cloud Provider Plugin.

Answer: D

NEW QUESTION 64

Which statement would the architect document as a design decision within the logical design?

- A. Service Levels will align with the defined Business Impact Analysis findings.
- B. The solution must provide the ability to patch an existing template.
- C. The VMware Distributed Resource Scheduler (DRS) latency sensitivity value will be set to high for the workload cluster.
- D. vSphere High Availability (HA) will be enabled.

Answer: C

NEW QUESTION 65

An architect has compiled a list of design choices following a design workshop with the business stakeholders. Which statement represents a logical design decision?

- A. Synchronous data replication will be used to meet the stated Recovery Point Objective (RPO) between site A and B.
- B. Users must experience application availability in under 2 seconds.
- C. Sites A and B will each have a /16 subnet for their networks.
- D. Users must connect to the application servers via a shared Global Load Balancer.

Answer: A

NEW QUESTION 66

Which statement defines the purpose of Technical Requirements?

- A. They define which goals and objectives can be achieved.
- B. They define what goals and objectives need to be achieved.
- C. They define which audience need to be involved.
- D. They define how the goals and objectives can be achieved.

Answer: D

NEW QUESTION 68

An architect is designing a solution with Istio Service Mesh. What two types of groups can collect and manage objects? (Choose two.)

- A. Service
- B. Cluster
- C. Security
- D. API
- E. Node

Answer: AB

NEW QUESTION 72

During a design workshop, the security team provides the following requirement for the VMware Cloud Foundation (VCF) Automation deployment:
? All Virtual Machine images must be reviewed and vetted by the security team prior to consumption.
Which Content Library type supports the requirement?

- A. Subscribed Content Library
- B. Tenant-managed Content Library
- C. Local Content Library
- D. Provider-managed Content Library

Answer: D

NEW QUESTION 76

The architect documented a requirement for 99.95% high availability to meet the customer's resiliency needs. Which two physical design decisions will help meet this requirement in the management domain? (Choose two.)

- A. Configure vCenter HA for the management domain vCenter server.
- B. ESX Host Uplink Setting: EtherChannel = Enable
- C. Advanced Cluster Setting: das.iostatsinterval = 0
- D. Set the restart priority policy for the vCenter Server appliance to high.
- E. ESX Host Uplink Setting: EtherChannel = Disable

Answer:

AD

NEW QUESTION 80

An architect is responsible for designing a new VMware Cloud Foundation (VCF)-based Private Cloud solution. During the requirements gathering workshop with key customer stakeholders, the following information was captured:

- The solution must support the monitoring of up to 10,000 objects.
- The solution must support 24 months retention for all monitoring data.

When creating the design document, which design quality should be used to classify the stated requirements?

- A. Performance
- B. Manageability
- C. Availability
- D. Recoverability

Answer: B

NEW QUESTION 84

An architect is responsible for designing a VMware Cloud Foundation (VCF)-based private cloud for a customer. The architect noted the following requirements during a design workshop:

- ? Co-locate application workloads with VCF management component workloads within the same vSphere cluster.
- ? Shared storage data is always available and 100% current in the event of a single site outage.
- ? Have two sites available no more than 10 miles apart (10ms latency) connected with high-speed network technology to host their virtual infrastructure.
- ? Protect against outages of a single site designated as an availability zone.

Which two storage technologies could meet the stated requirements? (Choose two.)

- A. NVMe over TCP
- B. NVMe over Fibre Channel (FC)
- C. VMFS on Fibre Channel (FC)
- D. vSAN
- E. vSphere Virtual Volumes (vVols)

Answer: DE

NEW QUESTION 89

An architect is responsible for designing a VMware Cloud Foundation (VCF)-based solution for a customer. During a discovery workshop, the following requirements were stated by the customer:

- All applications/workloads designated as business critical have a Recovery Point Objective (RPO) of 1 business hour.
- The infrastructure components of the VCF solution must have a Recovery Time Objective (RTO) of 4 business hours.

In the context provided, what does the RTO determine?

- A. The maximum tolerable amount of time allowed before an application/service should be recovered to a usable state
- B. The maximum amount of data loss that can be tolerated
- C. The minimum tolerable amount of time allowed before an application/service should be recovered to a usable state
- D. The minimum amount of data loss that can be tolerated

Answer: A

NEW QUESTION 93

During an initial design workshop with stakeholders, an Architect was provided with an overview of the current state and other information required to proceed to the design phase.

Which statement should be documented as a requirement?

- A. Existing shared storage array must be used.
- B. Block-based storage must be used within a workload domain.
- C. Existing storage arrays provide sufficient capacity for building the environment.
- D. The customer network team is not trained to support NSX VPC.

Answer: B

NEW QUESTION 98

An organization is evacuating their current datacenter and moving all workloads to a new datacenter. The organization has a total of 800 workloads to move, and the migration must be completed with no downtime within a planned change window that is scheduled to occur in four weeks.

What migration method will meet the requirements?

- A. Cross vCenter vMotion
- B. HCX OS Assisted Migration
- C. HCX Bulk Migration
- D. HCX Replication Assisted vMotion

Answer: D

NEW QUESTION 102

A large financial institution is designing a VMware Cloud Foundation (VCF) solution. During the initial discovery meetings, the customer detailed the following requirements:

- Management of the physical network environment is handled by an outsourced team.
- The VMware Administration team cannot re-configure the physical network.
- All hosts must use Link Aggregation.

- The storage environment is disaggregated.
 - NFS will be used as principal storage.
- The customer provided the bill-of-materials for the physical servers being purchased. Each server will have four 25 GbE physical NICs: two connected to the network fabric for Management, vMotion, and virtual machine traffic; and two connected to the storage fabric hosting the NFS server. How does the information provided impact the overall design?
- A. Link Aggregation cannot be used in the Workload Domain.
 - B. NIC teaming for Virtual Standard Switch (vSS) must be configured.
 - C. Multiple Link Aggregation Groups are not supported.
 - D. Link Aggregation cannot be used in the Management Domain.

Answer: D

NEW QUESTION 105

An architect is responsible for the design of a VMware Cloud Foundation (VCF) Fleet and the following risk has been identified:

- RISK001: There is a risk that frequent infrastructure design changes may break Disaster Recovery (DR) plans and Service Level Objectives. What should the architect suggest to mitigate this risk?

- A. Setup monitoring & alerting against defined infrastructure service level objectives.
- B. Develop a process to review and update DR plans between changes and schedule monthly end-to-end DR tests.
- C. Limit infrastructure design change frequency to a maximum of once a month.
- D. Configure VM replication with recovery point objective of 5 minutes or less for all workloads from the primary to DR site.

Answer: B

NEW QUESTION 106

An architect had been given a constraint to use an existing storage array to support the virtual infrastructure design project.

The architect documents the following:

? Assumption 01: The existing storage array has sufficient capacity and performance to support the intended workloads.

? Risk 01: There is a risk that the performance and capacity of the existing storage array may not be sufficient for the solution. How would the architect mitigate the risk?

- A. Ensure that the customer allocates budget for new hardware in case the risk is realized.
- B. Setup a RAID mirror configuration on the existing storage array for redundancy.
- C. Ignore the constraint and design the solution using VMware vSAN Express Storage Architecture (ESA).
- D. Request for additional budget to purchase more Fibre Channel switches.

Answer: A

NEW QUESTION 107

An architect is responsible for designing a new VMware Cloud Foundation (VCF)-based Private Cloud solution. During the requirements gathering workshop with key customer stakeholders, the following information was captured:

? The solution must support a yearly workload growth of up to 10%.

When creating the design document, which design quality should be used to classify the stated requirements?

- A. Performance
- B. Availability
- C. Manageability
- D. Security

Answer: A

NEW QUESTION 111

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 2V0-13.25 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 2V0-13.25 Product From:

<https://www.2passeasy.com/dumps/2V0-13.25/>

Money Back Guarantee

2V0-13.25 Practice Exam Features:

- * 2V0-13.25 Questions and Answers Updated Frequently
- * 2V0-13.25 Practice Questions Verified by Expert Senior Certified Staff
- * 2V0-13.25 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 2V0-13.25 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year