



Cisco

Exam Questions 300-710

Securing Networks with Cisco Firepower (SNCF)

NEW QUESTION 1

Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

- A. The units must be the same version
- B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
- C. The units must be different models if they are part of the same series.
- D. The units must be configured only for firewall routed mode.
- E. The units must be the same model.

Answer: AE

NEW QUESTION 2

What are the minimum requirements to deploy a managed device inline?

- A. inline interfaces, security zones, MTU, and mode
- B. passive interface, MTU, and mode
- C. inline interfaces, MTU, and mode
- D. passive interface, security zone, MTU, and mode

Answer: C

NEW QUESTION 3

What is the difference between inline and inline tap on Cisco Firepower?

- A. Inline tap mode can send a copy of the traffic to another device.
- B. Inline tap mode does full packet capture.
- C. Inline mode cannot do SSL decryption.
- D. Inline mode can drop malicious traffic.

Answer: D

NEW QUESTION 4

Which interface type allows packets to be dropped?

- A. passive
- B. inline
- C. ERSPAN
- D. TAP

Answer: B

NEW QUESTION 5

Which Cisco Firepower Threat Defense, which two interface settings are required when configuring a routed interface? (Choose two.)

- A. Redundant Interface
- B. EtherChannel
- C. Speed
- D. Media Type
- E. Duplex

Answer: CE

NEW QUESTION 6

What are two application layer preprocessors? (Choose two.)

- A. CIFS
- B. IMAP
- C. SSL
- D. DNP3
- E. ICMP

Answer: BC

NEW QUESTION 7

Which two routing options are valid with Cisco Firepower Threat Defense? (Choose two.)

- A. BGPv6
- B. ECMP with up to three equal cost paths across multiple interfaces
- C. ECMP with up to three equal cost paths across a single interface
- D. BGPv4 in transparent firewall mode
- E. BGPv4 with nonstop forwarding

Answer: AC

NEW QUESTION 8

Which Cisco Firepower rule action displays an HTTP warning page?

- A. Monitor
- B. Block
- C. Interactive Block
- D. Allow with Warning

Answer: C

NEW QUESTION 9

Which Firepower feature allows users to configure bridges in routed mode and enables devices to perform Layer 2 switching between interfaces?

- A. FlexConfig
- B. BDI
- C. SGT
- D. IRB

Answer: D

NEW QUESTION 10

In which two places can thresholding settings be configured? (Choose two.)

- A. on each IPS rule
- B. globally, within the network analysis policy
- C. globally, per intrusion policy
- D. on each access control rule
- E. per preprocessor, within the network analysis policy

Answer: AC

NEW QUESTION 10

In which two ways do access control policies operate on a Cisco Firepower system? (Choose two.)

- A. Traffic inspection can be interrupted temporarily when configuration changes are deployed.
- B. The system performs intrusion inspection followed by file inspection.
- C. They can block traffic based on Security Intelligence data.
- D. File policies use an associated variable set to perform intrusion prevention.
- E. The system performs a preliminary inspection on trusted traffic to validate that it matches the trusted parameters.

Answer: AC

NEW QUESTION 15

Which two types of objects are reusable and supported by Cisco FMC? (Choose two.)

- A. dynamic key mapping objects that help link HTTP and HTTPS GET requests to Layer 7 application protocols.
- B. reputation-based objects that represent Security Intelligence feeds and lists, application filters based on category and reputation, and file lists
- C. network-based objects that represent IP address and networks, port/protocols pairs, VLAN tags, security zones, and origin/destination country
- D. network-based objects that represent FQDN mappings and networks, port/protocol pairs, VXLAN tags, security zones and origin/destination country
- E. reputation-based objects, such as URL categories

Answer: BC

NEW QUESTION 20

What is the benefit of selecting the trace option for packet capture?

- A. The option indicates whether the packet was dropped or successful.
- B. The option indicated whether the destination host responds through a different path.
- C. The option limits the number of packets that are captured.
- D. The option captures details of each packet.

Answer: C

NEW QUESTION 22

After deploying a network-monitoring tool to manage and monitor networking devices in your organization, you realize that you need to manually upload an MIB for the Cisco FMC. In which folder should you upload the MIB file?

- A. /etc/sf/DCMIB.ALERT
- B. /sf/etc/DCEALERT.MIB
- C. /etc/sf/DCEALERT.MIB
- D. system/etc/DCEALERT.MIB

Answer: C

NEW QUESTION 27

Which command is run at the CLI when logged in to an FTD unit, to determine whether the unit is managed locally or by a remote FMC server?

- A. system generate-troubleshoot
- B. show configuration session
- C. show managers
- D. show running-config | include manager

Answer: C

NEW QUESTION 31

How many report templates does the Cisco Firepower Management Center support?

- A. 20
- B. 10
- C. 5
- D. unlimited

Answer: D

NEW QUESTION 36

Which action should be taken after editing an object that is used inside an access control policy?

- A. Delete the existing object in use.
- B. Refresh the Cisco FMC GUI for the access control policy.
- C. Redeploy the updated configuration.
- D. Create another rule using a different object name.

Answer: C

NEW QUESTION 41

Which report template field format is available in Cisco FMC?

- A. box lever chart
- B. arrow chart
- C. bar chart
- D. benchmark chart

Answer: C

NEW QUESTION 45

DRAG DROP

Drag and drop the steps to restore an automatic device registration failure on the standby Cisco FMC from the left into the correct order on the right. Not all options are used.

Select and Place:

- A. Mastered
- B. Not Mastered

Answer: A

NEW QUESTION 48

Which command-line mode is supported from the Cisco Firepower Management Center CLI?

- A. privileged
- B. user
- C. configuration
- D. admin

Answer: C

NEW QUESTION 51

Which command is typed at the CLI on the primary Cisco FTD unit to temporarily stop running high-availability?

- A. configure high-availability resume
- B. configure high-availability disable
- C. system support network-options
- D. configure high-availability suspend

Answer: B

NEW QUESTION 55

Within Cisco Firepower Management Center, where does a user add or modify widgets?

- A. dashboard
- B. reporting

- C. context explorer
- D. summary tool

Answer: A

NEW QUESTION 57

Which two statements about deleting and re-adding a device to Cisco FMC are true? (Choose two.)

- A. An option to re-apply NAT and VPN policies during registration is available, so users do not need to re-apply the policies after registration is completed.
- B. Before re-adding the device in Cisco FMC, you must add the manager back in the device.
- C. No option to delete and re-add a device is available in the Cisco FMC web interface.
- D. The Cisco FMC web interface prompts users to re-apply access control policies.
- E. No option to re-apply NAT and VPN policies during registration is available, so users need to re-apply the policies after registration is completed.

Answer: DE

NEW QUESTION 61

What is a behavior of a Cisco FMC database purge?

- A. User login and history data are removed from the database if the User Activity check box is selected.
- B. Data can be recovered from the device.
- C. The appropriate process is restarted.
- D. The specified data is removed from Cisco FMC and kept for two weeks.

Answer: C

NEW QUESTION 63

Which two packet captures does the FTD LINA engine support? (Choose two.)

- A. Layer 7 network ID
- B. source IP
- C. application ID
- D. dynamic firewall importing
- E. protocol

Answer: BE

NEW QUESTION 66

Which two features of Cisco AMP for Endpoints allow for an uploaded file to be blocked? (Choose two.)

- A. application blocking
- B. simple custom detection
- C. file repository
- D. exclusions
- E. application whitelisting

Answer: AB

NEW QUESTION 68

Which action should you take when Cisco Threat Response notifies you that AMP has identified a file as malware?

- A. Add the malicious file to the block list.
- B. Send a snapshot to Cisco for technical support.
- C. Forward the result of the investigation to an external threat-analysis engine.
- D. Wait for Cisco Threat Response to automatically block the malware.

Answer: A

NEW QUESTION 72

Which Cisco Advanced Malware Protection for Endpoints policy is used only for monitoring endpoint actively?

- A. Windows domain controller
- B. audit
- C. triage
- D. protection

Answer: B

NEW QUESTION 75

Which two remediation options are available when Cisco FMC is integrated with Cisco ISE? (Choose two.)

- A. dynamic null route configured
- B. DHCP pool disablement
- C. quarantine
- D. port shutdown

E. host shutdown

Answer: CD

NEW QUESTION 78

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

300-710 Practice Exam Features:

- * 300-710 Questions and Answers Updated Frequently
- * 300-710 Practice Questions Verified by Expert Senior Certified Staff
- * 300-710 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * 300-710 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 300-710 Practice Test Here](#)