



Cisco

Exam Questions 300-710

Securing Networks with Cisco Firepower (SNCF)

NEW QUESTION 1

Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

- A. The units must be the same version
- B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
- C. The units must be different models if they are part of the same series.
- D. The units must be configured only for firewall routed mode.
- E. The units must be the same model.

Answer: AE

NEW QUESTION 2

Which two deployment types support high availability? (Choose two.)

- A. transparent
- B. routed
- C. clustered
- D. intra-chassis multi-instance
- E. virtual appliance in public cloud

Answer: AB

NEW QUESTION 3

Which two OSPF routing features are configured in Cisco FMC and propagated to Cisco FTD? (Choose two.)

- A. OSPFv2 with IPv6 capabilities
- B. virtual links
- C. SHA authentication to OSPF packets
- D. area boundary router type 1 LSA filtering
- E. MD5 authentication to OSPF packets

Answer: BD

NEW QUESTION 4

When creating a report template, how can the results be limited to show only the activity of a specific subnet?

- A. Create a custom search in Firepower Management Center and select it in each section of the report.
- B. Add an Input Parameter in the Advanced Settings of the report, and set the type to Network/IP.
- C. Add a Table View section to the report with the Search field defined as the network in CIDR format.
- D. Select IP Address as the X-Axis in each section of the report.

Answer: B

NEW QUESTION 5

What is the disadvantage of setting up a site-to-site VPN in a clustered-units environment?

- A. VPN connections can be re-established only if the failed master unit recovers.
- B. Smart License is required to maintain VPN connections simultaneously across all cluster units.
- C. VPN connections must be re-established when a new master unit is elected.
- D. Only established VPN connections are maintained when a new master unit is elected.

Answer: C

NEW QUESTION 6

Which two statements about bridge-group interfaces in Cisco FTD are true? (Choose two.)

- A. The BVI IP address must be in a separate subnet from the connected network.
- B. Bridge groups are supported in both transparent and routed firewall modes.
- C. Bridge groups are supported only in transparent firewall mode.
- D. Bidirectional Forwarding Detection echo packets are allowed through the FTD when using bridge-group members.
- E. Each directly connected network must be on the same subnet.

Answer: CD

NEW QUESTION 7

Which object type supports object overrides?

- A. time range
- B. security group tag
- C. network object
- D. DNS server group

Answer: C

NEW QUESTION 8

Which command should be used on the Cisco FTD CLI to capture all the packets that hit an interface?

- A. configure coredump packet-engine enable
- B. capture-traffic
- C. capture
- D. capture WORD

Answer: B

NEW QUESTION 9

How many report templates does the Cisco Firepower Management Center support?

- A. 20
- B. 10
- C. 5
- D. unlimited

Answer: D

NEW QUESTION 10

Which Cisco Firepower feature is used to reduce the number of events received in a period of time?

- A. rate-limiting
- B. suspending
- C. correlation
- D. thresholding

Answer: D

NEW QUESTION 10

Which report template field format is available in Cisco FMC?

- A. box lever chart
- B. arrow chart
- C. bar chart
- D. benchmark chart

Answer: C

NEW QUESTION 11

Which command is entered in the Cisco FMC CLI to generate a troubleshooting file?

- A. show running-config
- B. show tech-support chassis
- C. system support diagnostic-cli
- D. sudo sf_troubleshoot.pl

Answer: D

Explanation:

41 Which CLI command is used to control special handling of ClientHello messages?

- A. system support ssl-client-hello-tuning
- B. system support ssl-client-hello-display
- C. system support ssl-client-hello-force-reset
- D. system support ssl-client-hello-enabled

NEW QUESTION 13

Which command is typed at the CLI on the primary Cisco FTD unit to temporarily stop running high-availability?

- A. configure high-availability resume
- B. configure high-availability disable
- C. system support network-options
- D. configure high-availability suspend

Answer: B

NEW QUESTION 14

Which command must be run to generate troubleshooting files on an FTD?

- A. system support view-files
- B. sudo sf_troubleshoot.pl
- C. system generate-troubleshoot all
- D. show tech-support

Answer: B

NEW QUESTION 16

What is a functionality of port objects in Cisco FMC?

- A. to mix transport protocols when setting both source and destination port conditions in a rule
- B. to represent protocols other than TCP, UDP, and ICMP
- C. to represent all protocols in the same way
- D. to add any protocol other than TCP or UDP for source port conditions in access control rules.

Answer: B

NEW QUESTION 19

Within Cisco Firepower Management Center, where does a user add or modify widgets?

- A. dashboard
- B. reporting
- C. context explorer
- D. summary tool

Answer: A

NEW QUESTION 21

What is the maximum bit size that Cisco FMC supports for HTTPS certificates?

- A. 1024
- B. 8192
- C. 4096
- D. 2048

Answer: D

NEW QUESTION 25

Which two statements about deleting and re-adding a device to Cisco FMC are true? (Choose two.)

- A. An option to re-apply NAT and VPN policies during registration is available, so users do not need to re-apply the policies after registration is completed.
- B. Before re-adding the device in Cisco FMC, you must add the manager back in the device.
- C. No option to delete and re-add a device is available in the Cisco FMC web interface.
- D. The Cisco FMC web interface prompts users to re-apply access control policies.
- E. No option to re-apply NAT and VPN policies during registration is available, so users need to re-apply the policies after registration is completed.

Answer: DE

NEW QUESTION 27

Which action should you take when Cisco Threat Response notifies you that AMP has identified a file as malware?

- A. Add the malicious file to the block list.
- B. Send a snapshot to Cisco for technical support.
- C. Forward the result of the investigation to an external threat-analysis engine.
- D. Wait for Cisco Threat Response to automatically block the malware.

Answer: A

NEW QUESTION 30

Which connector is used to integrate Cisco ISE with Cisco FMC for Rapid Threat Containment?

- A. pxGrid
- B. FTD RTC
- C. FMC RTC
- D. ISEGrid

Answer: A

NEW QUESTION 34

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

300-710 Practice Exam Features:

- * 300-710 Questions and Answers Updated Frequently
- * 300-710 Practice Questions Verified by Expert Senior Certified Staff
- * 300-710 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 300-710 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 300-710 Practice Test Here](#)